

Develop the Smart City Road Navigation System

Theme: Trees, Graphs, and Advanced Algorithms

GitHub:

https://github.com/mayank24000/University_Assignments/tree/main/Ds_%20Assignments/Theory_Assignments/Theory_Assignment_4

Code:

```
#include <iostream>
#include <string>
#include <vector>
#include <queue>
#include <stack>
#include <algorithm>
#include <climits>
#include <iomanip>
#include <map>
#include <set>

using namespace std;

class RoadNode {
public:
```

```

int nodeID;
string nodeName;
string zoneDetails;

RoadNode() {
    nodeID = -1;
    nodeName = "";
    zoneDetails = "";
}

RoadNode(int id, string name, string zone) {
    nodeID = id;
    nodeName = name;
    zoneDetails = zone;
}

void display() {
    cout << "Node " << nodeID << ": " << nodeName
         << " [" << zoneDetails << "]" << endl;
}

};

// ===== GRAPH REPRESENTATION =====

class RoadNetwork {
private:
    int numNodes;
    vector<vector<int>> adjacencyMatrix;

```

```

        vector<vector<pair<int, int>>> adjacencyList; //
pair<destination, weight>

        map<int, RoadNode> nodes;

public:
    RoadNetwork() {
        numNodes = 0;
    }

    void initializeNetwork(int n) {
        numNodes = n;
        adjacencyMatrix.resize(n, vector<int>(n, INT_MAX));
        adjacencyList.resize(n);

        // Initialize diagonal elements to 0
        for(int i = 0; i < n; i++) {
            adjacencyMatrix[i][i] = 0;
        }
    }

    void addNode(RoadNode node) {
        nodes[node.nodeID] = node;
    }

    void addRoad(int from, int to, int distance) {
        if(from < numNodes && to < numNodes) {
            // Add to adjacency matrix
            adjacencyMatrix[from][to] = distance;
            adjacencyMatrix[to][from] = distance; // Undirected road
        }
    }

```

```

        // Add to adjacency list
        adjacencyList[from].push_back({to, distance});
        adjacencyList[to].push_back({from, distance}); //
Undirected road
    }
}

void addDirectedRoad(int from, int to, int distance) {
    if(from < numNodes && to < numNodes) {
        // Add to adjacency matrix
        adjacencyMatrix[from][to] = distance;

        // Add to adjacency list
        adjacencyList[from].push_back({to, distance});
    }
}

void displayAdjacencyMatrix() {
    cout << "\n--- Adjacency Matrix Representation ---" << endl;
    cout << "    ";
    for(int i = 0; i < numNodes; i++) {
        cout << setw(8) << i;
    }
    cout << endl;

    for(int i = 0; i < numNodes; i++) {
        cout << setw(4) << i;
        for(int j = 0; j < numNodes; j++) {

```

```

        if(adjacencyMatrix[i][j] == INT_MAX) {
            cout << setw(8) << "INF";
        } else {
            cout << setw(8) << adjacencyMatrix[i][j];
        }
    }
    cout << endl;
}

}

void displayAdjacencyList() {
    cout << "\n--- Adjacency List Representation ---" << endl;
    for(int i = 0; i < numNodes; i++) {
        cout << "Node " << i;
        if(nodes.count(i)) {
            cout << " (" << nodes[i].nodeName << ")";
        }
        cout << ": ";

        for(auto& edge : adjacencyList[i]) {
            cout << "[" << edge.first << ", " << edge.second <<
"km] ";
        }
        cout << endl;
    }
}

// ===== DIJKSTRA'S ALGORITHM =====

```

```

void dijkstraShortestPath(int start, int end) {
    if(start >= numNodes || end >= numNodes) {
        cout << "Invalid node IDs!" << endl;
        return;
    }

    vector<int> distance(numNodes, INT_MAX);
    vector<int> parent(numNodes, -1);
    vector<bool> visited(numNodes, false);

    distance[start] = 0;

    // Priority queue: pair<distance, node>
    priority_queue<pair<int, int>, vector<pair<int, int>>,
greater<pair<int, int>>> pq;
    pq.push({0, start});

    while(!pq.empty()) {
        int u = pq.top().second;
        pq.pop();

        if(visited[u]) continue;
        visited[u] = true;

        // Check all adjacent nodes
        for(auto& edge : adjacencyList[u]) {
            int v = edge.first;
            int weight = edge.second;

```

```

        if(distance[u] != INT_MAX && distance[u] + weight <
distance[v]) {
            distance[v] = distance[u] + weight;
            parent[v] = u;
            pq.push({distance[v], v});
        }
    }
}

// Display result
cout << "\n--- Dijkstra's Shortest Path ---" << endl;
cout << "From: " << start;
if(nodes.count(start)) cout << " (" << nodes[start].nodeName
<< ")";
cout << "\nTo: " << end;
if(nodes.count(end)) cout << " (" << nodes[end].nodeName <<
")";
cout << endl;

if(distance[end] == INT_MAX) {
    cout << "No path exists!" << endl;
    return;
}

cout << "Shortest Distance: " << distance[end] << " km" <<
endl;

// Reconstruct path
vector<int> path;
int current = end;

```

```

while(current != -1) {
    path.push_back(current);
    current = parent[current];
}

reverse(path.begin(), path.end());

cout << "Path: ";
for(int i = 0; i < path.size(); i++) {
    cout << path[i];
    if(nodes.count(path[i])) {
        cout << " (" << nodes[path[i]].nodeName << ")";
    }
    if(i < path.size() - 1) cout << " -> ";
}
cout << endl;
}

// ===== FLOYD-WARSHALL ALGORITHM =====

void floydWarshallAllPairs() {
    cout << "\n--- Floyd-Warshall All Pairs Shortest Path ---"
<< endl;

    // Create distance matrix
    vector<vector<int>> dist(numNodes, vector<int>(numNodes));

    // Initialize with adjacency matrix
    for(int i = 0; i < numNodes; i++) {

```



```

        for(int j = 0; j < numNodes; j++) {
            dist[i][j] = adjacencyMatrix[i][j];
        }
    }

// Floyd-Warshall algorithm
for(int k = 0; k < numNodes; k++) {
    for(int i = 0; i < numNodes; i++) {
        for(int j = 0; j < numNodes; j++) {
            if(dist[i][k] != INT_MAX && dist[k][j] !=
INT_MAX &&
                dist[i][k] + dist[k][j] < dist[i][j]) {
                dist[i][j] = dist[i][k] + dist[k][j];
            }
        }
    }
}

// Display distance matrix
cout << "\nShortest Distances Between All Pairs:" << endl;
cout << "    ";
for(int i = 0; i < numNodes; i++) {
    cout << setw(6) << i;
}
cout << endl;

for(int i = 0; i < numNodes; i++) {
    cout << setw(5) << i;
    for(int j = 0; j < numNodes; j++) {

```

```

        if(dist[i][j] == INT_MAX) {
            cout << setw(6) << "INF";
        } else {
            cout << setw(6) << dist[i][j];
        }
    }
    cout << endl;
}

// ===== PRIM'S ALGORITHM FOR MST =====

void primMST() {
    cout << "\n--- Prim's Algorithm for Minimum Spanning Tree --
-" << endl;

    vector<bool> inMST(numNodes, false);
    vector<int> key(numNodes, INT_MAX);
    vector<int> parent(numNodes, -1);

    // Start from node 0
    key[0] = 0;

    priority_queue<pair<int, int>, vector<pair<int, int>>,
greater<pair<int, int>>> pq;
    pq.push({0, 0});

    int totalCost = 0;

```

```

while(!pq.empty()) {
    int u = pq.top().second;
    int weight = pq.top().first;
    pq.pop();

    if(inMST[u]) continue;

    inMST[u] = true;
    totalCost += weight;

    for(auto& edge : adjacencyList[u]) {
        int v = edge.first;
        int w = edge.second;

        if(!inMST[v] && w < key[v]) {
            key[v] = w;
            parent[v] = u;
            pq.push({w, v});
        }
    }
}

cout << "\nMinimum Spanning Tree Edges (Prim's):" << endl;
for(int i = 1; i < numNodes; i++) {
    if(parent[i] != -1) {
        cout << "Road: " << parent[i];
        if(nodes.count(parent[i])) cout << " (" <<
nodes[parent[i]].nodeName << ")";
        cout << " - " << i;
    }
}

```

```

        if(nodes.count(i)) cout << " (" << nodes[i].nodeName
<< ")";

        cout << " | Cost: " << key[i] << " km" << endl;
    }
}

cout << "Total Cost of MST: " << totalCost << " km" << endl;
}

```

// ===== KRUSKAL'S ALGORITHM FOR MST =====

```

struct Edge {
    int src, dest, weight;
    bool operator<(const Edge& other) const {
        return weight < other.weight;
    }
};

```

```

int findParent(vector<int>& parent, int i) {
    if(parent[i] != i) {
        parent[i] = findParent(parent, parent[i]);
    }
    return parent[i];
}

```

```

void unionSets(vector<int>& parent, vector<int>& rank, int x,
int y) {
    int xroot = findParent(parent, x);
    int yroot = findParent(parent, y);

```

```

        if(rank[xroot] < rank[yroot]) {
            parent[xroot] = yroot;
        } else if(rank[xroot] > rank[yroot]) {
            parent[yroot] = xroot;
        } else {
            parent[yroot] = xroot;
            rank[xroot]++;
        }
    }
}

void kruskalMST() {
    cout << "\n--- Kruskal's Algorithm for Minimum Spanning Tree
---" << endl;

    vector<Edge> edges;

    // Collect all edges
    for(int i = 0; i < numNodes; i++) {
        for(auto& edge : adjacencyList[i]) {
            if(i < edge.first) { // Avoid duplicates in
undirected graph
                edges.push_back({i, edge.first, edge.second});
            }
        }
    }

    // Sort edges by weight
    sort(edges.begin(), edges.end());

```

```

vector<int> parent(numNodes);
vector<int> rank(numNodes, 0);
for(int i = 0; i < numNodes; i++) {
    parent[i] = i;
}

cout << "\nMinimum Spanning Tree Edges (Kruskal's):" <<
endl;

int totalCost = 0;
int edgesAdded = 0;

for(const Edge& e : edges) {
    int x = findParent(parent, e.src);
    int y = findParent(parent, e.dest);

    if(x != y) {
        cout << "Road: " << e.src;
        if(nodes.count(e.src)) cout << " (" <<
nodes[e.src].nodeName << ")";
        cout << " - " << e.dest;
        if(nodes.count(e.dest)) cout << " (" <<
nodes[e.dest].nodeName << ")";
        cout << " | Cost: " << e.weight << " km" << endl;

        totalCost += e.weight;
        unionSets(parent, rank, x, y);
        edgesAdded++;

        if(edgesAdded == numNodes - 1) break;
    }
}

```

```

    }

    cout << "Total Cost of MST: " << totalCost << " km" << endl;
}

// ===== TOPOLOGICAL SORT =====

void topologicalSort() {
    cout << "\n--- Topological Sort for Construction Priority --
-" << endl;

    // Calculate in-degree for each node
    vector<int> inDegree(numNodes, 0);
    for(int i = 0; i < numNodes; i++) {
        for(auto& edge : adjacencyList[i]) {
            inDegree[edge.first]++;
        }
    }

    queue<int> q;
    for(int i = 0; i < numNodes; i++) {
        if(inDegree[i] == 0) {
            q.push(i);
        }
    }

    vector<int> topOrder;

    while(!q.empty()) {

```

```

    int u = q.front();
    q.pop();
    topOrder.push_back(u);

    for(auto& edge : adjacencyList[u]) {
        inDegree[edge.first]--;
        if(inDegree[edge.first] == 0) {
            q.push(edge.first);
        }
    }
}

if(topOrder.size() != numNodes) {
    cout << "Graph contains a cycle! Topological sort not
possible." << endl;
    return;
}

cout << "Construction Priority Order:" << endl;
for(int i = 0; i < topOrder.size(); i++) {
    cout << "Priority " << (i+1) << ": Node " <<
topOrder[i];
    if(nodes.count(topOrder[i])) {
        cout << " (" << nodes[topOrder[i]].nodeName << ")";
    }
    cout << endl;
}
}
};

```



```
// ===== BINARY SEARCH TREE FOR ZONES  
=====
```

```
class ZoneNode {  
public:  
    int zoneID;  
    string zoneName;  
    string zoneType;  
    ZoneNode* left;  
    ZoneNode* right;  
  
    ZoneNode(int id, string name, string type) {  
        zoneID = id;  
        zoneName = name;  
        zoneType = type;  
        left = nullptr;  
        right = nullptr;  
    }  
};  
  
class ZoneBST {  
private:  
    ZoneNode* root;  
  
    ZoneNode* insertHelper(ZoneNode* node, int id, string name,  
string type) {  
        if(node == nullptr) {  
            return new ZoneNode(id, name, type);  
        }  
    }  
};
```

```

    }

    if(id < node->zoneID) {
        node->left = insertHelper(node->left, id, name, type);
    } else if(id > node->zoneID) {
        node->right = insertHelper(node->right, id, name, type);
    }

    return node;
}

void inorderHelper(ZoneNode* node) {
    if(node != nullptr) {
        inorderHelper(node->left);
        cout << "Zone " << node->zoneID << ": " << node-
>zoneName
            << " [" << node->zoneType << "]" << endl;
        inorderHelper(node->right);
    }
}

ZoneNode* searchHelper(ZoneNode* node, int id) {
    if(node == nullptr || node->zoneID == id) {
        return node;
    }

    if(id < node->zoneID) {
        return searchHelper(node->left, id);
    }
}

```

```

        return searchHelper(node->right, id);
    }

public:
    ZoneBST() {
        root = nullptr;
    }

    void insertZone(int id, string name, string type) {
        root = insertHelper(root, id, name, type);
    }

    void displayZones() {
        cout << "\n--- City Zones (BST Inorder Traversal) ---" <<
endl;
        inorderHelper(root);
    }

    ZoneNode* searchZone(int id) {
        return searchHelper(root, id);
    }
};

// ===== AVL TREE FOR ZONES =====

class AVLZoneNode {
public:
    int zoneID;

```

```

string zoneName;
string zoneType;
AVLZoneNode* left;
AVLZoneNode* right;
int height;

AVLZoneNode(int id, string name, string type) {
    zoneID = id;
    zoneName = name;
    zoneType = type;
    left = nullptr;
    right = nullptr;
    height = 1;
}
};

class ZoneAVL {
private:
    AVLZoneNode* root;

    int getHeight(AVLZoneNode* node) {
        if(node == nullptr) return 0;
        return node->height;
    }

    int getBalance(AVLZoneNode* node) {
        if(node == nullptr) return 0;
        return getHeight(node->left) - getHeight(node->right);
    }
}

```

```

AVLZoneNode* rotateRight(AVLZoneNode* y) {
    AVLZoneNode* x = y->left;
    AVLZoneNode* T2 = x->right;

    x->right = y;
    y->left = T2;

    y->height = max(getHeight(y->left), getHeight(y->right)) +
1;
    x->height = max(getHeight(x->left), getHeight(x->right)) +
1;

    return x;
}

```

```

AVLZoneNode* rotateLeft(AVLZoneNode* x) {
    AVLZoneNode* y = x->right;
    AVLZoneNode* T2 = y->left;

    y->left = x;
    x->right = T2;

    x->height = max(getHeight(x->left), getHeight(x->right)) +
1;
    y->height = max(getHeight(y->left), getHeight(y->right)) +
1;

    return y;
}

```

```

    AVLZoneNode* insertHelper(AVLZoneNode* node, int id, string
name, string type) {
    // Standard BST insertion
    if(node == nullptr) {
        return new AVLZoneNode(id, name, type);
    }

    if(id < node->zoneID) {
        node->left = insertHelper(node->left, id, name, type);
    } else if(id > node->zoneID) {
        node->right = insertHelper(node->right, id, name, type);
    } else {
        return node; // Duplicate IDs not allowed
    }

    // Update height
    node->height = 1 + max(getHeight(node->left),
getHeight(node->right));

    // Get balance factor
    int balance = getBalance(node);

    // Left Left Case
    if(balance > 1 && id < node->left->zoneID) {
        return rotateRight(node);
    }

    // Right Right Case

```

```

        if(balance < -1 && id > node->right->zoneID) {
            return rotateLeft(node);
        }

        // Left Right Case
        if(balance > 1 && id > node->left->zoneID) {
            node->left = rotateLeft(node->left);
            return rotateRight(node);
        }

        // Right Left Case
        if(balance < -1 && id < node->right->zoneID) {
            node->right = rotateRight(node->right);
            return rotateLeft(node);
        }

        return node;
    }

    void inorderHelper(AVLZoneNode* node) {
        if(node != nullptr) {
            inorderHelper(node->left);
            cout << "Zone " << node->zoneID << ": " << node-
>zoneName
                << " [" << node->zoneType << "]" << endl;
            inorderHelper(node->right);
        }
    }
}

```

```

public:
    ZoneAVL() {
        root = nullptr;
    }

    void insertZone(int id, string name, string type) {
        root = insertHelper(root, id, name, type);
    }

    void displayZones() {
        cout << "\n--- City Zones (AVL Tree Balanced) ---" << endl;
        inorderHelper(root);
    }
};

```

```

class SmartCityNavigationSystem {
private:
    RoadNetwork roadNetwork;
    ZoneBST zoneBST;
    ZoneAVL zoneAVL;
    bool networkInitialized;

public:
    SmartCityNavigationSystem() {
        networkInitialized = false;
    }

    void initializeSystem() {
        int numNodes;

```



```

cout << "\n--- Initialize Road Network ---" << endl;
cout << "Enter number of intersections/nodes: ";
cin >> numNodes;

roadNetwork.initializeNetwork(numNodes);

// Add node details
cin.ignore();
for(int i = 0; i < numNodes; i++) {
    string name, zone;
    cout << "\nNode " << i << ":" << endl;
    cout << "  Name: ";
    getline(cin, name);
    cout << "  Zone Type
(Residential/Commercial/Industrial): ";
    getline(cin, zone);

    RoadNode node(i, name, zone);
    roadNetwork.addNode(node);

    // Add to trees
    zoneBST.insertZone(i, name, zone);
    zoneAVL.insertZone(i, name, zone);
}

networkInitialized = true;
cout << "\nRoad network initialized successfully!" << endl;
}

```

```

void addRoads() {
    if(!networkInitialized) {
        cout << "Please initialize the network first!" << endl;
        return;
    }

    int numRoads;
    cout << "\n--- Add Roads ---" << endl;
    cout << "Enter number of roads to add: ";
    cin >> numRoads;

    cout << "\n1. Bidirectional Roads" << endl;
    cout << "2. Unidirectional Roads (for Topological Sort)" <<
endl;
    cout << "Choose road type: ";
    int choice;
    cin >> choice;

    for(int i = 0; i < numRoads; i++) {
        int from, to, distance;
        cout << "\nRoad " << (i+1) << ":" << endl;
        cout << "  From Node ID: ";
        cin >> from;
        cout << "  To Node ID: ";
        cin >> to;
        cout << "  Distance (km): ";
        cin >> distance;

        if(choice == 1) {

```

```

        roadNetwork.addRoad(from, to, distance);
    } else {
        roadNetwork.addDirectedRoad(from, to, distance);
    }
}

cout << "\nRoads added successfully!" << endl;
}

void displayNetwork() {
    if(!networkInitialized) {
        cout << "Please initialize the network first!" << endl;
        return;
    }

    cout << "\n--- Display Options ---" << endl;
    cout << "1. Adjacency Matrix" << endl;
    cout << "2. Adjacency List" << endl;
    cout << "3. City Zones (BST)" << endl;
    cout << "4. City Zones (AVL)" << endl;
    cout << "Enter choice: ";

    int choice;
    cin >> choice;

    switch(choice) {
        case 1:
            roadNetwork.displayAdjacencyMatrix();
            break;

```

```

        case 2:
            roadNetwork.displayAdjacencyList();
            break;
        case 3:
            zoneBST.displayZones();
            break;
        case 4:
            zoneAVL.displayZones();
            break;
        default:
            cout << "Invalid choice!" << endl;
    }
}

void findShortestPath() {
    if(!networkInitialized) {
        cout << "Please initialize the network first!" << endl;
        return;
    }

    cout << "\n--- Shortest Path Algorithms ---" << endl;
    cout << "1. Dijkstra's Algorithm (Single Source)" << endl;
    cout << "2. Floyd-Warshall (All Pairs)" << endl;
    cout << "Enter choice: ";

    int choice;
    cin >> choice;

    if(choice == 1) {

```

```

        int start, end;

        cout << "\nEnter start node ID: ";
        cin >> start;
        cout << "Enter end node ID: ";
        cin >> end;

        roadNetwork.dijkstraShortestPath(start, end);
    } else if(choice == 2) {
        roadNetwork.floydWarshallAllPairs();
    } else {
        cout << "Invalid choice!" << endl;
    }
}

void planInfrastructure() {
    if(!networkInitialized) {
        cout << "Please initialize the network first!" << endl;
        return;
    }

    cout << "\n--- Infrastructure Planning ---" << endl;
    cout << "1. Minimum Spanning Tree (Prim's Algorithm)" <<
endl;
    cout << "2. Minimum Spanning Tree (Kruskal's Algorithm)" <<
endl;
    cout << "3. Construction Priority (Topological Sort)" <<
endl;
    cout << "Enter choice: ";

    int choice;

```

```

    cin >> choice;

    switch(choice) {
        case 1:
            roadNetwork.primMST();
            break;
        case 2:
            roadNetwork.kruskalMST();
            break;
        case 3:
            roadNetwork.topologicalSort();
            break;
        default:
            cout << "Invalid choice!" << endl;
    }
}

void loadSampleData() {
    cout << "\n--- Loading Sample Smart City Data ---" << endl;

    // Initialize with 7 nodes
    roadNetwork.initializeNetwork(7);

    // Add nodes (intersections)
    roadNetwork.addNode(RoadNode(0, "Central Station",
"Commercial"));
    roadNetwork.addNode(RoadNode(1, "Tech Park", "Industrial"));
    roadNetwork.addNode(RoadNode(2, "City Mall", "Commercial"));

```

```
roadNetwork.addNode(RoadNode(3, "Residential Area",  
"Residential"));  
roadNetwork.addNode(RoadNode(4, "Hospital", "Healthcare"));  
roadNetwork.addNode(RoadNode(5, "University",  
"Educational"));  
roadNetwork.addNode(RoadNode(6, "Airport",  
"Transportation"));
```

```
// Add to BST and AVL trees
```

```
zoneBST.insertZone(0, "Central Station", "Commercial");  
zoneBST.insertZone(1, "Tech Park", "Industrial");  
zoneBST.insertZone(2, "City Mall", "Commercial");  
zoneBST.insertZone(3, "Residential Area", "Residential");  
zoneBST.insertZone(4, "Hospital", "Healthcare");  
zoneBST.insertZone(5, "University", "Educational");  
zoneBST.insertZone(6, "Airport", "Transportation");
```

```
zoneAVL.insertZone(0, "Central Station", "Commercial");  
zoneAVL.insertZone(1, "Tech Park", "Industrial");  
zoneAVL.insertZone(2, "City Mall", "Commercial");  
zoneAVL.insertZone(3, "Residential Area", "Residential");  
zoneAVL.insertZone(4, "Hospital", "Healthcare");  
zoneAVL.insertZone(5, "University", "Educational");  
zoneAVL.insertZone(6, "Airport", "Transportation");
```

```
// Add roads (edges with distances in km)
```

```
roadNetwork.addRoad(0, 1, 5);    // Central Station - Tech  
Park  
roadNetwork.addRoad(0, 2, 3);    // Central Station - City  
Mall
```

```

        roadNetwork.addRoad(1, 2, 4);    // Tech Park - City Mall
        roadNetwork.addRoad(1, 3, 6);    // Tech Park - Residential
Area
        roadNetwork.addRoad(2, 3, 7);    // City Mall - Residential
Area
        roadNetwork.addRoad(2, 4, 8);    // City Mall - Hospital
        roadNetwork.addRoad(3, 4, 2);    // Residential Area -
Hospital
        roadNetwork.addRoad(3, 5, 5);    // Residential Area -
University
        roadNetwork.addRoad(4, 5, 3);    // Hospital - University
        roadNetwork.addRoad(4, 6, 10);   // Hospital - Airport
        roadNetwork.addRoad(5, 6, 7);    // University - Airport


        networkInitialized = true;


        cout << "Sample data loaded successfully!" << endl;
        cout << "7 intersections and 11 roads added to the network."
<< endl;
    }


void analyzeNetwork() {
    if(!networkInitialized) {
        cout << "Please initialize the network first!" << endl;
        return;
    }


    cout << "\n===== NETWORK ANALYSIS REPORT =====" << endl;


    // Display all representations

```



```

    cout << "\n1. GRAPH REPRESENTATIONS:" << endl;
    roadNetwork.displayAdjacencyMatrix();
    roadNetwork.displayAdjacencyList();

    // Display zones
    cout << "\n2. CITY ZONE INDEXING:" << endl;
    zoneBST.displayZones();

    // Show shortest paths from central node (0)
    cout << "\n3. SHORTEST PATHS FROM CENTRAL STATION:" << endl;
    for(int i = 1; i < 7; i++) {
        roadNetwork.dijkstraShortestPath(0, i);
        cout << endl;
    }

    // Show MST
    cout << "\n4. MINIMUM SPANNING TREE ANALYSIS:" << endl;
    roadNetwork.primMST();
    cout << endl;
    roadNetwork.kruskalMST();

    cout << "\n===== END OF ANALYSIS REPORT =====" << endl;
}

void compareAlgorithms() {
    if(!networkInitialized) {
        cout << "Please initialize the network first!" << endl;
        return;
    }
}

```

```

cout << "\n--- Algorithm Comparison ---" << endl;

cout << "\n1. SHORTEST PATH ALGORITHMS:" << endl;
cout << "    Dijkstra's Algorithm:" << endl;
cout << "    - Time Complexity:  $O((V + E) \log V)$  with
priority queue" << endl;
cout << "    - Best for: Single source shortest path" <<
endl;
cout << "    - Use case: Navigation from current location" <<
endl;

cout << "\n    Floyd-Warshall Algorithm:" << endl;
cout << "    - Time Complexity:  $O(V^3)$ " << endl;
cout << "    - Best for: All pairs shortest paths" << endl;
cout << "    - Use case: Precomputing all routes" << endl;

cout << "\n2. MINIMUM SPANNING TREE ALGORITHMS:" << endl;
cout << "    Prim's Algorithm:" << endl;
cout << "    - Time Complexity:  $O((V + E) \log V)$ " << endl;
cout << "    - Best for: Dense graphs" << endl;

cout << "\n    Kruskal's Algorithm:" << endl;
cout << "    - Time Complexity:  $O(E \log E)$ " << endl;
cout << "    - Best for: Sparse graphs" << endl;

cout << "\n3. TREE STRUCTURES:" << endl;
cout << "    Binary Search Tree:" << endl;
cout << "    - Average:  $O(\log n)$ , Worst:  $O(n)$ " << endl;

```

```

        cout << "\n    AVL Tree:" << endl;
        cout << "    - Guaranteed:  $O(\log n)$  for all operations" <<
endl;
    }
};

int main() {
    SmartCityNavigationSystem system;
    int choice;

    cout << "=====" << endl;
    cout << "    SMART CITY ROAD NAVIGATION SYSTEM    " << endl;
    cout << "=====" << endl;

    while(true) {
        cout << "\n--- Main Menu ---" << endl;
        cout << "1.  Initialize Road Network" << endl;
        cout << "2.  Add Roads" << endl;
        cout << "3.  Display Network" << endl;
        cout << "4.  Find Shortest Path" << endl;
        cout << "5.  Plan Infrastructure (MST/Topological Sort)" <<
endl;
        cout << "6.  Analyze Network (Complete Analysis)" << endl;
        cout << "7.  Compare Algorithms" << endl;
        cout << "8.  Load Sample Data" << endl;
        cout << "9.  Exit" << endl;
        cout << "Enter your choice: ";
        cin >> choice;
    }
}

```

```
switch(choice) {
    case 1:
        system.initializeSystem();
        break;
    case 2:
        system.addRoads();
        break;
    case 3:
        system.displayNetwork();
        break;
    case 4:
        system.findShortestPath();
        break;
    case 5:
        system.planInfrastructure();
        break;
    case 6:
        system.analyzeNetwork();
        break;
    case 7:
        system.compareAlgorithms();
        break;
    case 8:
        system.loadSampleData();
        break;
    case 9:
        cout << "\nThank you for using Smart City Navigation
System!" << endl;
        cout << "Goodbye!" << endl;
```

```
        return 0;
    default:
        cout << "Invalid choice! Please try again." << endl;
    }
}

return 0;
}
```

OUTPUT:

```
=====
SMART CITY ROAD NAVIGATION SYSTEM
=====
```

```
--- Main Menu ---
```

1. Initialize Road Network
2. Add Roads
3. Display Network
4. Find Shortest Path
5. Plan Infrastructure (MST/Topological Sort)
6. Analyze Network (Complete Analysis)
7. Compare Algorithms
8. Load Sample Data
9. Exit

```
Enter your choice: 1
```

```
--- Initialize Road Network ---
```

```
Enter number of intersections/nodes: 2
```

```
Node 0:
```

```
  Name: a
```

```
  Zone Type (Residential/Commercial/Industrial): ab
```

```
Node 1:
```

```
  Name: c
```

```
  Zone Type (Residential/Commercial/Industrial): cd
```

```
Road network initialized successfully!
```

```
--- Main Menu ---
```