

QQC Waiver Request

Vendor Input		Vendor Input	
Program:	Memphis-Project	Waiver Request Date:	-
Vendor:	Dpamstech	Planned Shipment Date:	2026-03-19
APN:	817-11238	Judgment :	PASS
Revision:	MCO Rev.11 / MSoP Rev.1 / PGM Rev.01	OK Quantity:	400,320
Build:	MP	Waived Quantity:	0
Config:	-	Shipment Quantity:	400,320

[illegible]

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	-----

Table 1. Summary of the data sets used in the study			
Dataset	Number of samples	Number of features	Number of classes
Dataset 1	1000	100	10
Dataset 2	2000	200	20
Dataset 3	3000	300	30
Dataset 4	4000	400	40
Dataset 5	5000	500	50
Dataset 6	6000	600	60
Dataset 7	7000	700	70
Dataset 8	8000	800	80
Dataset 9	9000	900	90
Dataset 10	10000	1000	100

FAI Data Sheet Enclosures MD

FA#	DRAWING SPECIFICATIONS				INSPECTION RESULTS										INSPECTION ANALYSIS				Supplier Comment
	Description	Nominal	+TOL	TOL	Inspection Method	Sample Number				Deviation from Nominal	3	Mean	% Tolerance	Alert/Reject		Line			
						E#1	E#2	E#3	E#4					1	2		3		
2-1	Straightness	0.000	0.008	0.000	CMM	0.004	0.004	0.004	0.003	0.004	0.004	0.003	48%				OK		
2-2	Straightness	0.000	0.008	0.000	CMM	0.003	0.003	0.004	0.003	0.003	0.004	0.003	51%				OK		
2-3	Straightness	0.000	0.008	0.000	CMM	0.003	0.003	0.005	0.003	0.003	0.005	0.004	60%				OK		
2-4	Straightness	0.000	0.008	0.000	CMM	0.002	0.003	0.004	0.002	0.003	0.004	0.003	49%				OK		
3	Flatness	0.000	0.000	0.000	CMM	0.000	0.000	0.000	0.000	0.000	0.000	0.000	23%				OK		
4-a	Distance	0.500	0.015	-0.010	CMM	0.506	0.505	0.499	0.008	0.005	-0.001	0.503	39%	12%			OK		
4-b	Distance	0.500	0.015	-0.010	CMM	0.505	0.502	0.491	0.005	0.002	-0.009	0.499	33%	89%			Alert		
4-c	Distance	0.500	0.015	-0.010	CMM	0.505	0.507	0.499	0.005	0.007	-0.001	0.503	44%	14%			OK		
4-d	Distance	0.720	0.020	-0.020	CMM	0.728	0.720	0.725	0.008	0.010	0.005	0.724	50%				OK		
4-e	Distance	0.720	0.020	-0.020	CMM	0.728	0.719	0.725	0.005	0.005	-0.001	0.005	0.723	27%	5%			OK	
7	Distance	0.500	0.018	-0.015	CMM	0.492	0.497	0.502	-0.008	-0.003	0.002	0.497	9%	52%			OK		
8	Distance	0.500	0.018	-0.015	CMM	0.495	0.492	0.508	-0.005	-0.008	0.006	0.498	43%	58%			OK		
9-1	Distance	3.100	0.030	-0.035	CMM	3.093	3.098	3.099	-0.007	-0.002	-0.002	3.093	2%	33%			OK		
9-2	Distance	3.100	0.030	-0.035	CMM	3.101	3.105	3.100	0.001	0.006	0.000	3.102	18%	0%			OK		
9-3	Distance	3.100	0.030	-0.035	CMM	3.103	3.091	3.106	0.002	-0.009	0.006	3.100	19%	27%			OK		
9-4	Distance	3.100	0.030	-0.035	CMM	3.098	3.093	3.099	-0.002	-0.007	-0.001	3.097	0%	20%			OK		
9-5	Distance	3.100	0.030	-0.035	CMM	3.095	3.091	3.093	-0.010	-0.009	-0.007	3.090	0%	41%			OK		
9-6	Distance	3.100	0.030	-0.035	CMM	3.102	3.101	3.104	0.002	0.001	0.003	3.102	12%	0%			OK		
9-7	Distance	3.100	0.030	-0.035	CMM	3.093	3.107	3.084	-0.007	0.007	-0.016	3.095	24%	46%			OK		
9-8	Distance	3.100	0.030	-0.035	CMM	3.100	3.087	3.102	0.000	-0.013	0.002	3.096	5%	37%			OK		
11	Perpendicular	0.000	0.025	-0.000	CMM	0.001	0.012	0.016	0.001	0.012	0.016	0.010	46%				OK		
12-1	Distance	0.520	0.030	-0.030	CMM	0.522	0.520	0.523	0.006	0.002	0.003	0.524	21%	0%			OK		
12-2	Distance	0.520	0.030	-0.030	CMM	0.517	0.517	0.519	-0.003	-0.003	-0.001	0.518	0%	10%			OK		
12-3	Distance	0.520	0.030	-0.030	CMM	0.526	0.526	0.533	0.006	0.006	0.013	0.528	43%	0%			OK		
12-4	Distance	0.520	0.030	-0.030	CMM	0.529	0.520	0.535	0.009	0.000	0.015	0.528	51%	0%			OK		
13-1	Distance	3.230	0.030	-0.030	CMM	3.227	3.213	3.217	-0.003	-0.017	-0.013	3.219	0%	49%			OK		
13-2	Distance	3.230	0.030	-0.035	CMM	3.224	3.214	3.216	-0.006	-0.016	-0.014	3.218	0%	46%			OK		
14-1	Distance	14.264	0.030	-0.030	CMM	14.272	14.267	14.271	0.008	0.003	0.007	14.270	26%	0%			OK		
14-2	Distance	14.264	0.030	-0.030	CMM	14.277	14.273	14.283	0.013	0.009	0.019	14.278	63%	0%			OK		
15-1	Distance	1.840	0.025	-0.020	CMM	1.837	1.837	1.851	-0.003	-0.003	0.011	1.842	46%	17%			OK		
15-2	Distance	1.840	0.025	-0.020	CMM	1.838	1.849	1.851	-0.004	0.009	0.011	1.845	44%	18%			OK		
15-3	Distance	1.840	0.025	-0.020	CMM	1.847	1.838	1.840	0.007	-0.002	0.000	1.842	27%	8%			OK		
15-4	Distance	1.840	0.025	-0.020	CMM	1.846	1.840	1.840	0.006	0.000	0.000	1.842	24%	0%			OK		
20	Distance	15.454	0.030	-0.030	CMM	15.447	15.451	15.461	-0.007	-0.003	0.007	15.453	24%	22%			OK		
21	Distance	0.900	0.020	-0.020	CMM	0.899	0.900	0.894	-0.001	0.000	-0.006	0.895	0%	3%			OK		
22	Distance	15.448	0.030	-0.030	CMM	15.448	15.465	15.450	0.000	0.007	0.002	15.451	36%	0%			OK		
23	Distance	13.094	0.030	-0.020	CMM	13.101	13.093	13.112	0.007	-0.001	0.018	13.102	61%	6%			OK		
24	Distance	13.324	0.025	-0.040	CMM	13.325	13.324	13.330	0.001	0.000	0.006	13.326	24%	0%			OK		
25-1	Position	0.530	0.025	-0.025	CMM	0.534	0.527	0.525	0.004	-0.003	-0.005	0.529	15%	26%			OK		
25-2	Position	0.530	0.025	-0.025	CMM	0.533	0.526	0.524	0.002	-0.005	-0.007	0.527	10%	26%			OK		
26-1	Distance	0.970	0.030	-0.020	CMM	0.980	0.971	0.973	0.010	0.001	0.003	0.974	32%	0%			OK		
26-2	Distance	0.970	0.030	-0.020	CMM	0.978	0.968	0.972	0.008	-0.002	0.002	0.973	27%	8%			OK		
27	Distance	15.225	0.035	-0.020	CMM	15.245	15.233	15.248	0.017	0.005	0.020	15.242	57%	0%			OK		
28	Distance	0.260	0.020	-0.020	CMM	0.260	0.262	0.262	0.000	0.002	0.002	0.262	25%	0%			OK		
29	Distance	0.520	0.030	-0.020	CMM	0.521	0.522	0.530	0.001	0.002	0.000	0.521	8%	0%			OK		
31	Distance	2.068	0.030	-0.030	CMM	2.080	2.070	2.075	0.012	0.002	0.007	2.075	59%	0%			OK		
33	Distance	1.137	0.025	-0.035	CMM	1.116	1.128	1.115	-0.021	-0.009	-0.022	1.119	0%	64%			OK		
34	Distance	13.574	0.030	-0.030	CMM	13.579	13.570	13.584	0.005	-0.004	0.010	13.578	23%	13%			OK		
35-1	Distance	0.090	0.010	-0.030	CMM	0.092	0.083	0.074	-0.009	-0.007	-0.016	0.085	0%	54%			OK		
35-2	Distance	0.090	0.010	-0.030	CMM	0.079	0.085	0.074	-0.011	-0.005	-0.016	0.079	0%	52%			OK		
36	Distance	11.277	0.030	-0.030	CMM	11.278	11.277	11.286	0.001	0.000	0.000	11.280	29%	0%			OK		
37-1	Distance	0.300	0.030	-0.030	CMM	0.308	0.304	0.312	0.008	0.004	0.012	0.308	39%	0%			OK		
37-2	Distance	0.300	0.030	-0.030	CMM	0.309	0.296	0.307	0.001	-0.005	0.007	0.302	40%	0%			OK		
38-1	Distance	0.300	0.030	-0.030	CMM	0.313	0.294	0.294	0.013	-0.006	-0.006	0.301	44%	20%			OK		
38-2	Distance	0.300	0.030	-0.030	CMM	0.313	0.293	0.289	0.013	-0.007	-0.011	0.299	44%	35%			OK		
39	Distance	14.450	0.030	-0.030	CMM	14.447	14.462	14.474	-0.003	0.002	-0.016	14.464	7%	52%			OK		
40	Distance	2.648	0.030	-0.030	CMM	2.648	2.648	2.648	0.000	0.000	0.000	2.648	44%	0%			OK		
41	Distance	2.648	0.030	-0.030	CMM	2.668	2.661	2.664	0.019	0.013	0.016	2.664	60%	0%			OK		
45	Distance	3.229	0.035	-0.035	CMM	3.227	3.230	3.222	-0.002	0.001	-0.007	3.228	2%	19%			OK		
46	Distance	12.572	0.040	-0.020	CMM	12.562	12.569	12.560	-0.010	-0.003	-0.012	12.564	0%	58%			OK		
47	Distance	16.858	0.025	-0.025	CMM	16.863	16.851	16.860	0.005	-0.007	0.002	16.858	21%	27%			OK		
49	Distance	0.071	0.020	-0.020	CMM	0.072	0.068	0.077	0.004	0.007	0.004	0.071	39%	0%			OK		
51	Distance	0.280	0.020	-0.020	CMM	0.282	0.291	0.289	0.012	0.011	0.009	0.290	61%	0%			OK		
52	Distance	2.440	0.030	-0.020	CMM	2.435	2.428	2.426	-0.005	-0.012	-0.014	2.430	0%	64%			Alert		
53	Distance	1.280	0.010	-0.040	CMM	1.272	1.273	1.275	-0.008	-0.008	-0.005	1.273	0%	20%			OK		
54-1	Position	0.000	0.075	0.000	CMM	0.007	0.007	0.001	0.017	0.007	0.027	0.022	96%				OK		
54-2	Position	0.000	0.075	0.000	CMM	0.020	0.041	0.040	0.020	0.041	0.044	0.035	98%				OK		
55-1	Position	0.000	0.085	0.000	CMM	0.027	0.038	0.028	0.027	0.038	0.028	0.031	45%				OK		
55-2	Position	0.000	0.085	0.000	CMM	0.052	0.055	0.052	0.052	0.055	0.052	0.056	73%				Alert		
56-1	Distance	0.648	0.030	-0.020	CMM	0.644	0.649	0.638	-0.005	0.000	-0.011	0.644	1%	55%			OK		
56-2	Distance	0.648	0.030	-0.020	CMM	0.650	0.644	0.644	0.000	-0.006	-0.005	0.644	37%	0%			OK		
57	Distance	16.768	0.020	-0.040	CMM	16.795	16.774	16.777	0.007										

[illegible][illegible]

Cosmetic Waiver List

[illegible]

Dimensional Waiver List

[illegible]

Functional Waiver List

[illegible]

Reliability Waiver List

[illegible]

Revision	Date	Author	Comments
1	2018-08-03	Tim Burks	Initial Release