

QQC Waiver Request

Vendor Input		Vendor Input	
Program:	Memphis-Project	Waiver Request Date:	-
Vendor:	Dpamstech	Planned Shipment Date:	2026-03-29
APN:	817-11233	Judgment :	PASS
Revision:	MCO Rev.7 / MSoP Rev.1 /PGM Rev.1	OK Quantity:	720
Build:	MP	Waived Quantity:	-
Config:	-	Shipment Quantity:	720

[illegible]

APN	Shipping Date	Build	Inner package	Shipping Lot No	Total Q'TY	Cavity	Shipping Qty	Unit
817-11233	2026-03-29	MP	3HUR00019A/720/DP252242080F3BXM	20250603-25-B	10800	3	720	PCS

FAI Data Sheet Enclosures MD

DRAWING SPECIFICATIONS						INSPECTION RESULTS						INSPECTION ANALYSIS					Supplier Comment
FAI#	Description	Nominal	+TOL	TOL	Inspection Method	Sample Number			Deviation from Nominal			Mean	% Tolerance	Alert/Reject			
						J#2	H#3	G#3	1	2	3		Upper	Lower	High	Low	
4-1	Height	0.500	0.010	-0.010	OMM	0.501	0.500	0.503	0.001	0.000	0.003	0.501	29%	0%		OK	
4-2	Height	0.500	0.010	-0.010	OMM	0.502	0.498	0.500	0.002	-0.002	0.000	0.500	21%	21%		OK	
4-3	Height	0.500	0.010	-0.010	OMM	0.503	0.500	0.497	0.003	0.000	-0.003	0.500	31%	30%		OK	
6-1	Height	0.500	0.010	-0.010	OMM	0.503	0.501	0.499	0.003	0.001	-0.001	0.501	25%	11%		OK	
6-2	Height	0.500	0.010	-0.010	OMM	0.504	0.503	0.501	0.004	0.003	0.001	0.503	36%	0%		OK	
6-3	Height	0.500	0.010	-0.010	OMM	0.505	0.505	0.497	0.005	0.005	-0.003	0.502	53%	33%		OK	
8	Parallelism	0.000	0.030	0.000	OMM	0.002	0.002	0.003	0.002	0.002	0.003	0.002	9%			OK	
9	Perpendicularity	0.000	0.030	0.000	OMM	0.011	0.003	0.012	0.011	0.003	0.012	0.009	40%			OK	
10-1	Distance	1.090	0.015	-0.010	OMM	1.093	1.094	1.096	0.003	0.004	0.006	1.094	38%	0%		OK	
10-2	Distance	1.090	0.015	-0.010	OMM	1.089	1.097	1.089	-0.001	0.007	-0.001	1.092	45%	12%		OK	
10-3	Distance	1.090	0.015	-0.010	OMM	1.084	1.093	1.090	-0.006	0.003	0.000	1.089	18%	59%		OK	
23	Distance	1.852	0.020	-0.020	OMM	1.861	1.855	1.853	0.008	0.003	0.001	1.856	42%	0%		OK	
24	Distance	0.214	0.020	-0.020	OMM	0.218	0.212	0.213	0.004	-0.002	-0.001	0.214	20%	10%		OK	
25A-1	Distance	1.290	0.030	-0.030	OMM	1.289	1.291	1.286	-0.001	0.001	-0.004	1.289	2%	12%		OK	
25A-2	Distance	1.290	0.030	-0.030	OMM	1.282	1.276	1.271	-0.008	-0.014	-0.019	1.276	0%	64%		OK	
25A-3	Distance	1.290	0.030	-0.030	OMM	1.301	1.287	1.310	0.011	-0.003	0.020	1.299	67%	9%	Alert	OK	
26	Distance	15.262	0.030	-0.030	OMM	15.272	15.272	15.272	0.010	0.010	0.010	15.272	34%	0%		OK	
27	Distance	12.839	0.030	-0.030	OMM	12.828	12.833	12.820	-0.011	-0.006	-0.019	12.827	0%	62%		OK	
28	Distance	2.627	0.030	-0.030	OMM	2.642	2.635	2.629	0.015	0.008	0.002	2.636	51%	0%		OK	
30	Distance	12.482	0.030	-0.030	OMM	12.477	12.480	12.486	-0.005	-0.002	0.004	12.481	13%	17%		OK	
31	Distance	11.089	0.030	-0.030	OMM	11.073	11.094	11.086	-0.016	0.005	-0.003	11.085	17%	52%		OK	
32	Distance	2.092	0.030	-0.030	OMM	2.102	2.098	2.094	0.010	0.006	0.002	2.098	35%	0%		OK	
33	Distance	0.000	0.030	0.000	OMM	0.008	0.009	0.021	0.008	0.009	0.021	0.013	69%		Alert	OK	
34	Distance	0.000	0.020	0.000	OMM	0.001	0.007	0.002	0.001	0.007	0.002	0.003	35%			OK	
35	Distance	13.614	0.030	-0.030	OMM	13.639	13.637	13.617	0.025	0.023	0.003	13.631	84%	0%	Alert	OK	
36	Distance	1.951	0.030	-0.030	OMM	1.961	1.950	1.950	0.010	-0.001	-0.001	1.954	34%	3%		OK	
37	Distance	2.355	0.030	-0.030	OMM	2.348	2.368	2.375	-0.007	0.013	0.020	2.364	66%	23%	Alert	OK	
38	Distance	10.182	0.030	-0.030	OMM	10.165	10.187	10.189	-0.017	0.005	0.007	10.181	25%	56%		OK	
39	Distance	0.200	0.030	-0.030	OMM	0.201	0.189	0.220	0.001	-0.011	0.020	0.203	66%	37%		OK	
40-1	Tolerance	0.350	0.030	-0.030	MIC	0.322	0.327	0.329	-0.028	-0.023	-0.021	0.326	0%	93%		Alert	OK
40-2	Tolerance	0.350	0.030	-0.030	MIC	0.321	0.323	0.320	-0.029	-0.027	-0.030	0.321	0%	100%		Alert	OK
40-3	Tolerance	0.350	0.030	-0.030	MIC	0.322	0.344	0.338	-0.028	-0.006	-0.012	0.335	0%	93%		Alert	OK
40-4	Tolerance	0.350	0.030	-0.030	MIC	0.320	0.348	0.340	-0.030	-0.002	-0.010	0.336	0%	100%		Alert	OK
41	Distance	1.902	0.020	-0.020	OMM	1.896	1.920	1.908	-0.006	0.018	0.006	1.908	89%	32%	Alert		OK
54	Distance	1.740	0.030	-0.030	OMM	1.734	1.743	1.756	-0.006	0.003	0.016	1.744	52%	19%		OK	
55	Distance	1.740	0.030	-0.030	OMM	1.726	1.744	1.749	-0.014	0.004	0.009	1.740	31%	47%		OK	
56	Distance	10.772	0.030	-0.030	OMM	10.770	10.786	10.778	-0.002	0.014	0.006	10.778	47%	7%		OK	
57	Distance	14.854	0.030	-0.030	OMM	14.836	14.860	14.836	-0.018	0.006	-0.018	14.844	19%	61%		OK	
58	Distance	13.270	0.030	-0.030	OMM	13.254	13.263	13.261	-0.016	-0.007	-0.009	13.259	0%	53%		OK	
59	Distance	0.642	0.030	-0.030	OMM	0.657	0.650	0.648	0.015	0.008	0.006	0.652	50%	0%		OK	
60	Distance	0.403	0.030	-0.030	OMM	0.424	0.420	0.412	0.021	0.017	0.009	0.419	69%	0%	Alert		OK
61	Distance	1.986	0.030	-0.030	OMM	1.996	1.991	1.987	0.010	0.005	0.001	1.991	35%	0%		OK	
62	Distance	2.226	0.030	-0.030	OMM	2.229	2.224	2.224	0.003	-0.002	-0.002	2.226	10%	6%		OK	
63	Distance	1.718	0.020	-0.020	OMM	1.703	1.725	1.711	-0.015	0.007	-0.007	1.713	37%	74%		Alert	OK
64	Distance	0.385	0.220	-0.220	OMM	0.384	0.433	0.391	-0.001	0.048	0.006	0.403	22%	1%		OK	
65	Distance	5.278	0.300	-0.300	OMM	5.311	5.360	5.340	0.033	0.082	0.062	5.337	27%	0%		OK	
66	Angle	0.000	3.000	-3.000	OMM	1.330	1.238	1.256	1.330	1.238	1.256	1.275	44%			OK	
68-1	Distance	1.030	0.020	-0.020	OMM	1.024	1.027	1.029	-0.006	-0.003	-0.001	1.027	0%	32%		OK	
68-2	Distance	1.030	0.020	-0.020	OMM	1.038	1.038	1.032	0.008	0.008	0.002	1.036	42%	0%		OK	
69	Distance	14.496	0.020	-0.020	OMM	14.504	14.501	14.503	0.008	0.005	0.007	14.502	38%	0%		OK	
70-1	Distance	0.770	0.020	-0.020	OMM	0.774	0.778	0.767	0.004	0.008	-0.003	0.773	38%	15%		OK	
70-2	Distance	0.770	0.020	-0.020	OMM	0.772	0.779	0.764	0.002	0.009	-0.006	0.772	47%	29%		OK	
71	Distance	11.777	0.020	-0.020	OMM	11.777	11.773	11.766	0.000	-0.004	-0.011	11.772	0%	54%		OK	

[illegible]

Cosmetic Waiver List

[illegible]

Dimensional Waiver List

[illegible]

Functional Waiver List

[illegible]

Reliability Waiver List

[illegible]

Revision	Date	Author	Comments
1	2018-08-03	Tim Burks	Initial Release