

QQC Waiver Request

Vendor Input		Vendor Input		Vendor Input Input
Program:	Memphis-Project	Waiver Request Date:	-	
Vendor:	Dpamstech	Planned Shipment Date:	2026-04-04	
APN:	817-10714	Judgment :	PASS	
Revision:	MCO Rev.7 / MSoP Rev.1 / PGM Rev.1	OK Quantity:	480	
Build:	MP	Waived Quantity:	0	
Config:	-	Shipment Quantity:	480	

[illegible]

APN	Shipping Date	Build	Inner package	Shipping Lot No	Total Q'TY	Cavity	Shipping Qty	Unit
817-10714	2026-04-04	MP	3HUR00022A/480/DP252222070C1BSM	20250529-20-B	5760	1	480	PCS

FAI Data Sheet Enclosures MD

DRAWING SPECIFICATIONS						INSPECTION RESULTS						INSPECTION ANALYSIS					Supplier Comment
FAI#	Description	Nominal	+TOL	TOL	Inspection Method	Sample Number			Deviation from Nominal			Mean	% Tolerance		Alert/Reject		
						G#1	D#4	C#4	1	2	3		Upper	Lower	High	Low	
1	Flatness	0.000	0.070	0.000	OMM	0.016	0.027	0.019	0.016	0.027	0.019	0.021	38%				OK
2-1	Distance	2.065	0.040	-0.020	OMM	2.078	2.076	2.083	0.013	0.011	0.018	2.079	44%	0%			OK
2-2	Distance	2.065	0.040	-0.020	OMM	2.085	2.074	2.087	0.020	0.009	0.022	2.082	55%	0%			OK
2-3	Distance	2.065	0.040	-0.020	OMM	2.077	2.090	2.071	0.012	0.025	0.006	2.079	63%	0%			OK
2-4	Distance	2.065	0.040	-0.020	OMM	2.088	2.093	2.078	0.023	0.028	0.013	2.086	71%	0%	Alert		OK
5-1	Bumper height	0.300	0.030	-0.030	OMM	0.293	0.301	0.302	-0.007	0.001	0.002	0.299	7%	25%			OK
5-2	Bumper height	0.300	0.030	-0.030	OMM	0.295	0.303	0.295	-0.005	0.003	-0.005	0.298	11%	17%			OK
6-1	Bumper height	0.320	0.030	-0.030	OMM	0.303	0.310	0.314	-0.017	-0.010	-0.006	0.309	0%	58%			OK
6-2	Bumper height	0.320	0.030	-0.030	OMM	0.303	0.310	0.315	-0.017	-0.010	-0.005	0.309	0%	57%			OK
7-1	Bumper height	0.100	0.010	-0.040	OMM	0.087	0.087	0.089	-0.013	-0.013	-0.012	0.087	0%	34%			OK
7-2	Bumper height	0.100	0.010	-0.040	OMM	0.084	0.086	0.087	-0.016	-0.014	-0.013	0.086	0%	39%			OK
7-3	Bumper height	0.100	0.010	-0.040	OMM	0.090	0.086	0.089	-0.010	-0.014	-0.011	0.089	0%	34%			OK
7-4	Bumper height	0.100	0.010	-0.040	OMM	0.086	0.083	0.088	-0.014	-0.017	-0.012	0.086	0%	43%			OK
9-1	Angle	90.000	1.000	-2.000	OMM	89.710	89.046	89.392	-0.290	-0.954	-0.608	89.383	0%	48%			OK
9-2	Angle	90.000	1.000	-2.000	OMM	88.595	89.189	89.287	-1.405	-0.811	-0.713	89.024	0%	70%	Alert		OK
10-1	Angle	90.000	1.000	-2.000	OMM	89.928	89.538	88.932	-0.072	-0.463	-1.068	89.466	0%	53%			OK
10-2	Angle	90.000	1.000	-2.000	OMM	89.623	88.681	89.423	-0.377	-1.319	-0.578	89.242	0%	66%	Alert		OK
12	Bumper height	0.122	0.010	-0.020	OMM	0.127	0.118	0.121	0.005	-0.004	-0.001	0.122	49%	19%			OK
13	Bumper height	0.122	0.010	-0.020	OMM	0.122	0.116	0.122	0.000	-0.006	0.000	0.120	4%	31%			OK
14	Bumper height	0.078	0.010	-0.020	OMM	0.073	0.073	0.078	-0.005	-0.005	0.000	0.075	1%	27%			OK
15	Bumper height	0.078	0.010	-0.020	OMM	0.080	0.074	0.072	0.002	-0.004	-0.006	0.075	22%	32%			OK
16	Distance	12.494	0.030	-0.030	OMM	12.491	12.508	12.476	-0.003	0.014	-0.018	12.492	46%	60%			OK
17-1	Distance	0.533	0.030	-0.030	OMM	0.536	0.538	0.537	0.003	0.005	0.004	0.537	15%	0%			OK
17-2	Distance	0.533	0.030	-0.030	OMM	0.536	0.533	0.538	0.003	0.000	0.005	0.536	16%	0%			OK
19-1	Distance	15.518	0.030	-0.030	OMM	15.519	15.526	15.516	0.001	0.008	-0.002	15.520	26%	6%			OK
19-2	Distance	15.518	0.030	-0.030	OMM	15.520	15.517	15.518	0.002	-0.001	0.000	15.518	6%	5%			OK
20	Distance	1.015	0.030	-0.030	OMM	1.020	1.027	1.000	0.005	0.012	-0.015	1.015	40%	50%			OK
21	Distance	14.803	0.030	-0.040	OMM	14.819	14.810	14.776	0.016	0.007	-0.027	14.802	53%	68%	Alert		OK
22	Distance	11.644	0.030	-0.030	OMM	11.633	11.649	11.655	-0.011	0.005	0.011	11.646	38%	37%			OK
23	Distance	0.860	0.030	-0.030	OMM	0.871	0.869	0.856	0.011	0.009	-0.004	0.865	36%	15%			OK
24-1	Distance	9.939	0.030	-0.030	OMM	9.936	9.939	9.941	-0.003	0.000	0.002	9.938	6%	11%			OK
24-2	Distance	9.939	0.030	-0.030	OMM	9.938	9.944	9.949	-0.001	0.005	0.010	9.944	35%	2%			OK
25-1	Distance	0.575	0.030	-0.030	OMM	0.573	0.576	0.580	-0.002	0.001	0.005	0.576	18%	8%			OK
25-2	Distance	0.575	0.030	-0.030	OMM	0.576	0.580	0.582	0.001	0.005	0.007	0.579	22%	0%			OK
26	Distance	1.125	0.030	-0.030	OMM	1.131	1.123	1.104	0.006	-0.002	-0.021	1.119	19%	71%	Alert		OK
27-1	Distance	3.899	0.030	-0.030	OMM	3.895	3.899	3.901	-0.004	0.000	0.002	3.898	7%	14%			OK
27-2	Distance	3.899	0.030	-0.030	OMM	3.900	3.906	3.911	0.001	0.007	0.012	3.906	42%	0%			OK
28	Distance	4.634	0.030	-0.030	OMM	4.637	4.634	4.639	0.003	0.000	0.005	4.637	15%	0%			OK
29	Distance	1.010	0.030	-0.030	OMM	1.009	1.014	0.988	-0.001	0.004	-0.022	1.004	14%	72%	Alert		OK
31	Distance	11.074	0.030	-0.030	OMM	11.074	11.071	11.080	0.000	-0.003	0.006	11.075	21%	10%			OK
32	Distance	14.793	0.030	-0.030	OMM	14.794	14.794	14.774	0.001	0.001	-0.019	14.787	3%	64%			OK
33	Thickness	0.135	0.005	-0.005	MIC	0.138	0.133	0.134	0.003	-0.002	-0.001	0.135	60%	40%			OK
34-1	Distance	2.170	0.030	-0.030	OMM	2.185	2.160	2.181	0.015	-0.010	0.011	2.175	50%	33%			OK
34-2	Distance	2.170	0.030	-0.030	OMM	2.159	2.153	2.171	-0.011	-0.017	0.001	2.161	2%	55%			OK
35-1	Distance	14.344	0.030	-0.030	OMM	14.348	14.351	14.345	0.004	0.007	0.001	14.348	22%	0%			OK
35-2	Distance	14.344	0.030	-0.030	OMM	14.345	14.344	14.348	0.001	0.000	0.004	14.346	14%	0%			OK
39-1	Distance	0.200	0.040	-0.070	OMM	0.162	0.175	0.181	-0.038	-0.025	-0.019	0.173	0%	54%			OK
39-2	Distance	0.200	0.040	-0.070	OMM	0.188	0.168	0.174	-0.012	-0.032	-0.026	0.177	0%	46%			OK
40	Distance	1.090	0.030	-0.030	OMM	1.104	1.091	1.085	0.014	0.001	-0.005	1.094	47%	16%			OK
41	Distance	14.918	0.030	-0.030	OMM	14.908	14.915	14.918	-0.010	-0.003	0.000	14.913	0%	35%			OK
42	Distance	1.000	0.030	-0.030	OMM	0.990	0.995	0.993	-0.010	-0.005	-0.007	0.993	0%	34%			OK
43	Distance	0.950	0.030	-0.030	OMM	0.953	0.954	0.942	0.003	0.004	-0.008	0.949	12%	28%			OK
44-1	Distance	2.170	0.030	-0.030	OMM	2.150	2.166	2.162	-0.020	-0.004	-0.008	2.159	0%	67%	Alert		OK
44-2	Distance	2.170	0.030	-0.030	OMM	2.152	2.157	2.146	-0.018	-0.013	-0.024	2.152	0%	80%	Alert		OK
46	Distance	12.546	0.030	-0.030	OMM	12.556	12.550	12.538	0.010	0.004	-0.008	12.548	32%	25%			OK
47	Distance	1.200	0.030	-0.030	OMM	1.181	1.184	1.184	-0.019	-0.016	-0.016	1.183	0%	64%			OK
48	Distance	0.990	0.030	-0.030	OMM	0.990	0.982	0.973	0.000	-0.008	-0.017	0.982	0%	58%			OK
49	Distance	15.043	0.030	-0.040	OMM	15.041	15.046	15.038	-0.002	0.003	-0.005	15.042	11%	14%			OK
50-1	Distance	16.118	0.030	-0.030	OMM	16.115	16.117	16.109	-0.003	-0.001	-0.009	16.114	0%	29%			OK
50-2	Distance	16.118	0.030	-0.030	OMM	16.126	16.127	16.106	0.008	0.009	-0.012	16.120	29%	39%			OK
51-1	Emboss height	0.070	0.030	-0.030	OMM	0.065	0.070	0.072	-0.005	0.000	0.002	0.069	8%	18%			OK
51-2	Emboss height	0.070	0.030	-0.030	OMM	0.063	0.060	0.059	-0.007	-0.010	-0.011	0.061	0%	36%			OK
52-1	Emboss height	0.070	0.030	-0.030	OMM	0.063	0.064	0.062	-0.007	-0.006	-0.008	0.063	0%	26%			OK
52-2	Emboss height	0.070	0.030	-0.030	OMM	0.061	0.064	0.065	-0.009	-0.006	-0.005	0.063	0%	30%			OK
53-1	Emboss height	0.070	0.030	-0.030	OMM	0.060	0.062	0.064	-0.010	-0.008	-0.006	0.062	0%	33%			OK
53-2	Emboss height	0.070	0.030	-0.030	OMM	0.060	0.063	0.065	-0.010	-0.007							

DRAWING SPECIFICATIONS										CALCULATED RESULTS			
NO.	PAID	DESCRIPTION	REMARKS	UNIT	QTY	UNIT PRICE	AMOUNT	QTY	UNIT PRICE	AMOUNT	UNIT PRICE	REMARKS	
1	1	Foundation	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	100%		
2	1	Foundation	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	100%		
3	1	Foundation	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	100%		
4	2	Foundation	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	100%		
5	2	Foundation	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	100%		
6	2	Foundation	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	100%		
7	2	Foundation	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	100%		
8	2	Foundation	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	100%		
9	2	Foundation	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	100%		
10	2	Foundation	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	100%		
11	2	Foundation	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	100%		
12	2	Foundation	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	100%		
13	2	Foundation	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	100%		
14	2	Foundation	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	100%		
15	2	Foundation	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	100%		
16	2	Foundation	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	100%		
17	2	Foundation	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	100%		
18	2	Foundation	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	100%		
19	2	Foundation	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	100%		
20	2	Foundation	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	100%		
21	2	Foundation	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	100%		
22	2	Foundation	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	100%		
23	2	Foundation	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	100%		
24	2	Foundation	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	100%		
25	2	Foundation	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	100%		
26	2	Foundation	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	100%		
27	2	Foundation	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	100%		
28	2	Foundation	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	100%		
29	2	Foundation	0.0000	0.0000	0								

[illegible]

Cosmetic Waiver List

[illegible]

Dimensional Waiver List

[illegible]

Functional Waiver List

[illegible]

Reliability Waiver List

[illegible]

Revision	Date	Author	Comments
1	2018-08-03	Tim Burks	Initial Release