

Main

Default

```
#let test(description) = {  
  set text(  
    ..default(  
      when: text.fill == luma(0%),  
      value: (fill: red), false  
    )  
  )  
  description  
}
```

```
#context test[Custom default.]
```

```
#set text(fill: blue)
```

```
#context test[Default overridden.]
```

```
#repr(  
  content2str[ *Foo* #emph[Bar] Baz ]  
)
```

Custom default.

Default overridden.

" Foo Bar Baz "

Storage

```
#storage.add("foo", 42)
#storage.add("bar", (a: 1))
#storage.add("bar", (b: 2), append: true)
#storage.add("baz", 1)
#storage.add("baz", 2, append: true)
#storage.add("qux", 3)
#storage.remove("qux")

#context raw(yaml.encode(storage.get()), lang: "yaml")
```

```
foo: 42
bar:
  a: 1
  b: 2
baz:
- 1
- 2
```

Components

```
#comp.url("eg@mail.com", <foo>)[URL]\  
#comp.url(<foo>)
```

URL¹

URL¹

```
#comp.pkg("https://example.com/{name}/slug/")\  
#comp.pkg("https://example.com/name", <bar>)\  
#comp.pkg(<bar>)
```

*name*²

*name*³

*name*³

```
#comp.callout(lorem(6))  
#comp.callout(  
  title: "Title",  
  icon: "bars-3",  
  lorem(6)  
)  
#comp.callout(  
  text: white,  
  background: blue,  
  lorem(6)  
)
```

① Lorem ipsum dolor sit amet, consectetur.

≡ Title

Lorem ipsum dolor sit amet, consectetur.

① Lorem ipsum dolor sit amet, consectetur.

¹eg@mail.com

²https://example.com/name/slug/

³https://example.com/name

Get

Null

```
#get.null      null
```

Auto value

```
#get.auto-val(auto, 42)\  42  
#get.auto-val([AB], 42)  AB
```

Date

```
#get.date(2025)      datetime(year: 2025, month: 1, day: 1)
```

```
#get.date(2025, 9)    datetime(year: 2025, month: 9, day: 1)
```

```
#get.date(2025, 9, 5)  datetime(year: 2025, month: 9, day: 5)
```

```
#get.date(2025, month: 9, day: 5)  datetime(year: 2025, month: 9, day:  
5)
```

Has

Field

```
#has.field([A B], "text")\n#has.field([A B], "body")
```

```
true  
false
```

Key

```
#has.key((foo: 1), "foo")\  
#has.key((foo: 1), "bar")
```

```
true  
false
```

Value

```
#has.value((foo: 1), 1)\n#has.value((foo: 1), 2)
```

```
true  
false
```

Item

```
#has.item((0, 1), 1)\n#has.item((0, 1), 2)
```

```
true  
false
```

It's

None value

<pre>#its.none-val(none)\ #its.none-val(auto)</pre>	<pre>true false</pre>
---	---------------------------

Null

<pre>#its.null(get.null)\ #its.null("string")</pre>	<pre>true false</pre>
---	---------------------------

Empty

<pre>#its.empty("")\ #its.empty([])</pre>	<pre>true false</pre>
--	---------------------------

Context value

<pre>#its.context-val(context())\ #its.context-val([content])</pre>	<pre>true false</pre>
---	---------------------------

Sequence content

<pre>#its.sequence([*A* _B_])\ #its.sequence([A B])</pre>	<pre>true false</pre>
---	---------------------------

Space content

<pre>#its.space([])\ #its.space([])</pre>	<pre>true false</pre>
--	---------------------------

Function

<pre>#its.func([*A*], (image, strong))\ #its.func([_A_], (image, strong))</pre>	<pre>true false</pre>
---	---------------------------

Type

<pre>#its.type("string", (array, str))\ #its.type(content, (array, str))</pre>	<pre>true false</pre>
--	---------------------------