

Main

Default

```
#let test(description) = {  
  set text(  
    ..default(  
      when: text.fill == luma(0%),  
      value: (fill: red), false  
    )  
  )  
  description  
}
```

```
#context test[Custom default.]
```

```
#set text(fill: blue)
```

```
#context test[Default overridden.]
```

```
#repr(  
  content2str[ *Foo* #emph[Bar] Baz ]  
)
```

Custom default.

Default overridden.

" Foo Bar Baz "

Storage

```
#storage.add("foo", 42)
#storage.add("bar", (a: 1))
#storage.add("bar", (b: 2), append: true)
#storage.add("baz", 1)
#storage.add("baz", 2, append: true)
#storage.add("qux", 3)
#storage.remove("qux")

#context raw(yaml.encode(storage.get()), lang: "yaml")
```

```
foo: 42
bar:
  a: 1
  b: 2
baz:
- 1
- 2
```

Components

```
#comp.url("eg@mail.com", <foo>)[URL]\  
#comp.url(<foo>)
```

URL¹

URL¹

```
#comp.pkg("https://example.com/{name}/slug/")\  
#comp.pkg("https://example.com/name", <bar>)\  
#comp.pkg(<bar>)
```

*name*²

*name*³

*name*³

```
#comp.callout(lorem(6))  
#comp.callout(  
  title: "Title",  
  icon: "bars-3",  
  lorem(6)  
)  
#comp.callout(  
  text: white,  
  background: blue,  
  lorem(6)  
)
```

① Lorem ipsum dolor sit amet, consectetur.

≡ Title

Lorem ipsum dolor sit amet, consectetur.

① Lorem ipsum dolor sit amet, consectetur.

¹eg@mail.com

²https://example.com/name/slug/

³https://example.com/name

Get

Null

`#get.null`

null

Auto value

`#get.auto-val(auto, 42)\`
`#get.auto-val([AB], 42)`

42
AB

Date

`#get.date(2025)`

`datetime(year: 2025, month: 1, day: 1)`

`#get.date(2025, 9)`

`datetime(year: 2025, month: 9, day: 1)`

`#get.date(2025, 9, 5)`

`datetime(year: 2025, month: 9, day: 5)`

`#get.date(2025, month: 9, day: 5)`

`datetime(year: 2025, month: 9, day: 5)`

Date difference

`#get.date-diff(`
 `"2020-3-11",`
 `"2023-5-5"`
`)`

`(years: 3, months: 1, days: 24)`

`#let start = datetime(`
 `year: 2020,`
 `month: 3,`
 `day: 11`
`)`
`#let end = datetime(`
 `year: 2023,`
 `month: 5,`
 `day: 5`
`)`
`#get.date-diff(start, end)`

`(years: 3, months: 1, days: 24)`

Relative luminance

`#get.relative-luminance(white)`

1

`#get.relative-luminance(black)`

0

`#get.relative-luminance(red)`

0.41019534756243226

Dynamic colors

`#get.dynamic-color(white)`

`luma(0%)`

`#get.dynamic-color(black)`

`luma(100%)`

`#get.dynamic-color(red)`

`luma(100%)`

`#get.dynamic-color(red.lighten(25%))`

`luma(0%)`

Has

Field

<pre>#has.field([A B], "text")\ #has.field([A B], "body")</pre>	<pre>true false</pre>
---	---------------------------

Key

<pre>#has.key((foo: 1), "foo")\ #has.key((foo: 1), "bar")</pre>	<pre>true false</pre>
---	---------------------------

Value

<pre>#has.value((foo: 1), 1)\ #has.value((foo: 1), 2)</pre>	<pre>true false</pre>
---	---------------------------

Item

<pre>#has.item((0, 1), 1)\ #has.item((0, 1), 2)</pre>	<pre>true false</pre>
---	---------------------------

It's

None value

```
#its.none-val(none)\
#its.none-val(auto)
```

true
false

Null

```
#its.null(get.null)\
#its.null("string")
```

true
false

Empty

```
#its.empty("")\
#its.empty([ ])
```

true
false

Context value

```
#its.context-val(context())\
#its.context-val([content])
```

true
false

Sequence content

```
#its.sequence([*A* _B_])\
#its.sequence([A B])
```

true
false

Space content

```
#its.space([ ])\
#its.space([])
```

true
false

Function

```
#its.func([*A*], (image, strong))\
#its.func([_A_], (image, strong))
```

true
false

Type

```
#its.type("string", (array, str))\
#its.type(content, (array, str))
```

true
false