



Text Case

Manual

Simple, multilingual solution for capitalization formatting

typst

text-case^{*}

0.1.0

MIT-0

Maycon F. Melo[†]

Contents

Quick Start	2
Description	2
Sentence case	2
Sentence case title	3
Convert text case	3
Title case	5
String case	5
Detect case	6
Locales	6
Copyright	6

^{*}<https://github.com/mayconfmelo/text-case>

[†]<https://github.com/mayconfmelo>

Quick Start

```
#import "@preview/textcase:0.1.0": contextual

// "Sentence case text."
#contextual.sentence-case("sentence case text.")

// "Sentence case title: Subtitle"
#contextual.sentence-case-title("sentence title: subtitle")

// "Title Case: Subtitle"
#contextual.title-case("title case: subtitle")

// "sentence-title"
#contextual.detect-case("Sentence title: Subtitle")

// "camelCaseString"
#contextual.convert("camel case string", mode: "camel")
```

Description

Multilingual sentence and title recasing for Latin-script languages. This recases text whose capitalization is wrong or missing — lowercase feeds, SHOUTED titles, Title Cased Prose — while preserving capitalization that carries information. It works without any external data. Conversion to string cases is also supported, as well as the detection of prose or string case¹ of a text.

Sentence case

```
#sentence-case(
  text,
  locale: "en",
)
```

Transforms texts to conform to sentence capitalization rules.

¹Prose cases are linguistic rules of text capitalization; and string cases are common naming conventions used in code

text string raw

Text to be transformed.

locale: string

Language for capitalization rules.

The `#contextual.sentence-case` command automatically retrieve the locale from `#text.lang`.

Sentence case title

```
#sentence-case-title(
  text,
  locale: "en",
)
```

Transforms title texts to conform to sentence capitalization rules, with automatic subtitle detection and capitalization.

text string raw

Text to be transformed.

locale: string

Language for capitalization rules.

The `#contextual.sentence-case-title` command automatically retrieve the locale from `#text.lang`.

Convert text case

```
#convert(
  text,
  locale: "en",
  mode: "sentence",
  subtitle-separator-style: "preserve",
  capitalize-after-subtitle-separator: true,
  preserve-acronyms: true,
  preserve-mixed-case: true,
  preserve-known-proper-nouns: true,
  preserve-existing-capitals: true,
```

```

    normalize-whitespace: true,
    german-mode: "conservative",
)

```

Performs text case transformation with support for fine-tuning the process. This command provides access to advanced text transformation options.

text `string` `raw`

Text to be transformed.

locale: `string`

Language for capitalization rules.

mode: `string`

Text conversion mode: title, sentence-title, sentence, lower, upper, camel, pascal, kebab, train, snake, constant.

subtitle-separator-style: `string`

Subtitle separator conversion: preserve, colon-space, space-dash-space, em-dash-space.

capitalize-after-subtitle-separator: `boolean`

Whether to capitalize subtitles.

preserve-acronyms: `boolean`

Preserve upper case acronyms.

preserve-mixed-case: `boolean`

Preserve mixed case (lower and upper case) as is.

preserve-known-proper-nouns: `boolean`

Transform proper nouns internally known by *textcase*.

preserve-existing-capitals: `boolean`

Preserve capitalized mid-sentence words in sentence case.

normalize-whitespace: `boolean`

Collapse additional whitespace characters.

german-mode: `boolean`

Special *handling*² for German language: conservative, balanced, aggressive.

²<https://github.com/Pajn/textcase/blob/main/docs/german.md>

The `#contextual.convert` command automatically retrieve the locale from `#text.lang`.

Title case

```
#title-case(  
  text,  
  locale: "en",  
)
```

Transforms title texts to conform to title case capitalization rules, with automatic subtitle detection and capitalization.

text `string`

Text to be transformed.

locale: `string`

Language for capitalization rules.

The `#contextual.text-case` command automatically retrieve the locale from `#text.lang`.

String case

```
#string-case(  
  text,  
  mode: "kebab",  
)
```

Converts the text to one of the common string casing conventions.

text `string`

Text to be transformed.

mode: `string`

String case convention: camel, pascal, kebab, train, snake, constant, lower, upper.

Detect case

```
#detect-case(  
  text,  
  locale: "en",  
  string-case: true,  
)
```

Detects the capitalization format of a string. It is also possible to detect some common string cases—naming conventions used in code. Returns one of: `title`, `sentence-title`, `sentence`, `lower`, `upper`, `camel`, `pascal`, `kebab`, `train`, `snake`, `constant`, `unknown`

text `string`

Text to be tested.

locale: `string`

Language for capitalization rules.

string-case: `boolean`

Detect common string cases.

Locales

The crate has dedicated profiles for "en", "de", "fr", "es", "pt", "it", "nl", "sv", "da", "no", "fi", "tr", "az", and "lt" languages. A profile contributes stop words and lowercase particles (title mode), abbreviation classes (sentence splitting), contraction tails (don't, O'Brien), and elision prefixes (d'affaires → d'Affaires). Any other locale gets a neutral profile that assumes nothing beyond a few Latin abbreviations.

Copyright

Copyright © 2026 Maycon F. Melo.

This manual is licensed under MIT.

The manual source code is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

The logo was obtained from Flaticon website.