

Text Case

Manual

Simple, multilingual solution for capitalization formatting

---

typst	text-case[*]	0.1.0	MIT-0

Maycon F. Melo[†]

Contents

Quick Start 2
Description 2
Sentence case 2
Sentence case title 3
Convert text case 3
Title case 5
String case 5
Detect case 6
Locales 6
Copyright 6

[*] https://github.com/mayconfmelo/text-case
[†] https://github.com/mayconfmelo

Quick Start

```
#import "@preview/textcase:0.1.0": contextual

// "Sentence case text."
#contextual.sentence-case("sentence case text.")

// "Sentence case title: Subtitle"
#contextual.sentence-case-title("sentence title: subtitle")

// "Title Case: Subtitle"
#contextual.title-case("title case: subtitle")

// "sentence-title"
#contextual.detect-case("Sentence title: Subtitle")

// "camelCaseString"
#contextual.convert("camel case string", mode: "camel")
```

Description

Multilingual sentence and title recasing for Latin-script languages. This recases text whose capitalization is wrong or missing — lowercase feeds, SHOUTED titles, Title Cased Prose — while preserving capitalization that carries information. It works without any external data. Conversion to string cases is also supported, as well as the detection of prose or string case[1] of a text.

Sentence case

```
#sentence-case(
  text,
  locale: "en",
)
```

Transforms texts to conform to sentence capitalization rules.

[1]Prose cases are linguistic rules of text capitalization; and string cases are common naming conventions used in code

`text` string raw

Text to be transformed.

`locale:` string

Language for capitalization rules.

The `#contextual.sentence-case` command automatically retrieve the locale from `#text.lang`.

Sentence case title

```
#sentence-case-title(
  text,
  locale: "en",
)
```

Transforms title texts to conform to sentence capitalization rules, with automatic subtitle detection and capitalization.

`text` string raw

Text to be trabsformed.

`locale:` string

Language for capitalization rules.

The `#contextual.sentence-case-title` command automatically retrieve the locale from `#text.lang`.

Convert text case

```
#convert(
  text,
  locale: "en",
  mode: "sentence",
  subtitle-separator-style: "preserve",
  capitalize-after-subtitle-separator: true,
  preserve-acronyms: true,
  preserve-mixed-case: true,
  preserve-known-proper-nouns: true,
  preserve-existing-capitals: true,
```

```
    normalize-whitespace: true,
    german-mode: "conservative",
  )
```

Performs text case transformation with support for fine-tuning the process. This command provides access to advanced text transformation options.

`text` string raw

Text to be transformed.

`locale:` string

Language for capitalization rules.

`mode:` string

Text conversion mode: `title`, `sentence-title`, `sentence`, `lower`, `upper`, `camel`, `pascal`, `kebab`, `train`, `snake`, `constant`.

`subtitle-separator-style:` string

Subtitle separator conversion: `preserve`, `colon-space`, `space-dash-space`, `em-dash-space`.

`capitalize-after-subtitle-separator:` boolean

Whether to capitalize subtitles.

`preserve-acronyms:` boolean

Preserve upper case acronyms.

`preserve-mixed-case:` boolean

Preserve mixed case (lower and upper case) as is.

`preserve-known-proper-nouns:` boolean

Transform proper nouns internally known by *textcase.*

`preserve-existing-capitals:` boolean

Preserve capitalized mid-sentence words in sentence case.

`normalize-whitespace:` boolean

Collapse additional whitespace characters.

`german-mode:` boolean

Special *handling*[2] for German language: `conservative`, `balanced`, `aggressive`.

[2] https://github.com/Pajn/textcase/blob/main/docs/german.md

The `#contextual.convert` command automatically retrieve the locale from `#text.lang`.

Title case

```
#title-case(
  text,
  locale: "en",
)
```

Transforms title texts to conform to title case capitalization rules, with automatic subtitle detection and capitalization.

`text` string

Text to be transformed.

`locale:` string

Language for capitalization rules.

The `#contextual.text-case` command automatically retrieve the locale from `#text.lang`.

String case

```
#string-case(
  text,
  mode: "kebab",
)
```

Converts the text to one of the common string casing conventions.

`text` string

Text to be transformed.

`mode:` string

String case convention: camel, pascal, kebab, train, snake, constant, lower, upper.

Detect case

```
#detect-case(
  text,
  locale: "en",
  string-case: true,
)
```

Detects the capitalization format of a string. It is also possible to detect some common string cases—naming conventions used in code. Returns one of: `title`, `sentence-title`, `sentence`, `lower`, `upper`, `camel`, `pascal`, `kebab`, `train`, `snake`, `constant`, `unknown`

`text` string

Text to be tested.

`locale:` string

Language for capitalization rules.

`string-case:` boolean

Detect common string cases.

Locales

The crate has dedicated profiles for `"en"`, `"de"`, `"fr"`, `"es"`, `"pt"`, `"it"`, `"nl"`, `"sv"`, `"da"`, `"no"`, `"fi"`, `"tr"`, `"az"`, and `"lt"` languages. A profile contributes stop words and lowercase particles (title mode), abbreviation classes (sentence splitting), contraction tails (don't, O'Brien), and elision prefixes (d'affaires → d'Affaires). Any other locale gets a neutral profile that assumes nothing beyond a few Latin abbreviations.

Copyright

Copyright © 2026 Maycon F. Melo.
This manual is licensed under MIT.
The manual source code is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

The logo was obtained from Flaticon website.