

## TECHNICAL DATASHEET

# ANTICO

### PRODUCT DESCRIPTION

ANTICO is a wall coating providing a prestigious finish very similar to that of traditional marble. It renders a textured antique effect and can be overcoated with Patina giving a wide selection of colored patterns.

### PRODUCT BENEFITS

- 1- Attractive antique effect
- 2- High performance and outstanding durability
- 3- Great adhesion
- 4- Easy to apply
- 5- Excellent washability and color retention
- 6- High resistance to oils, fats and detergent solutions

### RECOMMENDED USES

Antico can be used for interior surfaces such as cement, gypsum plaster, concrete, building boards and previously primed or painted wood and metal substrates, etc.

### SURFACE PREPARATION

Prepare the substrate as mentioned below:

- Rigid Surfaces should be cleaned, dust free, and free from all traces of oil and laitance.
- Alkaline and acid surfaces should be cleaned and neutralized.
- Chalky, glossy surfaces, previous coating, blistered paints should be cleaned by scrapers or roughened with sand paper.

### PHYSICAL AND CHEMICAL PROPERTIES

#### Physical Properties

Physical State	Paste
Appearance	textured
Color range	white (overcoat with patina for colors)

Specific Gravity, ISO 2811	1.7 ± 0.05 g/cm <sup>3</sup>
Viscosity, ISO 2884	100-120 Poises
Drying Time, ASTM D5894	4- 6 Hours
Wet Film Thickness, ISO 2808	500 µm -1 mm
Dry film Thickness, ISO 2808	250-500 µm
Recoat Time	After 6 hours
Sag Resistance, ASTM D3730	Excellent

### **Chemical Properties**

% Solids by Weight	75 ± 2 %
% Solids by Volume	44 ± 2%

### **PRIMING/ THINNING/APPLYING**

Fill any major holes or loose plaster.

If needed, prime the surface with primer Sealer.

Apply one coat of Antico with a trowel leaving a layer of about 1mm in thickness. Repeat the process if needed.

Multiple patterns and finishes could be obtained by using different tools.

After complete drying, overcoat with patina.

Clean tools and equipment with water immediately after use.

### **PACKING**

In cylindrical tin containers of the following capacities:

- 1 US quart = 0.94 L
- 1 US gallon = 3.78 L
- 1 Pail (5 U.S.G.) = 20 L

### **STORAGE**

Avoid frost & excessive heat.

The technical information contained in this Technical Data Sheet is to be understood as advice only and not binding in any respect.  
All details about working with our products should be adapted to prevailing local conditions and materials used.