

## TECHNICAL DATASHEET

# COARSE TEXTURE WATERPROOF

### PRODUCT DESCRIPTION

High-build, weather-resistant, water-based coating used to decorate and protect above-grade concrete, masonry and acrylic stucco finishes. It is specially designed to provide waterproofing properties to the system.

It can be used as a primer for textured finishes.

### PRODUCT BENEFITS

- 1- Eco-friendly, Odorless & Nonflammable product.
- 2- Excellent water resistance
- 3- Excellent vapor permeability
- 4- Excellent flexibility and crack resistance
- 5- Excellent durability
- 6- Strong adhesion
- 7- Low maintenance
- 8- Easy to apply
- 9- Water based

### RECOMMENDED USES

Coarse Texture Waterproof is suitable for application on Cement Render surface, Autoclaved Aerated Concrete rendered surface Fiber, Cement Sheeting (Fibro/Blue board), Clay and Concrete Brickwork, Concrete blocks...

It can also be used as a waterproofing primer for exterior textured coatings.

### SURFACE PREPARATION

All surfaces should be clean, dry and free from oil, grease and loose materials.

Water blast cleaning is the preferred method of preparation and special attention should be paid to moss and lichen, these areas should be treated with Fungicidal Wash.

Oil and grease should be removed.

## PHYSICAL AND CHEMICAL PROPERTIES

### Physical Properties

Physical State	Thick gritty viscous liquid
Appearance	Textured finish
Color Range	see catalogue
Odor	None

Specific Gravity, ISO 2811	1.7 ± 0.05g/cm <sup>3</sup>
Viscosity, ISO 2884	70-80 poises
Drying Time, ASTM D5894	3- 4 hours per coat
Recoat Time	overnight
Coverage	15-18 m <sup>2</sup> /pail

Sag Resistance, ASTM D3730	Excellent
Water resistance	Excellent
Water vapor permeability	Excellent

### Chemical Properties

Solids by Weight	80 %
------------------	------

## THINNING & APPLYING

- 1- When used as a primer thin with water (dilution rate: up to 20%)
- 2- Apply one coat with a trowel.
- 3- Clean tools and equipment with water immediately after use.

## PACKING

In cylindrical tin containers of the following capacities:

- 1 US gallon = 3.78 L.
- 1Pail (5 U.S.G.) = 20L

## STORAGE

Avoid frost & excessive heat.

The technical information contained in this Technical Data Sheet is to be understood as advice only and not binding in any respect.  
All details about working with our products should be adapted to prevailing local conditions and materials used.