

## **TECHNICAL DATASHEET**

# **SUPER VINYL MATT EMULSION**

### **PRODUCT DESCRIPTION**

Super Vinyl Matt Emulsion is a vinyl acrylic paint designed for interior and exterior walls and ceilings where high performance is required. It provides a flat decorative and protective finish.

### **PRODUCT BENEFITS**

- 1- Non-toxic, Odorless & Nonflammable product.
- 2- Long lasting performance
- 3- Excellent leveling and coverage.
- 4- High Resistance to UV and various climatic conditions
- 5- Resistance to the alkalinity of concrete.
- 6- Water resistance
- 7- Water vapor permeability
- 8- Excellent washability

### **RECOMMENDED USES**

All interior and exterior walls and ceilings of concrete, masonry, stucco, fairfaced concrete, gypsum boards, non-chalking old paints, cement plaster, tyrolean or glats, brick, concrete structures and facades.

### **SURFACE PREPARATION**

Surfaces should be solid, clean and dry, free from oil, grease, salt, dust and other contaminants.

Alkaline and acid surfaces should be cleaned and neutralized.

Deteriorated previous coatings, weak and blistered paints or chalky substances should be removed by scrapers, paint removers or flame spraying.

Non-disintegrated paints or glossy surfaces of previous coatings should be roughened slightly with sand paper to ensure good intercoat adhesion.

Pores and holes must be filled with Ready Putty before priming.

## PHYSICAL AND CHEMICAL PROPERTIES

### Physical Properties

Physical State Viscous  
Appearance Matte Finish  
Color Range See Catalogue

Temperature 30°C  
Relative Humidity 60%

Specific Gravity, ISO 2811 1.3 g/cm<sup>3</sup>  
Viscosity, ISO 2884 7- 10 poises  
pH. 8- 9

Drying Time, ASTM D5894 2-4 hrs/coat  
Wet Film Thickness, ISO 2808 100 µm  
Dry film Thickness, ISO 2808 70 µm  
Recoat Time After 4- 6 hours  
Coverage 50- 60 m<sup>2</sup> per US gallon per one coat  
Opacity, ISO 6504-3 > 90%

Sag Resistance, ASTM D3730 Excellent  
Leveling, ASTM D2801 Excellent

Scratching Resistance, ASTM D3003 Excellent (ISO 0)

### Chemical Properties

% Solids by Weight 54 ± 2%  
% Solids by Volume 35 ± 2%  
% Binders by volume 45 %

## PRIMING/ THINNING/ APPLYING

Prime the surface with one coat of sealer (with a specific dilution depending on the surface condition).

Fill surface with ready putty as necessary to repair all defects before applying undercoat.

Thin Super Vinyl Emulsion with clean water (20 – 30% for brush/roller application).  
Thickness of paint film depends on condition of surface.

Apply 2-3 coats depending on the color of the product.

Clean tools and equipment with water immediately after use.

### **PACKING**

In cylindrical tin containers of the following capacities:

- 1 US gallon = 3.78 L.
- 1 Pail (5 U.S.G.) = 20L

### **STORAGE**

1 year under normal storage conditions from the issue date.  
Avoid frost & excessive heat.

The technical information contained in this Technical Data Sheet is to be understood as advice only and not binding in any respect.  
All details about working with our products should be adapted to prevailing local conditions and materials used.