

P.O.Box: 85 – Zouk Mikhaël / Lebanon Tel.: +961 9 218 645 - +961 9 218 656

Fax: +961 9 220 215 www.Amazonapaints.com info@Happywallpaints.com

# **TECHNICAL DATASHEET**

# **THINNER 2K**

#### PRODUCT DESCRIPTION

Multipurpose thinner used for dilution of all 2K acrylic products. It promotes high gloss and good flow. Suitable as a cleaner for spray gun and tools.

## **PRODUCT BENEFITS**

- 1- High purity of solvents
- 2- Strong dissolving power
- 3- Improves application characteristics
- 4- Compatible with all 2K systems
- 5- Blush Resistant
- 6- Moderate Evaporation Rate
- 7- Excellent Leveling and Gloss

#### RECOMMENDED USES

Thinner 2K is used with 2K systems to reach the desired application viscosity.

#### PHYSICAL PROPERTIES

Physical State Liquid Appearance Clear Flash Point 30°C

#### **INSTRUCTIONS FOR USE**

Thinner 2K must be mixed with the product very well and added until the desired viscosity is achieved.

Recommended Application Conditions:

Temperature 15 - 30°C

Relative Humidity 20 - 90%

#### **CAUTION**

Flammable Liquid and Vapor



P.O.Box: 85 – Zouk Mikhaël / Lebanon Tel.: +961 9 218 645 - +961 9 218 656

Fax: +961 9 220 215 www.Amazonapaints.com info@Happywallpaints.com

#### **PACKING**

In cylindrical containers of the following capacities: 1 L, 4L, 5L, 15L and 200 L

## **STORAGE**

Avoid frost & excessive heat.

The technical information contained in this Technical Data Sheet is to be understood as advice only and not binding in any respect.

All details about working with our products should be adapted to prevailing local conditions and materials used.