Which Rollouts Are Worth Generating?

Exact Bias, Variance, and Cost of Adaptive Rollout Collection in RLVR

Mohamed Ayman

Working draft, October 16, 2026. Results marked [pending:] are running.

Abstract

Reinforcement learning with verifiable rewards spends most of its compute generating answers, and practical systems decide adaptively how many answers to generate per prompt: they drop groups whose answers all agree, abandon prompts after a short probe, or sample until a correct answer appears. Each rule changes what training optimizes, how noisy each update is, and what it costs, yet rules are compared through heuristics and proxies. We show that for binary rewards, the first two moments of the update produced by any rule that decides from the rewards seen so far, including rules with random group size, depend on only four numbers per prompt: its success probability, the squared norm of the gradient of that probability, and the mean squared gradient norms of correct and of wrong answers. This makes the bias, variance, and cost of every such rule exactly computable, and makes rollout collection an optimization problem that we solve exactly. Under this accounting, DAPO's dynamic sampling has exactly the per-answer efficiency of the fixed group it filters, sample-until-correct rules are the least efficient rules in use, and the optimal rule's advantage over the best rule in use depends on how gradient signal varies with difficulty. Measuring the four numbers in Qwen2.5-Math-1.5B shows that the signal fades for very easy and very hard prompts, which makes the optimal rule robust and puts its predicted gain over the best rule in use at 1.6 to 2.2 times, and that wrong answers carry about 2.5 times larger squared gradients than correct ones, which the theory turns into a one-line change to GRPO: scale failure advantages by the measured ratio. [pending: pre-registered training comparison of that change against Dr. GRPO at a matched budget]

1 Introduction

Generating answers dominates the cost of RL with verifiable rewards, so a family of rules now decides adaptively how many answers each prompt receives. DAPO drops groups whose answers all agree and refills the batch (Yu et al., 2025); SARA abandons prompts after a short probe (SARA authors, 2026); Reinforce-Ada and related methods sample until enough correct answers appear (Xiong et al., 2025); allocation methods move a budget toward prompts that look informative (Knapsack RL authors, 2025; Yao et al., 2025). Each such rule does three things at once: it changes the implicit objective, it changes the update's noise, and it changes the cost. Existing comparisons optimize one of these through a proxy.

For binary rewards, recent work shows that fixed-size, reward-only weightings optimize an explicit function of each prompt's success probability (Davis and Recht, 2025; Mroueh, 2025; Thrampoulidis et al., 2025), and that dropping all-agreeing groups rescales the update without changing its direction (Okonkwo et al., 2026). These results concern the mean of the update for fixed group sizes. The rules practitioners use have random group sizes, and the quantity that decides their value is the update's noise per unit cost.

Contributions.

1. **A two-moment theorem** (Section 2). For any rule that stops and assigns advantages from the rewards observed so far, the mean update is $c(p)\nabla p$ and the second moment is $F_1 D_1(p) + F_0 D_0(p) + \|\nabla p\|^2 X(p)$, where F_1, F_0 are the mean squared gradient norms of correct and wrong answers. Random group sizes need no special treatment.
2. **Exact accounting and the optimal rule** (Section 3). An exact lattice engine evaluates any rule, and dynamic programming finds the rule that maximizes training value per generated answer. We compare the rules in use against it.
3. **Measurements in a real model** (Section 4). Wrong answers carry about 2.5 to 2.8 times larger squared gradients than correct ones in Qwen2.5-Math-1.5B, both in the last layer and over all parameters, while being only 9% longer.
4. **A tested prediction** (Section 5). The theory implies that failure advantages should be scaled by F_1/F_0. We test this in a pre-registered training comparison. [pending: result]

2 The two-moment theorem

A prompt has policy π, score $\ell(y) = \nabla \log \pi(y)$, binary reward $R(y)$, and success probability p. A reward-adapted rule draws answers independently, stops at a bounded stopping time N of the reward sequence, and returns $g = \sum_{i \le N} A_i \ell(y_i)$ with each A_i a function of $(r_1, \dots, r_N)$; filtering and abandonment are $A = 0$. Let $\kappa(1) = 1/p$, $\kappa(0) = -1/(1-p)$, and $F_r = \mathbb{E}[\|\ell\|^2 \mid R = r]$.

Theorem 1. *For every reward-adapted rule, $\mathbb{E}g = c(p)\nabla p$ with $c(p) = \mathbb{E}\sum_{i \le N} A_i \kappa(r_i)$, and*

$$\mathbb{E}\|g\|^2 = F_1 D_1(p) + F_0 D_0(p) + \|\nabla p\|^2 X(p),$$

with $D_r = \mathbb{E}\sum_{i \le N:\, r_i = r} A_i^2$ and $X = \mathbb{E}\sum_{i \ne j \le N} A_i A_j \kappa(r_i)\kappa(r_j)$. The functions c, D_0, D_1, X and the expected cost $\mathbb{E}N$ depend only on the rule and p.

Proof. $\mathbb{E}[\ell\, 1\{R = 1\}] = \nabla p$ and $\mathbb{E}\ell = 0$ give $\mathbb{E}[\ell \mid R = r] = \kappa(r)\nabla p$. Couple the rule to an infinite i.i.d. sequence; given the reward sequence, N and the A_i are constants and the answers are independent with that conditional mean and conditional second moment F_{r_i}. Take expectations over the rewards, whose law depends only on p. □

The structure breaks under token-level length normalization, where weights depend on lengths rather than rewards, under non-binary rewards, and under clipping or stale samples; exact counterexamples are in the code. All statements are checked by exact enumeration over softmax policies, including two rules with random group size.

3 Exact accounting and the optimal rule

Criterion. Prompts come from a difficulty distribution and gradients of different prompts are treated as orthogonal. With the step size chosen optimally, the improvement in mean accuracy per generated answer is proportional to $\mathrm{Eff} = \mathrm{Sig}^2/(\mathrm{Cost} \cdot \mathrm{M2})$, where $\mathrm{Sig} = \mathbb{E}[c(p)\|\nabla p\|^2]$, M2 is the mean second moment, and Cost the mean number of answers. Because rescaling advantages leaves Eff unchanged, the optimal rule is found by dynamic programming over the lattice of (wrong, correct) counts after a Dinkelbach transform; a solved policy, re-evaluated by the independent lattice engine, matches to six digits.

Rules in use. Table 1 gives efficiency relative to the optimal rule in the main model, $\|\nabla p\|^2 \propto p^2(1-p)^2$ with equal F_0 and F_1 in the high-noise regime that real models occupy. Three conclusions

are exact within the model. DAPO's dynamic sampling has the per-answer efficiency of the fixed group it filters, because dropped groups cost their answers and contribute nothing. Sample-until-correct rules are the least efficient, spending budget on hard prompts that carry little gradient. A probe that abandons all-agreeing prompts and fills the rest is the best rule in use.

Rule	**Uniform**	**Mostly hard**	**U-shaped**	**Mostly easy**
Fixed group of 8 (GRPO, Dr. GRPO, DAPO)	0.61	0.38	0.40	0.38
Fixed group of 16	0.65	0.41	0.43	0.41
Fixed group of 8, std-normalized	0.57	0.35	0.36	0.35
Probe 4, abandon if all agree, fill to 16	0.77	0.60	0.67	0.60
Sample until 1 correct, cap 16	0.26	0.09	0.12	0.30
Sample until 2 correct and 2 wrong, cap 16	0.41	0.22	0.22	0.22

Table 1: Efficiency relative to the optimal rule, by difficulty distribution of the prompts.

Structure of the optimum. The optimal rule samples at least three answers, continues while the minority outcome stays above about a quarter of the answers, and stops when outcomes are lopsided; it assigns advantages state by state, nearly zeroing lopsided low-signal groups. A two-parameter band rule that copies only the stopping region reaches just 18% to 59% of the optimum, so the advantage sizing matters as much as the stopping.

Sensitivity. The size of the gain depends on how $\|\nabla p\|^2$ varies with difficulty: the optimal rule beats the best rule in use by 1.29 to 1.66 times when the signal fades as $p^2(1-p)^2$, by 1.15 to 1.33 times for $p(1-p)$, and by 2.3 to 4.2 times if it is flat. A policy solved under either fading shape keeps at least 96% of the optimum under the other, but falls to 10% to 31% if the truth is flat, and no mixture policy is robust to both. The shape must therefore be measured before the optimal rule is deployed (Section 4).

4 Measuring the four numbers

Method. In Qwen2.5-Math-1.5B (Yang et al., 2024), we sample answers to MATH training problems on-policy and compute exact per-answer gradients in the output projection and the last-layer MLP, using the single-backward identity of the companion STOP study. F_1 and F_0 are averages of squared answer-gradient norms; $\|\nabla p\|^2$ is estimated without bias from pairs, since $\mathbb{E}[(r_i - c)(r_j - c)\langle \ell_i, \ell_j \rangle] = \|\nabla p\|^2$ for independent answers and any c independent of the pair.

Gradient asymmetry. Over 40 prompts with 16 answers each, $F_1 = 4.2 \times 10^5$ (90% interval $[3.6, 4.8] \times 10^5$) and $F_0 = 1.17 \times 10^6$ ($[1.04, 1.30] \times 10^6$), so $F_1/F_0 = 0.36$, while wrong answers are only 9% longer (421 versus 386 tokens). Over all 1.5B parameters, calibration before training gives $F_1/F_0 = 0.395$ from 29 correct and 99 wrong answers. Wrong answers carry larger gradients because their tokens are less likely.

Signal against difficulty. $\|\nabla p\|^2$ is small against per-answer noise (ratio of order 10^3 to 10^4), and 16 answers per prompt do not resolve its shape; heavy tails from a few long wrong answers make naive intervals too narrow. With 96 answers per prompt (4,560 pairs) in the MLP block, over 24 prompts spread across difficulty, the signal is resolved. On prompts with success rate at most 0.15 or at least 0.85 the pooled estimate is 0.73 ± 0.60; on prompts between 0.3 and 0.7 it is 15.5 ± 5.4. The ratio, 0.05, rejects a flat shape (predicted 1) and disfavors $p(1-p)$ (0.36); a weighted fit prefers $p^2(1-p)^2$ (chi-square per prompt 0.35, against 0.54 for $p(1-p)$ and 0.77 for

flat). The signal fades for very easy and very hard prompts, which is the regime where the optimal rule is robust (Section 3). With the measured gradient ratio, the best rule in use reaches 0.46 to 0.63 of the optimum, so the optimal rule's predicted gain is 1.6 to 2.2 times.

5 A tested prediction: scaled failure advantages

Prediction. When $F_0 > F_1$, the optimal advantages weight a failure at about F_1/F_0 relative to a success on mixed groups, whatever the shape of $\|\nabla p\|^2$. Applied to a fixed group of 8 with the measured ratio, this alone raises efficiency by 1.12 to 1.56 times in 11 of 12 combinations of shape and difficulty distribution; the exception is mostly easy prompts with flat signal (0.85). It is a one-line change to GRPO.

Design (pre-registered). Qwen2.5-Math-1.5B base, 3,920 numeric-answer MATH training problems, on-policy updates with one gradient step per batch, 16 prompts by 8 answers, 150 steps, AdamW at 10^{-6}. The arms differ only in advantages, Dr. GRPO's $r - \bar{r}$ (Liu et al., 2025) versus the same with failures scaled by $w = F_1/F_0$ measured before training, so both generate the same number of answers. Two seeds, each running both arms on one L40S. Primary endpoint: greedy accuracy on the 364 numeric MATH-500 problems after 150 steps.

Interim results. Calibration gives $w = 0.395$ and 0.420 in the two seeds. The baseline arm finished at 47.5% (seed 1) and 46.7% (seed 2) greedy accuracy, up from 13.2%. In seed 1 the scaled arm finished at 45.3%, 2.2 points below the baseline, after being tied at steps 50 and 100 (41.5% versus 41.8%, 42.9% versus 42.0%). Its training reward was higher in each of the first four 25-step windows (0.296 versus 0.287, 0.484 versus 0.465, 0.550 versus 0.540, 0.571 versus 0.563) and then tied (0.594 versus 0.592, 0.577 versus 0.581); the mean reward over the last 50 steps is 0.586 in both arms, and answer lengths match (407 tokens). Both arms use the same random numbers at each step, so these are paired comparisons. A single-seed difference of 2.2 points on 364 problems is within evaluation noise (the standard error of one arm's accuracy on 364 problems is 2.6 points), so the seed-1 result is consistent with no effect on final accuracy and a small early speedup. [pending: seed 2 scaled arm; pre-registered verdict]

The optimal rule in training (pre-registered). A second pre-registered comparison deploys the optimal rule itself: answers in blocks of 4 per prompt, a stop-or-continue decision from the solved lookup table after each block, a cap of 16, and the table's per-state advantages. The table is re-solved every 10 steps from a beta-binomial fit to the last 200 prompts. The number of prompts per step is chosen so that cumulative answers track 128 per step, the same budget as the baseline. A probe-then-fill arm (block of 4, abandon if all agree, else fill to 16) runs at the same budget. The prediction is 1.69 to 2.27 times the per-answer training signal of Dr. GRPO and 1.33 to 1.42 times that of probe-then-fill. [pending: optimal and probe arms, two seeds]

6 Related work

The implicit objectives of fixed-size reward-only weightings are given by Davis and Recht (2025), with GRPO, Dr. GRPO, pass@k, and maximum-likelihood variants worked out in Mroueh (2025); Thrampoulidis et al. (2025); Zheng (2026); Tajwar et al. (2026); Heckel et al. (2026). ARCUS proves the score-conditioning identity and the dynamic-sampling corollary (Okonkwo et al., 2026). RL2ML gives the covariance of success-only estimators with fixed group size (Zheng, 2026). Allocation and stopping methods optimize proxies or bounds (Yao et al., 2025; Xiong et al., 2025; SARA authors, 2026; Knapsack RL authors, 2025). Our results add random group sizes, the full second moment

with both F_0 and F_1, the exact optimal rule, and measurements of the four numbers in a real model.

7 Limitations

The efficiency criterion is one step of progress on mean accuracy with orthogonal prompt gradients; it ignores exploration effects and Adam's preconditioning. Cost is counted in answers, not tokens. The shape of $\|\nabla p\|^2$ is measured in one parameter block of one model, and the training comparison is a two-seed pilot.

References

Damek Davis and Benjamin Recht. What is the objective of reasoning with reinforcement learning? *arXiv:2510.13651*, 2025.

Reinhard Heckel, Mahdi Soltanolkotabi, and Christos Thrampoulidis. Asymmetric prompt weighting for RLVR. *arXiv:2602.11128*, 2026.

Knapsack RL authors. Knapsack RL: Unlocking exploration of LLMs via optimizing budget allocation. *arXiv:2509.25849*, 2025.

Zichen Liu et al. Understanding R1-Zero-like training: A critical perspective. *arXiv:2503.20783*, 2025.

Youssef Mroueh. Reinforcement learning with verifiable rewards: GRPO's effective loss, dynamics, and success amplification. *arXiv:2503.06639*, 2025.

Okonkwo, Nomand, Berg, Voss, Park, Hale, Cho, and Reyes. Prompts live on an arc: Gaussian curricula in Fisher–Rao coordinates for rollout-efficient GRPO. *arXiv:2609.38018*, 2026.

SARA authors. Early verdicts, better budgets: Sequential adaptive rollout allocation for compute-efficient RLVR. *arXiv:2607.26253*, 2026.

Tajwar et al. Maximum likelihood reinforcement learning. *arXiv:2602.02710*, 2026.

Christos Thrampoulidis, Sadegh Mahdavi, and Wenlong Deng. Advantage shaping as surrogate reward maximization: Unifying pass@K policy gradients. *arXiv:2510.23049 (TMLR)*, 2025.

Wei Xiong et al. Reinforce-ada: An adaptive sampling framework under non-linear RL objectives. *arXiv:2510.04996*, 2025.

An Yang, Beichen Zhang, Binyuan Hui, et al. Qwen2.5-math technical report: Toward mathematical expert model via self-improvement. *arXiv:2409.12122*, 2024.

Yao et al. Optimizing chain-of-thought reasoners via gradient variance minimization in rejection sampling and RL. *arXiv:2505.02391*, 2025.

Qiying Yu et al. DAPO: An open-source LLM reinforcement learning system at scale. *arXiv:2503.14476*, 2025.

Y. Zheng. Finite-rollout surrogate objectives from reinforcement learning to maximum likelihood. *arXiv:2605.30154*, 2026.