



Affest

ATTESTCOIN PROTOCOL INTEGRATION

Affest + Attestcoin

A simple explanation of how Affest turns activity on Ethereum into a verified, policy-controlled action on Creditcoin.

THE ONE-LINE IDEA

Affest never trusts a backend claim that an Ethereum event happened. Creditcoin verifies the Attestcoin proof before any portfolio action is allowed.

BUIDL CTC 2026 Fall / Testnet submission material

What Attestcoin does for Affest

Affest is an agent-first portfolio dashboard. An AI agent can monitor a strategy and prepare a rebalance, but it cannot turn an unverified message into permission to move funds. Attestcoin is the bridge between the source-chain fact and the destination-chain rule.

In plain English

A user creates a signal on Ethereum Sepolia. Attestcoin produces a cryptographic proof that the transaction is included in an attested Ethereum block. Affest sends that proof to Creditcoin. The Affest verifier checks the proof, the receipt, and the exact event. Only then can the strategy manager allow a rebalance.

The real flow

01 Ethereum Sepolia PortfolioSignal event	02 Attestcoin attestation + proof	03 Creditcoin proof verification	04 Affest policy limits are checked	05 Vault action approved or automatic
---	--	---	--	---

What is verified

CHECK	WHY IT MATTERS
Source-chain key	The proof must identify the configured Ethereum Sepolia chain.
Receipt status	Proof inclusion alone is not enough. The source transaction must have succeeded.
Emitter contract	The event must come from Affest's configured PortfolioSignalEmitter.
Event and fields	Signature, user, asset, signal type, amount, and log index must match the strategy.
Replay key	A verified source log can only be consumed once.

Where the logic lives

The database and worker coordinate the experience. They do not grant permission. Permission is enforced by Creditcoin contracts.

1. SOURCE EVENT

PortfolioSignalEmitter emits a structured event with a unique signalId, the user, an asset, an amount, and signalType.

2. PROOF BUILDER

The worker waits for the source block to be attested, then uses the official @gluwa/usc-sdk proof builder. The response is validated at the TypeScript boundary.

3. CREDITCOIN VERIFIER

AffestAttestationVerifier calls the official BlockProver/native query verifier, decodes the proven transaction, and checks receipt success and application-level event conditions.

4. POLICY AND VAULT

AffestExecutor and AffestStrategyManager enforce owner, asset, adapter, amount, allocation, expiry, cooldown, pause, and replay rules before the vault can act.

Verified testnet addresses

Component	Address
Source signal emitter	0x5b185D...e73C2b6
Attestation verifier	0xD5ed47...9861D1D
Strategy manager	0xf016A4...779020B
Executor	0x254461...44cA883

Current boundary

Affest's Attestcoin verification path is real and contract-enforced. The CC3 swap adapter is a labelled demo adapter while reliable, documented CC3 DEX liquidity is unavailable. The demo never presents that adapter as a production exchange.

Judge takeaway: the AI can suggest and coordinate, but it cannot manufacture the cross-chain fact or bypass the user's on-chain limits.