LX-240 Industrial Air Compressor

Key features

- Oil-lubricated twin-cylinder pump
- Thermal overload protection
- Low-noise operation at 68 dB(A)
- 50 l galvanised tank

Certifications

- CE marking
- EN 1012-1
- RoHS compliant

The LX-240 is a compact, belt-driven compressor for workshops and small production lines. It delivers 240 litres of free air per minute at 8 bar and starts reliably at low temperatures.

Technical specifications

Parameter	Value	Unit
Performance		
Maximum working pressure	10	bar
Free air delivery at 8 bar	240	l/min
Tank volume	50	l
Duty cycle	70	%
Electrical		
Rated voltage	230	V
Motor power	1.8	kW
Starting current	24	A
Physical		
Noise level at 1 m	68	dB(A)
Weight	46	kg
Inlet connection	G 1/4	inch

Performance data

Free air delivery falls as the working pressure rises, as shown below.

Pressure (bar)	Delivery (l/min)	Power (kW)
4	286	1.4
6	262	1.6
8	240	1.8
10	214	1.8

Dimensions

Length	780 mm
Width	340 mm
Height	690 mm
Wheel diameter	200 mm

Ordering information

Order code	Description	Voltage	List price (EUR)
LX240-230-S	LX-240 compressor, 230 V, standard plug	230 V	689.00
LX240-230-E	LX-240 compressor, 230 V, with hour meter	230 V	742.00
LX240-115-S	LX-240 compressor, 115 V, standard plug	115 V	689.00

Accessories

- Air hose sets
  - 10 m polyurethane hose with quick coupling
  - 20 m reinforced hose on a wall reel
- Filtration
  - Coalescing filter, 5 micron
- Anti-vibration feet, set of four

Warranty

The compressor carries a warranty of 24 months from the date of purchase. The warranty covers defects in material and workmanship but not wear parts such as belts and valves.