Safety Data Sheet: KLARSOL Industrial Degreaser 500

according to Regulation (EC) No 1907/2006 (REACH), Annex II, as amended

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name	KLARSOL Industrial Degreaser 500
Product code	MCP-KL500
UFI	N7Q0-T0VG-8005-2K4R

1.2 Relevant identified uses and uses advised against

Water-based alkaline cleaner for removing oil and grease from metal surfaces in industrial settings. This product is not intended for use by consumers.

1.3 Details of the supplier of the safety data sheet

Supplier	Merrow Chemical Products Ltd. Unit 12, Riverside Works, Leek ST13 6DT, United Kingdom
Telephone	+44 1538 300 410
E-mail (competent person)	sds@merrow-chemical.example
1.4 Emergency telephone number	+44 1538 300 499 (24 hours)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Hazard class and category	Hazard statement
Acute Tox. 4 (oral)	H302: Harmful if swallowed.
Acute Tox. 4 (inhalation)	H332: Harmful if inhaled.
Skin Irrit. 2	H315: Causes skin irritation.
Eye Dam. 1	H318: Causes serious eye damage.

2.2 Label elements

Signal word: **DANGER**

Precautionary statements:

P280 Wear protective gloves and eye protection.

P301+P312 IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents and container in accordance with local regulations.

2.3 Other hazards

The mixture does not contain substances assessed as PBT or vPvB. No endocrine-disrupting properties have been identified.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Substance	Identifiers	Concentration (% w/w)	Classification (EC) No 1272/2008
2-butoxyethanol	CAS 111-76-2 EC 203-905-0	5 – < 10	Acute Tox. 4, H302, H312, H332 Skin Irrit. 2, H315; Eye Irrit. 2, H319
Sodium metasilicate	CAS 6834-92-0 EC 229-912-9	1 – < 3	Met. Corr. 1, H290 Skin Corr. 1B, H314; STOT SE 3, H335
Alcohols, C9–11, ethoxylated	CAS 68439-46-3 Polymer	1 – < 5	Acute Tox. 4, H302 Eye Dam. 1, H318

The full text of the hazard statements is given in section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- After inhalation: move the person to fresh air and keep at rest.
- After skin contact: remove contaminated clothing and wash the skin with plenty of water.
- After eye contact: rinse immediately with plenty of water for at least 15 minutes.
  - Hold the eyelids apart while rinsing.
  - Get medical attention without delay.
- After ingestion: rinse the mouth with water. Do not induce vomiting.

4.2 Most important symptoms and effects

Contact with the eyes causes pain, redness and a risk of permanent damage. Inhalation of spray mist may cause headache and nausea.

SECTION 5: Firefighting measures

The product is not flammable. Use extinguishing media appropriate to the surrounding fire. Firefighters should wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

Absorb spills with sand or another inert material and place in a closed container for disposal. Prevent the product from entering drains and surface water.

SECTION 7: Handling and storage

Store in the original container at temperatures between 5 °C and 35 °C. Keep away from acids and from aluminium and zinc surfaces.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Substance	Long-term exposure limit (8-h TWA)		Short-term exposure limit (15 min)		Source
	ppm	mg/m³	ppm	mg/m³	
2-butoxyethanol	25	123	50	246	UK EH40/2005
Sodium metasilicate	–	–	–	–	No limit established

8.2 Exposure controls

Eye protection	Tightly fitting safety goggles (EN 166).
Hand protection	Nitrile rubber gloves, thickness at least 0.4 mm, breakthrough time over 480 minutes (EN ISO 374).
Respiratory protection	Not normally required; use a filter mask type A2/P2 when spraying in confined spaces.

SECTION 9: Physical and chemical properties

Property	Value	Method
Physical state	Liquid	Visual
Colour	Pale yellow	Visual
pH (undiluted)	12.8	ISO 4316
Relative density at 20 °C	1.06	OECD 109
Solubility in water	Fully miscible	–

SECTION 10: Stability and reactivity

The product is stable under normal conditions of storage and use. Contact with strong acids releases heat.

SECTION 16: Other information

Changes compared with the previous version are made in sections 2, 3 and 8. This safety data sheet replaces all earlier versions.