PSU-450 Series DIN-Rail Power Supplies

The PSU-450 series converts single-phase mains into a stable 24 V or 48 V supply for control cabinets. All models are cooled by natural convection and need no fan.

Key features

- Wide input range for use on any mains supply
- Power reserve of 20% for five seconds
- DC OK relay contact for remote monitoring
- Tool-free mounting on 35 mm rails

Typical applications

- Machine control cabinets
- Building automation panels
- Conveyor and packaging lines
- Water treatment plants

Table 1. Output ratings by model

Model	Output			Efficiency	Width	Weight
	Voltage	Current	Power			
PSU-450-24	24 V DC	10 A	240 W	93.5%	40 mm	0.62 kg
PSU-450-24H	24 V DC	20 A	480 W	94.8%	60 mm	0.98 kg
PSU-450-48	48 V DC	5 A	240 W	94.0%	40 mm	0.61 kg
PSU-450-48H	48 V DC	10 A	480 W	95.2%	60 mm	0.97 kg

Derating and installation

Above 60 °C the output power must be reduced by 2.5% per degree. Leave at least 25 mm of free space above and below each unit so that air can circulate. Two units of the same model can be connected in parallel for redundancy. In that case, fit a redundancy module to decouple the outputs.

General data	
Input voltage	100–240 V AC
Frequency	50/60 Hz
Operating temperature	−25 to +70 °C
Protection class	IP20
MTBF	> 900,000 h

Ordering information

Order code	Description
HE-450-24	PSU-450-24 with screw terminals
HE-450-24H	PSU-450-24H with screw terminals
HE-450-48P	PSU-450-48 with push-in terminals
HE-450-48HP	PSU-450-48H with push-in terminals