



Q Commands + Code + Text ▶ Run all

RAM
Disk

Files



sample_data

Cleaned_Social_Engine_Data.csv

EDA_Visual.png

Social_Engine_Posts_Corrupted....

Social_Engine_Users.csv

Disk 87.40 GB available

[11]

✓ 0s



```
print(""" --- E3: Average Engagement by Platform --- """)
display(pd.read_sql_query(query, conn))

# E3 Query
run_sql("""
SELECT platform, AVG(likes) AS avg_likes, AVG(shares) AS avg_shares,
      AVG(comments) AS avg_comments, AVG(likes + shares + comments) AS avg_total_engagement
FROM social_data
GROUP BY platform ORDER BY avg_total_engagement DESC;
""", "E3: Average Engagement by Platform")

# M2 Query
run_sql("""
SELECT
  CASE WHEN follower_count >= 25000 THEN 'High Follower (>= 25k)' ELSE 'Low Follower (< 25k)' END AS user_category,
  COUNT(DISTINCT user_id) as num_users, COUNT(post_id) as total_posts,
  AVG(likes + shares + comments) AS avg_engagement_per_post
FROM social_data GROUP BY user_category;
""", "M2: Do High Follower Users Get More Engagement?")

# H6 Query
run_sql("""
WITH OverallAvg AS (SELECT AVG(likes + shares + comments) AS global_avg FROM social_data),
UserStats AS (
  SELECT user_id, location, follower_count, COUNT(post_id) AS num_posts,
        AVG(likes + shares + comments) AS avg_engagement, SUM(likes + shares + comments) AS total_engagement,
        SUM(CASE WHEN shares > likes THEN 1 ELSE 0 END) AS suspicious_posts
  FROM social_data GROUP BY user_id, location, follower_count
)
SELECT u.user_id, u.location, u.follower_count, u.num_posts, u.avg_engagement, u.total_engagement
FROM UserStats u CROSS JOIN OverallAvg o
WHERE u.follower_count < 10000 AND u.avg_engagement > o.global_avg AND u.suspicious_posts > 0
ORDER BY u.total_engagement DESC LIMIT 10;
""", "H6: Find the Most Suspicious High Impact Users")
```

--- E3: Average Engagement by Platform ---