

```

#include<stdio.h>
#include<stdlib.h>
int main()
{
    int RQ[100],i,j,n,TotalHeadMoment=0,initial,size,move;
    printf("Enter the number of Requests\n");
    scanf("%d",&n);
    printf("Enter the Requests sequence\n");
    for(i=0;i<n;i++)
        scanf("%d",&RQ[i]);
    printf("Enter initial head position\n");
    scanf("%d",&initial);
    printf("Enter total disk size\n");
    scanf("%d",&size);
    printf("Enter the head movement direction for high 1 and for low 0\n");
    scanf("%d",&move);

    // logic for C-look disk scheduling

    /*logic for sort the request array */
    for(i=0;i<n;i++)
    {
        for( j=0;j<n-i-1;j++)
        {
            if(RQ[j]>RQ[j+1])
            {
                int temp;
                temp=RQ[j];
                RQ[j]=RQ[j+1];
                RQ[j+1]=temp;
            }
        }
    }

    int index;
    for(i=0;i<n;i++)
    {
        if(initial<RQ[i])
        {
            index=i;
            break;
        }
    }

    // if movement is towards high value
    if(move==1)
    {
        for(i=index;i<n;i++)
        {
            TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
            initial=RQ[i];
        }
    }
}

```

```

    }

    for( i=0;i<index;i++)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }
}
// if movement is towards low value
else
{
    for(i=index-1;i>=0;i--)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }

    for(i=n-1;i>=index;i--)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }
}

printf("Total head movement is %d",TotalHeadMoment);
return 0;
}
/*Output:-

```

Enter the number of Request

8

Enter the Requests Sequence

95 180 34 119 11 123 62 64

Enter initial head position

50

Enter the head movement direction for high 1 and for low 0

1

Total head movement is 322\*/