

Name : Mayuri Shridatta Yerande
Class : D15B
Roll no. : 70

Experiment – Module 4: MongoDB

AIM: To study and implement Module 4: MongoDB and REST API

PROBLEM STATEMENT:

1. Build a RESTful API using MongoDB.
2. Create a full database in MongoDB
 - a) create a bd: question-> code-> snapshot of result
 - b) create collections
 - c) create doc: insert one doc and insert many documents at once
 - d) delta one or many documents
 - e) search with conditions

IMPLEMENTATION:

★ INSTALLATION:

Link: <https://www.mongodb.com/try/download/community>

Link: <https://www.mongodb.com/try/download/shell>

- After Installation, Agree to the terms and conditions, click on next
- Choose “complete” package to install all the features of MongoDB
- Choose the default service name and click install
- Check the installation using cmd
- Add the environment variables for both MongoDB and MongoShell

```
C:\Users\mayuri>mongod --version
db version v6.0.5
Build Info: {
  "version": "6.0.5",
  "gitVersion": "c9a99c120371d4d4c52cbb15dac34a36ce8d3b1d",
  "modules": [],
  "allocator": "tcmalloc",
  "environment": {
    "distmod": "windows",
    "distarch": "x86_64",
    "target_arch": "x86_64"
  }
}
```

★ REST API

1. In command prompt, Run the following commands

- npm init
- npm install express
- npm install mongoose@6.10.2
- npm install body-parser
- npm install -g nodemon

2. Create index.js, contactModel.js, contactcontroller.js, api-routes.js files

3. Mongodb --> create a db named as “phone” with collection name as “one” and update that name in index.js

Index.js

```
// Import express
let express = require('express');
// Import Body parser
let bodyParser = require('body-parser');
// Import Mongoose
let mongoose = require('mongoose');
// Initialise the app
let app = express();

// Import routes
let apiRoutes = require("./api-routes");
// Configure bodyparser to handle post requests
app.use(bodyParser.urlencoded({
  extended: true
}));
app.use(bodyParser.json());
// Connect to Mongoose and set connection variable
mongoose.connect('mongodb://localhost:27017/phone', { useNewUrlParser: true });
var db = mongoose.connection;
```

```
// Added check for DB connection
if (!db)
  console.log("Error connecting db")
else
  console.log("Db connected successfully")

// Setup server port
var port = process.env.PORT || 8080;

// Send message for default URL
app.get('/', (req, res) => res.send('Hello World with Express'));

// Use Api routes in the App
app.use('/api', apiRoutes);
// Launch app to listen to specified port
app.listen(port, function() {
  console.log("Running RestHub on port " + port);
});
```

contactModel.js

```
var mongoose = require('mongoose'); // Setup schema
var contactSchema = mongoose.Schema({
  name: {
    type: String,
    required: true
  },
  email: {
    type: String,
    required: true
  },
  gender: String,
  phone: String,
  create_date: {
    type: Date,
    default: Date.now
  }
}); // Export Contact model
var Contact = module.exports = mongoose.model('contact', contactSchema);
module.exports.get = function(callback, limit) {
  Contact.find(callback).limit(limit);
}
```

ContactController.js

```
// contactController.js// Import contact model
Contact = require('./contactModel'); // Handle index actions
exports.index = function(req, res) {
    Contact.get(function(err, contacts) {
        if (err) {
            res.json({
                status: "error",
                message: err,
            });
        }
        res.json({
            status: "success",
            message: "Contacts retrieved successfully",
            data: contacts
        });
    });
}; // Handle create contact actions
exports.new = function(req, res) {
    var contact = new Contact();
    contact.name = req.body.name ? req.body.name : contact.name;
    contact.gender = req.body.gender;
    contact.email = req.body.email;
    contact.phone = req.body.phone; // save the contact and check for errors
    contact.save(function(err) {
        if (err)
            res.json(err);
        res.json({
            message: 'New contact created!',
            data: contact
        });
    });
}; // Handle view contact info
exports.view = function(req, res) {
    Contact.findById(req.params.contact_id, function(err, contact) {
        if (err)
            res.send(err);
        res.json({
            message: 'Contact details loading..',
            data: contact
        });
    });
}; // Handle update contact info
exports.update = function(req, res) {
    Contact.findById(req.params.contact_id, function(err, contact) {
        if (err)
            res.send(err);
        contact.name = req.body.name ? req.body.name : contact.name;
        contact.gender = req.body.gender;
```

```
        contact.email = req.body.email;
        contact.phone = req.body.phone; // save the contact and check for
errors
        contact.save(function(err) {
            if (err)
                res.json(err);
            res.json({
                message: 'Contact Info updated',
                data: contact
            });
        });
    });
}; // Handle delete contact
exports.delete = function(req, res) {
    Contact.remove({
        _id: req.params.contact_id
    }, function(err, contact) {
        if (err)
            res.send(err);
        res.json({
            status: "success",
            message: 'Contact deleted'
        });
    });
};
};
```

api-routes.js


```
// api-routes.js// Initialize express router
let router = require('express').Router(); // Set default API response
router.get('/', function(req, res) {
    res.json({
        status: 'API Its Working',
        message: 'Welcome to RESTHub crafted with love!',
    });
}); // Import contact controller
var contactController = require('./contactController'); // Contact routes
router.route('/contacts')
    .get(contactController.index)
    .post(contactController.new);
router.route('/contacts/:contact_id')
    .get(contactController.view)
    .patch(contactController.update)
    .put(contactController.update)
    .delete(contactController.delete); // Export API routes
module.exports = router;
```

4. Run node index in vscode terminal and check if db is connected successfully.

```
PS C:\node projects\RESTHub> node index
Db connected successfully
(node:19568) [MONGODBSE] DeprecationWarning: Mongoose: the `strictQuery` option will be switched back to `false` by default in Mongoose 7. Use `mongoose.set('strictQuery', false);` if you want to prepare for this change. Or use `mongoose.set('strictQuery', true);` to suppress this warning.
(Use `node --trace-deprecation ...` to show where the warning was created)
Running RestHub on port 8080
```


5. Install thunder client

6. Go to localhost:5053/api/contacts




```
{\"status\": \"success\", \"message\": \"Contacts retrieved successfully\", \"data\": []}
```

7. GET Contacts




```
{\"status\": \"success\", \"message\": \"Contacts retrieved successfully\", \"data\": [{\"_id\": \"643566ce6bb57b8d4df60a32\", \"create_date\": \"2023-04-11T13:55:26.382Z\", \"name\": \"ghanihtha\", \"gender\": \"female\", \"email\": \"ghanihtha.talele09@gmail.com\", \"phone\": \"9876543210\", \"_v\": 0}, {\"_id\": \"643567306bb57b8d4df60a35\", \"create_date\": \"2023-04-11T13:57:13.113Z\", \"name\": \"aditi\", \"gender\": \"female\", \"email\": \"aditi.miniyar@gmail.com\", \"phone\": \"9876543210\", \"_v\": 0}, {\"_id\": \"643567810bb57b8d4df60a38\", \"create_date\": \"2023-04-11T13:58:25.913Z\", \"name\": \"mayuri\", \"gender\": \"female\", \"email\": \"mayuri.yerande@gmail.com\", \"phone\": \"9876543210\", \"_v\": 0}]}}
```


8. POST A new Value




```
{\"message\": \"New contact created!\", \"data\": {\"_id\": \"643567810bb57b8d4df60a38\", \"create_date\": \"2023-04-11T13:58:25.913Z\", \"name\": \"mayuri\", \"gender\": \"female\", \"email\": \"mayuri.yerande@gmail.com\", \"phone\": \"9876543210\", \"_v\": 0}}
```



9. PUT - Updating email value



10. DELETE contact



★ DATABASE

• Creating database

```
cscorner> use mayuridb
switched to db mayuridb
```

• Creating collections

```
mayuridb> db.createCollection("students")
{ ok: 1 }

mayuridb> db.createCollection("teachers")
{ ok: 1 }

mayuridb> db.createCollection("subjects")
{ ok: 1 }
```

```
mayuridb> show collections
students
subjects
teachers
```

- **Inserting values**

- **(Inserting one value at a time)**

```
mayuridb> db.students.insertOne({"rollno":1,"name":"mayuri"})
{
  acknowledged: true,
  insertedId: ObjectId("643411fda406ea8eb3a09029")
}
```

- **(Inserting many values at a time)**

```
mayuridb> db.students.insertOne([{"rollno":4,"name":"sakshi"}, {"rollno":5,"name":"pushkaraj"}])
{
  acknowledged: true,
  insertedId: ObjectId("64341428a406ea8eb3a0902c")
}
```

```
mayuridb> db.students.find().pretty()
[
  {
    _id: ObjectId("643411fda406ea8eb3a09029"),
    rollno: 1,
    name: 'mayuri'
  },
  {
    _id: ObjectId("64341381a406ea8eb3a0902a"),
    rollno: 2,
    name: 'samiksha'
  },
  {
    _id: ObjectId("6434139da406ea8eb3a0902b"),
    rollno: 3,
    name: 'riya'
  },
  {
    '0': { rollno: 4, name: 'sakshi' },
    '1': { rollno: 5, name: 'pushkaraj' },
    _id: ObjectId("64341428a406ea8eb3a0902c")
  }
]
```

- **Deleting Values**

- **(Deleting one value at a time)**

- **(Deleting using object ID of that value)**

```
mayuridb> db.students.deleteOne({"_id" : ObjectId("6434139da406ea8eb3a0902b")})
{ acknowledged: true, deletedCount: 1 }
```


- (Deleting many values at a time)
- There are three roll number 1 hence we will drop them all

```
mayuridb> db.students.find().pretty()
[
  {
    _id: ObjectId("643411fda406ea8eb3a09029"),
    rollno: 1,
    name: 'mayuri'
  },
  {
    '0': { rollno: 4, name: 'sakshi' },
    '1': { rollno: 5, name: 'pushkaraj' },
    _id: ObjectId("64341428a406ea8eb3a0902c")
  },
  {
    _id: ObjectId("64341732a406ea8eb3a0902d"),
    rollno: 1,
    name: 'justin'
  },
  {
    _id: ObjectId("64341740a406ea8eb3a0902e"),
    rollno: 1,
    name: 'lance'
  }
]

mayuridb> db.students.deleteMany({"rollno":1})
{ acknowledged: true, deletedCount: 3 }
mayuridb>
```

- Search with conditions

- Find

```
mayuridb> db.subjects.find({"name":"webx"})
[
  {
    _id: ObjectId("64341847a406ea8eb3a09031"),
    name: 'webx',
    score: 80
  }
]
```

- Distinct

```
mayuridb> db.subjects.distinct("score")
[ 10, 40, 50, 70, 80 ]
mayuridb> ■
```

- Count

```
mayuridb> db.subjects.count()
6
mayuridb> █
```

➤ **Displaying score of subjects greater than 40**

```
mayuridb> db.subjects.find({score:{>40}});
[
  { _id: ObjectId("64341847a406ea8eb3a0902f"), name: 'wt', score: 50 },
  {
    _id: ObjectId("64341847a406ea8eb3a09030"),
    name: 'aids',
    score: 70
  },
  {
    _id: ObjectId("64341847a406ea8eb3a09031"),
    name: 'webx',
    score: 80
  },
  {
    _id: ObjectId("6434191ba406ea8eb3a09034"),
    name: 'webx',
    score: 50
  }
]
```

➤ **Displaying score of subjects lower than 80**

```
mayuridb> db.subjects.find({score:{<80}});
[
  { _id: ObjectId("64341847a406ea8eb3a0902f"), name: 'wt', score: 50 },
  {
    _id: ObjectId("64341847a406ea8eb3a09030"),
    name: 'aids',
    score: 70
  },
  { _id: ObjectId("6434191ba406ea8eb3a09032"), name: 'wt', score: 10 },
  {
    _id: ObjectId("6434191ba406ea8eb3a09033"),
    name: 'aids',
    score: 40
  },
  {
    _id: ObjectId("6434191ba406ea8eb3a09034"),
    name: 'webx',
    score: 50
  }
]
..
```

CONCLUSION: Thus we successfully installed MongoDB and Mongo Shell in our system. We implemented the REST API with it. Then we performed CRUD operations on the database in mongo shell.