TI-DE

Threat Intelligence & Detection Engineering

TLP:WHITE — Unrestricted Distribution

LiteLLM PyPI Supply Chain Attack by TeamPCP

CVE-2026-33634 · CVSS 9.4 Critical · 9-Platform Detection Package

REPORT DATE	THREAT ACTOR	CVSS SCORE	FIRST SEEN	PLATFORMS
2026-03-26	TeamPCP	9.4 Critical	2026-03-19	9

TI-DE · github.com/mazlumbaydar/TI-DE
Automated Daily Detection Briefing — Mon–Fri 10:00 TR

Prepared by: Mazlum Baydar
Detection Engineering Team

Executive Summary

- TeamPCP injected a malicious backdoor into **litellm 1.82.7 and 1.82.8** on PyPI, a widely-used AI/LLM proxy library with millions of downloads.
- The attack installs **litellm_init.pth** into Python site-packages — auto-executes on every Python startup (T1546.018), giving persistent code execution without any user action.
- Payload beacons to TeamPCP C2 domains (**models.litellm.cloud**, **checkmarx.zone**) masquerading as legitimate security vendor infrastructure.
- Persistence via **systemd user service** (sysmon.service) mimicking Sysinternals Sysmon to evade analyst suspicion.
- Any system that ran `pip install litellm` between **2026-03-19 and 2026-03-24** should be treated as compromised and immediately isolated.

CVE Details

CVSS SCORE	SEVERITY	CVE ID	VERSIONS	ATTACK VECTOR
9.4	CRITICAL	CVE-2026-33634	1.82.7 & 1.82.8	PyPI Supply Chain

Attack Chain

STAGE 1	STAGE 2	STAGE 3	STAGE 4	STAGE 5
Supply Chain	**.pth Hook**	**Persistence**	**C2 Beacon**	**Credential Theft**
Malicious litellm uploaded to PyPI	litellm_init.pth auto-executes on every Python startup	sysmon.py + systemd user service installed	Connects to models.litellm.cloud, checkmarx.zone	Harvests API keys, env vars, secrets
T1195.001	T1546.018	T1547.016	T1041	T1552

MITRE ATT&CK Techniques

Technique	Name	Usage in this Campaign
T1195.001	Supply Chain: Software Dependencies	Malicious litellm package on PyPI
T1546.018	Python Path Interception (.pth)	litellm_init.pth auto-executed on startup
T1547.016	Boot Autostart: systemd Service	sysmon.service user-level persistence
T1036.005	Masquerading: Match Legitimate Name	sysmon.py mimics Sysinternals Sysmon
T1041	Exfiltration Over C2 Channel	Beaconing to typosquat C2 domains

Technique	Name	Usage in this Campaign
T1552	Unsecured Credentials	Harvests API keys and environment variables

Indicators of Compromise

Type	Value	Description	Conf.	Source	Source URL
DOMAIN	`models.litellm.cloud`	TeamPCP C2 typosquat — NOT litellm.ai	**High**	ReversingLabs	github.com/reversinglabs/reversinglabs-yara-rules
DOMAIN	`checkmarx.zone`	TeamPCP C2 typosquat	**High**	Sysdig	sysdig.com/blog/teampcp-pypi-supply-chain/
IP	`45.148.10.212`	TeamPCP staging (scan.aquasecurity.org)	**High**	Snyk	snyk.io/articles/poisoned-security-scanner-backdooring-litellm/
IP	`83.142.209.11`	TeamPCP staging (checkmarx.zone)	**High**	Sysdig	sysdig.com/blog/teampcp-pypi-supply-chain/
SHA256	`ceNa7wMJnNHy1kRnNCcwJaFjWX3pORLfMh7xGL8TUjg`	litellm_init.pth payload (34628 bytes)	**High**	FutureSearch	futuresearch.ai/blog/litellm-pypi-supply-chain-attack/
FILE	`litellm_init.pth`	Malicious .pth hook in site-packages	**High**	Multiple	futuresearch.ai/blog/litellm-pypi-supply-chain-attack/
FILE	`~/.config/sysmon/sysmon.py`	TeamPCP persistent backdoor script	**High**	ReversingLabs	github.com/reversinglabs/reversinglabs-yara-rules
FILE	`~/.config/systemd/user/sysmon.service`	TeamPCP systemd persistence unit	**High**	Datadog	securitylabs.datadoghq.com/articles/litellm-compromised-pypi-teampcp
FILE	`/tmp/pglog`	Temporary payload drop	**Medium**	Sonatype	sonatype.com/blog/litellm-pypi-supply-chain
FILE	`/tmp/.pg_state`	Infection state tracker	**Medium**	Sonatype	sonatype.com/blog/litellm-pypi-supply-chain
PACKAGE	`litellm==1.82.7`	Malicious PyPI package version	**High**	PyPI/Checkmarx	pypi.org/project/litellm/

Type	Value	Description	Conf.	Source	Source URL
PACKAGE	`litellm==1.82.8`	Malicious PyPI package (.pth variant)	**High**	PyPI/ReversingLabs	futuresearch.ai/blog/litellm-pypi-supply-chain-attack/
ARCHIVE	`tpcp.tar.gz`	TeamPCP malware archive	**High**	Kaspersky	kaspersky.com/blog/critical-supply-chain-attack-trivy-litellm-checkmarx-teampcp/
CVE	`CVE-2026-33634`	LiteLLM supply chain — CVSS 9.4	**High**	NVD	nvd.nist.gov/vuln/detail/CVE-2026-33634

Detection Rules

All rules verified against official platform documentation. Ready for direct deployment.

Sigma YAML · SIEM-Agnostic

```
# CVE-2026-33634 — LiteLLM PyPI Supply Chain Attack (TeamPCP)
# CVSS 9.4 Critical | Threat Actor: TeamPCP | First Seen: 2026-03-24
# ATT&CK: T1195.001, T1546.018, T1547.016, T1041, T1552

---
title: TeamPCP - Malicious LiteLLM PyPI Package Installation
id: a1b2c3d4-1111-4444-aaaa-000000000001
status: stable
description: >
  Detects installation of malicious LiteLLM PyPI packages (versions 1.82.7 and 1.82.8)
  used by TeamPCP supply chain campaign. These versions install litellm_init.pth
  which executes arbitrary code on every Python interpreter startup (T1546.018).
author: Mazlum BAYDAR
date: 2026/03/26
references:
  - https://sysdig.com/blog/teampcp-pypi-supply-chain/
  - https://futuresearch.ai/blog/litellm-pypi-supply-chain-attack/
logsource:
  category: process_creation
  product: linux
detection:
  selection_pip:
    Image|endswith:
      - '/pip'
      - '/pip3'
    CommandLine|contains:
      - 'litellm==1.82.7'
      - 'litellm==1.82.8'
  selection_python_m_pip:
    Image|endswith: '/python'
    CommandLine|contains|all:
      - '-m pip'
      - 'install'
    CommandLine|contains:
      - 'litellm==1.82.7'
      - 'litellm==1.82.8'
  condition: 1 of selection_*
falsepositives:
  - None — these exact version strings are confirmed malicious
level: critical
tags:
  - attack.t1195.001
  - attack.initial_access
  - cve.2026.33634

---
title: TeamPCP - Malicious .pth Hook File in site-packages (T1546.018)
id: a1b2c3d4-2222-4444-aaaa-000000000002
status: stable
description: >
  Detects creation of litellm_init.pth in any Python site-packages directory.
  Python .path configuration files (.pth) are auto-executed on interpreter
  startup, making this a stealthy persistence and code execution mechanism.
author: Mazlum BAYDAR
date: 2026/03/26
references:
  - https://futuresearch.ai/blog/litellm-pypi-supply-chain-attack/
  - https://github.com/reversinglabs/reversinglabs-yara-rules
logsource:
  category: file_event
  product: linux
detection:
  selection:
    TargetFilename|contains: 'site-packages'
    TargetFilename|endswith: 'litellm_init.pth'
  condition: selection
falsepositives:
  - None — legitimate litellm does not ship this file
level: critical
```

```
tags:
  - attack.t1546.018
  - attack.persistence
  - cve.2026.33634

---
title: TeamPCP - Backdoor Script Created at Hidden sysmon Path
id: a1b2c3d4-3333-4444-aaaa-000000000003
status: stable
description: >
  Detects creation of ~/.config/sysmon/sysmon.py, TeamPCP's persistent
  backdoor. The path mimics the legitimate Sysinternals Sysmon to evade detection.
author: Mazlum BAYDAR
date: 2026/03/26
references:
  - https://github.com/reversinglabs/reversinglabs-yara-rules
logsource:
  category: file_event
  product: linux
detection:
  selection:
    TargetFilename|contains: '/.config/sysmon/'
    TargetFilename|endswith: 'sysmon.py'
  condition: selection
falsepositives:
  - None expected on Linux systems
level: high
tags:
  - attack.t1036.005
  - attack.defense_evasion
  - cve.2026.33634

---
title: TeamPCP - systemd User Persistence Unit (T1547.016)
id: a1b2c3d4-4444-4444-aaaa-000000000004
status: stable
description: >
  Detects creation of ~/.config/systemd/user/sysmon.service.
  TeamPCP uses user-level systemd to survive reboots without root privileges.
author: Mazlum BAYDAR
date: 2026/03/26
references:
  - https://securitylabs.datadoghq.com/articles/litellm-compromised-pypi-teampcp-supply-chain-campaign/
logsource:
  category: file_event
  product: linux
detection:
  selection:
    TargetFilename|contains: '/.config/systemd/user/'
    TargetFilename|endswith: 'sysmon.service'
  condition: selection
falsepositives:
  - None — legitimate sysmon.service does not exist in Linux user systemd
level: high
tags:
  - attack.t1547.016
  - attack.persistence
  - cve.2026.33634

---
title: TeamPCP - DNS Query to C2 Typosquat Domains
id: a1b2c3d4-5555-4444-aaaa-000000000005
status: stable
description: >
  Detects DNS resolution of confirmed TeamPCP C2 domains.
  models.litellm.cloud impersonates litellm.ai; checkmarx.zone impersonates
  the legitimate Checkmarx vendor.
author: Mazlum BAYDAR
date: 2026/03/26
references:
  - https://sysdig.com/blog/teampcp-pypi-supply-chain/
logsource:
  category: dns_query
```

```
  product: linux
detection:
  selection:
    QueryName|endswith:
      - 'models.litellm.cloud'
      - 'checkmarx.zone'
  condition: selection
falsepositives:
  - None — confirmed malicious C2 infrastructure
level: critical
tags:
  - attack.t1041
  - attack.command_and_control
  - cve.2026.33634

---
title: TeamPCP - Network Connection to C2 IP Infrastructure
id: a1b2c3d4-6666-4444-aaaa-000000000006
status: stable
description: >
  Detects outbound connections to TeamPCP staging infrastructure.
  45.148.10.212 masquerades as scan.aquasecurity.org.
  83.142.209.11 serves as the checkmarx.zone C2 endpoint.
author: Mazlum BAYDAR
date: 2026/03/26
references:
  - https://snyk.io/articles/poisoned-security-scanner-backdooring-litellm/
logsource:
  category: network_connection
  product: linux
detection:
  selection:
    DestinationIp:
      - '45.148.10.212'
      - '83.142.209.11'
  condition: selection
falsepositives:
  - None — confirmed malicious IPs
level: critical
tags:
  - attack.t1041
  - attack.command_and_control
  - cve.2026.33634

---
title: TeamPCP - Temporary Payload Drop Files in /tmp
id: a1b2c3d4-7777-4444-aaaa-000000000007
status: stable
description: >
  Detects creation of /tmp/pglog (payload staging) and /tmp/.pg_state
  (infection state tracking) used by TeamPCP to manage payload execution.
author: Mazlum BAYDAR
date: 2026/03/26
references:
  - https://www.sonatype.com/blog/litellm-pypi-supply-chain
logsource:
  category: file_event
  product: linux
detection:
  selection:
    TargetFilename:
      - '/tmp/pglog'
      - '/tmp/.pg_state'
  condition: selection
falsepositives:
  - PostgreSQL may write to /tmp/pglog — verify initiating process is not python/pip
level: medium
tags:
  - attack.t1036
  - attack.defense_evasion
  - cve.2026.33634
```

YARA Binary & File Analysis

```
/*
 * CVE-2026-33634 — LiteLLM PyPI Supply Chain Attack (TeamPCP)
 * CVSS 9.4 Critical | Threat Actor: TeamPCP | First Seen: 2026-03-24
 * ATT&CK: T1195.001, T1546.018, T1547.016, T1041, T1552
 */

rule TeamPCP_LiteLLM_PTH_Hook_File
{
    meta:
        description   = "Detects litellm_init.pth malicious Python path hook installed by TeamPCP supply
chain attack"
        author        = "Mazlum BAYDAR"
        date          = "2026-03-26"
        severity      = "critical"
        mitre_attack  = "T1546.018"
        reference     = "https://futuresearch.ai/blog/litellm-pypi-supply-chain-attack/"
        hash_sha256   = "ceNa7wMJnNHy1kRnNCcwJaFjWX3pORLfMh7xGL8TUjg"

    strings:
        /* .pth files that execute code use 'import' prefix on each line */
        $pth_exec1    = "import subprocess" ascii nocase
        $pth_exec2    = "import os" ascii nocase
        $pth_exec3    = "import sys" ascii nocase

        /* TeamPCP C2 domains embedded in payload */
        $c2_domain1   = "models.litellm.cloud" ascii wide
        $c2_domain2   = "checkmarx.zone" ascii wide

        /* TeamPCP artifact paths */
        $path_sysmon  = ".config/sysmon/sysmon.py" ascii
        $path_service = ".config/systemd/user/sysmon.service" ascii
        $path_pglog   = "/tmp/pglog" ascii
        $path_pgstate = "/tmp/.pg_state" ascii

        /* Archive payload name */
        $archive      = "tpcp.tar.gz" ascii

    condition:
        /* .pth hook: has Python exec prefix + C2 or artifact path */
        (any of ($pth_exec*) and (any of ($c2_domain*) or any of ($path_*)))
        or
        /* Archive: named tpcp with C2 domain reference */
        ($archive and any of ($c2_domain*))
        or
        /* Any two TeamPCP artifact paths together */
        2 of ($path_*)
}

rule TeamPCP_Backdoor_Script_sysmon_py
{
    meta:
        description   = "Detects TeamPCP persistent backdoor script masquerading as sysmon.py"
        author        = "Mazlum BAYDAR"
        date          = "2026-03-26"
        severity      = "high"
        mitre_attack  = "T1036.005, T1547.016"
        reference     = "https://github.com/reversinglabs/reversinglabs-yara-rules"

    strings:
        /* Python script with C2 beaconing and /tmp state tracking */
        $beacon1      = "checkmarx.zone" ascii wide
        $beacon2      = "models.litellm.cloud" ascii wide
        $state_file   = "/tmp/.pg_state" ascii
        $payload_drop = "/tmp/pglog" ascii

        /* Common backdoor patterns */
        $exec_cmd     = "subprocess" ascii
        $encode_b64   = "base64" ascii
```

```
    condition:
        any of ($beacon*) and (1 of ($state_file, $payload_drop)) and any of ($exec_cmd, $encode_b64)
}

rule TeamPCP_systemd_Service_Unit
{
    meta:
        description   = "Detects TeamPCP sysmon.service systemd persistence unit content"
        author        = "Mazlum BAYDAR"
        date          = "2026-03-26"
        severity      = "high"
        mitre_attack  = "T1547.016"
        reference     = "https://securitylabs.datadoghq.com/articles/litellm-compromised-pypi-teampcp-
supply-chain-campaign/"

    strings:
        /* systemd unit file structure markers */
        $unit_section = "[Unit]" ascii
        $svc_section  = "[Service]" ascii
        $install_sec  = "[Install]" ascii

        /* ExecStart pointing to the backdoor */
        $execstart    = "ExecStart" ascii
        $sysmon_path  = "sysmon.py" ascii

        /* WantedBy for user-level persistence */
        $wantedby     = "WantedBy" ascii

    condition:
        all of ($unit_section, $svc_section, $execstart, $sysmon_path)
}

rule TeamPCP_Malicious_PyPI_Package_Indicators
{
    meta:
        description   = "Detects TeamPCP IOCs in Python package installation artifacts (setup.py, METADATA,
dist-info)"
        author        = "Mazlum BAYDAR"
        date          = "2026-03-26"
        severity      = "critical"
        mitre_attack  = "T1195.001"
        reference     = "https://sysdig.com/blog/teampcp-pypi-supply-chain/"

    strings:
        /* Malicious version strings in METADATA */
        $ver_1        = "Version: 1.82.7" ascii
        $ver_2        = "Version: 1.82.8" ascii

        /* .pth file reference in package data */
        $pth_ref      = "litellm_init.pth" ascii

        /* C2 endpoints */
        $c2_1         = "models.litellm.cloud" ascii wide
        $c2_2         = "checkmarx.zone" ascii wide

    condition:
        (1 of ($ver_*) and $pth_ref)
        or
        (1 of ($ver_*) and 1 of ($c2_*))
}
```

KQL Microsoft Defender XDR · Sentinel

```
// CVE-2026-33634 — LiteLLM PyPI Supply Chain Attack (TeamPCP)
// CVSS 9.4 Critical | Platform: Microsoft Defender XDR + Microsoft Sentinel
// ATT&CK: T1195.001, T1546.018, T1547.016, T1041, T1552
// Author: Mazlum BAYDAR | Date: 2026-03-26

// ============================================================
// RULE 1: Malicious LiteLLM Package Installation
// Table: DeviceProcessEvents | T1195.001 Initial Access
// ============================================================
DeviceProcessEvents
| where TimeGenerated > ago(7d)
| where FileName in~ ("pip", "pip3", "python", "python3")
| where ProcessCommandLine has_any ("litellm==1.82.7", "litellm==1.82.8")
| project TimeGenerated, DeviceName, AccountName, FileName,
          ProcessCommandLine, InitiatingProcessFileName,
          InitiatingProcessCommandLine, FolderPath
| order by TimeGenerated desc

// ============================================================
// RULE 2: litellm_init.pth Hook File Created in site-packages
// Table: DeviceFileEvents | T1546.018 Persistence
// ============================================================
DeviceFileEvents
| where TimeGenerated > ago(7d)
| where ActionType == "FileCreated"
| where FileName == "litellm_init.pth"
| where FolderPath has "site-packages"
| project TimeGenerated, DeviceName, AccountName, FileName, FolderPath,
          InitiatingProcessFileName, InitiatingProcessCommandLine, SHA1, MD5
| order by TimeGenerated desc

// ============================================================
// RULE 3: TeamPCP Backdoor Script or Persistence Files Created
// Table: DeviceFileEvents | T1036.005 + T1547.016
// ============================================================
DeviceFileEvents
| where TimeGenerated > ago(7d)
| where ActionType == "FileCreated"
| where (FileName == "sysmon.py" and FolderPath has ".config/sysmon")
    or  (FileName == "sysmon.service" and FolderPath has ".config/systemd/user")
    or  FileName in ("/tmp/pglog", "/tmp/.pg_state")
    or  FolderPath has "site-packages" and FileName == "litellm_init.pth"
| project TimeGenerated, DeviceName, AccountName, FileName, FolderPath,
          InitiatingProcessFileName, InitiatingProcessCommandLine
| order by TimeGenerated desc

// ============================================================
// RULE 4: DNS Query to TeamPCP C2 Typosquat Domains
// Table: DeviceNetworkEvents | T1041 Exfiltration
// ============================================================
DeviceNetworkEvents
| where TimeGenerated > ago(7d)
| where RemoteUrl has_any ("models.litellm.cloud", "checkmarx.zone")
| project TimeGenerated, DeviceName, AccountName,
          InitiatingProcessFileName, InitiatingProcessCommandLine,
          RemoteUrl, RemoteIP, RemotePort, ActionType
| order by TimeGenerated desc

// ============================================================
// RULE 5: Network Connection to TeamPCP C2 IP Infrastructure
// Table: DeviceNetworkEvents | T1041 C2
// ============================================================
DeviceNetworkEvents
| where TimeGenerated > ago(7d)
| where RemoteIP in ("45.148.10.212", "83.142.209.11")
| project TimeGenerated, DeviceName, AccountName,
          InitiatingProcessFileName, InitiatingProcessCommandLine,
          RemoteIP, RemotePort, RemoteUrl, ActionType
| order by TimeGenerated desc
```

```
// ============================================================
// RULE 6: Python Process Making Outbound C2 Connection
// Correlated: DeviceProcessEvents + DeviceNetworkEvents
// T1041 Exfiltration / T1552 Credential Access
// ============================================================
let c2_ips = dynamic(["45.148.10.212", "83.142.209.11"]);
let c2_domains = dynamic(["models.litellm.cloud", "checkmarx.zone"]);
let python_procs = DeviceProcessEvents
| where TimeGenerated > ago(7d)
| where FileName has_any ("python", "python3")
| project DeviceId, ProcessId, ProcessCommandLine, TimeGenerated;
DeviceNetworkEvents
| where TimeGenerated > ago(7d)
| where RemoteIP in (c2_ips) or RemoteUrl has_any (c2_domains)
| join kind=inner python_procs on DeviceId, $left.InitiatingProcessId == $right.ProcessId
| project TimeGenerated, DeviceName, ProcessCommandLine,
          RemoteIP, RemoteUrl, RemotePort
| order by TimeGenerated desc

// ============================================================
// SENTINEL RULE 7: Malicious pip Install from SecurityEvent
// Table: SecurityEvent (Windows) | T1195.001
// ============================================================
SecurityEvent
| where TimeGenerated > ago(7d)
| where EventID == 4688
| where CommandLine has_any ("litellm==1.82.7", "litellm==1.82.8")
| project TimeGenerated, Computer, Account, CommandLine,
          ParentProcessName, NewProcessName
| order by TimeGenerated desc
```

XQL Palo Alto Cortex XDR · XSIAM

```
// CVE-2026-33634 — LiteLLM PyPI Supply Chain Attack (TeamPCP)
// CVSS 9.4 Critical | Platform: Palo Alto Cortex XDR / XSIAM
// ATT&CK: T1195.001, T1546.018, T1547.016, T1041, T1552
// Author: Mazlum BAYDAR | Date: 2026-03-26
// Note: XQL uses stage-based pipeline; ENUM constants for event types

// ============================================================
// RULE 1: Malicious LiteLLM PyPI Installation
// Event: Process Start | T1195.001
// ============================================================
dataset = xdr_data
| filter event_type = ENUM.PROCESS and event_sub_type = ENUM.PROCESS_START
| filter actor_process_image_name in ("pip", "pip3", "python", "python3")
        and (actor_process_command_line contains "litellm==1.82.7"
             or actor_process_command_line contains "litellm==1.82.8")
| fields timestamp_desc, agent_hostname, actor_primary_username,
         actor_process_image_name, actor_process_command_line,
         actor_process_image_path
| sort desc timestamp_desc
| limit 100

// ============================================================
// RULE 2: litellm_init.pth Hook File Created
// Event: File Create | T1546.018
// ============================================================
dataset = xdr_data
| filter event_type = ENUM.FILE and event_sub_type = ENUM.FILE_CREATE_NEW
| filter action_file_name = "litellm_init.pth"
        and action_file_path contains "site-packages"
| fields timestamp_desc, agent_hostname, actor_primary_username,
         action_file_path, actor_process_image_name,
         actor_process_command_line
| sort desc timestamp_desc
| limit 100

// ============================================================
// RULE 3: TeamPCP Backdoor or Persistence Files Created
// Event: File Create | T1036.005 + T1547.016
// ============================================================
dataset = xdr_data
| filter event_type = ENUM.FILE and event_sub_type = ENUM.FILE_CREATE_NEW
| filter (action_file_name = "sysmon.py" and action_file_path contains ".config/sysmon")
      or (action_file_name = "sysmon.service" and action_file_path contains ".config/systemd/user")
      or action_file_path in ("/tmp/pglog", "/tmp/.pg_state")
| fields timestamp_desc, agent_hostname, actor_primary_username,
         action_file_name, action_file_path,
         actor_process_image_name, actor_process_command_line
| sort desc timestamp_desc
| limit 100

// ============================================================
// RULE 4: DNS / Network Connection to C2 Domains
// Event: Network | T1041
// ============================================================
dataset = xdr_data
| filter event_type = ENUM.NETWORK
| filter dst_host in ("models.litellm.cloud", "checkmarx.zone")
      or dst_ip in ("45.148.10.212", "83.142.209.11")
| fields timestamp_desc, agent_hostname, actor_primary_username,
         actor_process_image_name, actor_process_command_line,
         dst_host, dst_ip, dst_port, protocol
| sort desc timestamp_desc
| limit 100

// ============================================================
// RULE 5: Python Process Connecting to C2 Infrastructure
// Correlated process + network | T1041 + T1552
// ============================================================
dataset = xdr_data
```

```
| filter event_type = ENUM.NETWORK
| filter dst_ip in ("45.148.10.212", "83.142.209.11")
      or dst_host in ("models.litellm.cloud", "checkmarx.zone")
| filter actor_process_image_name in ("python", "python3", "sysmon.py")
| fields timestamp_desc, agent_hostname, actor_primary_username,
         actor_process_image_name, actor_process_command_line,
         dst_host, dst_ip, dst_port
| sort desc timestamp_desc
| limit 100

// ============================================================
// RULE 6: Abnormal Child Process Spawned from Python (C2 beacon)
// Actor: python | Action: spawn shell/curl/wget
// T1059 + T1041
// ============================================================
dataset = xdr_data
| filter event_type = ENUM.PROCESS and event_sub_type = ENUM.PROCESS_START
| filter actor_process_image_name in ("python", "python3")
        and action_process_image_name in ("curl", "wget", "bash", "sh", "nc", "ncat")
| fields timestamp_desc, agent_hostname, actor_primary_username,
         actor_process_image_name, actor_process_command_line,
         action_process_image_name, action_process_command_line
| sort desc timestamp_desc
| limit 100
```

Splunk SPL Splunk SIEM · Sysmon TA

```
| Comment "CVE-2026-33634 — LiteLLM PyPI Supply Chain Attack (TeamPCP)"
| Comment "CVSS 9.4 Critical | Platform: Splunk (Sysmon + Linux TA)"
| Comment "ATT&CK: T1195.001, T1546.018, T1547.016, T1041, T1552"
| Comment "Author: Mazlum BAYDAR | Date: 2026-03-26"
| Comment "Field Mapping: CIM-compliant (Sysmon TA) — EventCode 1=Process, 3=Network, 11=FileCreate"

| Comment "============================================================"
| Comment "RULE 1: Malicious LiteLLM PyPI Package Installation"
| Comment "Sysmon EventCode 1 (Process Create) | T1195.001"
| Comment "============================================================"

index=linux_logs OR index=windows
sourcetype=xmlwineventlog:microsoft-windows-sysmon/operational EventCode=1
(Image="*/pip" OR Image="*/pip3" OR Image="*/python" OR Image="*/python3")
(CommandLine="*litellm==1.82.7*" OR CommandLine="*litellm==1.82.8*")
| rename ComputerName AS host, User AS user, Image AS process, CommandLine AS process_command_line,
ParentImage AS parent_process
| table _time, host, user, process, process_command_line, parent_process
| sort - _time

| Comment "============================================================"
| Comment "RULE 2: litellm_init.pth Hook File Created (T1546.018)"
| Comment "Sysmon EventCode 11 (FileCreate)"
| Comment "============================================================"

index=linux_logs OR index=windows
sourcetype=xmlwineventlog:microsoft-windows-sysmon/operational EventCode=11
TargetFilename="*site-packages*litellm_init.pth"
| rename ComputerName AS host, User AS user, Image AS process, TargetFilename AS file_path
| table _time, host, user, process, file_path
| sort - _time

| Comment "============================================================"
| Comment "RULE 3: TeamPCP Backdoor / Persistence Files Created"
| Comment "Sysmon EventCode 11 | T1036.005 + T1547.016"
| Comment "============================================================"

index=linux_logs OR index=windows
sourcetype=xmlwineventlog:microsoft-windows-sysmon/operational EventCode=11
(TargetFilename="*/.config/sysmon/sysmon.py"
 OR TargetFilename="*/.config/systemd/user/sysmon.service"
 OR TargetFilename="/tmp/pglog"
 OR TargetFilename="/tmp/.pg_state")
| rename ComputerName AS host, User AS user, Image AS process, TargetFilename AS file_path
| table _time, host, user, process, file_path
| sort - _time

| Comment "============================================================"
| Comment "RULE 4: DNS Query to TeamPCP C2 Domains"
| Comment "Sysmon EventCode 22 (DNS Query) | T1041"
| Comment "============================================================"

index=linux_logs OR index=windows
sourcetype=xmlwineventlog:microsoft-windows-sysmon/operational EventCode=22
(QueryName="models.litellm.cloud" OR QueryName="*litellm.cloud"
 OR QueryName="checkmarx.zone" OR QueryName="*.checkmarx.zone")
| rename ComputerName AS host, User AS user, Image AS process, QueryName AS dns_query
| table _time, host, user, process, dns_query
| sort - _time

| Comment "============================================================"
| Comment "RULE 5: Network Connection to C2 IPs"
| Comment "Sysmon EventCode 3 (Network Connect) | T1041"
| Comment "============================================================"

index=linux_logs OR index=windows
sourcetype=xmlwineventlog:microsoft-windows-sysmon/operational EventCode=3
(DestinationIp="45.148.10.212" OR DestinationIp="83.142.209.11")
| rename ComputerName AS host, User AS user, Image AS process,
```

```
          SourceIp AS src_ip, DestinationIp AS dest_ip, DestinationPort AS dest_port
| table _time, host, user, process, src_ip, dest_ip, dest_port
| sort - _time

| Comment "============================================================"
| Comment "RULE 6: Aggregated — Hosts with Multiple C2 Indicators"
| Comment "High-confidence detection combining process + network | T1041"
| Comment "============================================================"

index=linux_logs OR index=windows
sourcetype=xmlwineventlog:microsoft-windows-sysmon/operational
((EventCode=1 AND (CommandLine="*litellm==1.82.7*" OR CommandLine="*litellm==1.82.8*"))
 OR (EventCode=3 AND (DestinationIp="45.148.10.212" OR DestinationIp="83.142.209.11"))
 OR (EventCode=22 AND (QueryName="models.litellm.cloud" OR QueryName="checkmarx.zone")))
| rename ComputerName AS host
| stats count by host, EventCode
| where count >= 1
| sort - count
```

QRadar AQL IBM QRadar SIEM

```
-- CVE-2026-33634 — LiteLLM PyPI Supply Chain Attack (TeamPCP)
-- CVSS 9.4 Critical | Platform: IBM QRadar SIEM
-- ATT&CK: T1195.001, T1546.018, T1547.016, T1041, T1552
-- Author: Mazlum BAYDAR | Date: 2026-03-26
-- Note: Use ILIKE for case-insensitive pattern match (SQL LIKE %)
--       Use IMATCHES for case-insensitive regex (PCRE, escape dots with \.)
--       Use MATCHES for case-sensitive regex

-- ============================================================
-- RULE 1: Malicious LiteLLM PyPI Package Installation
-- T1195.001 | Source: Process/Command Audit logs
-- ============================================================
SELECT
    DATEFORMAT(devicetime, 'yyyy-MM-dd HH:mm:ss') AS event_time,
    LOGSOURCENAME(logsourceid) AS log_source,
    sourceIP,
    username,
    "Message" AS command_line
FROM events
WHERE devicetime > CURRENT_TIMESTAMP - 7 DAYS
  AND ("Message" ILIKE '%litellm==1.82.7%'
       OR "Message" ILIKE '%litellm==1.82.8%')
ORDER BY devicetime DESC
LIMIT 500

-- ============================================================
-- RULE 2: litellm_init.pth File Creation Detected
-- T1546.018 | Source: File Integrity / Endpoint logs
-- ============================================================
SELECT
    DATEFORMAT(devicetime, 'yyyy-MM-dd HH:mm:ss') AS event_time,
    LOGSOURCENAME(logsourceid) AS log_source,
    sourceIP,
    username,
    "Message" AS file_event
FROM events
WHERE devicetime > CURRENT_TIMESTAMP - 7 DAYS
  AND "Message" ILIKE '%litellm_init.pth%'
  AND "Message" ILIKE '%site-packages%'
ORDER BY devicetime DESC
LIMIT 200

-- ============================================================
-- RULE 3: TeamPCP Backdoor or Persistence Artifacts
-- T1036.005 + T1547.016 | Backdoor + systemd persistence
-- ============================================================
SELECT
    DATEFORMAT(devicetime, 'yyyy-MM-dd HH:mm:ss') AS event_time,
    LOGSOURCENAME(logsourceid) AS log_source,
    sourceIP,
    username,
    "Message" AS file_event
FROM events
WHERE devicetime > CURRENT_TIMESTAMP - 7 DAYS
  AND ("Message" ILIKE '%/.config/sysmon/sysmon.py%'
       OR "Message" ILIKE '%/.config/systemd/user/sysmon.service%'
       OR "Message" LIKE '%/tmp/pglog%'
       OR "Message" LIKE '%/tmp/.pg_state%')
ORDER BY devicetime DESC
LIMIT 200

-- ============================================================
-- RULE 4: DNS Query to TeamPCP C2 Domains
-- T1041 C2 | Source: DNS logs / Passive DNS
-- ============================================================
SELECT
    DATEFORMAT(devicetime, 'yyyy-MM-dd HH:mm:ss') AS event_time,
    LOGSOURCENAME(logsourceid) AS log_source,
    sourceIP,
```

```
    username,
    "Message" AS dns_query
FROM events
WHERE devicetime > CURRENT_TIMESTAMP - 7 DAYS
  AND ("Message" ILIKE '%models.litellm.cloud%'
       OR "Message" ILIKE '%checkmarx.zone%')
ORDER BY devicetime DESC
LIMIT 500

-- ============================================================
-- RULE 5: Network Connection to C2 IPs
-- T1041 | Match on destination IP fields
-- ============================================================
SELECT
    DATEFORMAT(devicetime, 'yyyy-MM-dd HH:mm:ss') AS event_time,
    LOGSOURCENAME(logsourceid) AS log_source,
    sourceIP,
    destinationIP,
    destinationPort,
    username,
    "Message" AS net_event
FROM events
WHERE devicetime > CURRENT_TIMESTAMP - 7 DAYS
  AND destinationIP IN ('45.148.10.212', '83.142.209.11')
ORDER BY devicetime DESC
LIMIT 500

-- ============================================================
-- RULE 6: Aggregated C2 Hits by Source IP
-- High-confidence pivot — correlate all C2 indicators
-- ============================================================
SELECT
    sourceIP,
    COUNT(*) AS hit_count,
    MIN(DATEFORMAT(devicetime, 'yyyy-MM-dd HH:mm:ss')) AS first_seen,
    MAX(DATEFORMAT(devicetime, 'yyyy-MM-dd HH:mm:ss')) AS last_seen
FROM events
WHERE devicetime > CURRENT_TIMESTAMP - 7 DAYS
  AND (destinationIP IN ('45.148.10.212', '83.142.209.11')
       OR "Message" ILIKE '%models.litellm.cloud%'
       OR "Message" ILIKE '%checkmarx.zone%'
       OR "Message" ILIKE '%litellm_init.pth%'
       OR "Message" ILIKE '%litellm==1.82.7%'
       OR "Message" ILIKE '%litellm==1.82.8%')
GROUP BY sourceIP
HAVING COUNT(*) >= 1
ORDER BY hit_count DESC
LIMIT 100
```

Carbon Black VMware Carbon Black Cloud

```
# CVE-2026-33634 — LiteLLM PyPI Supply Chain Attack (TeamPCP)
# CVSS 9.4 Critical | Platform: VMware Carbon Black Cloud (CBC)
# ATT&CK: T1195.001, T1546.018, T1547.016, T1041, T1552
# Author: Mazlum BAYDAR | Date: 2026-03-26
#
# IMPORTANT CBC SYNTAX NOTES (from official docs):
#   - All indexed text is stored as LOWERCASE — regex must use lowercase
#   - Paths use FORWARD SLASHES: c:/windows not c:\windows
#   - Wildcard (*) works only in single terms, NOT inside quoted phrases
#   - Implicit AND between terms; use OR/NOT explicitly
#   - Regex via field:/pattern/ uses Java regex engine (all lowercase text)
#   - Range queries: field:[N TO *] (inclusive), * means infinity

# ============================================================
# RULE 1: Malicious LiteLLM PyPI Package Installation
# process_name + cmdline fields | T1195.001
# ============================================================
process_name:pip AND (cmdline:"litellm==1.82.7" OR cmdline:"litellm==1.82.8")

process_name:pip3 AND (cmdline:"litellm==1.82.7" OR cmdline:"litellm==1.82.8")

process_name:python AND cmdline:"-m" AND cmdline:"pip" AND cmdline:"install" AND (cmdline:"litellm==1.82.7"
OR cmdline:"litellm==1.82.8")

# ============================================================
# RULE 2: litellm_init.pth Hook File Created in site-packages
# filemod_name field | T1546.018
# ============================================================
filemod_name:"litellm_init.pth" AND filemod_name:*site-packages*

# ============================================================
# RULE 3: TeamPCP Backdoor Script Created
# sysmon.py file creation | T1036.005
# NOTE: CBC path uses forward slash; tilde (~) is user home
# ============================================================
filemod_name:*/.config/sysmon/sysmon.py

# ============================================================
# RULE 4: TeamPCP systemd Persistence Unit Created
# sysmon.service in user systemd path | T1547.016
# ============================================================
filemod_name:*/.config/systemd/user/sysmon.service

# ============================================================
# RULE 5: TeamPCP Temporary Payload Drop Files
# /tmp staging and state tracking | T1036
# ============================================================
(filemod_name:"/tmp/pglog" OR filemod_name:"/tmp/.pg_state")

# ============================================================
# RULE 6: Network Connection to C2 IP Infrastructure
# netconn_ipv4 field | T1041
# ============================================================
netconn_ipv4:45.148.10.212

netconn_ipv4:83.142.209.11

# ============================================================
# RULE 7: DNS Query to C2 Domains
# netconn_domain field | T1041
# Domain suffix matching uses leading dot for subdomains
# ============================================================
netconn_domain:models.litellm.cloud

netconn_domain:checkmarx.zone

# ============================================================
# RULE 8: Python Process Connecting to C2 Infrastructure
# Correlated: python process + C2 netconn | T1041 + T1552
```

```
# ============================================================
(process_name:python OR process_name:python3) AND (netconn_ipv4:45.148.10.212 OR
netconn_ipv4:83.142.209.11)

(process_name:python OR process_name:python3) AND (netconn_domain:models.litellm.cloud OR
netconn_domain:checkmarx.zone)

# ============================================================
# RULE 9: Obfuscated Command in Python Process (regex)
# Long base64/encoded strings in cmdline | T1027
# NOTE: regex must be all lowercase (CBC lowercases all text)
# ============================================================
process_name:/python.*/ AND cmdline:/[a-z0-9+/]{200,}/

# ============================================================
# RULE 10: Multiple C2 Connections from Same Process (volume)
# High netconn count from python | T1041
# ============================================================
(process_name:python OR process_name:python3) AND netconn_count:[10 TO *]
```

SentinelOne Deep Visibility v2 Enhanced · STAR

```
// CVE-2026-33634 — LiteLLM PyPI Supply Chain Attack (TeamPCP)
// CVSS 9.4 Critical | Platform: SentinelOne Deep Visibility (v2 Enhanced)
// ATT&CK: T1195.001, T1546.018, T1547.016, T1041, T1552
// Author: Mazlum BAYDAR | Date: 2026-03-26
//
// IMPORTANT S1 SYNTAX NOTES (from official docs):
//   - EventType values are exact strings (case-sensitive with double quotes)
//   - Dot notation required: TgtFile.Path (NOT TgtFilePath — that is v1 legacy)
//   - Contains = case-INSENSITIVE substring | StartsWith = case-SENSITIVE
//   - ContainsCIS = explicit case-insensitive | EndsWith = case-SENSITIVE
//   - In Contains = list-based case-insensitive contains check
//   - Regexp operator uses case-sensitive regex
//   - No aggregation in query itself — use UI time picker for time range

// ============================================================
// RULE 1: Malicious LiteLLM PyPI Package Installation
// EventType: Process Creation | T1195.001
// ============================================================
EventType = "Process Creation"
AND TgtProcName In ("pip", "pip3", "python", "python3")
AND (TgtProcCmdLine Contains "litellm==1.82.7"
     OR TgtProcCmdLine Contains "litellm==1.82.8")

// ============================================================
// RULE 2: litellm_init.pth Hook File Created (T1546.018)
// EventType: File Creation | Persistence via .pth
// ============================================================
EventType = "File Creation"
AND TgtFile.Name = "litellm_init.pth"
AND TgtFile.Path Contains "site-packages"

// ============================================================
// RULE 3: TeamPCP Backdoor Script Created
// EventType: File Creation | T1036.005
// ============================================================
EventType = "File Creation"
AND TgtFile.Name = "sysmon.py"
AND TgtFile.Path Contains ".config/sysmon"

// ============================================================
// RULE 4: TeamPCP systemd Persistence Unit Created
// EventType: File Creation | T1547.016
// ============================================================
EventType = "File Creation"
AND TgtFile.Name = "sysmon.service"
AND TgtFile.Path Contains ".config/systemd/user"

// ============================================================
// RULE 5: TeamPCP Temporary Payload Drop Files
// EventType: File Creation | T1036
// ============================================================
EventType = "File Creation"
AND TgtFile.Path In ("/tmp/pglog", "/tmp/.pg_state")

// ============================================================
// RULE 6: DNS Query to TeamPCP C2 Domains
// EventType: DNS Request | T1041
// ============================================================
EventType = "DNS Request"
AND (DnsRequest.Name = "models.litellm.cloud"
     OR DnsRequest.Name EndsWith ".litellm.cloud"
     OR DnsRequest.Name = "checkmarx.zone"
     OR DnsRequest.Name EndsWith ".checkmarx.zone")

// ============================================================
// RULE 7: Network Connection to C2 IP Infrastructure
// EventType: IP Connect | T1041
// ============================================================
EventType = "IP Connect"
```

```
AND Dst.IP In ("45.148.10.212", "83.142.209.11")

// ============================================================
// RULE 8: Python/pip Process Making Outbound C2 Connection
// Correlated: Process + Network | T1041 + T1552
// ============================================================
EventType = "IP Connect"
AND Dst.IP In ("45.148.10.212", "83.142.209.11")
AND SrcProcName In ("python", "python3", "pip", "pip3")

// ============================================================
// RULE 9: Module Loaded from Temp or site-packages by Python
// EventType: Module Load | T1546.018 variant
// ============================================================
EventType = "Module Load"
AND SrcProcName In ("python", "python3")
AND (TgtModule.Path Contains "/tmp/"
     OR TgtModule.Path Contains "litellm_init")

// ============================================================
// RULE 10: TeamPCP — All Primary IOCs Combined (High Confidence)
// Composite rule for alerting | Multiple ATT&CK techniques
// ============================================================
(
  (EventType = "Process Creation"
   AND TgtProcCmdLine In Contains ("litellm==1.82.7", "litellm==1.82.8"))
  OR
  (EventType = "File Creation"
   AND TgtFile.Name In ("litellm_init.pth", "sysmon.py", "sysmon.service"))
  OR
  (EventType = "DNS Request"
   AND DnsRequest.Name In ("models.litellm.cloud", "checkmarx.zone"))
  OR
  (EventType = "IP Connect"
   AND Dst.IP In ("45.148.10.212", "83.142.209.11"))
)
```

Kaspersky EDR Expert KEDR · KATA

```
// CVE-2026-33634 — LiteLLM PyPI Supply Chain Attack (TeamPCP)
// CVSS 9.4 Critical | Platform: Kaspersky EDR Expert (KEDR) / KATA
// ATT&CK: T1195.001, T1546.018, T1547.016, T1041, T1552
// Author: Mazlum BAYDAR | Date: 2026-03-26
//
// IMPORTANT KEDR SYNTAX NOTES (from official docs):
//   - ALL operators must be UPPERCASE: CONTAINS, STARTS_WITH, ENDS_WITH, IN, MATCHES, AND, OR, NOT
//   - Field names use dot notation: Process.Name, File.Path, Network.DestinationIP
//   - CONTAINS, STARTS_WITH, ENDS_WITH, IN are case-INSENSITIVE by default
//   - MATCHES uses full PCRE regex (case-SENSITIVE by default)
//   - String values in double quotes; numeric values without quotes
//   - Use parentheses for grouping complex boolean logic
//   - Do NOT use TAA reserved fields: IOATechnique, IOATactics, IOAImportance, IOAConfidence

// ==============================================================
// RULE 1: Malicious LiteLLM PyPI Package Installation
// T1195.001 | Process: pip/python with malicious version
// ==============================================================
Process.Name IN ("pip", "pip3", "python", "python3")
AND (Process.CommandLine CONTAINS "litellm==1.82.7"
     OR Process.CommandLine CONTAINS "litellm==1.82.8")

// ==============================================================
// RULE 2: litellm_init.pth Hook File Created (T1546.018)
// File.Path in site-packages + filename match
// ==============================================================
File.Name = "litellm_init.pth"
AND File.Path CONTAINS "site-packages"

// ==============================================================
// RULE 3: TeamPCP Backdoor Script Created at Hidden Path
// T1036.005 — Masquerading as legitimate sysmon
// ==============================================================
File.Name = "sysmon.py"
AND File.Path CONTAINS ".config/sysmon"

// ==============================================================
// RULE 4: TeamPCP systemd Persistence Unit Created (T1547.016)
// User-level systemd service for reboot persistence
// ==============================================================
File.Name = "sysmon.service"
AND File.Path CONTAINS ".config/systemd/user"

// ==============================================================
// RULE 5: TeamPCP Temporary Payload Files in /tmp
// /tmp/pglog = payload drop | /tmp/.pg_state = infection state
// ==============================================================
File.Path IN ("/tmp/pglog", "/tmp/.pg_state")

// ==============================================================
// RULE 6: DNS / Network Connection to TeamPCP C2 Domains
// T1041 | Exfiltration over encrypted channel
// ==============================================================
Network.DestinationHost IN ("models.litellm.cloud", "checkmarx.zone")

// ==============================================================
// RULE 7: Network Connection to TeamPCP C2 IP Infrastructure
// T1041 | Direct IP C2 communication
// ==============================================================
Network.DestinationIP IN ("45.148.10.212", "83.142.209.11")

// ==============================================================
// RULE 8: Python Process Communicating with C2 Infrastructure
// Correlated: python + C2 network activity | T1041 + T1552
// ==============================================================
Process.Name IN ("python", "python3", "pip", "pip3")
AND (Network.DestinationIP IN ("45.148.10.212", "83.142.209.11")
     OR Network.DestinationHost IN ("models.litellm.cloud", "checkmarx.zone"))
```

```
// ============================================================
// RULE 9: Suspicious Python Child Process Spawned (C2 beacon)
// T1059 — Command execution via backdoor
// ============================================================
Process.ParentName IN ("python", "python3")
AND Process.Name IN ("bash", "sh", "curl", "wget", "nc")

// ============================================================
// RULE 10: Obfuscated Payload Pattern in Python CommandLine
// T1027 — Long encoded strings (base64/hex) in cmdline
// MATCHES uses PCRE — case sensitive; long token = encoded payload
// ============================================================
Process.Name IN ("python", "python3")
AND Process.CommandLine MATCHES ".*[A-Za-z0-9+/=]{200,}.*"

// ============================================================
// RULE 11: TeamPCP SHA256 Hash Match
// Direct indicator — litellm_init.pth malicious payload
// Hash: ceNa7wMJnNHy1kRnNCcwJaFjWX3pORLfMh7xGL8TUjg (base64url)
// ============================================================
File.Name = "litellm_init.pth"
AND Process.Name IN ("python", "python3", "pip", "pip3")

// ============================================================
// RULE 12: TeamPCP — High Confidence Composite Alert
// Multiple IOC classes combined (OR logic) for SIEM alerting
// ============================================================
(
  (Process.CommandLine CONTAINS "litellm==1.82.7"
   OR Process.CommandLine CONTAINS "litellm==1.82.8")
  OR
  (File.Name IN ("litellm_init.pth", "sysmon.py", "sysmon.service")
   AND (File.Path CONTAINS "site-packages"
        OR File.Path CONTAINS ".config/sysmon"
        OR File.Path CONTAINS ".config/systemd/user"))
  OR
  Network.DestinationIP IN ("45.148.10.212", "83.142.209.11")
  OR
  Network.DestinationHost IN ("models.litellm.cloud", "checkmarx.zone")
)
```

References

Source	URL
Sysdig	https://sysdig.com/blog/teampcp-pypi-supply-chain/
FutureSearch	https://futuresearch.ai/blog/litellm-pypi-supply-chain-attack/
Snyk	https://snyk.io/articles/poisoned-security-scanner-backdooring-litellm/
Datadog Security Labs	https://securitylabs.datadoghq.com/articles/litellm-compromised-pypi-teampcp-supply-chain-campaign/
Sonatype	https://www.sonatype.com/blog/litellm-pypi-supply-chain
ARMO	https://www.armosec.io/blog/teampcp-kubernetes-attack/
Kaspersky	https://www.kaspersky.com/blog/critical-supply-chain-attack-trivy-litellm-checkmarx-teampcp/55510/
ReversingLabs YARA	https://github.com/reversinglabs/reversinglabs-yara-rules
NVD	https://nvd.nist.gov/vuln/detail/CVE-2026-33634