

R Basics and Examples - A short introduction

Markus Baaske

Faculty of Mathematics and Computer Science (FSU Jena)

April 30, 2018

The R Project for Statistical Computing

The R project <http://www.r-project.org> develops a free software environment for statistical computing and graphics. R compiles and runs on a wide variety of UNIX platforms, Windows and MacOS, is mostly used for statistics but can also be used as a programming (script) language alone.

R is organized as a core distribution of base packages which can be extended by further packages loaded into the a user workspace (or interpreter global environment). Some useful links are

- ▶ Tutorials on using R can be found at <http://www.r-tutor.com/>
- ▶ Meta search and package documentation
<https://www.rdocumentation.org/>
- ▶ R CRAN repository for contributed packages:
<https://cran.r-project.org/>
- ▶ A short reference card <https://cran.r-project.org/doc/contrib/Short-refcard.pdf>

R Basics

```
R> PATH <- getwd()           # get working directory
R> INFO <- Sys.info()        # get system info
R> objects()                 # show all loaded variables

[1] "a"      "b"      "d"      "d0"     "d.0"    "d00"    "dd"     "fac"    "g"
[11] "L3"     "PATH"   "x"      "XYZ"    "y"      "z"
```

R> ls() # objects in your workspace

```
[1] "a"      "b"      "d"      "d0"     "d.0"    "d00"    "dd"     "fac"    "g"
[11] "L3"     "PATH"   "x"      "XYZ"    "y"      "z"
```

Whats is in these objects?

```
R> PATH

[1] "/home/baaske/workspace/RIntro/doc"

R> INFO[c("sysname", "nodename", "user")]

      sysname          nodename          user
"Linux" "baaskelap.rdm.de"      "baaske"
```

Important: On quitting, R offers the option of saving the workspace image, by default in the file `"*.RData"`. Use before ending the R session:

```
R> rm(list=ls())
R> q()
```

R Help and vectors

Getting help:

```
R> help()           # general help
R> ?length          # help for `length`
R> help.search(lapply) # help for function `lapply`
R> help.start()      # start html help system
```

Vectors:

```
R> 2+2
[1] 4

R> round(pi,3)
[1] 3.142

R> sqrt(10)
[1] 3.162

R> 1000*(1+0.075)^5-1000
[1] 435.6

R> sin(c(30,60,90)*pi/180)
[1] 0.500 0.866 1.000
```

R variables and subsetting

```
R> a <- 2*3
```

```
R> a
```

```
[1] 6
```

```
R> a^2
```

```
[1] 36
```

```
R> b <- a^2
```

```
R> a <- c(17,1,3,9)
```

```
R> a
```

```
[1] 17  1  3  9
```

```
R> a[2]
```

```
[1] 1
```

```
R> a[c(1,3)]
```

```
[1] 17  3
```

```
R> a[-2]
```

```
[1] 17  3  9
```

```
R> a[2] <- 1
```

```
R> a
```

```
[1] 17  1  3  9
```

Characters and categories

```
R> (x <- "Hallo") # character vector
[1] "Hallo"

R> (y <- factor(c("C","A","C","B"))) # characters as categories
[1] C A C B
Levels: A B C

R> (z <- factor(c(1,1,2))) # numbers as factors
[1] 1 1 2
Levels: 1 2

R> (x <- c(1,2,3)) # destroy x and overwrite
[1] 1 2 3

R> x[4] # NA = Not Available
[1] NA

R> try(x[4]) # catch error
[1] NA
```

R object classes

```
R> class(1.7) # "numeric"
[1] "numeric"
R> class(x)    # "character" = character vector
[1] "numeric"
R> class(y)    # "factor" categories
[1] "factor"
R> class(z)
[1] "factor"
R> mode(1.7)
[1] "numeric"
R> x <- as.integer(x)
R> class(x)
[1] "integer"
R> z <- as.character(z)
R> class(z)
[1] "character"
```

Characters and categories

```
R> # Save contents of workspace, into the file .RData
R> save.image()
R> # Save into the file archive.RData
R> save.image(file="archive.RData")
R> # save single objects
R> save(x, y,z, file="tmpobj.RData")
R> # save as RDS (could be big data)
R> saveRDS(list(x,y,z),file="myfile.rds")
R> # read as RDS
R> XYZ <- readRDS(file="myfile.rds")

R> # attach (reload) to current workspace
R> attach("tmpobj.RData")
R> ls()
```

```
[1] "a"      "b"      "d"      "d0"     "d.0"    "d00"    "dd"     "fac"    "g"
[11] "L3"     "PATH"   "x"      "XYZ"    "y"      "z"
```


R data frame object

```
R> ?data.frame      # help on data frames
```

```
R> example(data.frame)  # some examples
```

Construct a data frame of study courses

```
R> g <- data.frame(StG=c("GTB", "MPV", "BGM"), Anz=c(75, 11, 62))
```

```
R> g
```

```
  StG Anz
```

```
1 GTB  75
```

```
2 MPV  11
```

```
3 BGM  62
```

```
R> class(g)      # "data.frame" = Datenmatrix
```

```
[1] "data.frame"
```

```
R> names(g)      # categories in g
```

```
[1] "StG" "Anz"
```

```
R> g[,2]          # 2nd column
```

```
[1] 75 11 62
```

```
R> g[3,]          # 3rd row
```

```
  StG Anz
```

```
3 BGM  62
```

```
R> g[3,2]          # single element
```

R data frame object

```
R> g[c(2,3),] # select 2nd and 3rd row
```

```
  StG Anz
```

```
2 MPV  11
```

```
3 BGM  62
```

```
R> g$Anz      # select category `Anz`
```

```
[1] 75 11 62
```

```
R> g$Anz[1]   # select first element of `Anz`
```

```
[1] 75
```

```
R> # Extending the data frame
```

```
R> (g <- rbind(g,c("GTB",26)))
```

```
  StG Anz
```

```
1 GTB  75
```

```
2 MPV  11
```

```
3 BGM  62
```

```
4 GTB  26
```

R data frame object

```
R> g <- cbind(g, Sem=c(3,1,3,5))
```