


HEAVY DUTY COUPLINGS — PIPE THREAD (NPT)

- Heat-treated stainless steel ideal for tube cleaning

| PART NO. | CONNECTION TYPES | | MAXIMUM OPERATING PRESSURE | |
|---------------|-------------------|-------------------|----------------------------|------|
| | Connection 1 (C1) | Connection 2 (C2) | psi | bar |
| GP 052-P1P1 | 1/16 NPT Female | 1/16 NPT Female | 15k | 1000 |
| GP 052-P1P2 | 1/16 NPT Female | 1/8 NPT Female | 15k | 1000 |
| GP 052-P1P4 | 1/16 NPT Female | 1/4 NPT Female | 15k | 1000 |
| GP 052-P1P8 | 1/16 NPT Female | 1/2 NPT Female | 15k | 1000 |
| GP 052-P2P2 | 1/8 NPT Female | 1/8 NPT Female | 15k | 1000 |
| GP 052-P2P4 | 1/8 NPT Female | 1/4 NPT Female | 15k | 1000 |
| GP 052-P2P6 | 1/8 NPT Female | 3/8 NPT Female | 15k | 1000 |
| GP 052-P2P8 | 1/8 NPT Female | 1/2 NPT Female | 15k | 1000 |
| GP 052-P4P4 | 1/4 NPT Female | 1/4 NPT Female | 15k | 1000 |
| GP 052-P4P4-S | 1/4 NPT Female | 1/4 NPT Female | 15k | 1000 |
| GP 052-P4P6 | 1/4 NPT Female | 3/8 NPT Female | 15k | 1000 |
| GP 052-P4P8 | 1/4 NPT Female | 1/2 NPT Female | 15k | 1000 |
| GP 052-P4P12 | 1/4 NPT Female | 3/4 NPT Female | 15k | 1000 |
| GP 052-P6P6 | 3/8 NPT Female | 3/8 NPT Female | 15k | 1000 |
| GP 052-P6P8 | 3/8 NPT Female | 1/2 NPT Female | 15k | 1000 |
| GP 052-P6P12 | 3/8 NPT Female | 3/4 NPT Female | 15k | 1000 |
| GP 052-P8P8 | 1/2 NPT Female | 1/2 NPT Female | 15k | 1000 |
| GP 052-P8P12 | 1/2 NPT Female | 3/4 NPT Female | 15k | 1000 |
| GP 052-P8P16 | 1/2 NPT Female | 1" NPT Female | 12k | 1000 |
| GP 052-P12P12 | 3/4 NPT Female | 3/4 NPT Female | 15k | 1000 |
| GP 052-P12P16 | 3/4 NPT Female | 1" NPT Female | 12k | 830 |
| GP 052-P16P16 | 1" NPT Female | 1" NPT Female | 12k | 830 |
| GP 052-P20P20 | 1-1/4 NPT Female | 1-1/4 NPT Female | 7.5k | 520 |



SLIMLINE COUPLINGS

- Heat-treated stainless steel ideal for tube cleaning

| PART NO. | CONNECTION TYPES | | MAXIMUM OPERATING PRESSURE | |
|----------------|-------------------|-------------------|----------------------------|------|
| | Connection 1 (C1) | Connection 2 (C2) | psi | bar |
| GP 052-P1P1-SL | 1/16 NPT Female | 1/16 NPT Female | 10k | 700 |
| GP 052-P1P4-SL | 1/16 NPT Female | 1/4 NPT Female | 10k | 700 |
| GP 052-P2P2-SL | 1/8 NPT Female | 1/8 NPT Female | 10k | 700 |
| GP 052-P4P4-SL | 1/4 NPT Female | 1/4 NPT Female | 10k | 700 |
| GP 052-P6P6-SL | 3/8 NPT Female | 3/8 NPT Female | 10k | 700 |
| GP 052-P8P8-SL | 1/2 NPT Female | 1/2 NPT Female | 10k | 700 |
| AF 073-P1P1-SL | 1/16 NPT Female | 1/16 NPT Female | 15k | 1000 |
| AF 073-P2P2-SL | 1/8 NPT Female | 1/8 NPT Female | 15k | 1000 |
| AF 073-P4P4-SL | 1/4 NPT Female | 1/4 NPT Female | 15k | 1000 |
| AF 073-P6P6-SL | 3/8 NPT Female | 3/8 NPT Female | 15k | 1000 |
| AF 073-P8P8-SL | 1/2 NPT Female | 1/2 NPT Female | 15k | 1000 |

