

TUBE CLEANING

AUTOBOX® ABX-3L

The StoneAge AutoBox ABX-3L is an automated system for hands-free heat exchanger tube cleaning applications. It is designed to run **triple, dual, or single flex lance setups** with an emphasis on portability, ease of setup, and safety.

The ABX-3L can be used with any pressure rated hose ranging in size from 3/2 to 8/4. Paired with StoneAge Banshee rotary tube cleaning nozzles and Lightweight Positioner, the ABX-3L offers safe and efficient tube cleaning in the harshest exchanger environments.

FEATURES:

- Triple, dual, or single lance operation
- Lightweight, modular design allows a single operator to move, set up, and run
- Handles hose sizes from 3/2 to 8/4 with no modifications
- Hose clamp pressure and feed rates can be remotely adjusted on the fly for repeatable, consistent cleaning
- Proven reliability on the toughest jobs and most corrosive environments
- Low cost of ownership – low cost components, quick and easy maintenance

Package it with AUTOPACKS!

View www.stoneagetools.com for more info

PACKAGES INCLUDE:

- | | |
|--------------------------|------------------------|
| • ABX-3L Hose Tractor | • Guide Tube Assembly |
| • Guide Tubes | • Backout Collet |
| • Hose Feed Stop | • Control Box |
| • Lightweight Positioner | • Plate Clamp Assembly |

Contact StoneAge for prices and availability:
(970) 259-2869 • WWW.STONEAGETOOLS.COM



The AutoBox ABX-3L enabled us to remove hard scale in a difficult vertical exchanger that hadn't been successfully cleaned in 20 years."

**DAVID LAMOUREUX
PROJECT MANAGER**



**OPERATING WATERBLASTING EQUIPMENT
CAN BE POTENTIALLY HAZARDOUS.**

SEE PAGE 121 FOR IMPORTANT SAFETY INFORMATION



SPECIFICATIONS

HOSE FEED RATE	0.3–3.0 ft/sec (0.09–0.90 m/sec)
PITCH ADJUSTMENT	Dual: 0.6–3.0 in. (16–76 mm) Triple: 0.6–1.5 in. (16–38 mm)
HOSE SIZES	3/2–8/4
WEIGHT	49 lbs (22 kg)

 **STONEAGE®**
ENGINEERING THE POWER OF WATER
1-866-795-1586 • WWW.STONEAGETOOLS.COM





REMOTELY ADJUSTABLE HOSE CLAMP

Adjust to changing conditions on the fly and minimize hose wear without interrupting workflow

INDEPENDENT FWD/REV SPEED CONTROL

Consistent cleaning in both directions produces better results in less time


HIGH VISIBILITY GUIDE ASSEMBLY

Quick clamps for easy pitch adjustment with no additional tools or adapters required

STEEL-REINFORCED DRIVE BELT

Replacement takes minutes, requires no tools and costs a fraction of competing drive systems

ACCESSORIES



LIGHTWEIGHT POSITIONER

Proven versatility, quick and easy to install.




AUTOSTROKE AST-200

Increases efficiency in applications with plugged tubes.



HOSE CONTAINMENT

Protects hose and improves workplace safety.



FIN FAN ACCESSORY

Adapts the AutoBox family to clean Fin Fan style exchangers.