
FITTINGS 20K PSI (1380 BAR)

FITTINGS 20K PSI (1380 BAR)

20K AIR-OPERATED DUMP VALVES

The Air-Operated Dump Valve allows an operator to remotely control pressure in cleaning applications from 20k psi (1400 bar). When air is sent to the cylinder, the valve closes and allows the system to build pressure. The valve opens when the air is exhausted, reducing system pressure to near atmospheric.


PART NO.	DESCRIPTION
ACDA 61020019-K	Kit, Dump Valve Assembly w/Air Hose and Fittings, 20k, w/Air Fittings
ACDA 610200342	Dump Assembly, Air Diverter Valve, 20k/50gpm, w/Base Plate
ACDA 610200342-K	Kit, Dump Valve Assembly w/Air Hose and Fittings, 20k/50gpm w/Base Plate



HIGH PRESSURE REPLACEMENT CARTRIDGES


Cartridge Style Design allows dump valve to be rebuilt in under a minute with no special tools.

PART NO.	DESCRIPTION
ACRC 60020010	Cartridge Assy. APS 20K Hand/Foot, J/S 51869
ACRC 60200003	Cartridge Assy. 20k GDWJ Hand/ Foot, GDWJ 3102121
ACRC 61020030	Cartridge Assy. CF H/F Mag, J/S 52750
ACRC 61050026	Cartridge Assy. C-15 1", J/S 53915
ACRC 70020011	Cartridge Assy. 20k FDV/PRV, J/S 52255
ACRC 70025000	Kit, 15k/20k PRV/FDV Repair, GDWJ 77800030



ACCESSORY O-RINGS FOR CARTRIDGES


PART NO.	DESCRIPTION
ACOR 30001018	0-Ring 22-17046
ACOR 30001029	0-Ring
ACOR 30001120	0-Ring
ACOR 30001122	0-RING J/S 26776
ACOR 30001218	0-Ring GDWJ 22-74207
ACOR 30003018BU	B/U Ring GDWJ 22-17047
ACOR 30003120BU	Back Up Ring
ACOR 30003122BU	Back Up Ring
ACOR 30003218BU	Back Up Ring



MEDIUM PRESSURE TEES

All medium pressure tees include gland, nuts, and collars.

PART NO.	CONNECTION TYPE	MAX. OPERATING PRESSURE	
	551112511511 1 11 2	psi	bar
AF 052-MP4	1/4" MP Female	22k	1500
AF 052-MP6	3/8" MP Female	22k	1500
AF 052-MP9	9/16" MP Female	22k	1500
AF 052-MP12	3/4" MP Female	22k	1500
AF 052-MP16	1" MP Female	22k	1500



MEDIUM PRESSURE ELBOWS

All medium pressure elbows include gland, nuts, and collars.

PART NO.	CONNECTION TYPE	MAX. OPERATING PRESSURE	
TAIT IIO.	COMMEDITOR THE	psi	bar
AF 050-MP4	1/4" MP Female	22k	1500
AF 050-MP6	3/8" MP Female	22k	1500
AF 050-MP9	9/16" MP Female	22k	1500
AF 050-MP12	3/4" MP Female	22k	1500
AF 050-MP16	1" MP Female	22k	1500

