

HOSE WHIP RESTRAINT

Perhaps the simplest and least expensive safety measure to implement, hose whip restraints prevent injury by restraining the hose in the event of an end fitting failure.

A hose whip restraint can be attached at any point where two hoses are joined, or to a pump's fluid end at the discharge side, or where a hose attaches to any piece of water jetting equipment.

NOTE: Proper installation is essential. Never exceed safe working load. Follow manufacturer's recommendations and ratings.



STEEL WHIP RESTRAINT

Manufactured from stainless high tensile wire rope with spring-loaded retainers for easy installation and removal.

21" (533 MM) • PART NO. ACWC SS-21



STEEL WHIP RESTRAINT

NYLON HOSE WHIP RESTRAINT

Made from durable strap with extra-heavy stitching. Fits any high pressure hose.

31" (787 MM) • PART NO. ACWC NY-31

44" (1118 MM) • PART NO. ACWC NY-44



NYLON HOSE WHIP RESTRAINT

LUBRICANTS

MSDS sheets are available for all lubricants.

LUBRICANT	PART NUMBER	QTY	DESCRIPTION
VISCOUS FLUID	BJ 048-X*	6 oz.	Synthetic Silicone Lubricant
AIR MOTOR OIL	GP 041	32 oz.	Almo 525/ISO 46/SAE 10
AUTO TRANS. FLUID	GP 042	32 oz.	Mercon®/Dexron® ATF
ANTI-SEIZE	GP 043	2 oz.	Blue Goop®
MOTOR OIL	GP 044	32 oz.	10W-40
GEARBOX LUBE	GP 046	32 oz.	80W-85W-90
THREAD SEALANT	GP 047	4 oz.	ThreadMate®
GREASE	GP 048	14 oz.	Synthetic Grease SHC 100

* Please specify "fast" or "slow" for the type of viscous fluid needed.

