HOSE, FITTINGS& ACCESSORIES

BACKOUT PREVENTERS

Backout preventers increase safety by keeping the tool from backing out of the pipe. Several options are available including fixtures for small diameter pipes, pipes with various flange bolt circle diameters and adapters for pipes with no-flange entry.



Pipe Sizes 2-6 in. (51-150 mm) Hose Sizes (I.D.) 0.12-0.32 in. (3-8 mm)



VE-400™ BACKOUT PREVENTER

The VE-400 is designed to protect the operator from a flex-lance exiting the tube sheet during cleaning operations.

The VE-400 adapts to both horizontal and vertical applications and has a wide range of adjustments that easily accommodate different tube sheet sizes.

• Weight Complete: 20 lb - (9.0 kg)











ACCESSORIES

PRESSURE GAUGES

- Stainless steel construction
- Easy to read
- Precision movement
- Color-coded gauge faces
- Glycerin-filled for vibration protection
- Built in Snubbers



PART NO.	DIAL SIZE		MOUNTING Style	CONNECTION Type	SCALE		GRADUATIONS		MAXIMUM OPERATING PRESSURE	
	in	mm	SITLE	ITPE	psi	bar	psi	bar	psi	bar
ACPG 35001003	4	100	Bottom	1/2" NPT Male	0-20k	1400	200	20	20k	1400
ACPG 35001005	4	100	Bottom	1/4" HP Female	0-40k	2750	500	50	40k	2750
ACPG 35001007	6	152	Bottom	1/4" HP Female	0-60k	4150	500	50	60k	4150
ACPG 35001025	4	100	Bottom	9/16" HP Male	0-40k	2750	500	50	40k	2750
ACPG 35001028	6	152	Bottom	9/16" HP Male	0-60k	4150	500	50	60k	4150

THREAD LUBRICANTS

Protect NPT threads on water jetting connections from galling or seizing up.



PART NO. GP 047 Parker® ThreadMate™ Thread Lubricant 2 oz. (57g) Tube

TEFLON® TAPE

Seals NPT threads and helps prevent leaks. Excellent for both plastic and metal pipe fittings.



PART NO. GPT 049-050 1/2 x 520" (1.27 x 1320 cm) Roll

PART NO. GP 037-025 1/4 x 520" (5.08 x 1320 cm) Roll