
# **FITTINGS • 15,000 PSI**



## **NIPPLES/STINGERS** — PIPE THREAD (NPT)

- Stainless steel
- Additional lengths available upon request




| PART NO.         | CONNECTION TYPE | O.D. IN/MM | I.D. IN/MM | MAXIMUM OPERATING PRESSURE |      | STOCK LENGTHS IN INCHES                               |
|------------------|-----------------|------------|------------|----------------------------|------|---|
|                  |                 |            |            | psi                        | bar  |   |
| SA 527-P1P1-XX   | 1/16 NPT        | 0.310/7.9  | 0.182/4.6  | 15k                        | 1000 | 12, 18, 24, 36, 48                                    |
| SA 325-P2P2-XX   | 1/8 NPT         | 0.405/10.3 | 0.215/5.5  | 15k                        | 1000 | 12, 18, 24, 36, 49                                    |
| SA 335-P4P4-XX   | 1/4 NPT         | 0.540/13.7 | 0.302/7.7  | 15k                        | 1000 | 12, 18, 24, 36, 50                                    |
| SA 347-P6P6-XX   | 3/8 NPT         | 0.675/17.1 | 0.415/10.5 | 15k                        | 1000 | 4, 8, 10, 12, 18, 24, 36, 48                          |
| SA 356-P8P8-XX   | 1/2 NPT         | 0.640/21.3 | 0.534/136. | 15k                        | 1000 | 3, 4, 6, 8, 10, 12, 18, 24, 36, 48                    |
| SA 366-P12P12-XX | 3/4 NPT         | 1.05/26.7  | 0.614/15.6 | 15k                        | 1000 | 3, 4, 5, 6, 12, 18, 22, 27, 30, 36,<br>40, 44, 53, 60 |
| SA 376-P16P16-XX | 1" NPT          | 1.315/33.4 | 0.599/15.2 | 12k                        | 830  | 6, 8, 18  |

# PLUGS — PIPE THREAD (NPT)

#### **HEX HEAD**

Stainless steel



| PART NO.     | CONNECTION<br>Type | MATERIAL  | MAXIMUM OPERATING<br>PRESSURE |      |  |
|--------------|--------------------|-----------|-------------------------------|------|--|
|              |                    |           | psi                           | bar  |  |
| AP2 002      | 1/8 NPT            | Stainless | 15k                           | 1000 |  |
| GP 026-P4SS  | 1/4 NPT            | Stainless | 15k                           | 1000 |  |
| GP 026-P6SS  | 3/8 NPT            | Stainless | 15k                           | 1000 |  |
| GP 025-P8C   | 1/2 NPT            | Carbon    | 15k                           | 1000 |  |
| GP 026-P8SS  | 1/2 NPT            | Stainless | 15k                           | 1000 |  |
| GP 026-P12C  | 3/4 NPT            | Carbon    | 15k                           | 1000 |  |
| GP 026-P12SS | 3/4 NPT            | Stainless | 15k                           | 1000 |  |
| GP 026-P16SS | 1" NPT             | Stainless | 15k                           | 1000 |  |

### **SOCKET HEAD**

Stainless steel



| PART NO.     | CONNECTION<br>Type | MATERIAL  | MAXIMUM OPERATING PRESSURE |      |  |
|--------------|--------------------|-----------|----------------------------|------|--|
|              |                    |           | psi                        | bar  |  |
| GP 025-P1SS  | 1/16 NPT           | Stainless | 15k                        | 1000 |  |
| GP 025-P2SS  | 1/8 NPT            | Stainless | 15k                        | 1000 |  |
| GP 025-P4C   | 1/4 NPT            | Carbon    | 15k                        | 1000 |  |
| GP 025-P4SS  | 1/4 NPT            | Stainless | 15k                        | 1000 |  |
| GP 025-P6SS  | 3/8 NPT            | Stainless | 15k                        | 1000 |  |
| GP 025-P8C   | 1/2 NPT            | Carbon    | 15k                        | 1000 |  |
| GP 025-P8SS  | 1/2 NPT            | Stainless | 15k                        | 1000 |  |
| GP 025-P12C  | 3/4 NPT            | Carbon    | 15k                        | 1000 |  |
| GP 025-P12SS | 3/4 NPT            | Stainless | 15k                        | 1000 |  |