
FITTINGS • 20,000 PSI



MEDIUM PRESSURE MALE TO MEDIUM PRESSURE FEMALE CONNECTIONS


Fittings include gland nut and collar for female connection.

PART NO.	CONNECTION TYPE		MAX. OPERATING PRESSURE	
	Connection 1	Connection 2	psi	bar
AF 066-MP4MP6	1/4 MP Female	3/8 MP Male	22,000	1500
AF 066-MP4MP9	1/4 MP Female	9/16 MP Male	22,000	1500
AF 066-MP6MP9	3/8 MP Female	9/16 MP Male	22,000	1500
AF 066-MP6MP12	3/8 MP Female	3/4 MP Male	22,000	1500
AF 066-MP9MP12	9/16 MP Female	3/4 MP Male	22,000	1500
AF 066-MP9MP16	9/16 MP Female	1" MP Male	22,000	1500
AF 066-MP12MP16	3/4 MP Female	1" MP Male	22,000	1500



MEDIUM PRESSURE GLAND, NUTS, COLLARS, AND PLUGS

CONNECTION TYPE	PART NUMBERS			
001111201101111112	GLAND NUT	COLLAR	PLUG	
1/4 MP	AF 070-MP4	AF 071-MP4	AF 076-MP4	
3/8 MP	AF 070-MP6	AF 071-MP6	AF 076-MP6	
9/16 MP	AF 070-MP9	AF 071-MP9	AF 076-MP9	
3/4 MP	AF 070-MP12	AF 071-MP12	AF 076-MP12	
1" MP	AF 070-MP16	AF 071-MP16	AF 076-MP16	



MEDIUM PRESSURE ANTI-VIBRATION GLAND ASSEMBLIES

Used to reduce stress on tubing threads in conditions where bending or vibration are present, anti-vibration gland assemblies feature a collet that clamps onto the tubing when the connection is tightened to provide extra support and strength.

PART NO.	CONNECTION TYPE	COLLAR PART NUMBER
AF 072-MP4	1/4 MP Female	AF 071-MP4
AF 072-MP6	3/8 MP Female	AF 071-MP6
AF 072-MP9	9/16 MP Female	AF 071-MP9
AF 072-MP12	3/4 MP Female	AF 071-MP12
AF 072-MP16	1" MP Female	AF 071-MP16

