

**SINGLE, DOUBLE OR TRIPLE
JETS — FOR PRECISE &
ACCURATE SOIL REMOVAL**



HX-101

Single Head Assembly
• OCIH Carbide (1)



HX-102

Double Head Assembly
• AP2 Attack Tips (2)



HX-103S

Triple Head Assembly
• AP2 Attack Tips (3)

NON-ROTARY HYDRO-X

Static Hydro Excavation Tools

Utilizes replaceable 1/8" npt AP2 Attack Tip nozzles (HX-102/103 models) or a single OCIH 1/4" npt carbide nozzle (HX-101). Using a single nozzle channels all of your pumps power in one direction for the most digging power. Whereas the in-line 2 and 3 patterns give operators the ability to jet with a wider spray pattern to trench material faster.

Each head has a 1/2" npt inlet connection to attach to the operating wand.

The included high-visibility urethane guard is replaceable with three bolts.

HYDRO-X

Up to 5k psi (350 bar)

3–12 gpm Flows (9–58 l/min)

3 Jet Patterns Available

Specifications

PRESSURE RANGE	Up to 5k psi 340 bar
FLOW RANGE	Up to 12 gpm 45 l/min
INLET CONNECTION	1/2 NPT
NOZZLES	1 x OCIH Carbide, 2 or 3 AP2 Attack Tip
WEIGHT	1.1 lb 0.5 kg

 **STONEAGE®**
ENGINEERING THE POWER OF WATER
1-866-795-1586 • WWW.STONEAGETOOLS.COM