


FITTINGS • 20,000 PSI1380 BAR



SCREW TYPE QUICK CONNECT COUPLINGS

	PART NO.	CONNECTION Type	COUPLING HALVES		SEAL KIT	RETAINING RING	MAX. OPERATING PRESSURE	
			Female	Male		minu	psi	bar
	GP 060-MP9	9/16 MP Female	GP 060-MP9F	GP 060-MP9M	GP 660-MP9	GP 661-MP9	22,000	1500
	GP 060-MP12	3/4 MP Female	GP 060-MP12F	GP 060-MP12M	GP 660-MP12	GP 661-MP12	22,000	1500

MEDIUM PRESSURE MALE CONNECTORS

PART NO.	CONNECT	MAX. OPERATING PRESSURE		
	Connection 1	Connection 2	psi	bar
AF 078-MP4MP4	1/4 MP Male	1/4 MP Male	22,000	1,500
AF 078-MP4MP6	1/4 MP Male	3/8 MP Male	22,000	1,500
AF 078-MP4MP9	1/4 MP Male	9/16 MP Male	22,000	1,579
AF 078-MP6MP6	3/8 MP Male	3/8 MP Male	22,000	1,579
AF 078-MP6MP9	3/8 MP Male	9/16 MP Male	22,000	1,579
AF 078-MP6MP12	3/8 MP Male	3/4 MP Male	22,000	1,579
AF 078-MP9MP9	9/16 MP Male	9/16 MP Male	22,000	1,579
AF 078-MP9MP12	9/16 MP Male	3/4 MP Male	22,000	1,579
AF 078-MP9MP16	9/16 MP Male	1" MP Male	22,000	1,579
AF 078-MP12MP12	3/4 MP Male	3/4 MP Male	22,000	1,579
AF 078-MP12MP16	3/4 MP Male	1" MP Male	22,000	1,579
AF 078-MP16MP16	1" NPT Male	1" MP Male	22,000	1,579
AF 078-MP9H9	9/16 MP Male	9/16 MP Male	22,000	1,579

