
FITTINGS • 15,000 PSI



15K AIR-OPERATED DUMP VALVES

The Air-Operated Dump Valve allows an operator to remotely control pressure in cleaning applications from 15,000 psi. When air is sent to the cylinder, the valve closes and allows the system to build pressure. The valve opens when the air is exhausted, reducing system pressure to near atmospheric.


| PART NO. | DESCRIPTION |
|---------------|--|
| ACDA 61001007 | Dump Assembly, 15K Air Actuated W/Base Plate |
| ACDA 61010012 | Foot Gun Assembly, 15K 1/2 NPT Dump Style |
| ACDA 61050014 | Foot Gun Assy, 15K Air Actuated, High Flow, w/Base Plate |
| ACDU 61001006 | Air Diverter Valve, 15K 1/2 W/O Base Plate |



HIGH PRESSURE REPLACEMENT CARTRIDGES

Cartridge Style Design allows dump valve to be rebuilt in under a minute with no special tools.

| PART NO. | DESCRIPTION | PRESSURE | |
|---------------|----------------------------------|----------|------|
| | | psi | bar |
| ACRC 60010020 | APS 15K, Hand/Foot, J/S 50902 | 15,000 | 1034 |
| ACRC 60100004 | 15k GDWJ Hand/Foot, GDWJ 3102111 | 15,000 | 1034 |
| ACRC 61020030 | CF H/F Mag, J/S 52750 | 11,500 | 800 |
| ACRC 61050012 | 10k, High Flow | 20,000 | 690 |
| ACRC 61050026 | C-15 1in, J/S 53915 | 15,000 | 1034 |
| ACRC 70010004 | 15k FDV/PRV, J/S 50234 | 15,000 | 1034 |
| ACRC 70025000 | 15k/20k PRV/FDV Repair | 15,000 | 1034 |



ACCESSORY O-RINGS FOR CARTRIDGES

| PART NO. | DESCRIPTION |
|-----------------|------------------------|
| ACOR 30001018 | 0-Ring 22-17046 |
| ACOR 30001029 | 0-Ring |
| ACOR 30001120 | 0-Ring |
| ACOR 30001122 | 0-Ring J/S 26776 |
| ACOR 30001218 | 0-Ring GDWJ 22-74207 |
| ACOR 30003018BU | B/U Ring GDWJ 22-17047 |
| ACOR 30003120BU | Back Up Ring |
| ACOR 30003122BU | Back Up Ring |
| ACOR 30003218BU | Back Up Ring |

