
# **NEW FOR 2017**

# WGR SWITCHER™

The new WGR Switcher is two tools in one. Switch between pulling or cleaning without removing the nozzle from the pipe. When the pump is idled down and brought back to pressure the tool will switch the water flow between two different sets of jets.

#### **FEATURES:**

- Eliminates extra runs needed to swap nozzles
  saving water and time
- Run more jobs with one tank of water
- Switch to pulling jets for maximum thrust. Excellent for longer runs, climbing hills, going against the flow and flushing large amounts of material
- Switch to cleaning jets to maximize power for cutting roots and clearing debris, all with out affecting the houses




# WGR Switcher Specifications

**DOETSCH ENVIRONMENTAL SERVICES** 

MAXIMUM PRESSURE	5k psi 350 bar
OPERATING PRESSURE	1500-5k psi 100-350 bar
ROTATION SPEED	150-300 rpm
FLOW	50-80 gpm 190-300 l/min
FLOW RATING	6 Cv
INLET CONNECTION	1 in. NPT or 1in. BSPP
NOZZLE PORTS	7 x 1/8 NPT
DIAMETER	4.5 in. 114 mm
LENGTH	10.25 in. 260 mm
WEIGHT COMPLETE	13 lb 5.9 kg

## WGR SWITCHER

Exploded View - Part Names and Numbers



## Maintenance & Overhaul Kits

- Shaft
- Nut
eal O-Ring
/rench
0-Ring
KIT
/rench
l Press Tube
on Press Tube
Install Tool
-V /a ati