


# **FITTINGS • 15,000 PSI**

## **WAFER TEES — PIPE THREAD (NPT)**

• Stainless steel


PART NO.	CONNECTION TYPE	MAXIMUM OPERATING PRESSURE	
		psi	bar
GP 030-P12	3/4 NPT Female	15k	1000
GP 030-P16	1" NPT Female	12k	830
GP 030-P8	1/2 NPT Female	15k	1000



## 90° WAFER ELBOWS — PIPE THREAD (NPT)

Stainless steel


PART NO.	MAXIMUM OPERATING CONNECTION TYPE PRESSURE		
		psi	bar
GP 050-P8P8	1/2 NPT Female	15k	1000
GP 050-P12P12	3/4 NPT Female	15k	1000
GP 050-P16P16	1" NPT Female	12k	830



## 45° WAFER ELBOWS — PIPE THREAD (NPT)

Stainless steel

PART NO.	CONNECTION TYPES		MAXIMUM OPERATING PRESSURE	
	Connection 1 (C1)	Connection 2 (C2)	psi	bar
GP 050-P16P16-45	1" NPT Female	1" NPT Female	12k	830



### **Y-FITTINGS/WAFER WYES**

Stainless steel

PART NO.	CONNECTION TYPE
GP 030-P12	Wafer Wye, 3/4 X 3/4 X 9/4 NPT
GP 030-P16	Wafer Wye, 1 X 1 X 1 NPT
GP 030-P8	Wafer Wye, 1/2 X 1/2 X 1/2 NPT

