FITTINGS • 20,000 PSI



THREAD LUBRICANTS

Protect the threads on water jetting connections from galling or seizing up.



PART NO. GP 043
Parker® ThreadMate™ Thread Lubricant
2 oz. (57g) Tube

TEFLON® TAPE

Seals threads and helps prevent leaks. Excellent for both plastic and metal pipe fittings.



1/2 x 520" (1.27 x 1320 cm) Roll

PART NO. GP 037-025

 $1/4\ x\ 520"$ (5.08 x 1320 cm) Roll For use on pipe thread (NPT) connections.

LUBRICANTS

MSDS sheets are available for all lubricants.

LUBRICANT	PART NUMBER	QTY	SOURCE	SPECIFICATION
VISCOUS FLUID	BJ 048-X	6 oz.	StoneAge®	Synthetic Silicone Lubricant
AIR MOTOR OIL	GP 041	32 oz.	Mobil	Almo 525/ISO 46/SAE 10
AUTO TRANS. FLUID	GP 042	32 oz.	NAPA®	Mercon®/Dexron® ATF
ANTI-SEIZE	GP 043	2 oz.	Swagelok	Blue Goop®
MOTOR OIL	GP 044	32 oz.	NAPA®	10W-40
GEARBOX LUBE	GP 046	32 oz.	NAPA®	80W-85W-90
THREAD SEALANT	GP 047	4 oz.	Parker	ThreadMate [®]
GREASE	GP 048	14 oz.	Mobil	Synthetic Grease SHC 100



