FITTINGS • 20,000 PSI



THREAD LUBRICANTS

Protect the threads on water jetting connections from galling or seizing up.



PART NO. GP 043
Blue Goop Thread Lubricant 2 oz. Tube

LUBRICANTS

MSDS sheets are available for all lubricants.

LUBRICANT	PART NUMBER	QTY	DESCRIPTION	
VISCOUS FLUID	BJ 048-X	6 oz.	Synthetic Silicone Lubricant	
AIR MOTOR OIL	GP 041	32 oz.	Almo 525/ISO 46/SAE 10	
AUTO TRANS. FLUID	GP 042	32 oz.	Mercon®/Dexron® ATF	
ANTI-SEIZE	GP 043	2 oz.	Blue Goop®	
MOTOR OIL	GP 044	32 oz.	10W-40	
GEARBOX LUBE	GP 046	32 oz.	80W-85W-90	
THREAD SEALANT	GP 047	4 oz.	ThreadMate [®]	
GREASE	GP 048	14 oz.	Synthetic Grease SHC 100	





HIGH PRESSURE REPLACEMENT CARTRIDGES

Cartridge Style Design allows dump valve to be rebuilt in under a minute with no special tools.

PART NO.	DESCRIPTION	PRESSURE	
TAITI NO.	DESCRIPTION		bar
ACRC 60020010	APS 20K Hand/Foot, J/S 51869	20,000	1380
ACRC 60200003	20k GDWJ Hand/ Foot, GDWJ 3102121	20,000	1380
ACRC 70020011	20k FDV/PRV, J/S 52255	20,000	1380

