

# **FITTINGS • 40,000 PSI** 2800 BAR


## **HIGH PRESSURE LANCE (HP LANCE)**

 The same geometry and threads as a standard high pressure tubing connection with the option of righthanded threads.


#### **SIZE REFERENCE CHART**

MALE • ACTUAL SIZE

SIZE CONNECTION THREAD	CONNECTION THREAD	RECOMMENDED TORQUE	
	ft-lbs	N-m	
1/4 HP Lance LH	1/4-28UNF-LH	15	20
1/4 HP Lance RH	1/4-28UNF-RH		
3/8 HP Lance LH	3/8-24UNF-LH	20	27
3/8 HP Lance RH	3/8-24UNF-RH		
9/16 HP Lance LH	9/16-18UNF-LH	- 25	34
9/16 HP Lance RH	9/16-18UNF-RH		







**LEFT-HAND THREADS** 

#### TYPE M

• Industry standard connection

### **SIZE REFERENCE CHART**

SINGLE PIECE MALE • ACTUAL SIZE

SIZE	CONNECTION THREAD	RECOMMENDED TORQUE	
		ft-lb	Nm
9/16 Type M	9/16 – 18UNF	30	41
3/4 Type M	3/4 – 16UNF	45	61
Type M	1" – 12UNF	70	95
1-5/16 Type M	1-5/16 – 12UN	110	149

