

## PRESSURE GAUGES

- Stainless steel construction
- Easy to read
- Precision movement
- Color-coded gauge faces
- Glycerin-filled for vibration protection
- Built in Snubbers



PART NO.	DIAL SIZE		MOUNTING STYLE	CONNECTION TYPE	SCALE		GRADUATIONS		MAXIMUM OPERATING PRESSURE	
	in	mm			psi	bar	psi	bar	psi	bar
ACPG 35001003	4	100	Bottom	1/2 NPT Male	0-20k	1400	200	20	20k	1400
ACPG 35001005	4	100	Bottom	1/4 HP Female	0-40k	2750	500	50	40k	2750
ACPG 35001007	6	152	Bottom	1/4 HP Female	0-60k	4150	500	50	60k	4150
ACPG 35001025	4	100	Bottom	9/16 HP Male	0-40k	2750	500	50	40k	2750
ACPG 35001028	6	152	Bottom	9/16 HP Male	0-60k	4150	500	50	60k	4150

## THREAD LUBRICANTS

Protect NPT threads on water jetting connections from galling or seizing up.



### PART NO. GP 047

Parker® ThreadMate™ Thread Lubricant  
2 oz. (57g) Tube

## TEFLON® TAPE

Seals NPT threads and helps prevent leaks. Excellent for both plastic and metal pipe fittings.



### PART NO. GPT 049-050

1/2 x 520" (1.27 x 1320 cm) Roll

### PART NO. GP 037-025

1/4 x 520" (5.08 x 1320 cm) Roll