

WG-1 CLASSIC

8"-36" Lines

The **WG-1** model is used in municipal, industrial and commercial drain cleaning applications. By installing replaceable **AP2** nozzle tips that are sized to maximize the efficiency and effectiveness of your pump, these tools are highly productive. This tool is predominately used in large combination trucks with 1" hose.

Optional Descaling Head for the WG-1.

WG 040-DS-R5

WG-1 CLASSIC

8"-36" Lines (203-914 mm)

Up to 5k psi (350 bar)

50-80 gpm Flows (190-300 l/min)

Classic WG-1 Model

| WG-1 CLASSIC SPECS | | |
|----------------------|---------------|---------------|
| MODEL | WG-1 CLASSIC | |
| Maximum Pressure | 5k psi | 350 bar |
| Operating Pressure | 1500-5k psi | 100-350 bar |
| Rotation Speed | 150-300 rpm | |
| Flow | 50-80 gpm | 190-300 l/min |
| Flow Rating | 4.6 Cv | |
| Pulling Force | 70-100 lb | 310-450 Nm |
| Inlet Connection | 1 NPT or BSPP | |
| Length | 9.1 in. | 231 mm |
| Diameter Incl. Cent. | 4.8 in. | 122 mm |
| Nozzle Ports | 5 x 1/8 NPT | |
| Weight Complete | 10.9 lb | 4.9 kg |