

3"-6" LINES

WT-3/8-C WITH EXTENDED-LIFE CARBIDE BUTTONS, STANDARD ON EVERY MODEL.



WT-3/8-C
CLASSIC

3"-6" Lines with Elbows

Our smaller Classic series **WARTHOG** models can negotiate elbows and clean-outs commonly found in laterals at homes, buildings, restaurants and other light commercial facilities. This tool is most commonly used on small capacity pumps and cart jetters. Also an excellent choice for cutting roots, clearing ice and removing blockages. The **WT-3/8-C** is designed specifically to handle 3"-6" lines and clean-outs.

Pipes made of cast iron and those that have sand or silt can act as abrasive agents that can aggressively wear out the tool. We've added permanent carbide buttons to the **WT-3/8-C** to increase head life. Our carbide buttons are available in all offsets and add up to 5 times the life compared to previous **WT-3/8** models. It also features replaceable **AP2** nozzles.

WT-3/8-C 3"-6" Lines (76-152 mm)	Up to 5k psi (350 bar)
	5-12 gpm Flows (20-45 l/min)
	Classic Workhorse Model

WT-3/8-C SPECS	
Maximum Pressure	5k psi 350 bar
Operating Pressure	1500-5k psi 100-350 bar
Rotation Speed	300-500 rpm
Flow	5-12 gpm 20-45 l/min
Flow Rating	0.75 Cv
Pulling Force	5-20 lb 22-90 N
Inlet Connection	3/8 NPT or BSPP
Tool Diameter	1.9 in. 48 mm
Length	3.0 in. 76 mm
Nozzle Ports	3 x 1/8 NPT
Weight Complete	1.2 lb .54 kg