

HIGH PERFORMANCE LESS MAINTENANCE LONGER LIFE



WGR MAGNUM

Extended tool durability.

The **WGR MAGNUM** is the first tool in the Warthog Magnum series, specifically designed for extended tool durability and optimal handling of dirty or recycled water.

- Optimized speed control extends maintenance intervals
- Latest seal technology effectively handles dirty or recycled water for improved performance
- Flush style head protects front shaft seals for longer tool life
- Streamlined design keeps tool from catching inside pipe
- Carbide nozzles generate higher quality jets
- Descaling ports now come standard
- Hardened steel centralizer with 4x longer life
- Optional fin sizes for different pipe diameters
- Independently replaceable fins can be easily replaced as wear occurs without opening tool body
- Choose your rotation speed with 3 viscous fluid options

WGR

6"-36" Lines (20-90 cm)

Up to 5k psi (350 bar)

50-80 gpm Flows (190-300 l/min)

Standard Descaler or Puller Descaler

WGR	SPECS
Maximum Pressure	5k psi 350 bar
Operating Pressure	1500-5k psi 100-350 bar
Rotation Speed	150-300 rpm
Flow	50-80 gpm 190-300 l/min
Flow Rating	6 Cv
Inlet Connection	1 in. NPT or 1in. BSPP
Diameter	4.5 in. 114 mm
Length	10.25 in. 260 mm
Nozzle Ports	7 x 1/8 NPT
Weight Complete	13 lb 5.9 kg