

WS-1/2 CLASSIC

4"-8" Lines

The WS-1/2 is designed to handle 4"-8" lines and is most commonly used with trailer jetters. It is used to clean lines in restaurants, hospitals, multi-story apartment buildings, residential, and other applications. Easily removes grease, cut roots, ice and soil blockages.

WS-1/2

110-1/2

4"-8" Lines (102-204 mm)

Up to 5k psi (350 bar)

8-20 gpm Flows (30-76 l/min)

3 Models Available

JOINTED INLET MODELS

This model allows the inlet hose to bend to the side, shortening the rigid length of the tool and allowing limited access applications to be cleaned much easier. 1/2" NPT or BSPP inlet ports available.



OPTIONAL RIGID INLETS

The **WS-P8** is excellent for straight pipes. The whip hose is removed, allowing the hose to connect directly to the tool. Available with a female 1/2" NPT or BSPP connection. In this configuration 4" 90° bends are no longer negotiable.





Optional Descaling Head for the WS Line of Tools

WS 040-DS

WS-1/2 SPECS		
Maximum Pressure	5k psi	350 bar
Operating Pressure	1500-5k psi	100-350 bar
Rotation Speed	200-500 rpm	
Flow	8-20 gpm	30-76 l/min
Flow Rating	1.3 Cv	
Pulling Force	9-27 lb	40-120 N
Inlet Connection	1/2 NPT & BSPP	
Tool Diameter	1.9 in.	48 mm
Length	4.4 in.	112 mm
Nozzle Ports	3 x 1/8 NPT	
Weight Complete	2.95 lb	1.33 kg
14/ 66		

We now offer an optional 35 ft. hose with a 1/2" NPT inlet. **WS 020-35**