Crew 1.0 - Configuration Reference

This document has two parts. The first is short and hand-written: how crew's two config files combine, how to see what is in force, and the common setups. The second is generated from the code and lists every key.

How the Two Files Combine

crew reads two JSON files:

- `~/.claude/crew/config.json` - the **machine-global** file. Your personal defaults for every repo on this machine: providers and models, notifications, auto-clear, the guards, how far autopilot may go.
- `.crew/config.json` - the **repo** file. Facts about one checkout: the tracker, the board, scope enforcement, production declarations.

The repo file wins over the machine file, which wins over crew's defaults. Four exceptions, each named in the Layer column below:

- A **repo-only** key in the machine file takes effect nowhere. It is pruned on read and refused on write.
- A **ratcheted** key (`install.policy`, each guard `guards.profile` and `guards.overrides` expand to, `change.requireForProduction`, `environments.prodUnattended`) resolves to the narrower of the two values, so a cloned repo cannot widen what your machine allows.
- A **machine-armed** key (`resume.auto`, `context.autoClear.enabled`) can be turned on only in the machine file. A repo can only switch it off.
- A **personal** key (the five `autopilot.*` keys) resolves per key to the stricter of the layers that set it; a layer that says nothing imposes nothing. A machine value is your default for every repo, which a repo may narrow and never widen.

A `null` in the repo file over a machine value inherits the machine value. The `/crew:init` template writes every key except the personal ones, so it does not shadow your machine defaults for those; a repo `/crew:init` set up before that still spells `autopilot.mode: "off"`, which holds a machine `plan` down until you remove it (`--explain --all` names it as a `shadow:`).

Seeing What Is in Force

- `/crew:config --show` prints every machine-settable key, its value and the layer it came from, and names any key that takes effect nowhere.
- `/crew:config` with no argument is a menu that writes either file through the validated path. It shows a dry run first, refuses unknown keys and out-of-range values, and marks a widening with `!`.
- From a shell: `python3 plugin/crew/hooks/scripts/crew_config.py --explain` is the same table, `--explain --all` adds every repo-only key and names each shadowing repo value, and `--models` is the per-role provider table.

Backups and Rebuilding a Lost Config

Every write a crew script makes to either file first copies the old bytes to `~/.claude/crew/backups/` (the newest 20 per file kept) and is refused when that copy fails; a hand edit is not backed up. `crew_config.py --backups` lists the machine file's (add `--repo` for the repo file's) and `--restore <stamp> --apply` puts one back. Your non-default values are kept in `~/.claude/crew/profile.json` (and in your vault when `memory.vaultPath` is set), so `--rebuild --repo` or `--rebuild --global` regenerates a lost or corrupt file from the template plus that profile, as a dry run until `--apply`.

Common Setups

- **Personal defaults once, for every repo.** Put providers, models, `notify.*`, the guards and the `autopilot.*` keys in `~/.claude/crew/config.json`. Leave repo files to repo facts.
- **Self-approval under autopilot.** Set `autopilot.mode: "plan"` and choose `autopilot.approval` (`human`, `self` or `risk`) in either file, and set `scope.allowCliApproval: true` in the repo file, which is the only file that key is read from. Review acceptance and production deploys still stop for you.
- **Notifications.** In the machine file, set `notify.provider` and the name of the environment variable holding the token in `notify.tokenEnv`. The secret stays in your environment, never in the file. `tokenEnv` is machine-only: a repo file's value is ignored with a notice.

The key list is `plugin/crew/CONFIG.md`, which ships with the plugin; the reasoning behind the keys is in `docs/crew/config-rationale.md`.

Reference (Generated)

Generated from the code by `python3 docs/guides/crew/src/config_reference.py --write`. Do not edit by hand: `python3 scripts/check-marketplace.py` fails when this file is stale.

87 keys: 50 settable in the machine-global file, 37 repo-only.

Columns:

- **Layer**: which file may set the key.
- **Default**: what `default_config()` returns. Where the machine default differs, both are shown.
- **Values**: the values crew accepts, read from the same tuple the validator reads. "not validated" means crew checks nothing and names the file that reads the key.
- **Since**: the first crew version whose template declared the key. Keys in the first template (crew 0.11.0) read "0.11.0 or earlier".

Layers

- **repo**: only `.crew/config.json` may set it; the global file's value is pruned on read and refused on write.
- **both**: either file may set it; the repo value wins over the machine one.
- **both, ratchet**: either file may set it, and the NARROWER of the two wins (`crew_guards.RATCHETED_KEYS`). A repo can tighten what the machine allows, never loosen it.
- **both, widening warned**: either file may set it and the repo wins, but a write that widens it is flagged (`crew_config._RATCHETED`).
- **both, stricter wins**: a personal key (`crew_guards.PERSONAL_KEYS`): either file may set it, and where both do the STRICTER value wins; a layer that is silent (absent or `null`) imposes nothing, so a machine value is your default for every repo and a repo may only narrow it.
- **machine-arms**: only the global file can turn it on (exactly `true`); a repo may only veto it with `false` (`crew_config.REPO_VETO_ONLY`).
- **machine-only**: read from the global file alone; a repo's own value is never consulted.

Top-Level Keys

Setting	Layer	Default	Values	Since	Summary
`schema`	repo	`8`	not validated - read by `plugin/crew/hooks/scripts/crew_state.py` (expects integer)	0.11.0 or earlier	Config schema version; `/crew:migrate` upgrades an older one.
`tracker`	repo	`"files"`	`files` | `obsidian` | `jira` | `sdp`	0.11.0 or earlier	Where tickets live; `crew_tracker.resolve` answers `could not tell` when two configs disagree.
`verifyGate`	repo	`true`	not validated - read by `plugin/crew/hooks/scripts/verify-gate.sh` (expects boolean)	0.11.0 or earlier	Run the Stop verify gate.

Qa

Setting	Layer	Default	Values	Since	Summary
`qa.provider`	both	`"auto"`	`auto` | `claude` | `codex` | `copilot` | `kimi`	0.11.0 or earlier	Who reviews: `auto` walks `qa.order`; a named provider is used as-is.
`qa.order`	both	`["codex", "kimi", "copilot", "claude"]`	list of: `claude` | `codex` | `copilot` | `kimi`	0.14.6	The reviewers `auto` tries, in order. A list is one leaf, replaced wholesale.

Setting	Layer	Default	Values	Since	Summary
`qa.fallback`	both	`"claude-sonnet-5"`	not validated - read by `plugin/crew/commands/review.md` (expects model id)	0.16.6	Model a gone pin falls back to, on its family's provider (L-0712).
`qa.codex.model`	both	`null`	not validated - read by `plugin/crew/commands/review.md` (expects string or null)	0.14.6	Codex model for review; null passes no flag.
`qa.codex.reasoningEffort`	both	`null`	`none` | `minimal` | `low` | `medium` | `high` | `xhigh` | `max` (listed in `plugin/crew/commands/review.md`; not validated)	0.14.6	Codex reasoning effort for review; null passes no flag.
`qa.copilot.model`	both	`null`	not validated - read by `plugin/crew/commands/review.md` (expects string or null)	0.14.6	Copilot model for review; null uses the CLI default.
`qa.kimi.model`	both	`null`	not validated - read by `plugin/crew/commands/review.md` (expects string or null)	1.0.39	Kimi Code model id for review (`k3`, `kimi-for-coding`, ...); null uses the CLI's own default.
`qa.roles`	both	`{}`	object of role pins; each pin's provider	0.16.6	Per-role reviewer pins, `qa.roles.<role>`

Setting	Layer	Default	Values	Since	Summary
			is checked (checked in `plugin/crew/hooks/scripts/crew_config.py`)		`.provider` / `.model`; a pin beats the provider block for that role.

Dev

Setting	Layer	Default	Values	Since	Summary
`dev.provider`	both	`"claude"`	`claude` | `codex` | `copilot` | `kimi`	0.14.6	Who implements.
`dev.fallback`	both	`"claude-sonnet-5"`	not validated - read by `plugin/crew/skills/crew-providers/SKILL.md` (expects model id)	0.16.6	Model a gone dev pin falls back to, on its family's provider.
`dev.codex.model`	both	`null`	not validated - read by `plugin/crew/skills/crew-providers/SKILL.md` (expects string or null)	0.14.6	Codex model f implementatio
`dev.codex.reasoningEffort`	both	`null`	`none` | `minimal` | `low` | `medium` | `high` | `xhigh` | `max` (listed in `plugin/crew/commands/review.md`; not validated)	0.14.6	Codex reasoning effo for implementatio
`dev.copilot.model`	both	`null`	not validated - read by	0.14.	Copilot model for

Setting	Layer	Default	Values	Since	Summary
			`plugin/crew/skills/crew-providers/SKILL.md` (expects string or null)	6	implementatio
`dev.kimi.model`	both	`null`	not validated - read by `plugin/crew/skills/crew-providers/SKILL.md` (expects string or null)	1.0.39	Kimi Code model id for implementatio as `qa.kimi.model`.
`dev.roles`	both	`{}`	object of role pins; each pin's provider is checked (checked in `plugin/crew/hooks/scripts/crew_config.py`)	0.16.6	Per-role dev pins, as `qa.roles`.

`secondOpinion`

Setting	Layer	Default	Values	Since	Summary
`secondOpinion.provider`	both	`"none"`	not validated - read by `plugin/crew/commands/plan.md` (expects string)	0.11.0 or earlier	Second-opinion provider for plans; `none` is off.
`secondOpinion.mode`	both	`"cli"`	not validated - read by `plugin/crew/skills/crew-providers/SKILL.md` (expects string)	0.11.0 or earlier	How the second opinion is reached.

Setting	Layer	Default	Values	Since	Summary
`secondOpinion.model`	both	`null`	not validated - read by `plugin/crew/skills/crew-providers/SKILL.md` (expects string or null)	0.11.0 or earlier	Second-opinion model.

Jira

Setting	Layer	Default	Values	Since	Summary
`jira.project`	repo	`null`	not validated - read by `plugin/crew/commands/jira-sync.md` (expects string or null)	0.11.0 or earlier	Jira project key. No consumer found (docs/crew/config-rationale.md).
`jira.cloudId`	repo	`null`	not validated - read by `plugin/crew/commands/jira-sync.md` (expects string or null)	0.19.10	Jira cloud id, cached by `/crew:jira-sync`; read by nothing.

Obsidian

Setting	Layer	Default	Values	Since	Summary
`obsidian.vaultPath`	repo	`null`	not validated - read by `plugin/crew/hooks/scripts/crew_tracker.py` (expects path or null)	0.11.0 or earlier	Vault holding the board; falls back to `memory.vaultPath` and must hold `.obsidian/`.
`obsidian.boardDir`	repo	`null`	not validated - read by `plugin/crew/hooks/scripts/crew_tracker.py` (expects path or null)	0.11.0 or earlier	Board folder inside the vault (relative, no `..`).

Memory

Setting	Layer	Default	Values	Since	Summary
`memory.mode`	both	`"repo"`	not validated - read by `plugin/crew/skills/crew-memory/SKILL.md` (expects string)	0.11.0 or earlier	Where memory lives (`repo`, or a vault).
`memory.vaultPath`	both	`null`	not validated - read by `plugin/crew/hooks/scripts/crew_recall.py` (expects path or null)	0.11.0 or earlier	The Obsidian vault used for memory.

Context

Setting	Layer	Default	Values	Since	Su
`context.enabled`	repo	`true`	not validated -	0.11.0	Ru

Setting	Layer	Default	Values	Since	Su
			read by `plugin/crew/hooks/scripts/context-watch.sh` (expects boolean)	or earlier	co wa
`context.warnAt`	repo	`0.4`	not validated - read by `plugin/crew/hooks/scripts/context-watch.sh` (expects number)	0.11.0 or earlier	Fr th at th wa wr ar cl de si (w ar va ke
`context.reserveTokens`	repo	`0`	not validated - read by `plugin/crew/hooks/scripts/context-watch.sh` (expects integer or null)	0.11.0 or earlier	To ba th `nu` of
`context.autoClear.enabled`	machine-arms	`null`	`null` | `true` | `false` (checked in `plugin/crew/hooks/scripts/crew_autocycle.py`)	0.19.10	Au af wr On m ca (e `tr` re

Setting	Layer	Default	Values	Since	Su
context.autoClear.method	both	"auto"	auto | none | notify | tmux | xdotool | wtype; per OS: linux: auto, none, notify, tmux, xdotool, wtype; macos: auto, none, notify, tmux; windows: auto, none, notify; windows-bash: auto, none, notify, tmux	0.19.10	ve He is au pe pl m OS st au do
context.autoClear.delaySeconds	both	3	number (coerced in plugin/crew/hooks/scripts/crew_autocycle.py)	0.19.10	De be ty ur va ar as
context.autoClear.minHandoffLines	both	5	number (coerced in plugin/crew/hooks/scripts/crew_autocycle.py)	0.19.10	Sk ha m cl af no re
context.autoClear.onlyRepos	machine-only	null	list of absolute repo paths, or null (coerced in plugin/crew/hooks/scripts/crew_a	1.0.25	Na or m or na no

Setting	Layer	Default	Values	Since	Su
			`utocycle.py`)		lis or re a ar no
`context.autoClear.onlySessions`	machine-only	`null`	list of session ids, or null (coerced in `plugin/crew/hooks/scripts/crew_autocycle.py`)	1.0.25	As on fo id bo bo m
`context.autoClear.wrapUp`	machine-arms	`null`	`null` | `true` | `false` (checked in `plugin/crew/hooks/scripts/crew_autocycle.py`)	1.0.334	Au up au (T th be th pr ar cl fo re On m ar (e tr wi en ar re ve

Resume

Setting	Layer	Default	Values	Since	Summary
`resume.auto`	machine-arms	`null`	`null` | `true` | `false` (checked in `plugin/crew/hooks/scripts/crew_resume.py`)	1.0.40	Auto-resume after `/clear` or a manual `/compact`. Only the machine file can arm it (exactly `true`); a repo `false` vetoes it.

Emergency

Setting	Layer	Default	Values	Since	Summary
`emergency.standDown`	repo	`true`	not validated - read by `plugin/crew/hooks/scripts/_common.sh` (expects boolean)	0.11.0 or earlier	Whether a declared incident may stand gates down; `false` forbids it.
`emergency.maxTtlMinutes`	repo	`480`	integer (coerced in `plugin/crew/hooks/scripts/crew_incident.py`)	0.11.0 or earlier	Longest incident lifetime; never below `ttlMinutes`.

Notify

Setting	Layer	Default	Values	Since	Summary
`notify.provider`	both	`null`	telegram, teams, none or null; any other value sends nothing (coerced in `plugin/crew/ho`	0.11.0 or earlier	Where notifications go: `telegram`, `teams` or `none` (off). A repo null inherits the machine

Setting	Layer	Default	Values	Since	Summary
			`oks/scripts/crew_notify.py`)		provider; a repo `none` opts this repo out.
`notify.tokenEnv`	machine-only	`null`	not validated - read by `plugin/crew/hooks/scripts/crew_notify.py` (expects string or null)	0.11.0 or earlier	Name of the environment variable holding the Telegram bot token; null may be filled from the notify skill's `bot_token_env`. Honoured from the machine file only.
`notify.chatId`	both	`null`	not validated - read by `plugin/crew/hooks/scripts/crew_notify.py` (expects string or null)	0.11.0 or earlier	Telegram chat id; null may be filled from the notify skill's `chat_id`, and the skill's example value counts as unset.
`notify.events`	both	`["blocker", "deploy", "question"]`	list of event names; an unknown name is dropped with a notice (coerced in `plugin/crew/hooks/scripts/crew_notify.py`)	0.11.0 or earlier	Events that notify: `deploy`, `question`, and `blocker` (T-0060's four blocker reasons). The pre-1.0 names `gate`, `waiting`, `phase`, `review` and `done` are

Setting	Layer	Default	Values	Since	Summary
					mapped with a notice. A list is one leaf.

Platform

Setting	Layer	Default	Values	Since	Summary
`platform.os`	repo	`null`	not validated - read by `plugin/crew/hooks/scripts/crew_platform.py` (expects string or null)	0.11.0 or earlier	Detected OS, stamped by platform-sync.
`platform.wsl`	repo	`null`	not validated - read by `plugin/crew/hooks/scripts/crew_platform.py` (expects boolean or null)	0.11.0 or earlier	Detected WSL, stamped by platform-sync.
`platform.shell`	repo	`null`	not validated - read by `plugin/crew/hooks/scripts/crew_platform.py` (expects string or null)	0.11.0 or earlier	Detected shell, stamped by platform-sync.
`platform.windowsHostIp`	repo	`null`	not validated - read by `plugin/crew/hooks/scripts/crew_platform.py` (expects string or null)	0.11.0 or earlier	Windows host IP seen from WSL.

Pm

Setting	Layer	Default	Values	Since	Summary
`pm.authority`	both,	`"report-only"`	`report-only` |	0.11.0	How much the

Setting	Layer	Default	Values	Since	Summary
	widening warned		`act` | `autonomous`	or earlier	PM may do unasked. A widening is warned about; the two layers combine by precedence.
`pm.maxDispatches`	both	`3`	integer (coerced in `plugin/crew/hooks/scripts/crew_state.py`)	0.11.0 or earlier	Roles the PM may dispatch in one pass.

Graph

Setting	Layer	Default	Values	Since	Summary
`graph.out`	repo	`"graphify-out"`	not validated - read by `plugin/crew/hooks/scripts/crew_state.py` (expects path)	0.11.0 or earlier	Where the code graph is written.

Install

Setting	Layer	Default	Values	Since	Summary
`install.policy`	both, ratchet	`"manual"`	`manual` | `ask` | `auto` (ratchet: narrower layer wins; listed narrowest first)	0.19.18	Whether crew may install a missing prerequisite.

Guards

Setting	Layer	Default	Values	Since	Summary
`guards.profile`	both, ratche	`"off"`	`off` | `standard` |	1.2.62	One word for the twelve guards: `off`

Setting	Layer	Default	Values	Since	Summary
	t		`strict`		(today's defaults), `standard` or `strict`. Expands per layer; each guard's ratchet then runs on the expanded values.
`guards.overrides`	both, ratchet	`{}`	object of guard name to tier (checked in `plugin/crew/hooks/scripts/crew_guards.py`)	1.2.62	`guards.overrides.<guard>`: one guard's tier, replacing the profile's value for it. Each entry is checked against that guard's own tiers; a bad one reads as the floor.

Production

Setting	Layer	Default	Values	Since	Summary
`production.databases`	repo	`[]`	not validated - read by `plugin/crew/hooks/scripts/crew_config.py` (expects list of globs)	0.19.30	Globs naming production databases.
`production.hosts`	repo	`[]`	not validated - read by `plugin/crew/hooks/scripts/crew_config.py` (expects list of globs)	0.19.30	Globs naming production hosts.

Cloud

Setting	Layer	Default	Values	Since	Summary
`cloud.awsProfiles`	repo	`[]`	not validated -	1.0.2	AWS profiles

Setting	Layer	Default	Values	Since	Summary
			read by `plugin/crew/hooks/scripts/cloud_guard.py` (expects list of names)	5	this repo may use.
`cloud.awsRegions`	repo	`[]`	not validated - read by `plugin/crew/hooks/scripts/cloud_guard.py` (expects list of names)	1.0.25	AWS regions this repo may use.
`cloud.azureSubscriptions`	repo	`[]`	not validated - read by `plugin/crew/hooks/scripts/cloud_guard.py` (expects list of names)	1.0.25	Azure subscriptions this repo may use.

Environments

Setting	Layer	Default	Values	Since	Summary
`environments.nonProd`	repo	`[]`	not validated - read by `plugin/crew/hooks/scripts/crew_config.py` (expects list of globs)	1.0.37	Terraform targets that are not production and may run unattended.
`environments.prodUnattended`	both, ratchet	`false`	`false` | `true` (ratchet: narrower layer wins; listed narrowest	1.0.37	Whether production terraform may run unattended;

Setting	Layer	Default	Values	Since	Summary
			first)		`true` only when both layers say so.
`environments.workflows`	repo	`{}`	not validated - read by `plugin/crew/hooks/scripts/crew_config.py` (expects object of glob to string)	1.1.16	Deploy workflow globs, each mapped to its environment or `input:<name>`.

Change

Setting	Layer	Default	Values	Since	Summary
`change.requireForProduction`	both, ratchet	`false`	`true` | `false` (ratchet: narrower layer wins; listed narrowest first)	0.19.31	Require an approved change request before `/crew:promote production`: a repo may turn it on, never off.

Git

Setting	Layer	Default	Values	Since	Summary
`git.forbiddenTrailers`	both	`[]`	list of trailer tokens (letters, digits and `-`, no `:`) (checked in `plugin/crew/hoo`	1.0.328	Commit trailer tokens the owner forbids, reported by `/crew:done`. The two layers combine by

Setting	Layer	Default	Values	Since	Summary
			ks/scripts/crew_trailers.py)		union, so a repo can add a token and never remove the machine owner's; a value that is not a list of tokens makes the list unknown, never empty (docs/crew/config-rationale.md).

Scope

Setting	Layer	Default	Values	Since	Summary
scope.mode	repo	"off"	off | report | block | auto	1.0.25	Whether the scope guard enforces a ticket's Touch list; a value outside these fails closed to block.
scope.allowCliApproval	repo	false	false | true (checked in plugin/crew/hooks/scripts/crew_ticket.py)	1.0.25	Whether a CLI-written approval receipt counts; only exactly true allows it. autopilot.approval: self or risk needs it, and autopilot.mode: plan or backlog, to approve anything. A hand edit by the owner in the repo's .crew/config.json ("scope": {"allowCliApproval": true}); crew_config.py --set refuses it.

Autopilot

Setting	Layer	Default	Values	Since	Summ
`autopilot.mode`	both, stricter wins	`"off"`	`off` | `plan` | `backlog` (checked in `plugin/crew/hooks/scripts/crew_autopilot.py`); personal: listed strictest first, the stricter wins	1.0.41	Only t `plan` (and `ba` goal's deper inside `/crew:` anyth off, wi
`autopilot.maxPhases`	both, stricter wins	`12`	positive integer (checked in `plugin/crew/hooks/scripts/crew_autopilot.py`); personal: the smaller wins	1.0.41	Phase take; positiv as 12,
`autopilot.deploy`	both, stricter wins	`"none"`	`none` | `nonprod` | `all`; personal: listed strictest first, the stricter wins	1.0.42	Where run wi anyth `none`.
`autopilot.approval`	both, stricter wins	`"risk"`	`human` | `risk` | `self`; personal: listed strictest first, the stricter wins	1.0.42	Who a under anyth `human`. also n `autopi` `backlo` `scope.` `true` (repo's `.crew/` refuse each u its val file th under

Setting	Layer	Default	Values	Since	Summ
					risk th
`autopilot.questions`	both, stricter wins	`"risk"`	`human` | `risk` | `self`; personal: listed strictest first, the stricter wins	1.0.42	Who a open autop reads
`autopilot.maxAutoReplans`	repo	`0`	non-negative integer (checked in `plugin/crew/hooks/scripts/crew_autopilot.py`)	1.0.339	Succe autop reject round itself; anyth negat as 0, a with a
`autopilot.ship`	repo	`"merge"`	`pr` | `merge`	1.0.349	After pushe PR; `me` (a me the re allow. reads warni
`autopilot.sleep.schedule`	repo	`null`	HH:MM-HH:MM or null (checked in `plugin/crew/hooks/scripts/crew_sleep.py`)	1.0.332	A nigh `HH:MM-` local t midni two sl apply. could stricte applie
`autopilot.sleep.approval`	repo	`null`	`null` | `human` | `self` | `risk` (checked in `plugin/crew/hooks/scripts`	1.0.332	`autopi` inside windo day va

Setting	Layer	Default	Values	Since	Summ
			/crew_sleep.py)		else c the st warni
autopilot.sleep.questions	repo	null	null | human | self | risk (checked in plugin/crew/hooks/scripts/crew_sleep.py)	1.0.332	autopi inside windo day va else c the st warni
autopilot.sleep.deploy	repo	null	null | nonprod | none (checked in plugin/crew/hooks/scripts/crew_sleep.py)	1.1.21	autopi the sl (L-065 day va none r anyth includ with a an eff as non never asleep
autopilot.maxTicketsPerRun	repo	3	positive integer (checked in plugin/crew/hooks/scripts/crew_autopilot_backlog.py)	1.1.21	Ticket (one s the ne run. A positiv as 3, v
autopilot.maxTokensPerSession	repo	2000000	positive integer (checked in plugin/crew/hooks/scripts/crew_autopilot_backlog.py)	1.1.21	Input token may s assist counte the ru transc be rea

Setting	Layer	Default	Values	Since	Summ
`autopilot.maxLanes`	repo	`null`	positive integer or null (checked in `plugin/crew/hooks/scripts/crew_wave.py`)	1.1.6	Anyth integ 2000 warni Lanes `/crew` runs a resolv `pm.max` larger to it a positiv as it, warni What with a wave the fi `only` t round check `rerevi` ledge single (T-006 `rerevi` non-fi round lines i phase reviev else r a war accep
`autopilot.reviewPolicy`	repo	`"stop"`	`stop` | `clean-only` | `fix-and-rereview`	1.1.6	

Tickets

Setting	Layer	Default	Values	Since	Summary
`tickets.baseBranch`	repo	`null`	branch name or null (checked in `plugin/crew/hooks/scripts/scope_base.py`)	1.0.158	The branch ticket branches are cut from; null tries origin/HEAD's target, then origin/main, then main. A value that is not a branch name, or names no commit, makes the scope base could not tell.

Route

Setting	Layer	Default	Values	Since	Summary
`route.enabled`	both	`false`	`false` | `true` (checked in `plugin/crew/hooks/scripts/crew_route.py`)	1.0.42	Route plain-text prompts to `/crew:` commands; only the JSON value `true` arms it.

unattendedCloud

Setting	Layer	Default	Values	Since
`unattendedCloud.aws.readOnly.profile`	machine-only	`null`	profile name, or null (coerced in `plugin/crew/hooks/scripts/crew_unattended.py`)	1.1.10

Setting	Layer	Default	Values	Since
`unattendedCloud.aws.readOnly.identity`	machine-only	`null`	ARN prefix ending in `/`, or null (coerced in `plugin/crew/hooks/scripts/crew_unattended.py`)	1.1.10
`unattendedCloud.aws.readOnly.region`	machine-only	`null`	region, or null (coerced in `plugin/crew/hooks/scripts/crew_unattended.py`)	1.1.10
`unattendedCloud.aws.nonProd`	machine-only	`{}`	None (checked in `plugin/crew/hooks/scripts/crew_unattended.py`)	1.1.10

Coming (Not in Code Yet)

Keys from approved tickets that have not landed. Each moves into the table above when its ticket lands, because it is then in the code; a test fails until it does (`test_no_coming_key_is_in_code`).

T-0030

Setting	Change	Layer	Default	Values	Summary
`coord.ttlMinutes`	new key	set when T-0030 lands	30		Lifetime of a cross-session coordination claim (1-10080).
`coord.channel`	new key	set when T-0030 lands	set when T-0030 lands		Where sessions coordinate.

T-0050

Setting	Change	Layer	Default	Values	Summary
`scope.allowCliApproval`	changes layer	both, stricter wins	false		Becomes settable in the global file, the stricter layer winning, once its reader (`crew_ticket.cli_approval_allow`) reads the global layer in a harness-only follow-up to T-005