Crew 1.0 - Configuration Reference

This document has two parts. The first is short and hand-written: how crew's two config files combine, how to see what is in force, and the common setups. The second is generated from the code and lists every key.

How the Two Files Combine

crew reads two JSON files:

- `~/.claude/crew/config.json` - the **machine-global** file. Your personal defaults for every repo on this machine: providers and models, notifications, auto-clear, the guards, how far autopilot may go.
- `.crew/config.json` - the **repo** file. Facts about one checkout: the tracker, the board, scope enforcement, production declarations.

The repo file wins over the machine file, which wins over crew's defaults. Four exceptions, each named in the Layer column below:

- A **repo-only** key in the machine file takes effect nowhere. It is pruned on read and refused on write.
- A **ratcheted** key (`install.policy`, every `guards.*`, `change.requireForProduction`, `environments.prodUnattended`) resolves to the narrower of the two values, so a cloned repo cannot widen what your machine allows.
- A **machine-armed** key (`resume.auto`, `context.autoClear.enabled`) can be turned on only in the machine file. A repo can only switch it off.
- A **personal** key (the five `autopilot.*` keys) resolves per key to the stricter of the layers that set it; a layer that says nothing imposes nothing. A machine value is your default for every repo, which a repo may narrow and never widen.

A `null` in the repo file over a machine value inherits the machine value. The `/crew:init` template writes every key except the personal ones, so it does not shadow your machine defaults for those; a repo `/crew:init` set up before that still spells `autopilot.mode: "off"`, which holds a machine `plan` down until you remove it (`--explain --all` names it as a `shadow:`).

Seeing What Is in Force

- `/crew:config --show` prints every machine-settable key, its value and the layer it came from, and names any key that takes effect nowhere.
- `/crew:config` with no argument is a menu that writes either file through the validated path. It shows a dry run first, refuses unknown keys and out-of-range values, and marks a widening with `!`.
- From a shell: `python3 plugin/crew/hooks/scripts/crew_config.py --explain` is the same table, `--explain --all` adds every repo-only key and names each shadowing repo value, and `--models` is the per-role provider table.

Backups and Rebuilding a Lost Config

Every write a crew script makes to either file first copies the old bytes to `~/.claude/crew/backups/` (the newest 20 per file kept) and is refused when that copy fails; a hand edit is not backed up. `crew_config.py --backups` lists the machine file's (add `--repo` for the repo file's) and `--restore <stamp> --apply` puts one back. Your non-default values are kept in `~/.claude/crew/profile.json` (and in your vault when `memory.vaultPath` is set), so `--rebuild --repo` or `--rebuild --global` regenerates a lost or corrupt file from the template plus that profile, as a dry run until `--apply`.

Common Setups

- **Personal defaults once, for every repo.** Put providers, models, `notify.*`, the guards and the `autopilot.*` keys in `~/.claude/crew/config.json`. Leave repo files to repo facts.
- **Self-approval under autopilot.** Set `autopilot.mode: "plan"` and choose `autopilot.approval` (`human`, `self` or `risk`) in either file, and set `scope.allowCliApproval: true` in the repo file, which is the only file that key is read from. Review acceptance and production deploys still stop for you.
- **Notifications.** In the machine file, set `notify.provider` and the environment variable names in `notify.urlEnv` / `notify.tokenEnv`. The secret stays in your environment, never in the file. Those two are machine-only: a repo file's value is ignored with a notice.

The reasoning behind each key is in `plugin/crew/CONFIG.md`, which ships with the plugin.

Reference (Generated)

Generated from the code by `python3 docs/guides/crew/src/config_reference.py --write`. Do not edit by hand: `python3 scripts/check-marketplace.py` fails when this file is stale.

157 keys: 89 settable in the machine-global file, 68 repo-only.

Columns:

- **Layer**: which file may set the key.
- **Default**: what `default_config()` returns. Where the machine default differs, both are shown.
- **Values**: the values crew accepts, read from the same tuple the validator reads. "not validated" means crew checks nothing and names the file that reads the key.
- **Since**: the first crew version whose template declared the key. Keys in the first template (crew 0.11.0) read "0.11.0 or earlier".

Layers

- **repo**: only `.crew/config.json` may set it; the global file's value is pruned on read and refused on write.
- **both**: either file may set it; the repo value wins over the machine one.
- **both, ratchet**: either file may set it, and the NARROWER of the two wins (`crew_guards.RATCHETED_KEYS`). A repo can tighten what the machine allows, never loosen it.
- **both, widening warned**: either file may set it and the repo wins, but a write that widens it is flagged (`crew_config._RATCHETED`).
- **both, stricter wins**: a personal key (`crew_guards.PERSONAL_KEYS`): either file may set it, and where both do the STRICTER value wins; a layer that is silent (absent or `null`) imposes nothing, so a machine value is your default for every repo and a repo may only narrow it.
- **machine-arms**: only the global file can turn it on (exactly `true`); a repo may only veto it with `false` (`crew_config.REPO_VETO_ONLY`).
- **machine-only**: read from the global file alone; a repo's own value is never consulted.

Top-Level Keys

Setting	Layer	Default	Values	Since	Summary
`schema`	repo	`7`	not validated - read by `plugin/crew/hooks/scripts/crew_state.py` (expects integer)	0.11.0 or earlier	Config schema version; `/crew:migrate` upgrades an older one.
`tier`	repo	`0`	not validated - read by `plugin/crew/hooks/scripts/crew_state.py` (expects integer)	0.11.0 or earlier	Setup tier recorded by `/crew:init`.
`roles`	repo	`["explorer", "reviewer"]`	not validated - read by `plugin/crew/hooks/scripts/crew_state.py` (expects list of role names)	0.11.0 or earlier	Optional roles installed in this repo.
`tracker`	repo	`"files"`	`files` | `obsidian` | `jira` | `sdp`	0.11.0 or earlier	Where tickets live; `crew_tracker.resolve` answers `could not tell` when two configs disagree.
`verifyGate`	repo	`true`	not validated - read by `plugin/crew/hooks/scripts/verify-gate.sh` (expects boolean)	0.11.0 or earlier	Run the Stop verify gate.

Qa

Setting	Layer	Default	Values	Since	Summary
`qa.provider`	both	`"auto"`	`auto` | `claude` | `codex` | `copilot` | `kimi`	0.11.0 or earlier	Who reviews: `auto` walks `qa.order`; a named provider is used as-is.
`qa.order`	both	`["codex", "kimi", "copilot", "claude"]`	list of: `claude` | `codex` | `copilot` | `kimi`	0.14.6	The reviewers `auto` tries, in order. A list is one leaf, replaced wholesale.
`qa.fallback`	both	`"claude-sonnet-5"`	not validated - read by `plugin/crew/commands/review.md` (expects model id)	0.16.6	Model a gone pin falls back to, on its family's provider (L-0712).
`qa.codex.model`	both	`null`	not validated - read by `plugin/crew/commands/review.md` (expects string or null)	0.14.6	Codex model for review; null passes no flag.
`qa.codex.reasoningEffort`	both	`null`	`none` | `minimal` | `low` | `medium` | `high` | `xhigh` | `max` (listed in `plugin/crew/commands/review.md`; not	0.14.6	Codex reasoning effort for review; null passes no flag.

Setting	Layer	Default	Values	Since	Summary
			validated)		
`qa.copilot.model`	both	`null`	not validated - read by `plugin/crew/commands/review.md` (expects string or null)	0.14.6	Copilot model for review; null uses the CLI default.
`qa.kimi.model`	both	`null`	not validated - read by `plugin/crew/commands/review.md` (expects string or null)	1.0.39	Kimi Code model id for review (`k3`, `kimi-for-coding`, ...); null uses the CLI's own default.
`qa.roles`	both	`{}`	object of role pins; each pin's provider is checked (checked in `plugin/crew/hooks/scripts/crew_config.py`)	0.16.6	Per-role reviewer pins, `qa.roles.<role>.provider` / `.model`; a pin beats the provider block for that role.

Dev

Setting	Layer	Default	Values	Since	Summary
`dev.provider`	both	`"claude"`	`claude` | `codex` | `copilot` | `kimi`	0.14.6	Who implements.
`dev.fallback`	both	`"claude-sonnet-5"`	not validated - read by `plugin/crew/sk`	0.16.6	Model a gone dev pin falls back to, on its

Setting	Layer	Default	Values	Since	Summary
			`ills/crew-providers/SKILL.md` (expects model id)		family's provider.
`dev.codex.model`	both	`null`	not validated - read by `plugin/crew/skills/crew-providers/SKILL.md` (expects string or null)	0.14.6	Codex model for implementation.
`dev.codex.reasoningEffort`	both	`null`	`none` | `minimal` | `low` | `medium` | `high` | `xhigh` | `max` (listed in `plugin/crew/commands/review.md`; not validated)	0.14.6	Codex reasoning effort for implementation.
`dev.copilot.model`	both	`null`	not validated - read by `plugin/crew/skills/crew-providers/SKILL.md` (expects string or null)	0.14.6	Copilot model for implementation.
`dev.kimi.model`	both	`null`	not validated - read by `plugin/crew/skills/crew-providers/SKILL.md` (expects string or null)	1.0.39	Kimi Code model id for implementation, as `qa.kimi.model`.

Setting	Layer	Default	Values	Since	Summary
`dev.roles`	both	`{}`	object of role pins; each pin's provider is checked (checked in `plugin/crew/hooks/scripts/crew_config.py`)	0.16.6	Per-role dev pins, as `qa.roles`.

Worktree

Setting	Layer	Default	Values	Since	Summary
`worktree.root`	both	`null`	not validated - read by `plugin/crew/hooks/scripts/crew_state.py` (expects path or null)	0.16.27	Where crew creates linked worktrees; null uses the default.

secondOpinion

Setting	Layer	Default	Values	Since	Summary
`secondOpinion.provider`	both	`"none"`	not validated - read by `plugin/crew/commands/plan.md` (expects string)	0.11.0 or earlier	Second-opinion provider for plans; `none` is off.
`secondOpinion.mode`	both	`"cli"`	not validated - read by `plugin/crew/skills/crew-providers/SKILL.md` (expects	0.11.0 or earlier	How the second opinion is reached.

Setting	Layer	Default	Values	Since	Summary
			string)		
`secondOpinion.model`	both	`null`	not validated - read by `plugin/crew/skills/crew-providers/SKILL.md` (expects string or null)	0.11.0 or earlier	Second-opinion model.
`secondOpinion.keyEnv`	both	`"GEMINI_API_KEY"`	not validated - read by `plugin/crew/skills/crew-providers/SKILL.md` (expects string)	0.11.0 or earlier	Environment variable holding the provider's API key.
`secondOpinion.sendsCode`	both	`false`	not validated - read by `plugin/crew/skills/crew-providers/SKILL.md` (expects boolean)	0.11.0 or earlier	Whether code may be sent to the second-opinion provider.

`Jira`

Setting	Layer	Default	Values	Since	Summary
`jira.project`	repo	`null`	not validated - read by `plugin/crew/commands/jira-sync.md` (expects string or null)	0.11.0 or earlier	Jira project key. No consumer found (CONFIG.md section 9).

Setting	Layer	Default	Values	Since	Summary
`jira.cloudId`	repo	`null`	not validated - read by `plugin/crew/commands/jira-sync.md` (expects string or null)	0.19.10	Jira cloud id, cached by `/crew:jira-sync`; read by nothing.

Sdp

Setting	Layer	Default	Values	Since	Summary
`sdp.portal`	repo	`null`	not validated - read by `plugin/crew/commands/sdp-sync.md` (expects string or null)	0.11.0 or earlier	ServiceDesk Plus portal.
`sdp.noteVisibility`	repo	`"private"`	not validated - read by `plugin/crew/commands/sdp-sync.md` (expects string)	0.11.0 or earlier	Visibility of notes crew writes to SDP.
`sdp.closeOnDone`	repo	`false`	not validated - read by `plugin/crew/commands/sdp-sync.md` (expects boolean)	0.11.0 or earlier	Close the SDP request when the ticket is done.

Obsidian

Setting	Layer	Default	Values	Since	Summary
`obsidian.vaultPath`	repo	`null`	not validated - read by	0.11.0 or	Vault holding the board; falls back

Setting	Layer	Default	Values	Since	Summary
			`plugin/crew/hooks/scripts/crew_tracker.py` (expects path or null)	earlier	to `memory.vaultPath` and must hold `.obsidian/`.
`obsidian.boardDir`	repo	`null`	not validated - read by `plugin/crew/hooks/scripts/crew_tracker.py` (expects path or null)	0.11.0 or earlier	Board folder inside the vault (relative, no `..`).
`obsidian.board`	repo	`"Board.md"`	not validated - read by `plugin/crew/hooks/scripts/crew_tracker.py` (expects file name)	0.11.0 or earlier	Board file name.
`obsidian.columns.backlog`	repo	`"Backlog"`	not validated - read by `plugin/crew/hooks/scripts/crew_tracker.py` (expects string)	0.11.0 or earlier	Board column for backlog tickets (`direction`, `ready`, `needs-owner`).
`obsidian.columns.ready`	repo	`"Ready"`	not validated - read by `plugin/crew/hooks/scripts/crew_tracker.py` (expects string)	0.11.0 or earlier	Board column for ready tickets.
`obsidian.columns.inProgress`	repo	`"In Progress`	not validated -	0.11.	Board column for

Setting	Layer	Default	Values	Since	Summary
		`"`	read by `plugin/crew/hooks/scripts/crew_tracker.py` (expects string)	0 or earlier	tickets in progress.
`obsidian.columns.review`	repo	`"Review"`	not validated - read by `plugin/crew/hooks/scripts/crew_tracker.py` (expects string)	0.11.0 or earlier	Board column for tickets in review.
`obsidian.columns.done`	repo	`"Done"`	not validated - read by `plugin/crew/hooks/scripts/crew_tracker.py` (expects string)	0.11.0 or earlier	Board column for closed tickets (`done`, `cancelled`, `superseded`; each checked).

Memory

Setting	Layer	Default	Values	Since	Summary
`memory.mode`	both	`"repo"`	not validated - read by `plugin/crew/skills/crew-memory/SKILL.md` (expects string)	0.11.0 or earlier	Where memory lives (`repo`, or a vault).
`memory.vaultPath`	both	`null`	not validated - read by `plugin/crew/hooks/scripts/crew_recall.py` (expects	0.11.0 or earlier	The Obsidian vault used for memory.

Setting	Layer	Default	Values	Since	Summary
			path or null)		
`memory.inject`	repo	`true`	not validated - read by `plugin/crew/hooks/scripts/crew_context.py` (expects boolean)	1.0.25	Inject the handoff and recall at session start; only an explicit `false` stops it.
`memory.recall.vaults`	repo	`[]`	not validated - read by `plugin/crew/hooks/scripts/crew_recall.py` (expects list of vault names)	1.0.25	This repo's vault priority for recall; empty uses the obsidian config's roles.
`memory.recall.maxChars`	repo	`800`	positive integer (coerced in `plugin/crew/hooks/scripts/crew_recall.py`)	1.0.25	Recall output budget; a non-positive or non-integer value reads as 800.
`memory.recall.projects`	repo	`[]`	not validated - read by `plugin/crew/hooks/scripts/crew_recall.py` (expects list of project names)	1.1.11	Project names sent to vault recall as `--project` so this repo's notes rank first; empty sends the main checkout's directory name.

Context

Setting	Layer	Default	Values	Since
`context.enabled`	repo	`true`	not validated - read by `plugin/crew/hooks/scripts/context-watch.sh` (expects boolean)	0.11.0 or earlier
`context.warnAt`	repo	`0.4`	not validated - read by `plugin/crew/hooks/scripts/context-watch.sh` (expects number)	0.11.0 or earlier
`context.budgetTokens`	repo	`null`	not validated - read by `plugin/crew/hooks/scripts/context-watch.sh` (expects integer or null)	0.11.0 or earlier
`context.reserveTokens`	repo	`0`	not validated - read by `plugin/crew/hooks/scripts/context-watch.sh` (expects integer or null)	0.11.0 or earlier

Setting	Layer	Default	Values	Since
`context.handoffPath`	repo	`".work/HANDOFF.md"`	not validated - read by `plugin/crew/hooks/scripts/crew_autocycle.py` (expects path)	0.11.0 or earlier
`context.keepTranscripts`	repo	`5`	not validated - read by `plugin/crew/hooks/scripts/handoff-write.sh` (expects integer)	0.11.0 or earlier
`context.autoClear.enabled`	machine-arms	`null`	`null` | `true` | `false` (checked in `plugin/crew/hooks/scripts/crew_autocycle.py`)	0.19.10
`context.autoClear.method`	both	`"auto"`	`auto` | `none` | `notify` | `tmux` | `xdotool` | `wtype` | `sendkeys`; per OS: linux: auto, none, notify, tmux, xdotool, wtype; macos: auto, none, notify, tmux; windows: auto, none, notify, sendkeys; windows-bash:	0.19.10

Setting	Layer	Default	Values	Since
			auto, none, notify, tmux, sendkeys	
`context.autoClear.windowTitle`	both	`null`	not validated - read by `plugin/crew/hooks/scripts/auto-clear.ps1` (expects string or null)	0.19.10
`context.autoClear.command`	both	`"/clear"`	not validated - read by `plugin/crew/hooks/scripts/crew_autocycle.py` (expects string)	0.19.10
`context.autoClear.delaySeconds`	both	`3`	number (coerced in `plugin/crew/hooks/scripts/crew_autocycle.py`)	0.19.10
`context.autoClear.minHandoffLines`	both	`5`	number (coerced in `plugin/crew/hooks/scripts/crew_autocycle.py`)	0.19.10
`context.autoClear.unsafeFocus`	repo	`false`	not validated - read by `plugin/crew/hooks/scripts/auto-clear.sh` (expects	0.19.11

Setting	Layer	Default	Values	Since
			boolean)	
`context.autoClear.onlyRepos`	machine-only	`null`	list of absolute repo paths, or null (coerced in `plugin/crew/hooks/scripts/crew_autocycle.py`)	1.0.25
`context.autoClear.onlySessions`	machine-only	`null`	list of session ids, or null (coerced in `plugin/crew/hooks/scripts/crew_autocycle.py`)	1.0.25
`context.autoClear.wrapUp`	machine-arms	`null`	`null` | `true` | `false` (checked in `plugin/crew/hooks/scripts/crew_autocycle.py`)	1.0.334

Setting	Layer	Default	Values	Since
`context.autoWrapUp`	repo	`true`	not validated - read by `plugin/crew/hooks/scripts/context-watch.sh` (expects boolean)	0.19.10
`context.autoResume`	repo	`true`	not validated - read by `plugin/crew/commands/migrate.md` (expects boolean)	0.19.10
`context.staleHandoff.maxAgeHours`	repo	`72`	not validated - read by `plugin/crew/hooks/scripts/crew_state.py` (expects integer)	0.16.33
`context.staleHandoff.maxCommitsBehind`	repo	`3`	not validated - read by `plugin/crew/hooks/scripts/crew_state.py` (expects integer)	0.16.33

Resume

Setting	Layer	Default	Values	Since	Summary
`resume.auto`	machine-arms	`null`	`null` | `true` | `false` (checked in `plugin/crew/hooks/scripts/crew_resume.py`)	1.0.40	Auto-resume after `/clear` or a manual `/compact`. Only the machine file can arm it (exactly `true`); a repo `false` vetoes it.
`resume.typeDelaySeconds`	both	2	whole seconds; fraction cut, negative or non-number reads as the default (coerced in `plugin/crew/hooks/scripts/crew_autocycle.py`)	1.0.321	Wait before auto-resume types its command: before the tmux ready probe, and the only wait on Windows. Read from the machine file only.
`resume.readyTimeoutSeconds`	both	15	whole seconds; fraction cut, negative or non-number reads as the default (coerced in `plugin/crew/hooks/scripts/crew_a`	1.0.321	How long the tmux ready probe waits for an idle, empty input line before it types

Setting	Layer	Default	Values	Since	Summary
			`utocycle.py`)		nothing. Read from the machine file only.

Emergency

Setting	Layer	Default	Values	Since	Summary
`emergency.standDown`	repo	`true`	not validated - read by `plugin/crew/hooks/scripts/_common.sh` (expects boolean)	0.11.0 or earlier	Whether a declared incident may stand gates down; `false` forbids it.
`emergency.ttlMinutes`	repo	`120`	integer (coerced in `plugin/crew/hooks/scripts/crew_incident.py`)	0.11.0 or earlier	Default incident lifetime; a non-integer reads as the default.
`emergency.maxTtlMinutes`	repo	`480`	integer (coerced in `plugin/crew/hooks/scripts/crew_incident.py`)	0.11.0 or earlier	Longest incident lifetime; never below `ttlMinutes`.

Notify

Setting	Layer	Default	Values	Since	Summary
`notify.provider`	both	`null`	telegram, teams, none or	0.11.0 or	Where notification `telegram`, `teams` or

Setting	Layer	Default	Values	Since	Summary
			null; any other value sends nothing (coerced in `plugin/crew/hooks/scripts/crew_notify.py`)	earlier	A repo null inherits machine provider; `none` opts this repo
`notify.urlEnv`	machine-only	`null`	not validated - read by `plugin/crew/hooks/scripts/crew_notify.py` (expects string or null)	0.11.0 or earlier	Name of the enviro variable holding th webhook URL. Hon from the machine repo's is ignored w notice.
`notify.tokenEnv`	machine-only	`null`	not validated - read by `plugin/crew/hooks/scripts/crew_notify.py` (expects string or null)	0.11.0 or earlier	Name of the enviro variable holding th Telegram bot toke be filled from the r `bot_token_env`. Ho from the machine
`notify.chatId`	both	`null`	not validated - read by `plugin/crew/hooks/scripts/crew_notify.py` (expects string or null)	0.11.0 or earlier	Telegram chat id; r filled from the not `chat_id`, and the s example value cou unset.
`notify.events`	both	`["blocker", "deploy", "question"]`	list of event names; an unknown name is dropped with a notice	0.11.0 or earlier	Events that notify: `question`, and `bloc` (T-0060's four bloc reasons). The pre- `gate`, `waiting`, `phas`

Setting	Layer	Default	Values	Since	Summary
			(coerced in `plugin/crew/hooks/scripts/crew_notify.py`)		and `done` are mapp notice. A list is one
`notify.realertHours`	both	`6`	number of hours; negative or non-number reads as the default (coerced in `plugin/crew/hooks/scripts/crew_notify.py`)	1.0.350	The same event + reason is sent onc many hours; a que once per waiting e
`notify.questionTypes`	both	`null`	list of notification_type strings, or null; a non-list reads as null and a non-string entry is dropped (coerced in `plugin/crew/hooks/scripts/crew_notify.py`)	1.0.350	The Claude Code `notification_type` that count as a qu uses the built-in fi (`crew_notify.QUES`).

Platform

Setting	Layer	Default	Values	Since	Summary
`platform.os`	repo	`null`	not validated - read by `plugin/crew/hooks/scripts/crew_platform.py` (expects	0.11.0 or earlier	Detected OS, stamped by platform-sync.

Setting	Layer	Default	Values	Since	Summary
			string or null)		
`platform.wsl`	repo	`null`	not validated - read by `plugin/crew/hooks/scripts/crew_platform.py` (expects boolean or null)	0.11.0 or earlier	Detected WSL, stamped by platform-sync.
`platform.shell`	repo	`null`	not validated - read by `plugin/crew/hooks/scripts/crew_platform.py` (expects string or null)	0.11.0 or earlier	Detected shell, stamped by platform-sync.
`platform.windowsHostIp`	repo	`null`	not validated - read by `plugin/crew/hooks/scripts/crew_platform.py` (expects string or null)	0.11.0 or earlier	Windows host IP seen from WSL.

`shellRoute`

Setting	Layer	Default	Values	Since	Summary
`shellRoute.mode`	both	`null` (repo), `"auto"` (machine)	`auto` | `wsl` | `powershell` | `gitbash`	1.0.54	The shell long-running jobs use on native Windows; null inherits, and an unknown value reads as `auto` and is named.
`shellRoute.distro`	both	`null`	not validated -	1.0.54	WSL distro to

Setting	Layer	Default	Values	Since	Summary
			read by `plugin/crew/hooks/scripts/crew_shell.py` (expects string or null)		route to; null takes the default distro.

Pm

Setting	Layer	Default	Values	Since	Summary
`pm.enabled`	both	`true`	not validated - read by `plugin/crew/hooks/scripts/crew_state.py` (expects boolean)	0.11.0 or earlier	Run the PM brief.
`pm.mode`	both	`"adaptive"`	not validated - read by `plugin/crew/hooks/scripts/crew_state.py` (expects string)	0.11.0 or earlier	How the PM brief adapts its length.
`pm.quietLines`	both	`8`	integer (coerced in `plugin/crew/hooks/scripts/crew_state.py`)	0.11.0 or earlier	PM brief length when nothing changed.
`pm.maxLines`	both	`40`	integer (coerced in `plugin/crew/hooks/scripts/crew_state.py`)	0.11.0 or earlier	Longest PM brief.
`pm.authority`	both, wideni	`"report-only"`	`report-only` | `act` |	0.11.0 or	How much the PM may

Setting	Layer	Default	Values	Since	Summary
	ng warned		`autonomous`	earlier	do unasked. A widening is warned about; the two layers combine by precedence.
`pm.ticketGranularity`	both	`"system"`	`session` | `system` | `change`	0.16.34	How big a ticket the PM cuts.
`pm.maxDispatches`	both	`3`	integer (coerced in `plugin/crew/hooks/scripts/crew_state.py`)	0.11.0 or earlier	Roles the PM may dispatch in one pass.

Graph

Setting	Layer	Default	Values	Since	Summary
`graph.enabled`	repo	`true`	not validated - read by `plugin/crew/skills/crew-graph/SKILL.md` (expects boolean)	0.11.0 or earlier	No consumer found (CONFIG.md section 9).
`graph.tool`	repo	`"graphify"`	not validated - read by `plugin/crew/skills/crew-graph/SKILL.md` (expects string)	0.11.0 or earlier	No consumer found (CONFIG.md section 9).
`graph.out`	repo	`"graphify-out"`	not validated - read by	0.11.0 or	Where the code graph is

Setting	Layer	Default	Values	Since	Summary
			`plugin/crew/hooks/scripts/crew_state.py` (expects path)	earlier	written.
`graph.mode`	repo	`"code-only"`	not validated - read by `plugin/crew/skills/crew-graph/SKILL.md` (expects string)	0.11.0 or earlier	No consumer found (CONFIG.md section 9).
`graph.commitHook`	repo	`false`	not validated - read by `plugin/crew/skills/crew-graph/SKILL.md` (expects boolean)	0.11.0 or earlier	No consumer found (CONFIG.md section 9).

Docs

Setting	Layer	Default	Values	Since	Summary
`docs.theme`	both	`null`	not validated - read by `plugin/crew/skills/crew-house-style/SKILL.md` (expects string or null)	0.16.33	House-style theme for built documents; null uses the skill's own choice.
`docs.reportTheme`	both	`null`	not validated - read by `plugin/crew/skills/crew-house-style/SKILL.md` (expects string or null)	0.16.33	Theme for findings reports.

Bitbucket

Setting	Layer	Default	Values	Since	Summary
`bitbucket.mergeGate.enabled`	both	`false`	not validated - read by `plugin/crew/commands/promote.md` (expects boolean)	0.16.33	Let `/crew:promote` drive the Bitbucket merge gate.
`bitbucket.mergeGate.branch`	both	`null`	not validated - read by `plugin/crew/commands/promote.md` (expects string or null)	0.16.33	Branch the Bitbucket merge gate protects.
`bitbucket.mergeGate.preset`	both	`"standard"`	not validated - read by `plugin/crew/commands/promote.md` (expects string)	0.16.33	Selects nothing today (CONFIG.md section 9).

GitHub

Setting	Layer	Default	Values	Since	Summary
`github.mergeGate.enabled`	both	`false`	not validated - read by `plugin/crew/commands/promote.md` (expects boolean)	0.19.30	Let `/crew:promote` drive the GitHub merge gate.
`github.mergeGate.branch`	both	`null`	not validated -	0.19.30	Branch the

Setting	Layer	Default	Values	Since	Summary
			read by `plugin/crew/commands/promote.md` (expects string or null)		GitHub merge gate protects.

Install

Setting	Layer	Default	Values	Since	Summary
`install.policy`	both, ratchet	`"manual"`	`manual` | `ask` | `auto` (ratchet: narrower layer wins; listed narrowest first)	0.19.18	Whether crew may install a missing prerequisite.

Guards

Setting	Layer	Default	Values	Since	Summary
`guards.terraformApply`	both, ratchet	`"block"`	`block` | `ask` | `allow` (ratchet: narrower layer wins; listed narrowest first)	0.19.30	`terraform apply` and friends.
`guards.forcePush`	both, ratchet	`"block"`	`block` | `ask` | `allow` (ratchet:	0.19.30	`git push --force`.

Setting	Layer	Default	Values	Since	Summary
			narrower layer wins; listed narrowest first)		
`guards.adminMerge`	both, ratchet	`"block"`	`block` | `ask` | `allow` (ratchet: narrower layer wins; listed narrowest first)	0.19.30	`gh pr merge --admin`.
`guards.mergeGate`	both, ratchet	`"block"`	`block` | `ask` | `allow` (ratchet: narrower layer wins; listed narrowest first)	0.19.30	Taking a live repo's merge gate down (read by `/crew:gate`).
`guards.cloudDestructive`	both, ratchet	`"block"`	`block` | `ask` | `allow` (ratchet: narrower	1.0.25	Destructive cloud CLI commands.

Setting	Layer	Default	Values	Since	Summary
			layer wins; listed narrowest first)		
`guards.sqlDestructive`	both, ratchet	`"block"`	`block` | `ask` | `allow` (ratchet: narrower layer wins; listed narrowest first)	1.0.25	Destructive SQL.
`guards.deployWorkflow`	both, ratchet	`"block"`	`block` | `ask` | `allow` (ratchet: narrower layer wins; listed narrowest first)	1.1.16	A `gh workflow run` or `gh api .../dispatches` of a workflow `environments.workflows` lists.
`guards.prodDatabase`	both, ratchet	`"none"`	`none` | `read` | `full` (ratchet: narrower layer	0.19.30	How much of a declared production database crew may reach.

Setting	Layer	Default	Values	Since	Summary
			wins; listed narrowest first)		
`guards.prodServer`	both, ratchet	`"none"`	`none` | `read` | `full` (ratchet: narrower layer wins; listed narrowest first)	0.19.30	How much of a declared production host crew may reach.
`guards.roleWrites`	both, ratchet	`"off"`	`block` | `report` | `off` (ratchet: narrower layer wins; listed narrowest first)	0.19.92	Enforce each role's write scope. Default `off`; a malformed value reads as `block`.
`guards.cloudGuard`	both, ratchet	`"off"`	`block` | `report` | `off` (ratchet: narrower layer wins;	1.0.25	Whether the cloud guard judges commands at all. Default `off`; `report` logs only.

Setting	Layer	Default	Values	Since	Summary
			listed narrowest first)		
`guards.envGuard`	both, ratchet	`"off"`	`block` | `report` | `off` (ratchet: narrower layer wins; listed narrowest first)	1.2.26	Refuse a command that prints the whole environment or a credential-named variable. Default `off`; `report` logs only.

Production

Setting	Layer	Default	Values	Since	Summary
`production.databases`	repo	`[]`	not validated - read by `plugin/crew/hooks/scripts/crew_config.py` (expects list of globs)	0.19.30	Globs naming production databases.
`production.hosts`	repo	`[]`	not validated - read by `plugin/crew/hooks/scripts/crew_config.py` (expects list of globs)	0.19.30	Globs naming production hosts.

Cloud

Setting	Layer	Default	Values	Since	Summary
`cloud.awsProfiles`	repo	`[]`	not validated - read by `plugin/crew/hooks/scripts/cloud_guard.py` (expects list of names)	1.0.25	AWS profiles this repo may use.
`cloud.awsRegions`	repo	`[]`	not validated - read by `plugin/crew/hooks/scripts/cloud_guard.py` (expects list of names)	1.0.25	AWS regions this repo may use.
`cloud.azureSubscriptions`	repo	`[]`	not validated - read by `plugin/crew/hooks/scripts/cloud_guard.py` (expects list of names)	1.0.25	Azure subscriptions this repo may use.

Environments

Setting	Layer	Default	Values	Since	Summary
`environments.nonProd`	repo	`[]`	not validated - read by `plugin/crew/hooks/scripts/crew_config.py` (expects list of globs)	1.0.37	Terraform targets that are not production and may run unattended.
`environments.prodUnattended`	both, ratch	`false`	`false` | `true` (ratchet:	1.0.37	Whether production

Setting	Layer	Default	Values	Since	Summary
	et		narrower layer wins; listed narrowest first)		terraform may run unattended; `true` only when both layers say so.
`environments.workflows`	repo	`{}`	not validated - read by `plugin/crew/hooks/scripts/crew_config.py` (expects object of glob to string)	1.1.16	Deploy workflow globs, each mapped to its environment or `input:<name>`.

Change

Setting	Layer	Default	Values	Since	Summary
`change.requester`	both	`null`	not validated - read by `plugin/crew/hooks/scripts/crew_change.py` (expects string or null)	0.19.31	Who requests the change.
`change.implementor`	both	`null`	not validated - read by `plugin/crew/hooks/scripts/crew_change.py` (expects string or null)	0.19.31	Who implements the change.

Setting	Layer	Default	Values	Since	Summary
`change.requireForProduction`	both, ratchet	`false`	`true` | `false` (ratchet: narrower layer wins; listed narrowest first)	0.19.31	Require an approved change request before `/crew:promote production`: a repo may turn it on, never off.
`change.sdpTemplate`	both	`"Change Management Request"`	not validated - read by `plugin/crew/hooks/scripts/crew_change.py` (expects string)	0.19.31	SDP template for a change request.
`change.jiraIssueType`	both	`"Change"`	not validated - read by `plugin/crew/hooks/scripts/crew_change.py` (expects string)	0.19.31	Jira issue type for a change request.
`change.category`	both	`null`	not validated - read by `plugin/crew/hooks/scripts/crew_change.py` (expects string or null)	0.19.31	Change category.

Git

Setting	Layer	Default	Values	Since	Summary
`git.forbiddenTrailers`	both	`[]`	list of trailer tokens (letters, digits and `-`, no `:`) (checked in `plugin/crew/hooks/scripts/crew_trailers.py`)	1.0.328	Commit trailer tokens the owner forbids, reported by `/crew:done`. The two layers combine by union, so a repo can add a token and never remove the machine owner's; a value that is not a list of tokens makes the list unknown, never empty (CONFIG.md section 22).

Scope

Setting	Layer	Default	Values	Since	Summary
`scope.mode`	repo	`"off"`	`off` | `report` | `block` | `auto`	1.0.25	Whether the scope guard enforces a ticket's Touch list; a value outside these fails closed to

Setting	Layer	Default	Values	Since	Summary
					`block`.
`scope.allowCliApproval`	repo	`false`	`false` | `true` (checked in `plugin/crew/hooks/scripts/crew_ticket.py`)	1.0.25	Whether a CLI-written approval receipt counts; only exactly `true` allows it.

Autopilot

Setting	Layer	Default	Values	Since	Summar
`autopilot.mode`	both, stricter wins	`"off"`	`off` | `plan` | `backlog` (checked in `plugin/crew/hooks/scripts/crew_autopilot.py`); personal: listed strictest first, the stricter wins	1.0.41	Only the strings `p` ticket per `backlog` (goal's tic depende inside th `/crew:au` anything as off, wi warning.
`autopilot.maxPhases`	both, stricter wins	`12`	positive integer (checked in `plugin/crew/hooks/scripts/crew_autopilot.py`); personal: the smaller wins	1.0.41	Phases o take; any positive i reads as warning.
`autopilot.deploy`	both, stricter	`"none"`	`none` | `nonprod` | `all`; personal: listed strictest	1.0.42	Where a run witho anything

Setting	Layer	Default	Values	Since	Summar
	wins		first, the stricter wins		as `none`.
`autopilot.approval`	both, stricter wins	`"risk"`	`human` | `risk` | `self`; personal: listed strictest first, the stricter wins	1.0.42	Who app ticket un autopilot else read
`autopilot.questions`	both, stricter wins	`"risk"`	`human` | `risk` | `self`; personal: listed strictest first, the stricter wins	1.0.42	Who ans ticket's o question autopilot else read
`autopilot.maxAutoReplans`	repo	`0`	non-negative integer (checked in `plugin/crew/hooks/scripts/crew_autopilot.py`)	1.0.339	Successo autopilot by rejecti of-round review its and anyt non-nega reads as above 5 a warning.
`autopilot.ship`	repo	`"merge"`	`pr` | `merge`	1.0.349	After `/cr` pushes a the PR; `m` merges i commit) required allow. An reads as warning.
`autopilot.knownFailures`	repo	`[]`	list of check names	1.0.34	Required

Setting	Layer	Default	Values	Since	Summar
			(checked in `plugin/crew/hooks/scripts/crew_autopilot.py`)	9	whose `fa` block a m matched name; ar a list of s as `[]`, wit warning.
`autopilot.ciTimeoutMinutes`	repo	`60`	positive integer (checked in `plugin/crew/hooks/scripts/crew_autopilot.py`)	1.0.349	Minutes for the re checks; s or green stops. An positive i reads as warning.
`autopilot.sleep.schedule`	repo	`null`	HH:MM-HH:MM or null (checked in `plugin/crew/hooks/scripts/crew_sleep.py`)	1.0.332	A nightly `HH:MM-HH` machine (may cro midnight the two s overrides Anything could no stricter o applies.
`autopilot.sleep.approval`	repo	`null`	`null` | `human` | `self` | `risk` (checked in `plugin/crew/hooks/scripts/crew_sleep.py`)	1.0.332	`autopilo` inside th window; the day v anything

Setting	Layer	Default	Values	Since	Summar
					as huma strictest, warning.
`autopilot.sleep.questions`	repo	`null`	`null` | `human` | `self` | `risk` (checked in `plugin/crew/hooks/scripts/crew_sleep.py`)	1.0.332	`autopilo` inside th window; the day v anything as huma strictest, warning.
`autopilot.sleep.deploy`	repo	`null`	`null` | `nonprod` | `none` (checked in `plugin/crew/hooks/scripts/crew_sleep.py`)	1.1.21	`autopilo` inside th window (keeps th `nonprod` replaces else, `all` refused v warning. effective `nonprod`: never ru unattend
`autopilot.sleep.notifyHold`	repo	`null`	`null` | `true` (checked in `plugin/crew/hooks/scripts/crew_notify_hold.py`)	1.1.21	Inside th window (`true` hol that only attention Approval Review o

Setting	Layer	Default	Values	Since	Summar
					rounds) a them; the summary count. A deploy re refused S stalled la held. Onl armed ar the sched manual s outside it nothing); but null c nothing, warning.
`autopilot.maxTicketsPerRun`	repo	`3`	positive integer (checked in `plugin/crew/hooks/scripts/crew_autopilot_backlog.py`)	1.1.21	Tickets o (one sess start; the stops the Anything positive i reads as warning.
`autopilot.maxTokensPerSession`	repo	`2000000`	positive integer (checked in `plugin/crew/hooks/scripts/crew_autopilot_backlog.py`)	1.1.21	Input plu tokens o session r each assi message once, bef stops; a t that cann

Setting	Layer	Default	Values	Since	Summar
					stops too but a pos reads as with a wa
`autopilot.maxLanes`	repo	`null`	positive integer or null (checked in `plugin/crew/hooks/scripts/crew_wave.py`)	1.1.6	Lanes on `/crew:au` `wave` runs null is the `pm.maxDi` larger va capped t anything positive i reads as a warnin
`autopilot.reviewPolicy`	repo	`"stop"`	`stop` | `clean-only` | `fix-and-rereview`	1.1.6	What aut with a re A wave la ends at t verdict, c takes a C on to the checks, f `rereview` the ledge A single-t (T-0067): `and-rere` fixing a r FINDING BLOCK a itself (the

Setting	Layer	Default	Values	Since	Summar
					and re-re Anything as `stop`, warning; accepts a

Tickets

Setting	Layer	Default	Values	Since	Summary
`tickets.baseBranch`	repo	`null`	branch name or null (checked in `plugin/crew/hooks/scripts/scope_base.py`)	1.0.158	The branch ticket branches are cut from; null tries origin/HEAD's target, then origin/main, then main. A value that is not a branch name, or names no commit, makes the scope base could not tell.

Route

Setting	Layer	Default	Values	Since	Summary
`route.enabled`	both	`false`	`false` | `true` (checked in `plugin/crew/hooks/scripts/crew_route.py`)	1.0.42	Route plain-text prompts to `/crew:` commands; only the JSON value `true` arms it.

`unattendedCloud`

Setting	Layer	Default	Values	Since	S
`unattendedCloud.aws.readOnly.profile`	machine-only	`null`	profile name, or null (coerced in `plugin/crew/hooks/scripts/crew_unattended.py`)	1.1.10	T u e f e it te c fi
`unattendedCloud.aws.readOnly.identity`	machine-only	`null`	ARN prefix ending in `/`, or null (coerced in `plugin/crew/hooks/scripts/crew_unattended.py`)	1.1.10	T A re e re M
`unattendedCloud.aws.readOnly.region`	machine-only	`null`	region, or null (coerced in `plugin/crew/hooks/scripts/crew_unattended.py`)	1.1.10	T u n M
`unattendedCloud.aws.nonProd`	machine-only	`{}`	None (checked in `plugin/crew/hooks/scripts/crew_unattended.py`)	1.1.10	E { re u re a o

Coming (Not in Code Yet)

Keys from approved tickets that have not landed. Each moves into the table above when its ticket lands, because it is then in the code; a test fails until it does (`test_no_coming_key_is_in_code`).

T-0030

Setting	Change	Layer	Default	Values	Summary
`coord.ttlMinutes`	new key	set when T-0030 lands	30		Lifetime of a cross-session coordination claim (1-10080).
`coord.channel`	new key	set when T-0030 lands	set when T-0030 lands		Where sessions coordinate.

T-0050

Setting	Change	Layer	Default	Values	Summary
`scope.allowCliApproval`	changes layer	both, stricter wins	false		Becomes settable in the global file, the stricter layer winning, once its reader (`crew_ticket.cli_approval_allowed`) reads the global layer in a harness-only follow-up to T-0050.