

Working with Codex

In crew 1.0, the interactive Claude session implements and Codex reviews. Both agents read the same instructions, and the same context hook can run under both. This guide explains how to set up the Codex half and what is proven about it so far.

What Each Side Reads

Surface	Claude Code	Codex
AGENTS.md (80 lines or fewer, generated)	through @AGENTS.md in CLAUDE.md	natively
.claude/rules/<subsystem>.md (paths:-scoped)	yes, when a matching file is read	no (Codex has no path-scoped rules)
crew's context hook	plugins hooks.json	.codex/hooks.json (generated)
CLAUDE.md	natively	fallback via project_doc_fallback_filenames

Codex has no path-scoped rules, so its hook's PostToolUse slice is the only per-file channel.

Generate the Files

Run these from the repository root. Each command writes nothing if the files are already current. With --check, it writes nothing at all and exits 1 on drift.

```
S="<crew plugin root>/hooks/scripts"

python3 "$S/crew_instructions.py" agents      # AGENTS.md; only the crew:keep block
is yours

python3 "$S/crew_instructions.py" rules      # .claude/rules/<subsystem>.md
from .crew/codemap/

python3 "$S/crew_instructions.py" codex      # .codex/hooks.json and
.codex/config.toml
```

```
python3 "$S/crew_instructions.py" codex --check
```

- `.codex/hooks.json` is built from the same hook table as crew's Claude registration (`H00K_TABLE` in `crew_instructions.py`). Each entry has a `command` (bash) and a `commandWindows` (PowerShell, `-Harness codex`). The paths inside are absolute and belong to one machine, so regenerate the file on each machine rather than committing it.
- `.codex/config.toml` sets `project_doc_fallback_filenames = ["CLAUDE.md"]` only. **No [profiles.*] table** -- MEASURED on codex-cli 0.154.0: `profiles` is on Codex's own project-local config denylist and is stripped from this file every time it loads, trusted or not, so a review/work profile defined here would never apply. Codex reads project config only for a **trusted** project, and only that project-config subset survives the strip.

Review and Work

There are no project-scoped review/work profiles to select with `--profile` -- pass the settings explicitly instead:

```
codex exec --json --sandbox read-only "<review prompt>" # the reviewer
(review_run.py's command_for)

codex exec --sandbox workspace-write "<task>" # only if you choose
Codex to implement
```

If you want named review/work profiles for convenience, they are a **user-level** concept, not a project one: `codex exec --help` (codex-cli 0.155.1) documents `--profile NAME` as layering `$CODEX_HOME/NAME.config.toml` on top of the base user config -- a file under `$CODEX_HOME`, never this project's `.codex/config.toml`. Create `$CODEX_HOME/review.config.toml` / `$CODEX_HOME/work.config.toml` yourself and pass `--profile review/--profile work` against those.

A review that exits non-zero, prints nothing, times out or ends in a failed turn is **INCOMPLETE**, never **CLEAN**. That is a tool failure, and the round is refunded automatically, up to two per plan (for example when Codex answers with its usage-limit error event). What crew relies on from Codex's `--json` stream is in `plugin/crew/docs/external-tool-formats.md`.

What Is Proven, and What Is Only Configured

Run the probe. The sample below shows the probe's format with this build's values. The hooks feature value was measured with `codex features list`. The probe itself has only been run against a stub codex in the test suite (`tests/test_crew_instructions.py`).

```
python3 "$S/crew_instructions.py" codex-probe

codex: /usr/local/bin/codex (codex-cli 0.155.1)

hooks feature: enabled

project files: current

PostToolUse: configured, not proven

SessionStart: configured, not proven

SubagentStart: configured, not proven

UserPromptSubmit: configured, not proven
```

- **Established by reading the codex 0.155.1 binary, not its docs:** the hook events (`SessionStart`, `UserPromptSubmit`, `PostToolUse`, `SubagentStart` and others), the handler keys `command`, `commandWindows`, `timeout` and `additionalContextLimit`, and a `SubagentStartHookSpecificOutputWire` output type. `codex features list` reports `hooks stable true`.
- **Not measured:** whether a hook's `additionalContext` reaches the Codex model, and whether Codex honours profiles from a project's `.codex/config.toml`. A live test run would need Codex to write its session state under `~/.codex`, and this build did not do that.
- The probe changes an event's line from "configured, not proven" to "hook invoked Nx under Codex" only when the context log records an invocation under the codex harness. Even then it claims only that the hook ran, not that the model received the context. To prove delivery, rerun the seeded-note test from [Confirming recall reaches your sessions](#) with `codex exec` in place of `claude -p`.

When Codex Is Barred

A review is independent only when it comes from a different model family than the author. If Codex wrote the diff, it cannot review that diff. The order falls through to Copilot, then to Claude's reviewer.