

Memory and Obsidian

Crew keeps durable memory in plain Markdown: your repository's contracts, ADRs and code map stay authoritative for that repository, and an Obsidian vault holds the lessons that cross projects. The `obsidian-vault` plugin owns that vault. It sets it up, captures sessions into it, gardens the captures into notes, and answers recall queries from it. Crew calls the plugin rather than doing any of this itself.

Every command below is `vault_ops.py`, which ships with the plugin. It is **dry-run by default**: it prints the exact change and writes nothing until you repeat it with `--apply`. Exit 0 means done or healthy, 1 means there is something to do or something wrong, and 2 means the command was refused or mistyped.

Set a shorthand once per shell. It picks the newest installed version of the plugin:

```
# Linux / macOS / Git Bash
```

```
V0="python3 $(ls -d ~/.claude/plugins/cache/*/obsidian-vault/*/ |  
sort -V | tail -1)hooks/scripts/vault_ops.py"
```

```
# Windows PowerShell
```

```
$V0 = (Get-ChildItem  
"$env:USERPROFILE\.claude\plugins\cache\*\obsidian-  
vault\*\hooks\scripts\vault_ops.py" |
```

```
Sort-Object { [version]$_ .Directory.Parent.Parent.Name } | Select-  
Object -Last 1).FullName
```

```
function vo { python $V0 @args }
```

On Windows, read \$V0 ... in the examples below as vo Inside Claude Code you do not need either: /obsidian-vault:init runs the same steps and asks you before each one.

What Gets Captured

When a session ends, and before the context is compacted, a hook appends one line to the primary vault:

```
inbox/pending-reflect.<host>.md
```

```
- [ ] 2026-09-23 14:02 | SessionEnd | session=4f1c... |  
  cwd=/repos/app |  
  transcript=/home/you/.claude/projects/.../4f1c....jsonl
```

That is all it records: when, which session, which folder, and where the transcript is. It never copies conversation text into the vault. Each machine writes its own <host> file, so two machines syncing one vault never write the same file. One line per session, whichever trigger fires first. The capture hook cannot block or slow a session; if it fails it says so on stderr and moves on.

Capture, import and the gardener write to the primary vault only. If the primary is not available (an unmounted drive, say), they write nothing and say why; capture reports it on stderr and the session carries on. They never fall back to a recall vault.

An older version wrote a single inbox/pending-reflect.md. That file is no longer written, but it is still read, so an existing backlog drains rather than being stranded.

How Gardening Works

The gardener turns queued sessions into notes. It reads each transcript, writes or extends concept and decision notes with sources, and appends a line to the day's daily note.

It runs **on one host, once a day, in bounded passes**:

- at most **5 items or 10 minutes** per run, whichever comes first;
- an item is acknowledged only after the note it produced exists, is non-empty, and was written during that item's run. If the model fails, times out, or names a file it did not write (including one that was already there), the item stays queued for the next run;
- acknowledgements go to `inbox/reflected.<host>.md`, so the queue files keep one writer each;
- a session whose transcript lives on another machine is left for that machine and does not use up one of the five slots;
- only the designated host runs it (`gardener.host` in the config), and one run at a time;
- with `--commit`, it commits only the files that run wrote plus its own acknowledgement file. It never sweeps in anything else you had staged. `git`, including the vault's own `git hooks`, runs inside the same 10-minute bound: a hook still running then is stopped and the commit is reported as not made. Leave `--commit` off if Obsidian Git already commits the vault.

Run a pass by hand with `/obsidian-vault:garden`, or:

```
$V0 queue # what is waiting
```

```
$V0 garden-run # one bounded pass (designated host only)
```

A large backlog drains in the same bounded batches:

```
$V0 drain # dry run: backlog size, batch
count, first batch
```

```
$V0 drain --apply --batches 4 # up to 4 passes of 5, stops early
if one acknowledges nothing
```

Upkeep

When

Do

Daily, automatically

The scheduled gardener. Check `~/.claude/obsidian/gardener.log` now and then for lines that start `left queued`.

After a plugin update

Re-run `$V0 schedule --os <yours>` and reinstall the unit it prints. The unit names the plugin's versioned folder, which the update replaces.

When a vault moves
or you add one

`$V0 adopt` to review roles.

When recall seems
blind

`$V0 recall --query "<words you expect>"` and check which vaults it names.

When the bridge
misbehaves

`/obsidian-vault:doctor`, then `/obsidian-vault:repair`. The bridge is optional; capture, recall, import and gardening all work on the files without it.

When the code
changed a lot

`/crew:onboard --refresh <subsystem>` for the repository's own code map. That map lives in the repository, not the vault.

Setup

Every case ends in the same place: exactly one **primary** vault, which receives captures and imports, and optionally some **recall** vaults that are read but never written.

Case 1: Obsidian Is Not Installed

Linux

```
$V0 detect-obsidian
```

It checks snap (`/snap/bin/obsidian`), Flatpak (`md.obsidian.Obsidian`), the obsidian deb, AppImage locations and PATH, and answers `INSTALLED`, `MISSING` or `UNKNOWN`. `UNKNOWN` means none of those checks could run. It is not the same as missing, and install refuses it.

```
$V0 install-obsidian          # prints e.g.: Planned install  
(snap): sudo snap install obsidian --classic
```

```
$V0 install-obsidian --apply    # runs exactly that command
```

Without snap it offers `flatpak install -y flathub md.obsidian.Obsidian`. For a deb or AppImage it tells you what to download from `obsidian.md` and does not fetch anything. Choose one with `--method snap|flatpak|deb|appimage`.

Windows

```
vo detect-obsidian
```

```
vo install-obsidian          # Planned install (winget): winget  
install --id Obsidian.Obsidian -e ...
```

```
vo install-obsidian --apply
```

Then create the vault:

```
$V0 create-vault --name memory --path ~/vaults/memory
```

```
$V0 create-vault --name memory --path ~/vaults/memory --apply
```

```
$V0 adopt --role memory=primary --apply
```

On Windows use a path such as `C:\vaults\memory`. Open the folder once in Obsidian (**Open**

folder as vault) so Obsidian registers it too.

Success looks like: detect-obsidian prints INSTALLED, a second create-vault ... --apply prints Nothing to do, and \$V0 adopt lists memory primary.

Case 2: Obsidian with One Vault

```
$V0 adopt
```

```
1 vault(s). Ask for a role for each: primary (exactly one; receives
captures and imports), recall (read for injection), ignore.
```

```
notes
```

```
unassigned /home/you/notes
```

```
$V0 adopt --role notes=primary          # dry run: shows role and
default changes
```

```
$V0 adopt --role notes=primary --apply
```

Success looks like: running the same --apply again prints Every requested role is already set. Nothing to change. and exits 0.

Case 3: Several Vaults

adopt lists every vault in the config and every vault Obsidian itself knows about. Decide on each one separately:

- **primary:** this vault receives captures and imports. Choose exactly one.
- **recall:** this vault is searched for context but never written.
- **ignore:** leave this vault alone. The answer is stored so a re-run does not ask again.

Then write every answer in one call:

```
$V0 adopt --role memory=primary --role work-notes=recall --role
journal=ignore
```

```
$V0 adopt --role memory=primary --role work-notes=recall --role
journal=ignore --apply
```

The command refuses any result with no primary, with two, or with any listed vault left without a role, and writes nothing when it does. That is why every answer goes in one call. To move the primary later, demote the old one in the same call: `--role memory=recall --role new-memory=primary`.

Success looks like: `$V0 adopt` lists each vault with its role and no [FAIL] line.

Case 4: Importing a Folder

Bring notes from a plain Markdown folder, or from another vault by name, into the primary vault:

```
$V0 import --source ~/old-notes --dry-run # dry run: counts and
collisions
```

```
$V0 import --source ~/old-notes --apply
```

On Windows, for example: `vo import --source C:\Users\you\Documents\old-notes --apply`.

Notes land under `imported/<folder name>/` with the same sub-folders. Each one gets two

frontmatter keys: `imported_from` (the absolute source path) and `imported_at` (the UTC date). Line endings become LF. The import never overwrites a file. If a file already exists at the destination, the import skips it and reports it as a `COLLISION`. With `--suffix-collisions` it writes the new file beside it as `<name> (imported).md`; run again, it recognises that copy and writes nothing. A destination that passes through a symlinked folder, or lands outside the vault, is refused as `outside-vault`. Files that are not Markdown are counted and left behind. Use `--dest-subdir <folder>` to choose another destination inside the vault.

Success looks like: Imported N note(s); running it again reports `already-imported: N` and writes nothing.

Scheduling the Gardener

On the one machine that should garden, run:

```
$V0 schedule --os cron --designate          # Linux without a  
systemd user session (root, containers)
```

```
$V0 schedule --os systemd --designate      # Linux desktop with  
systemd --user
```

```
vo schedule --os windows --designate
```

Each command prints the unit, the install commands, a verify command and a remove command. It installs nothing. Paths are quoted for the shell that reads them, so a folder name with a quote, a space or \$ is safe to paste. Add `--apply` to make this machine the designated gardener, then run the printed install commands yourself. The default time is 02:23; change it with `--time HH:MM`.

Success looks like: after the first scheduled run, `~/ .claude/obsidian/gardener.log` has acked `<session>` lines, and `$V0 queue` shows fewer items.

Confirming Recall Reaches Your Sessions

(written by the context-hook ticket)

Confirming Recall Reaches Your Sessions

crew's context hook (`plugin/crew/hooks/scripts/crew_context.py`) puts two kinds of memory into a session: **code-map slices** from `.crew/codemap/`, and **vault recall** from the Obsidian vaults `obsidian-vault` manages. This page shows how to prove, on your own machine, that recall reaches the main session *and* the subagents it dispatches, and that the model actually uses it.

Which Channel Reaches Which Agent

Measured on Claude Code 2.1.281 on 2026-09-23 with a canary per hook event (one `claude -p run`, Haiku, a general-purpose subagent told to report what was in its context without using tools):

Hook event	Reaches the main agent	Reaches a subagent
SessionStart	yes	no
UserPromptSubmit	yes	no
SubagentStart	n/a	yes

The subagent's verbatim answer in that run: Harbour colour: UNKNOWN, Orchard number: UNKNOWN, Lighthouse keeper name: OSWIN-TARRANT-92, where only the last came from SubagentStart. So crew registers the hook on SubagentStart as well. That event's payload names the agent (`agent_id`, `agent_type`) but does not include the task, so the hook reads the task back from the parent transcript's latest Agent tool call. Commands that write a subagent prompt themselves can also paste in a slice:

```
python3 "<crew plugin root>/hooks/scripts/crew_context.py" --slice-for-subagent \
```

```
--query "<the task text>" --paths <files the task touches>
```

Where Recall Comes From

- The vaults and their roles come from `~/.claude/obsidian/config.json`. Each vault has a role: `primary`, `recall` or `ignore`. A vault with no role is `primary` if it is the default and `recall` otherwise. `crew` **never** asks an `ignore` vault, even if the repo lists it.
- A repo can set its own order in its crew config: `memory.recall.vaults` (an ordered list of names) and `memory.recall.maxChars` (default 800). Snippets come back in that vault order first, then in the order the search ranked them.
- `crew` calls `obsidian-vault`'s read-only CLI: `vault_ops.py recall --query ... --vaults a,b --max-chars N --json`. If the plugin is missing, or the CLI fails, times out or prints something other than JSON, the session goes on without recall and the log records a miss with the reason.
- Every recall line starts with the vault's name: `- [vault:<name>] <note path>: <text>`. Any snippet the CLI returns without a vault name is dropped.

The Seeded-Note Proof

1. Make a scratch vault holding one note whose wording appears nowhere else, for example `notes/tidewater-ledger.md`: "The Tidewater ledger reconciliation cutoff is 03:17 Kestrel time, and the approving steward is Marisol Quennell-Vantage."
2. Add that vault to your obsidian config with `"role": "recall"`. For a dry run that leaves the real config alone, write a copy and point `CREW_OBSIDIAN_CONFIG` at it.
3. In a scratch project that has a `.crew/` directory, register crew's hook in `.claude/settings.json` for `SessionStart`, `UserPromptSubmit` and `SubagentStart`. Use the command `bash "<crew plugin root>/hooks/scripts/crew-context.sh"`. `crew_instructions.py claude-hooks` prints the full set of entries.
4. Start a fresh session and ask for a subagent that may not use tools:

```
bash claude -p --model haiku --output-format stream-json --verbose --include-hook-events \
"Use the Task tool once with exactly this prompt: 'Without using any tools, answer only from \
your context: what is the Tidewater ledger reconciliation cutoff, and who is the approving \
steward? If it is not in your context, answer UNKNOWN. Name the source label.'" Then reply with \
the subagent's answer verbatim."
```

What success looks like. The Agent tool call's prompt does not contain the answer, the

SubagentStart hook response contains - [vault:ops-recall] notes/tidewater-ledger.md: ...
03:17 Kestrel time ... Marisol Quennell-Vantage, and the subagent answers with the answer
and cites the label, with tool_uses: 0. From the 2026-09-23 run, verbatim:

Based on the context provided:

****Tidewater ledger reconciliation cutoff:**** 03:17 Kestrel time

****Approving steward:**** Marisol Quennell-Vantage

****Source label:**** [vault:ops-recall]

That run used a stand-in for obsidian-vault's recall command: a word-overlap search over the scratch vault's files, implementing the same contract. It has since been re-run against the real command; see below.

Measured against the real vault_ops.py recall, 2026-09-23

Claude Code 2.1.281, claude -p --model haiku --no-session-persistence --setting-sources project --strict-mcp-config, crew 0.20.19 with memory.inject: true, in a scratch project and scratch vault. obsidian-vault's own CLI (plugin/obsidian-vault/hooks/scripts/vault_ops.py)

was named with CREW_VAULT_OPS, and both tools read a scratch obsidian config through CREW_OBSIDIAN_CONFIG and OBSIDIAN_VAULT_CONFIG. The seeded note: "The Brackenmoor sluice-gate audit window opens at 04:41 Corvid time, and the countersigning warden is Ysolde Pemberton-Karrow." The Agent call's prompt asked the question and did not contain the answer. The subagent answered with tool_uses: 0, verbatim:

Based on the vault recall in my context:

****Time:**** 04:41 Corvid time

****Countersigning Warden:**** Ysolde Pemberton-Karrow

****Source:**** [vault:proof-recall] notes/brackenmoor-sluice.md

The SubagentStart line in the emission log:

```
{"agent_id": "a74ce527b5ab3e7cb", "agent_type": "general-purpose",
"budget": 2000, "chars": 423, "dedupHits": 0, "event":
"SubagentStart", "harness": "claude", "lines": 4, "query_from":
"last-prompt", "recall": {"dropped": 0, "reason": "", "snippets": 2,
"status": "hit", "vaults": ["proof-recall"]}, "session": "08038c78-
3372-4ccb-85d0-2d765b8c79db", "sources": [{"kind": "vault", "note":
"notes/other.md", "vault": "proof-recall"}, {"kind": "vault", "note":
"notes/brackenmoor-sluice.md", "vault": "proof-recall"}],
"truncated": false, "ts": "2026-09-23T20:59:07Z"}
```

query_from: last-prompt means the recall query came from the session's last user prompt, not from the Agent call in the transcript. --no-session-persistence leaves no transcript to read

back. So this run proves that the real CLI's recall reaches a subagent. It does not prove that the query is taken from the Agent call.

Reading --Stats

Every emission adds one JSON line to `<git-common-dir>/crew/context-log.jsonl`, which all worktrees of the repo share. Outside git, the log is `.work/crew/context-log.jsonl`. To summarise it:

```
python3 "<crew plugin root>/hooks/scripts/crew_context.py" --stats
# add --json for machines
```

This is the output after the proof run above, without its first line (the log path):

```
emissions: 3  injected chars: 647  dedup hits: 0  truncated: 0
```

```
SessionStart: 1 emissions, 45 chars
```

```
SubagentStart: 1 emissions, 352 chars
```

```
UserPromptSubmit: 1 emissions, 250 chars
```

```
vault recall: 2 hit, 1 miss, 0 skipped; 2 snippets injected; code-map
slices: 0
```

```
miss reasons: no-hits=1
```

vault MCP/search tool calls seen: 0

by harness: claude=3

- **hit / miss / skipped** are counted per recall attempt. `cli-missing` means obsidian-vault is not installed where crew can find it. `cli-exit-N`, `cli-timeout` and `cli-bad-json` mean the CLI ran and failed. `no-vaults` means no vault is primary or recall. `no-hits` means the search matched nothing.
- **dedup hits** count slices that were not injected again because this context already had them. Deduplication applies per subsystem or vault note, and per compaction epoch: after `/compact` or `/clear`, crew injects them once more.
- **vault MCP/search tool calls seen** counts the times the model searched a vault itself (`mcp__obsidian-*`, `mcp__basic-memory__*`). The baseline before crew 1.0 was 5 calls in 305 sessions. If recall is helping, this number stays low while hits rise.
- **by harness** separates Claude Code from Codex (`codex`) and from dispatch slices (`cli`).