

# Crew 1.0 - Configuration Reference

This document has two parts. The first is short and hand-written: how crew's two config files combine, how to see what is in force, and the common setups. The second is generated from the code and lists every key.

## How the Two Files Combine

---

crew reads two JSON files:

- `~/.claude/crew/config.json` - the **machine-global** file. Your personal defaults for every repo on this machine: providers and models, notifications, auto-clear, the guards.
- `.crew/config.json` - the **repo** file. Facts about one checkout: the tracker, the board, scope enforcement, autopilot, production declarations.

The repo file wins over the machine file, which wins over crew's defaults. Three exceptions, each named in the Layer column below:

- A **repo-only** key in the machine file takes effect nowhere. It is pruned on read and refused on write.
- A **ratcheted** key (`install.policy`, every `guards.*`, `change.requireForProduction`, `environments.prodUnattended`) resolves to the narrower of the two values, so a cloned repo cannot widen what your machine allows.
- A **machine-armed** key (`resume.auto`, `context.autoClear.enabled`) can be turned on only in the machine file. A repo can only switch it off.

A `null` in the repo file over a machine value inherits the machine value. The `/crew:init` template writes every key, which would otherwise shadow your machine defaults.

## Seeing What Is in Force

---

- `/crew:config --show` prints every machine-settable key, its value and the layer it came from, and names any key that takes effect nowhere.
- `/crew:config` with no argument is a menu that writes either file through the validated path. It shows a dry run first, refuses unknown keys and out-of-range values, and marks a widening with `!`.
- From a shell: `python3 plugin/crew/hooks/scripts/crew_config.py --explain` is the same table, and `--models` is the per-role provider table.

## Common Setups

---

- **Personal defaults once, for every repo.** Put providers, models, notify.\* and the guards in ~/.claude/crew/config.json. Leave repo files to repo facts.
- **Self-approval under autopilot.** In the repo file, set scope.allowCliApproval: true and autopilot.mode: "plan", then choose autopilot.approval (human, self or risk). Review acceptance and production deploys still stop for you.
- **Notifications.** In the machine file, set notify.provider and the environment variable names in notify.urlEnv / notify.tokenEnv. The secret stays in your environment, never in the file.

The reasoning behind each key is in plugin/crew/CONFIG.md, which ships with the plugin.

## Reference (Generated)

---

Generated from the code by `python3 docs/guides/crew/src/config_reference.py --write`.  
Do not edit by hand: `python3 scripts/check-marketplace.py` fails when this file is stale.

**132 keys:** 74 settable in the machine-global file, 58 repo-only.

Columns:

- **Layer:** which file may set the key.
- **Default:** what default\_config() returns. Where the machine default differs, both are shown.
- **Values:** the values crew accepts, read from the same tuple the validator reads. "not validated" means crew checks nothing and names the file that reads the key.
- **Since:** the first crew version whose template declared the key. Keys in the first template (crew 0.11.0) read "0.11.0 or earlier".

## Layers

- **repo:** only .crew/config.json may set it; the global file's value is pruned on read and refused on write.
- **both:** either file may set it; the repo value wins over the machine one.
- **both, ratchet:** either file may set it, and the NARROWER of the two wins (crew\_guards.RATCHETED\_KEYS). A repo can tighten what the machine allows, never loosen it.
- **both, widening warned:** either file may set it and the repo wins, but a write that widens it is flagged (crew\_config.\_RATCHETED).

- **machine-arms:** only the global file can turn it on (exactly true); a repo may only veto it with false (crew\_config.REPO\_VETO\_ONLY).
- **machine-only:** read from the global file alone; a repo's own value is never consulted.

## Top-Level Keys

| Setting    | Layer | Default                         | Values                                                                                                           | Since                   | Summary                                                                                                 |
|------------|-------|---------------------------------|------------------------------------------------------------------------------------------------------------------|-------------------------|---------------------------------------------------------------------------------------------------------|
| schema     | repo  | 7                               | not validated -<br>read by<br>plugin/crew/hooks<br>/scripts/crew_sta<br>te.py (expects<br>integer)               | 0.11.0<br>or<br>earlier | Config schema<br>version;<br>/crew:upgrade<br>migrates an older<br>one.                                 |
| tier       | repo  | 0                               | not validated -<br>read by<br>plugin/crew/hooks<br>/scripts/crew_sta<br>te.py (expects<br>integer)               | 0.11.0<br>or<br>earlier | Setup tier recorded<br>by /crew:init.                                                                   |
| roles      | repo  | ["explorer"<br>,<br>"reviewer"] | not validated -<br>read by<br>plugin/crew/hooks<br>/scripts/crew_sta<br>te.py (expects<br>list of role<br>names) | 0.11.0<br>or<br>earlier | Optional roles<br>installed in this<br>repo.                                                            |
| tracker    | repo  | "files"                         | files   obsidian  <br>jira   sdp                                                                                 | 0.11.0<br>or<br>earlier | Where tickets live;<br>crew_tracker.resol<br>ve answers could<br>not tell when two<br>configs disagree. |
| verifyGate | repo  | true                            | not validated -<br>read by<br>plugin/crew/hooks<br>/scripts/verify-<br>gate.sh (expects<br>boolean)              | 0.11.0<br>or<br>earlier | Run the Stop verify<br>gate.                                                                            |

| Setting                  | Layer | Default                                         | Values                                                                                | Since             | Summary                                                                     |
|--------------------------|-------|-------------------------------------------------|---------------------------------------------------------------------------------------|-------------------|-----------------------------------------------------------------------------|
| qa.provider              | both  | "auto"                                          | auto  <br>claude  <br>codex  <br>copilot  <br>kimi                                    | 0.11.0 or earlier | Who reviews: auto walks qa.order; a named provider is used as-is.           |
| qa.order                 | both  | ["codex",<br>"kimi",<br>"copilot",<br>"claude"] | list of:<br>claude  <br>codex  <br>copilot  <br>kimi                                  | 0.14.6            | The reviewers auto tries, in order. A list is one leaf, replaced wholesale. |
| qa.fallback              | both  | "claude-sonnet-5"                               | not validated<br>- read by plugin/crew/commands/review.md<br>(expects model id)       | 0.16.6            | Claude model used when no other reviewer is available.                      |
| qa.codex.model           | both  | null                                            | not validated<br>- read by plugin/crew/commands/review.md<br>(expects string or null) | 0.14.6            | Codex model for review; null passes no flag.                                |
| qa.codex.reasoningEffort | both  | null                                            | none  <br>minimal  <br>low  <br>medium  <br>high                                      | 0.14.6            | Codex reasoning effort for review; null passes no flag.                     |

| Setting          | Layer | Default | Values                                                                                                | Since  | Summary                                                                                                                     |
|------------------|-------|---------|-------------------------------------------------------------------------------------------------------|--------|-----------------------------------------------------------------------------------------------------------------------------|
|                  |       |         | xhigh  <br>max<br>(listed in<br>plugin/crew/commands/review<br>.md; not<br>validated<br>)             |        |                                                                                                                             |
| qa.copilot.model | both  | null    | not<br>validated<br>- read by<br>plugin/crew/commands/review<br>.md<br>(expects<br>string or<br>null) | 0.14.6 | Copilot model<br>for review; null<br>uses the CLI<br>default.                                                               |
| qa.kimi.model    | both  | null    | not<br>validated<br>- read by<br>plugin/crew/commands/review<br>.md<br>(expects<br>string or<br>null) | 1.0.39 | Kimi Code<br>model id for<br>review (k3,<br>kimi-for-coding,<br>...); null uses<br>the CLI's own<br>default.                |
| qa.roles         | both  | {}      | object of<br>role pins;<br>each<br>pin's<br>provider<br>is<br>checked<br>(checked<br>in               | 0.16.6 | Per-role<br>reviewer pins,<br>qa.roles.<role><br>.provider / .model; a pin beats<br>the provider<br>block for that<br>role. |

| Setting                   | Layer | Default           | Values                                                                                                       | Since  | Summary                                                 |
|---------------------------|-------|-------------------|--------------------------------------------------------------------------------------------------------------|--------|---------------------------------------------------------|
|                           |       |                   | plugin/crew/hooks/scripts/crew_config.py)                                                                    |        |                                                         |
| Dev                       |       |                   |                                                                                                              |        |                                                         |
| Setting                   | Layer | Default           | Values                                                                                                       | Since  | Summary                                                 |
| dev.provider              | both  | "claude"          | claude   codex   copilot   kimi                                                                              | 0.14.6 | Who implements.                                         |
| dev.fallback              | both  | "claude-sonnet-5" | not validated - read by plugin/crew/skills/crew-providers/SKILL.md (expects model id)                        | 0.16.6 | Claude model used when the dev provider is unavailable. |
| dev.codex.model           | both  | null              | not validated - read by plugin/crew/skills/crew-providers/SKILL.md (expects string or null)                  | 0.14.6 | Codex model for implementation                          |
| dev.codex.reasoningEffort | both  | null              | none   minimal   low   medium   high   xhigh   max (listed in plugin/crew/commands/review.md; not validated) | 0.14.6 | Codex reasoning effort for implementation               |
| dev.copilot.model         | both  | null              | not validated - read by plugin/crew/sk                                                                       | 0.14.6 | Copilot model for                                       |

| Setting        | Layer | Default | Values                                                                                                    | Since  | Summary                                                 |
|----------------|-------|---------|-----------------------------------------------------------------------------------------------------------|--------|---------------------------------------------------------|
|                |       |         | ills/crew-providers/SKILL.md (expects string or null)                                                     |        | implementation                                          |
| dev.kimi.model | both  | null    | not validated - read by plugin/crew/skills/crew-providers/SKILL.md (expects string or null)               | 1.0.39 | Kimi Code model id for implementation as qa.kimi.model. |
| dev.roles      | both  | {}      | object of role pins; each pin's provider is checked (checked in plugin/crew/hooks/scripts/crew_config.py) | 0.16.6 | Per-role dev pins, as qa.roles.                         |

### Worktree

| Setting       | Layer | Default | Values                                                                                 | Since   | Summary                                                     |
|---------------|-------|---------|----------------------------------------------------------------------------------------|---------|-------------------------------------------------------------|
| worktree.root | both  | null    | not validated - read by plugin/crew/hooks/scripts/crew_state.py (expects path or null) | 0.16.27 | Where crew creates linked worktrees; null uses the default. |

### secondOpinion

| Setting                | Layer | Default | Values                  | Since     | Summary                     |
|------------------------|-------|---------|-------------------------|-----------|-----------------------------|
| secondOpinion.provider | both  | "none"  | not validated - read by | 0.11.0 or | Second-opinion provider for |

| Setting                 | Layer | Default          | Values                                                                                      | Since             | Summary                                                  |
|-------------------------|-------|------------------|---------------------------------------------------------------------------------------------|-------------------|----------------------------------------------------------|
|                         |       |                  | plugin/crew/commands/plan.md (expects string)                                               | earlier           | plans; none is off.                                      |
| secondOpinion.mode      | both  | "cli"            | not validated - read by plugin/crew/skills/crew-providers/SKILL.md (expects string)         | 0.11.0 or earlier | How the second opinion is reached.                       |
| secondOpinion.model     | both  | null             | not validated - read by plugin/crew/skills/crew-providers/SKILL.md (expects string or null) | 0.11.0 or earlier | Second-opinion model.                                    |
| secondOpinion.keyEnv    | both  | "GEMINI_API_KEY" | not validated - read by plugin/crew/skills/crew-providers/SKILL.md (expects string)         | 0.11.0 or earlier | Environment variable holding the provider's API key.     |
| secondOpinion.sendsCode | both  | false            | not validated - read by plugin/crew/skills/crew-providers/SKILL.md (expects boolean)        | 0.11.0 or earlier | Whether code may be sent to the second-opinion provider. |

## Jira

| Setting      | Layer | Default | Values          | Since  | Summary           |
|--------------|-------|---------|-----------------|--------|-------------------|
| jira.project | repo  | null    | not validated - | 0.11.0 | Jira project key. |



| Setting      | Layer | Default | Values                                                                                      | Since         | Summary                                                          |
|--------------|-------|---------|---------------------------------------------------------------------------------------------|---------------|------------------------------------------------------------------|
|              |       |         | read by<br>plugin/crew/commands/jira-sync.md<br>(expects string or null)                    | or<br>earlier | No consumer found<br>(CONFIG.md section 9).                      |
| jira.cloudId | repo  | null    | not validated -<br>read by<br>plugin/crew/commands/jira-sync.md<br>(expects string or null) | 0.19.10       | Jira cloud id, cached by<br>/crew:jira-sync;<br>read by nothing. |

#### Sdp

| Setting            | Layer | Default   | Values                                                                                     | Since                   | Summary                                        |
|--------------------|-------|-----------|--------------------------------------------------------------------------------------------|-------------------------|------------------------------------------------|
| sdp.portal         | repo  | null      | not validated -<br>read by<br>plugin/crew/commands/sdp-sync.md<br>(expects string or null) | 0.11.0<br>or<br>earlier | ServiceDesk Plus portal.                       |
| sdp.noteVisibility | repo  | "private" | not validated -<br>read by<br>plugin/crew/commands/sdp-sync.md<br>(expects string)         | 0.11.0<br>or<br>earlier | Visibility of notes crew writes to SDP.        |
| sdp.closeOnDone    | repo  | false     | not validated -<br>read by<br>plugin/crew/commands/sdp-sync.md<br>(expects boolean)        | 0.11.0<br>or<br>earlier | Close the SDP request when the ticket is done. |

## Obsidian

| Setting                  | Layer | Default    | Values                                                                                         | Since             | Summary                                                                           |
|--------------------------|-------|------------|------------------------------------------------------------------------------------------------|-------------------|-----------------------------------------------------------------------------------|
| obsidian.vaultPath       | repo  | null       | not validated<br>- read by plugin/crow/hooks/scripts/crow_tracker.py<br>(expects path or null) | 0.11.0 or earlier | Vault holding the board; falls back to memory.vaultPath and must hold .obsidian/. |
| obsidian.boardDir        | repo  | null       | not validated<br>- read by plugin/crow/hooks/scripts/crow_tracker.py<br>(expects path or null) | 0.11.0 or earlier | Board folder inside the vault (relative, no ..).                                  |
| obsidian.board           | repo  | "Board.md" | not validated<br>- read by plugin/crow/hooks/scripts/crow_tracker.py<br>(expects file name)    | 0.11.0 or earlier | Board file name.                                                                  |
| obsidian.columns.backlog | repo  | "Backlog"  | not validated<br>- read by plugin/crow/hooks/                                                  | 0.11.0 or earlier | Board column for backlog tickets.                                                 |

| Setting                     | Layer | Default              | Values                                                                                                                                                                          | Since                        | Summary                                     |
|-----------------------------|-------|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------|---------------------------------------------|
| obsidian.columns.ready      | repo  | "Ready"              | scripts/c<br>rew_track<br>er.py<br>(expects<br>string)<br><br>not<br>validated<br>- read by<br>plugin/cr<br>ew/hooks/<br>scripts/c<br>rew_track<br>er.py<br>(expects<br>string) | 0.11.<br>0 or<br>earlie<br>r | Board column<br>for ready tickets.          |
| obsidian.columns.inProgress | repo  | "In<br>Progress<br>" | not<br>validated<br>- read by<br>plugin/cr<br>ew/hooks/<br>scripts/c<br>rew_track<br>er.py<br>(expects<br>string)                                                               | 0.11.<br>0 or<br>earlie<br>r | Board column<br>for tickets in<br>progress. |
| obsidian.columns.review     | repo  | "Review"             | not<br>validated<br>- read by<br>plugin/cr<br>ew/hooks/<br>scripts/c<br>rew_track<br>er.py<br>(expects<br>string)                                                               | 0.11.<br>0 or<br>earlie<br>r | Board column<br>for tickets in<br>review.   |
| obsidian.columns.done       | repo  | "Done"               | not<br>validated<br>- read by                                                                                                                                                   | 0.11.<br>0 or<br>earlie      | Board column<br>for done tickets.           |

| Setting | Layer | Default | Values                                                        | Since | Summary |
|---------|-------|---------|---------------------------------------------------------------|-------|---------|
|         |       |         | plugin/crew/hooks/scripts/crew_tracker.py<br>(expects string) | r     |         |

## Memory

| Setting              | Layer | Default | Values                                                                                         | Since             | Summary                                                                          |
|----------------------|-------|---------|------------------------------------------------------------------------------------------------|-------------------|----------------------------------------------------------------------------------|
| memory.mode          | both  | "repo"  | not validated - read by plugin/crew/skills/crew-memory/SKILL.md (expects string)               | 0.11.0 or earlier | Where memory lives (repo, or a vault).                                           |
| memory.vaultPath     | both  | null    | not validated - read by plugin/crew/hooks/scripts/crew_recall.py (expects path or null)        | 0.11.0 or earlier | The Obsidian vault used for memory.                                              |
| memory.inject        | repo  | true    | not validated - read by plugin/crew/hooks/scripts/crew_context.py (expects boolean)            | 1.0.25            | Inject the handoff and recall at session start; only an explicit false stops it. |
| memory.recall.vaults | repo  | []      | not validated - read by plugin/crew/hooks/scripts/crew_recall.py (expects list of vault names) | 1.0.25            | This repo's vault priority for recall; empty uses repo's                         |

| Setting                | Layer | Default | Values                                                                    | Since  | Summary                                                                 |
|------------------------|-------|---------|---------------------------------------------------------------------------|--------|-------------------------------------------------------------------------|
|                        |       |         | ew_recall.py<br>(expects list of vault names)                             |        | the obsidian config's roles.                                            |
| memory.recall.maxChars | repo  | 800     | positive integer<br>(coerced in plugin/crew/hooks/scripts/crew_recall.py) | 1.0.25 | Recall output budget; a non-positive or non-integer value reads as 800. |

## Context

| Setting               | Layer | Default | Values                                                                                       | Since             |
|-----------------------|-------|---------|----------------------------------------------------------------------------------------------|-------------------|
| context.enabled       | repo  | true    | not validated - read by plugin/crew/hooks/scripts/context-watch.sh (expects boolean)         | 0.11.0 or earlier |
| context.warnAt        | repo  | 0.5     | not validated - read by plugin/crew/hooks/scripts/context-watch.sh (expects number)          | 0.11.0 or earlier |
| context.budgetTokens  | repo  | null    | not validated - read by plugin/crew/hooks/scripts/context-watch.sh (expects integer or null) | 0.11.0 or earlier |
| context.reserveTokens | repo  | 0       | not validated - read by                                                                      | 0.11.0 or         |

| Setting                   | Layer            | Default                | Values                                                                                                                                                                         | Since                   |
|---------------------------|------------------|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|
|                           |                  |                        | plugin/crew/hooks/scripts/context-watch.sh<br>(expects integer or null)                                                                                                        | earlier                 |
| context.handoffPath       | repo             | ".work/HANDOFF.m<br>d" | not validated -<br>read by<br>plugin/crew/hooks/scripts/crew_<br>_autocycle.py<br>(expects path)                                                                               | 0.11.0<br>or<br>earlier |
| context.keepTranscripts   | repo             | 5                      | not validated -<br>read by<br>plugin/crew/hooks/scripts/hand<br>off-write.sh<br>(expects integer)                                                                              | 0.11.0<br>or<br>earlier |
| context.autoClear.enabled | machine-<br>arms | null                   | null   true  <br>false (checked<br>in<br>plugin/crew/hooks/scripts/crew_<br>_autocycle.py)                                                                                     | 0.19.1<br>0             |
| context.autoClear.method  | both             | "auto"                 | auto   none  <br>notify   tmux  <br>xdotool   wtype  <br>sendkeys; per<br>OS: linux: auto,<br>none, notify,<br>tmux, xdotool,<br>wtype; macos:<br>auto, none,<br>notify, tmux; | 0.19.1<br>0             |

| Setting                           | Layer | Default  | Values                                                                                    | Since   |
|-----------------------------------|-------|----------|-------------------------------------------------------------------------------------------|---------|
|                                   |       |          | windows: auto, none, notify, sendkeys; windows-bash: auto, none, notify, tmux, sendkeys   |         |
| context.autoClear.windowTitle     | both  | null     | not validated - read by plugin/crew/hooks/scripts/auto-clear.ps1 (expects string or null) | 0.19.10 |
| context.autoClear.command         | both  | "/clear" | not validated - read by plugin/crew/hooks/scripts/crew_autocycle.py (expects string)      | 0.19.10 |
| context.autoClear.delaySeconds    | both  | 3        | number (coerced in plugin/crew/hooks/scripts/crew_autocycle.py)                           | 0.19.10 |
| context.autoClear.minHandoffLines | both  | 5        | number (coerced in plugin/crew/hooks/scripts/crew_autocycle.py)                           | 0.19.10 |
| context.autoClear.unsafeFocus     | repo  | false    | not validated - read by plugin/crew/hooks/scripts/auto                                    | 0.19.11 |

| Setting                        | Layer        | Default | Values                                                                                                         | Since       |
|--------------------------------|--------------|---------|----------------------------------------------------------------------------------------------------------------|-------------|
|                                |              |         | -clear.sh<br>(expects<br>boolean)                                                                              |             |
| context.autoClear.onlyRepos    | machine-only | null    | list of absolute<br>repo paths, or<br>null (coerced in<br>plugin/crew/hoo<br>ks/scripts/crew<br>_autocycle.py) | 1.0.25      |
| context.autoClear.onlySessions | machine-only | null    | list of session<br>ids, or null<br>(coerced in<br>plugin/crew/hoo<br>ks/scripts/crew<br>_autocycle.py)         | 1.0.25      |
| context.autoWrapUp             | repo         | true    | not validated -<br>read by<br>plugin/crew/hoo<br>ks/scripts/cont<br>ext-watch.sh<br>(expects<br>boolean)       | 0.19.1<br>0 |
| context.autoResume             | repo         | true    | not validated -<br>read by<br>plugin/crew/com<br>mands/migrate.m<br>d (expects<br>boolean)                     | 0.19.1<br>0 |



| Setting                               | Layer | Default | Values                                                                                     | Since   |
|---------------------------------------|-------|---------|--------------------------------------------------------------------------------------------|---------|
| context.staleHandoff.maxAgeHours      | repo  | 72      | not validated -<br>read by<br>plugin/crew/hooks/scripts/crew_state.py<br>(expects integer) | 0.16.33 |
| context.staleHandoff.maxCommitsBehind | repo  | 3       | not validated -<br>read by<br>plugin/crew/hooks/scripts/crew_state.py<br>(expects integer) | 0.16.33 |

## Resume

| Setting                 | Layer        | Default | Values                                                                       | Since   | Summary                                                                                                                 |
|-------------------------|--------------|---------|------------------------------------------------------------------------------|---------|-------------------------------------------------------------------------------------------------------------------------|
| resume.auto             | machine-arms | null    | null   true   false<br>(checked in plugin/crew/hooks/scripts/crew_resume.py) | 1.0.40  | Auto-resume after /clear or a manual /compact. Only the machine file can arm it (exactly true); a repo false vetoes it. |
| resume.typeDelaySeconds | both         | 2       | whole seconds; fraction cut, negative or                                     | 1.0.321 | Wait before auto-resume types its command: before the                                                                   |

| Setting                    | Layer | Default | Values                                                                                                                            | Since       | Summary                                                                                                                     |
|----------------------------|-------|---------|-----------------------------------------------------------------------------------------------------------------------------------|-------------|-----------------------------------------------------------------------------------------------------------------------------|
|                            |       |         | non-number reads as the default (coerced in plugin/crew/hooks/scripts/crew_autocycle.py)                                          |             | tmux ready probe, and the only wait on Windows. Read from the machine file only.                                            |
| resume.readyTimeoutSeconds | both  | 15      | whole seconds; fraction cut, negative or non-number reads as the default (coerced in plugin/crew/hooks/scripts/crew_autocycle.py) | 1.0.32<br>1 | How long the tmux ready probe waits for an idle, empty input line before it types nothing. Read from the machine file only. |

## Emergency

| Setting              | Layer | Default | Values                                                                         | Since             | Summary                                                             |
|----------------------|-------|---------|--------------------------------------------------------------------------------|-------------------|---------------------------------------------------------------------|
| emergency.standDown  | repo  | true    | not validated - read by plugin/crew/hooks/scripts/_common.sh (expects boolean) | 0.11.0 or earlier | Whether a declared incident may stand gates down; false forbids it. |
| emergency.ttlMinutes | repo  | 120     | integer (coerced in plugin/crew/ho                                             | 0.11.0 or earlier | Default incident lifetime; a                                        |

| Setting                 | Layer | Default | Values                                                          | Since             | Summary                                            |
|-------------------------|-------|---------|-----------------------------------------------------------------|-------------------|----------------------------------------------------|
|                         |       |         | oks/scripts/crew_incident.py)                                   |                   | non-integer reads as the default.                  |
| emergency.maxTtlMinutes | repo  | 480     | integer (coerced in plugin/crew/hooks/scripts/crew_incident.py) | 0.11.0 or earlier | Longest incident lifetime; never below ttlMinutes. |

## Notify

| Setting         | Layer | Default | Values                                                                               | Since             | Summary                                       |
|-----------------|-------|---------|--------------------------------------------------------------------------------------|-------------------|-----------------------------------------------|
| notify.provider | both  | "none"  | not validated - read by plugin/crew/hooks/scripts/notify.sh (expects string)         | 0.11.0 or earlier | Where notifications go; none is off.          |
| notify.urlEnv   | both  | null    | not validated - read by plugin/crew/hooks/scripts/notify.sh (expects string or null) | 0.11.0 or earlier | Environment variable holding the webhook URL. |
| notify.tokenEnv | both  | null    | not validated - read by plugin/crew/hooks/scripts/notify.sh (expects string or null) | 0.11.0 or earlier | Environment variable holding the token.       |
| notify.chatId   | both  | null    | not validated - read by                                                              | 0.11.0 or         | Chat id for chat providers.                   |

| Setting       | Layer | Default                            | Values                                                                                          | Since             | Summary                                 |
|---------------|-------|------------------------------------|-------------------------------------------------------------------------------------------------|-------------------|-----------------------------------------|
| notify.events | both  | ["phase",<br>"gate",<br>"waiting"] | plugin/crew/hooks/scripts/notify.sh<br>(expects string or null)                                 | earlier           | Events that notify. A list is one leaf. |
|               |       |                                    | not validated - read by<br>plugin/crew/hooks/scripts/notify.sh<br>(expects list of event names) | 0.11.0 or earlier |                                         |

## Platform

| Setting        | Layer | Default | Values                                                                                             | Since             | Summary                                   |
|----------------|-------|---------|----------------------------------------------------------------------------------------------------|-------------------|-------------------------------------------|
| platform.os    | repo  | null    | not validated - read by<br>plugin/crew/hooks/scripts/crew_platform.py<br>(expects string or null)  | 0.11.0 or earlier | Detected OS, stamped by platform-sync.    |
| platform.wsl   | repo  | null    | not validated - read by<br>plugin/crew/hooks/scripts/crew_platform.py<br>(expects boolean or null) | 0.11.0 or earlier | Detected WSL, stamped by platform-sync.   |
| platform.shell | repo  | null    | not validated - read by<br>plugin/crew/hooks/scripts/crew_platform.py<br>(expects string           | 0.11.0 or earlier | Detected shell, stamped by platform-sync. |

| Setting                | Layer | Default | Values                                                                                      | Since             | Summary                        |
|------------------------|-------|---------|---------------------------------------------------------------------------------------------|-------------------|--------------------------------|
|                        |       |         | or null)                                                                                    |                   |                                |
| platform.windowsHostIp | repo  | null    | not validated - read by plugin/crew/hooks/scripts/crew_platform.py (expects string or null) | 0.11.0 or earlier | Windows host IP seen from WSL. |

## shellRoute

| Setting           | Layer | Default                       | Values                                                                                   | Since  | Summary                                                                                                            |
|-------------------|-------|-------------------------------|------------------------------------------------------------------------------------------|--------|--------------------------------------------------------------------------------------------------------------------|
| shellRoute.mode   | both  | null (repo), "auto" (machine) | auto   wsl   powershell   gitbash                                                        | 1.0.54 | The shell long-running jobs use on native Windows; null inherits, and an unknown value reads as auto and is named. |
| shellRoute.distro | both  | null                          | not validated - read by plugin/crew/hooks/scripts/crew_shell.py (expects string or null) | 1.0.54 | WSL distro to route to; null takes the default distro.                                                             |

## Pm

| Setting    | Layer | Default | Values                                                       | Since             | Summary           |
|------------|-------|---------|--------------------------------------------------------------|-------------------|-------------------|
| pm.enabled | both  | true    | not validated - read by plugin/crew/hooks/scripts/crew_state | 0.11.0 or earlier | Run the PM brief. |

| Setting              | Layer                 | Default       | Values                                                                           | Since             | Summary                                                                                           |
|----------------------|-----------------------|---------------|----------------------------------------------------------------------------------|-------------------|---------------------------------------------------------------------------------------------------|
| pm.mode              | both                  | "adaptive"    | .py (expects boolean)                                                            | 0.11.0 or earlier | How the PM brief adapts its length.                                                               |
|                      |                       |               | not validated - read by plugin/crew/hooks/scripts/crew_state.py (expects string) |                   |                                                                                                   |
| pm.quietLines        | both                  | 8             | integer (coerced in plugin/crew/hooks/scripts/crew_state.py)                     | 0.11.0 or earlier | PM brief length when nothing changed.                                                             |
| pm.maxLines          | both                  | 40            | integer (coerced in plugin/crew/hooks/scripts/crew_state.py)                     | 0.11.0 or earlier | Longest PM brief.                                                                                 |
| pm.authority         | both, widening warned | "report-only" | report-only   act   autonomous                                                   | 0.11.0 or earlier | How much the PM may do unasked. A widening is warned about; the two layers combine by precedence. |
| pm.ticketGranularity | both                  | "system"      | session   system   change                                                        | 0.16.34           | How big a ticket the PM cuts.                                                                     |
| pm.maxDispatches     | both                  | 3             | integer (coerced in plugin/crew/hooks/script                                     | 0.11.0 or earlier | Roles the PM may dispatch in one pass.                                                            |

| Setting | Layer | Default | Values           | Since | Summary |
|---------|-------|---------|------------------|-------|---------|
|         |       |         | s/crew_state.py) |       |         |

Graph

| Setting          | Layer | Default        | Values                                                                           | Since             | Summary                                  |
|------------------|-------|----------------|----------------------------------------------------------------------------------|-------------------|------------------------------------------|
| graph.enabled    | repo  | true           | not validated - read by plugin/crew/skills/crew-graph/SKILL.md (expects boolean) | 0.11.0 or earlier | No consumer found (CONFIG.md section 9). |
| graph.tool       | repo  | "graphify"     | not validated - read by plugin/crew/skills/crew-graph/SKILL.md (expects string)  | 0.11.0 or earlier | No consumer found (CONFIG.md section 9). |
| graph.out        | repo  | "graphify-out" | not validated - read by plugin/crew/hooks/scripts/crew_state.py (expects path)   | 0.11.0 or earlier | Where the code graph is written.         |
| graph.mode       | repo  | "code-only"    | not validated - read by plugin/crew/skills/crew-graph/SKILL.md (expects string)  | 0.11.0 or earlier | No consumer found (CONFIG.md section 9). |
| graph.commitHook | repo  | false          | not validated - read by plugin/crew/skills/crew-graph/SKILL.md (expects          | 0.11.0 or earlier | No consumer found (CONFIG.md section 9). |

| Setting | Layer | Default | Values | Since | Summary |
|---------|-------|---------|--------|-------|---------|
|---------|-------|---------|--------|-------|---------|

boolean)

Docs

| Setting | Layer | Default | Values | Since | Summary |
|---------|-------|---------|--------|-------|---------|
|---------|-------|---------|--------|-------|---------|

|            |      |      |                                                                                               |         |                                                                          |
|------------|------|------|-----------------------------------------------------------------------------------------------|---------|--------------------------------------------------------------------------|
| docs.theme | both | null | not validated - read by plugin/crew/skills/crew-house-style/SKILL.md (expects string or null) | 0.16.33 | House-style theme for built documents; null uses the skill's own choice. |
|------------|------|------|-----------------------------------------------------------------------------------------------|---------|--------------------------------------------------------------------------|

|                  |      |      |                                                                                               |         |                             |
|------------------|------|------|-----------------------------------------------------------------------------------------------|---------|-----------------------------|
| docs.reportTheme | both | null | not validated - read by plugin/crew/skills/crew-house-style/SKILL.md (expects string or null) | 0.16.33 | Theme for findings reports. |
|------------------|------|------|-----------------------------------------------------------------------------------------------|---------|-----------------------------|

Bitbucket

| Setting | Layer | Default | Values | Since | Summary |
|---------|-------|---------|--------|-------|---------|
|---------|-------|---------|--------|-------|---------|

|                             |      |       |                                                                           |         |                                                   |
|-----------------------------|------|-------|---------------------------------------------------------------------------|---------|---------------------------------------------------|
| bitbucket.mergeGate.enabled | both | false | not validated - read by plugin/crew/commands/promote.md (expects boolean) | 0.16.33 | Let /crew:promote drive the Bitbucket merge gate. |
|-----------------------------|------|-------|---------------------------------------------------------------------------|---------|---------------------------------------------------|

|                            |      |      |                                                                  |         |                                           |
|----------------------------|------|------|------------------------------------------------------------------|---------|-------------------------------------------|
| bitbucket.mergeGate.branch | both | null | not validated - read by plugin/crew/commands/promote.md (expects | 0.16.33 | Branch the Bitbucket merge gate protects. |
|----------------------------|------|------|------------------------------------------------------------------|---------|-------------------------------------------|



| Setting                    | Layer | Default    | Values                                                                   | Since   | Summary                                      |
|----------------------------|-------|------------|--------------------------------------------------------------------------|---------|----------------------------------------------|
| bitbucket.mergeGate.preset | both  | "standard" | string or null)                                                          | 0.16.33 | Selects nothing today (CONFIG.md section 9). |
|                            |       |            | not validated - read by plugin/crew/commands/promote.md (expects string) |         |                                              |

## GitHub

| Setting                  | Layer | Default | Values                                                                           | Since   | Summary                                        |
|--------------------------|-------|---------|----------------------------------------------------------------------------------|---------|------------------------------------------------|
| github.mergeGate.enabled | both  | false   | not validated - read by plugin/crew/commands/promote.md (expects boolean)        | 0.19.30 | Let /crew:promote drive the GitHub merge gate. |
| github.mergeGate.branch  | both  | null    | not validated - read by plugin/crew/commands/promote.md (expects string or null) | 0.19.30 | Branch the GitHub merge gate protects.         |

## Install

| Setting        | Layer         | Default  | Values                                                    | Since   | Summary                            |
|----------------|---------------|----------|-----------------------------------------------------------|---------|------------------------------------|
| install.policy | both, ratchet | "manual" | manual   ask   auto (ratchet: narrower layer wins; listed | 0.19.18 | Whether crew may install a missing |

| Setting | Layer | Default | Values           | Since | Summary       |
|---------|-------|---------|------------------|-------|---------------|
|         |       |         | narrowest first) |       | prerequisite. |

## Guards

| Setting               | Layer         | Default | Values                                                                        | Since   | Summary                                                    |
|-----------------------|---------------|---------|-------------------------------------------------------------------------------|---------|------------------------------------------------------------|
| guards.terraformApply | both, ratchet | "block" | block   ask   allow<br>(ratchet: narrower layer wins; listed narrowest first) | 0.19.30 | terraform apply and friends.                               |
| guards.forcePush      | both, ratchet | "block" | block   ask   allow<br>(ratchet: narrower layer wins; listed narrowest first) | 0.19.30 | git push --force.                                          |
| guards.adminMerge     | both, ratchet | "block" | block   ask   allow<br>(ratchet: narrower layer wins; listed narrowest first) | 0.19.30 | gh pr merge --admin.                                       |
| guards.mergeGate      | both, ratchet | "block" | block   ask   allow<br>(ratchet: narrower layer wins; listed                  | 0.19.30 | Taking a live repo's merge gate down (read by /crew:gate). |

| Setting                              | Layer         | Default | Values                                                                        | Since   | Summary                                                    |
|--------------------------------------|---------------|---------|-------------------------------------------------------------------------------|---------|------------------------------------------------------------|
|                                      |               |         | narrowest first)                                                              |         |                                                            |
| <code>guards.cloudDestructive</code> | both, ratchet | "block" | block   ask   allow<br>(ratchet: narrower layer wins; listed narrowest first) | 1.0.25  | Destructive cloud CLI commands.                            |
| <code>guards.sqlDestructive</code>   | both, ratchet | "block" | block   ask   allow<br>(ratchet: narrower layer wins; listed narrowest first) | 1.0.25  | Destructive SQL.                                           |
| <code>guards.prodDatabase</code>     | both, ratchet | "none"  | none   read   full<br>(ratchet: narrower layer wins; listed narrowest first)  | 0.19.30 | How much of a declared production database crew may reach. |
| <code>guards.prodServer</code>       | both, ratchet | "none"  | none   read   full<br>(ratchet: narrower layer wins; listed narrowest first)  | 0.19.30 | How much of a declared production host crew may reach.     |
| <code>guards.roleWrites</code>       | both,         | "off"   | block                                                                         | 0.19.92 | Enforce each                                               |

| Setting           | Layer            | Default | Values                                                                                           | Since  | Summary                                                                                          |
|-------------------|------------------|---------|--------------------------------------------------------------------------------------------------|--------|--------------------------------------------------------------------------------------------------|
| guards.cloudGuard | ratchet          | "off"   | report   off<br>(ratchet:<br>narrower<br>layer wins;<br>listed<br>narrowest<br>first)            | 1.0.25 | role's write<br>scope. Default<br>off; a<br>malformed<br>value reads as<br>block.                |
|                   | both,<br>ratchet |         | block  <br>report   off<br>(ratchet:<br>narrower<br>layer wins;<br>listed<br>narrowest<br>first) |        | Whether the<br>cloud guard<br>judges<br>commands at<br>all. Default<br>off; report<br>logs only. |

## Production

| Setting              | Layer | Default | Values                                                                                                       | Since   | Summary                                     |
|----------------------|-------|---------|--------------------------------------------------------------------------------------------------------------|---------|---------------------------------------------|
| production.databases | repo  | []      | not validated -<br>read by<br>plugin/crew/hoo<br>ks/scripts/crew<br>_config.py<br>(expects list of<br>globs) | 0.19.30 | Globs<br>naming<br>production<br>databases. |
| production.hosts     | repo  | []      | not validated -<br>read by<br>plugin/crew/hoo<br>ks/scripts/crew<br>_config.py<br>(expects list of<br>globs) | 0.19.30 | Globs<br>naming<br>production<br>hosts.     |

## Cloud

| Setting                  | Layer | Default | Values                                                                                         | Since  | Summary                                      |
|--------------------------|-------|---------|------------------------------------------------------------------------------------------------|--------|----------------------------------------------|
| cloud.awsProfiles        | repo  | []      | not validated<br>- read by<br>plugin/crew/hooks/scripts/cloud_guard.py (expects list of names) | 1.0.25 | AWS profiles<br>this repo may use.           |
| cloud.awsRegions         | repo  | []      | not validated<br>- read by<br>plugin/crew/hooks/scripts/cloud_guard.py (expects list of names) | 1.0.25 | AWS regions<br>this repo may use.            |
| cloud.azureSubscriptions | repo  | []      | not validated<br>- read by<br>plugin/crew/hooks/scripts/cloud_guard.py (expects list of names) | 1.0.25 | Azure<br>subscriptions<br>this repo may use. |

## Environments

| Setting              | Layer | Default | Values                                                                                            | Since  | Summary                                                                          |
|----------------------|-------|---------|---------------------------------------------------------------------------------------------------|--------|----------------------------------------------------------------------------------|
| environments.nonProd | repo  | []      | not<br>validated -<br>read by<br>plugin/crew/hooks/scripts/crew_config.py (expects list of globs) | 1.0.37 | Terraform<br>targets that<br>are not<br>production<br>and may run<br>unattended. |

| Setting                     | Layer         | Default | Values                                                                 | Since  | Summary                                                                             |
|-----------------------------|---------------|---------|------------------------------------------------------------------------|--------|-------------------------------------------------------------------------------------|
| environments.prodUnattended | both, ratchet | false   | false   true<br>(ratchet: narrower layer wins; listed narrowest first) | 1.0.37 | Whether production terraform may run unattended; true only when both layers say so. |

## Change

| Setting                     | Layer         | Default | Values                                                                                       | Since   | Summary                                   |
|-----------------------------|---------------|---------|----------------------------------------------------------------------------------------------|---------|-------------------------------------------|
| change.requester            | both          | null    | not validated<br>- read by plugin/crew/hooks/scripts/crew_change.py (expects string or null) | 0.19.31 | Who requests the change.                  |
| change.implementor          | both          | null    | not validated<br>- read by plugin/crew/hooks/scripts/crew_change.py (expects string or null) | 0.19.31 | Who implements the change.                |
| change.requireForProduction | both, ratchet | false   | true   false<br>(ratchet: narrower layer                                                     | 0.19.31 | Require an approved change request before |

| Setting              | Layer | Default                           | Values                                                                                                      | Since       | Summary                                                                 |
|----------------------|-------|-----------------------------------|-------------------------------------------------------------------------------------------------------------|-------------|-------------------------------------------------------------------------|
|                      |       |                                   | wins;<br>listed<br>narrowest<br>first)                                                                      |             | /crew:promote<br>production: a<br>repo may<br>turn it on,<br>never off. |
| change.sdpTemplate   | both  | "Change<br>Management<br>Request" | not<br>validated<br>- read by<br>plugin/crew/hooks/scripts/crew_change.py<br>(expects<br>string)            | 0.19.3<br>1 | SDP<br>template for<br>a change<br>request.                             |
| change.jiraIssueType | both  | "Change"                          | not<br>validated<br>- read by<br>plugin/crew/hooks/scripts/crew_change.py<br>(expects<br>string)            | 0.19.3<br>1 | Jira issue<br>type for a<br>change<br>request.                          |
| change.category      | both  | null                              | not<br>validated<br>- read by<br>plugin/crew/hooks/scripts/crew_change.py<br>(expects<br>string or<br>null) | 0.19.3<br>1 | Change<br>category.                                                     |

## Scope

| Setting                | Layer | Default | Values                                                                        | Since  | Summary                                                                                              |
|------------------------|-------|---------|-------------------------------------------------------------------------------|--------|------------------------------------------------------------------------------------------------------|
| scope.mode             | repo  | "off"   | off   report<br>  block  <br>auto                                             | 1.0.25 | Whether the scope guard enforces a ticket's Touch list; a value outside these fails closed to block. |
| scope.allowCliApproval | repo  | false   | false   true<br>(checked in<br>plugin/crew/<br>hooks/scripts/crew_tickets.py) | 1.0.25 | Whether a CLI-written approval receipt counts; only exactly true allows it.                          |

## Autopilot

| Setting             | Layer | Default | Values                                                                          | Since  | Summary                                                                                      |
|---------------------|-------|---------|---------------------------------------------------------------------------------|--------|----------------------------------------------------------------------------------------------|
| autopilot.mode      | repo  | "off"   | off   plan<br>(checked in<br>plugin/crew/hooks/scripts/crew_autopilot.py)       | 1.0.41 | Only the exact string plan arms /crew:autopilot; anything else reads as off, with a warning. |
| autopilot.maxPhases | repo  | 12      | positive integer<br>(checked in<br>plugin/crew/hooks/scripts/crew_autopilot.py) | 1.0.41 | Phases one run may take; anything but a positive integer reads as 12, with a warning.        |
| autopilot.deploy    | repo  | "none"  | none   nonprod   all                                                            | 1.0.42 | Where a deploy may run without asking;                                                       |



| Setting             | Layer | Default | Values              | Since  | Summary                                                                              |
|---------------------|-------|---------|---------------------|--------|--------------------------------------------------------------------------------------|
|                     |       |         |                     |        | anything else reads as none.                                                         |
| autopilot.approval  | repo  | "risk"  | human   self   risk | 1.0.42 | Who approves a ticket under autopilot; anything else reads as human.                 |
| autopilot.questions | repo  | "risk"  | human   self   risk | 1.0.42 | Who answers a ticket's open questions under autopilot; anything else reads as human. |

## Tickets

| Setting            | Layer | Default | Values                                                                   | Since   | Summary                                                                                                                                                                                            |
|--------------------|-------|---------|--------------------------------------------------------------------------|---------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| tickets.baseBranch | repo  | null    | branch name or null (checked in plugin/crew/hooks/scripts/scope_base.py) | 1.0.158 | The branch ticket branches are cut from; null tries origin/HEAD's target, then origin/main, then main. A value that is not a branch name, or names no commit, makes the scope base could not tell. |

## Route

| Setting       | Layer | Default | Values                                                                          | Since  | Summary                                                                                    |
|---------------|-------|---------|---------------------------------------------------------------------------------|--------|--------------------------------------------------------------------------------------------|
| route.enabled | both  | false   | false   true<br>(checked in<br>plugin/crew/ho<br>oks/scripts/cr<br>ew_route.py) | 1.0.42 | Route plain-text<br>prompts to /crew:<br>commands; only<br>the JSON value<br>true arms it. |

## Coming (Not in Code Yet)

Keys from approved tickets that have not landed. Each moves into the table above when its ticket lands, because it is then in the code; a test fails until it does (test\_no\_coming\_key\_is\_in\_code).

### T-0009

| Setting                | Change  | Layer         | Default | Values | Summary                                      |
|------------------------|---------|---------------|---------|--------|----------------------------------------------|
| guards.deployWorkflow  | new key | both, ratchet | block   |        | Whether crew may dispatch a deploy workflow. |
| environments.workflows | new key | repo          | {}      |        | Deploy workflows per environment.            |

### T-0011

| Setting                 | Change  | Layer | Default | Values     | Summary                                                                                   |
|-------------------------|---------|-------|---------|------------|-------------------------------------------------------------------------------------------|
| autopilot.ship          | new key | repo  | merge   | pr   merge | After /crew:done, open a PR (pr) or also merge it once required checks are green (merge). |
| autopilot.knownFailures | new     | repo  | []      |            | Required checks                                                                           |

| Setting                    | Change  | Layer | Default | Values | Summary                                                         |
|----------------------------|---------|-------|---------|--------|-----------------------------------------------------------------|
|                            | key     |       |         |        | that may fail without blocking a merge, matched by exact name.  |
| autopilot.ciTimeoutMinutes | new key | repo  | 60      |        | How long ship waits for CI; still pending at the timeout stops. |

## T-0012

| Setting                       | Change         | Layer | Default     | Values               | Summary                                            |
|-------------------------------|----------------|-------|-------------|----------------------|----------------------------------------------------|
| autopilot.maxTicketsPerRun    | new key        | repo  | 3           |                      | Tickets one goal run may work before it stops.     |
| autopilot.maxTokensPerSession | new key        | repo  | 200000<br>0 |                      | Token cap for one goal session.                    |
| autopilot.mode                | changes values | repo  | off         | off   plan   backlog | Adds backlog: work a goal's tickets one at a time. |

## T-0017

| Setting                  | Change  | Layer        | Default | Values | Summary                                                     |
|--------------------------|---------|--------------|---------|--------|-------------------------------------------------------------|
| context.autoClear.wrapUp | new key | machine-arms | null    |        | Machine opt-in for the automatic wrap-up; only exactly true |

| Setting | Change | Layer | Default | Values | Summary  |
|---------|--------|-------|---------|--------|----------|
|         |        |       |         |        | arms it. |

## T-0029

| Setting                | Change  | Layer | Default                       | Values                               | Summary                                                              |
|------------------------|---------|-------|-------------------------------|--------------------------------------|----------------------------------------------------------------------|
| autopilot.maxLanes     | new key | repo  | the resolved pm.maxDispatches |                                      | Parallel lanes one autopilot wave may run; may only lower the limit. |
| autopilot.reviewPolicy | new key | repo  | stop                          | stop   clean-only   fix-and-rereview | What a lane does with review findings.                               |

## T-0030

| Setting          | Change  | Layer                 | Default               | Values | Summary                                                   |
|------------------|---------|-----------------------|-----------------------|--------|-----------------------------------------------------------|
| coord.ttlMinutes | new key | set when T-0030 lands | 30                    |        | Lifetime of a cross-session coordination claim (1-10080). |
| coord.channel    | new key | set when T-0030 lands | set when T-0030 lands |        | Where sessions coordinate.                                |

## T-0050

| Setting                | Change        | Layer               | Default | Values | Summary                                                                                  |
|------------------------|---------------|---------------------|---------|--------|------------------------------------------------------------------------------------------|
| autopilot.mode         | changes layer | both, stricter wins | off     |        | The personal autopilot keys become settable in the global file; the stricter layer wins. |
| scope.allowCliApproval | changes layer | both, stricter wins | false   |        | Becomes settable in the global file; the stricter layer wins.                            |