

Crew 1.0 - Configuration Reference

This document has two parts. The first is short and hand-written: how crew's two config files combine, how to see what is in force, and the common setups. The second is generated from the code and lists every key.

How the Two Files Combine

crew reads two JSON files:

- `~/.claude/crew/config.json` - the **machine-global** file. Your personal defaults for every repo on this machine: providers and models, notifications, auto-clear, the guards, how far autopilot may go.
- `.crew/config.json` - the **repo** file. Facts about one checkout: the tracker, the board, scope enforcement, production declarations.

The repo file wins over the machine file, which wins over crew's defaults. Four exceptions, each named in the Layer column below:

- A **repo-only** key in the machine file takes effect nowhere. It is pruned on read and refused on write.
- A **ratcheted** key (`install.policy`, every `guards.*`, `change.requireForProduction`, `environments.prodUnattended`) resolves to the narrower of the two values, so a cloned repo cannot widen what your machine allows.
- A **machine-armed** key (`resume.auto`, `context.autoClear.enabled`) can be turned on only in the machine file. A repo can only switch it off.
- A **personal** key (the five `autopilot.*` keys) resolves per key to the stricter of the layers that set it; a layer that says nothing imposes nothing. A machine value is your default for every repo, which a repo may narrow and never widen.

A `null` in the repo file over a machine value inherits the machine value. The `/crew:init` template writes every key except the personal ones, so it does not shadow your machine defaults for those; a repo `/crew:init` set up before that still spells `autopilot.mode: "off"`, which holds a machine plan down until you remove it (`--explain --all` names it as a shadow:).

Seeing What Is in Force

- `/crew:config --show` prints every machine-settable key, its value and the layer it

came from, and names any key that takes effect nowhere.

- `/crew:config` with no argument is a menu that writes either file through the validated path. It shows a dry run first, refuses unknown keys and out-of-range values, and marks a widening with `!`.
- From a shell: `python3 plugin/crew/hooks/scripts/crew_config.py --explain` is the same table, `--explain --all` adds every repo-only key and names each shadowing repo value, and `--models` is the per-role provider table.

Backups and Rebuilding a Lost Config

Every write a crew script makes to either file first copies the old bytes to `~/.claude/crew/backups/` (the newest 20 per file kept) and is refused when that copy fails; a hand edit is not backed up. `crew_config.py --backups` lists the machine file's (add `--repo` for the repo file's) and `--restore <stamp> --apply` puts one back. Your non-default values are kept in `~/.claude/crew/profile.json` (and in your vault when `memory.vaultPath` is set), so `--rebuild --repo` or `--rebuild --global` regenerates a lost or corrupt file from the template plus that profile, as a dry run until `--apply`.

Common Setups

- **Personal defaults once, for every repo.** Put providers, models, `notify.*`, the guards and the `autopilot.*` keys in `~/.claude/crew/config.json`. Leave repo files to repo facts.
- **Self-approval under autopilot.** Set `autopilot.mode: "plan"` and choose `autopilot.approval` (human, self or risk) in either file, and set `scope.allowCliApproval: true` in the repo file, which is the only file that key is read from. Review acceptance and production deploys still stop for you.
- **Notifications.** In the machine file, set `notify.provider` and the environment variable names in `notify.urlEnv / notify.tokenEnv`. The secret stays in your environment, never in the file.

The reasoning behind each key is in `plugin/crew/CONFIG.md`, which ships with the plugin.

Reference (Generated)

Generated from the code by `python3 docs/guides/crew/src/config_reference.py --write`. Do not edit by hand: `python3 scripts/check-marketplace.py` fails when this file is stale.

141 keys: 81 settable in the machine-global file, 60 repo-only.

Columns:

- **Layer:** which file may set the key.
- **Default:** what `default_config()` returns. Where the machine default differs, both are shown.
- **Values:** the values crew accepts, read from the same tuple the validator reads. "not validated" means crew checks nothing and names the file that reads the key.
- **Since:** the first crew version whose template declared the key. Keys in the first template (crew 0.11.0) read "0.11.0 or earlier".

Layers

- **repo:** only `.crew/config.json` may set it; the global file's value is pruned on read and refused on write.
- **both:** either file may set it; the repo value wins over the machine one.
- **both, ratchet:** either file may set it, and the NARROWER of the two wins (`crew_guards.RATCHETED_KEYS`). A repo can tighten what the machine allows, never loosen it.
- **both, widening warned:** either file may set it and the repo wins, but a write that widens it is flagged (`crew_config._RATCHETED`).
- **both, stricter wins:** a personal key (`crew_guards.PERSONAL_KEYS`): either file may set it, and where both do the STRICTER value wins; a layer that is silent (absent or `null`) imposes nothing, so a machine value is your default for every repo and a repo may only narrow it.
- **machine-arms:** only the global file can turn it on (exactly `true`); a repo may only veto it with `false` (`crew_config.REPO_VETO_ONLY`).
- **machine-only:** read from the global file alone; a repo's own value is never consulted.

Top-Level Keys

Setting	Layer	Default	Values	Since	Summary
schema	repo	7	not validated - read by plugin/crew/hooks /scripts/crew_sta te.py (expects integer)	0.11.0 or earlier	Config schema version; /crew: upgrade migrates an older one.

Setting	Layer	Default	Values	Since	Summary
tier	repo	0	not validated - read by plugin/crew/hooks /scripts/crew_sta te.py (expects integer)	0.11.0 or earlier	Setup tier recorded by /crew:init.
roles	repo	["explorer" , "reviewer"]	not validated - read by plugin/crew/hooks /scripts/crew_sta te.py (expects list of role names)	0.11.0 or earlier	Optional roles installed in this repo.
tracker	repo	"files"	files obsidian jira sdp	0.11.0 or earlier	Where tickets live; crew_tracker.resol ve answers could not tell when two configs disagree.
verifyGate	repo	true	not validated - read by plugin/crew/hooks /scripts/verify- gate.sh (expects boolean)	0.11.0 or earlier	Run the Stop verify gate.

Qa

Setting	Layer	Default	Values	Since	Summary
qa.provider	both	"auto"	auto claude codex copilot kimi	0.11. 0 or earlie r	Who reviews: auto walks qa.order; a named provider is used as-is.
qa.order	both	["codex", "kimi", "copilot", "claude"]	list of: claude codex	0.14. 6	The reviewers auto tries, in order. A list is

Setting	Layer	Default	Values	Since	Summary
			copilot kimi		one leaf, replaced wholesale.
qa.fallback	both	"claude-sonnet-5"	not validated - read by plugin/crew/commands/review.md (expects model id)	0.16.6	Claude model used when no other reviewer is available.
qa.codex.model	both	null	not validated - read by plugin/crew/commands/review.md (expects string or null)	0.14.6	Codex model for review; null passes no flag.
qa.codex.reasoningEffort	both	null	none minimal low medium high xhigh max (listed in plugin/crew/commands/review.md; not validated)	0.14.6	Codex reasoning effort for review; null passes no flag.
qa.copilot.model	both	null	not	0.14.	Copilot model

Setting	Layer	Default	Values	Since	Summary
			validated - read by plugin/crew/commands/review .md (expects string or null)	6	for review; null uses the CLI default.
qa.kimi.model	both	null	not validated - read by plugin/crew/commands/review .md (expects string or null)	1.0.3 9	Kimi Code model id for review (k3, kimi-for-coding, ...); null uses the CLI's own default.
qa.roles	both	{}	object of role pins; each pin's provider is checked (checked in plugin/crew/hooks/scripts/crew_config.py)	0.16. 6	Per-role reviewer pins, qa.roles.<role> .provider / .model; a pin beats the provider block for that role.

Setting	Layer	Default	Values	Since	Summary
dev.provider	both	"claude"	claude codex copilot kimi	0.14.6	Who implements.
dev.fallback	both	"claude-sonnet-5"	not validated - read by plugin/crew/skills/crew-providers/SKILL.md (expects model id)	0.16.6	Claude model used when the dev provider is unavailable.
dev.codex.model	both	null	not validated - read by plugin/crew/skills/crew-providers/SKILL.md (expects string or null)	0.14.6	Codex model for implementation
dev.codex.reasoningEffort	both	null	none minimal low medium high xhigh max (listed in plugin/crew/commands/review.md; not validated)	0.14.6	Codex reasoning effort for implementation
dev.copilot.model	both	null	not validated - read by plugin/crew/skills/crew-providers/SKILL.md (expects string or null)	0.14.6	Copilot model for implementation
dev.kimi.model	both	null	not validated - read by plugin/crew/skills/crew-providers/SKILL	1.0.39	Kimi Code model id for implementation as

Setting	Layer	Default	Values	Since	Summary
			L.md (expects string or null)		qa.kimi.model.
dev.roles	both	{}	object of role pins; each pin's provider is checked (checked in plugin/crew/hooks/scripts/crew_config.py)	0.16.6	Per-role dev pins, as qa.roles.

Worktree

Setting	Layer	Default	Values	Since	Summary
worktree.root	both	null	not validated - read by plugin/crew/hooks/scripts/crew_state.py (expects path or null)	0.16.27	Where crew creates linked worktrees; null uses the default.

secondOpinion

Setting	Layer	Default	Values	Since	Summary
secondOpinion.provider	both	"none"	not validated - read by plugin/crew/commands/plan.md (expects string)	0.11.0 or earlier	Second-opinion provider for plans; none is off.
secondOpinion.mode	both	"cli"	not validated - read by plugin/crew/skills/crew-providers/SKILL.md (expects	0.11.0 or earlier	How the second opinion is reached.

Setting	Layer	Default	Values	Since	Summary
			string)		
<code>secondOpinion.model</code>	both	null	not validated - read by plugin/crew/skills/crew-providers/SKILL.md (expects string or null)	0.11.0 or earlier	Second-opinion model.
<code>secondOpinion.keyEnv</code>	both	"GEMINI_API_KEY"	not validated - read by plugin/crew/skills/crew-providers/SKILL.md (expects string)	0.11.0 or earlier	Environment variable holding the provider's API key.
<code>secondOpinion.sendsCode</code>	both	false	not validated - read by plugin/crew/skills/crew-providers/SKILL.md (expects boolean)	0.11.0 or earlier	Whether code may be sent to the second-opinion provider.

Jira

Setting	Layer	Default	Values	Since	Summary
<code>jira.project</code>	repo	null	not validated - read by plugin/crew/commands/jira-sync.md (expects string or null)	0.11.0 or earlier	Jira project key. No consumer found (CONFIG.md section 9).
<code>jira.cloudId</code>	repo	null	not validated - read by plugin/crew/commands/jira-sync.md	0.19.10	Jira cloud id, cached by /crew:jira-sync;

Setting	Layer	Default	Values	Since	Summary
			(expects string or null)		read by nothing.

Sdp

Setting	Layer	Default	Values	Since	Summary
sdp.portal	repo	null	not validated - read by plugin/crew/commands/sdp-sync.md (expects string or null)	0.11.0 or earlier	ServiceDesk Plus portal.
sdp.noteVisibility	repo	"private"	not validated - read by plugin/crew/commands/sdp-sync.md (expects string)	0.11.0 or earlier	Visibility of notes crew writes to SDP.
sdp.closeOnDone	repo	false	not validated - read by plugin/crew/commands/sdp-sync.md (expects boolean)	0.11.0 or earlier	Close the SDP request when the ticket is done.

Obsidian

Setting	Layer	Default	Values	Since	Summary
obsidian.vaultPath	repo	null	not validated - read by plugin/crew/hooks/scripts/crew_tracker.py	0.11.0 or earlier	Vault holding the board; falls back to memory.vaultPath and must hold .obsidian/.

Setting	Layer	Default	Values	Since	Summary
obsidian.boardDir	repo	null	(expects path or null) not validated - read by plugin/crow/hooks/scripts/crow_tracker.py (expects path or null)	0.11.0 or earlier	Board folder inside the vault (relative, no ..).
obsidian.board	repo	"Board.md"	not validated - read by plugin/crow/hooks/scripts/crow_tracker.py (expects file name)	0.11.0 or earlier	Board file name.
obsidian.columns.backlog	repo	"Backlog"	not validated - read by plugin/crow/hooks/scripts/crow_tracker.py (expects string)	0.11.0 or earlier	Board column for backlog tickets (direction, ready, needs-owner).
obsidian.columns.ready	repo	"Ready"	not validated - read by	0.11.0 or earlier	Board column for ready tickets.

Setting	Layer	Default	Values	Since	Summary
			plugin/crow/hooks/scripts/crow_tracker.py (expects string)	r	
obsidian.columns.inProgress	repo	"In Progress"	not validated - read by plugin/crow/hooks/scripts/crow_tracker.py (expects string)	0.11.0 or earlier	Board column for tickets in progress.
obsidian.columns.review	repo	"Review"	not validated - read by plugin/crow/hooks/scripts/crow_tracker.py (expects string)	0.11.0 or earlier	Board column for tickets in review.
obsidian.columns.done	repo	"Done"	not validated - read by plugin/crow/hooks/scripts/crow_tracker.py (expects string)	0.11.0 or earlier	Board column for closed tickets (done, cancelled, superseded; each checked).

Memory

Setting	Layer	Default	Values	Since	Summary
<code>memory.mode</code>	both	"repo"	not validated - read by plugin/crew/skills/crew-memory/SKILL.mmd (expects string)	0.11.0 or earlier	Where memory lives (repo, or a vault).
<code>memory.vaultPath</code>	both	null	not validated - read by plugin/crew/hooks/scripts/crew_recall.py (expects path or null)	0.11.0 or earlier	The Obsidian vault used for memory.
<code>memory.inject</code>	repo	true	not validated - read by plugin/crew/hooks/scripts/crew_context.py (expects boolean)	1.0.25	Inject the handoff and recall at session start; only an explicit false stops it.
<code>memory.recall.vaults</code>	repo	[]	not validated - read by plugin/crew/hooks/scripts/crew_recall.py (expects list of vault names)	1.0.25	This repo's vault priority for recall; empty uses the obsidian config's roles.
<code>memory.recall.maxChars</code>	repo	800	positive integer (coerced in plugin/crew/hooks/scripts/crew_recall.py)	1.0.25	Recall output budget; a non-positive or non-integer value reads as 800.

Context

Setting	Layer	Default	Values	Since
context.enabled	repo	true	not validated - read by plugin/crew/hooks/scripts/context-watch.sh (expects boolean)	0.11.0 or earlier
context.warnAt	repo	0.5	not validated - read by plugin/crew/hooks/scripts/context-watch.sh (expects number)	0.11.0 or earlier
context.budgetTokens	repo	null	not validated - read by plugin/crew/hooks/scripts/context-watch.sh (expects integer or null)	0.11.0 or earlier
context.reserveTokens	repo	0	not validated - read by plugin/crew/hooks/scripts/context-watch.sh (expects integer or null)	0.11.0 or earlier
context.handoffPath	repo	".work/HANDOFF.m d"	not validated - read by plugin/crew/hooks/scripts/crew_ _autocycle.py (expects path)	0.11.0 or earlier
context.keepTranscripts	repo	5	not validated - read by	0.11.0 or

Setting	Layer	Default	Values	Since
			plugin/crew/hooks/scripts/handoff-write.sh (expects integer)	earlier
context.autoClear.enabled	machine-arms	null	null true false (checked in plugin/crew/hooks/scripts/crew_autocycle.py)	0.19.10
context.autoClear.method	both	"auto"	auto none notify tmux xdotool wtype sendkeys; per OS: linux: auto, none, notify, tmux, xdotool, wtype; macos: auto, none, notify, tmux; windows: auto, none, notify, sendkeys; windows-bash: auto, none, notify, tmux, sendkeys	0.19.10
context.autoClear.windowTitle	both	null	not validated - read by plugin/crew/hooks/scripts/auto-clear.ps1 (expects string	0.19.10

Setting	Layer	Default	Values	Since
			or null)	
<code>context.autoClear.command</code>	both	<code>"/clear"</code>	not validated - read by plugin/crew/hooks/scripts/crew_autocycle.py (expects string)	0.19.10
<code>context.autoClear.delaySeconds</code>	both	3	number (coerced in plugin/crew/hooks/scripts/crew_autocycle.py)	0.19.10
<code>context.autoClear.minHandoffLines</code>	both	5	number (coerced in plugin/crew/hooks/scripts/crew_autocycle.py)	0.19.10
<code>context.autoClear.unsafeFocus</code>	repo	false	not validated - read by plugin/crew/hooks/scripts/auto-clear.sh (expects boolean)	0.19.11
<code>context.autoClear.onlyRepos</code>	machine-only	null	list of absolute repo paths, or null (coerced in plugin/crew/hooks/scripts/crew_autocycle.py)	1.0.25

Setting	Layer	Default	Values	Since
context.autoClear.onlySessions	machine-only	null	list of session ids, or null (coerced in plugin/crew/hooks/scripts/crew_autocycle.py)	1.0.25
context.autoClear.wrapUp	machine-arms	null	null true false (checked in plugin/crew/hooks/scripts/crew_autocycle.py)	1.0.334
context.autoWrapUp	repo	true	not validated - read by plugin/crew/hooks/scripts/context-watch.sh (expects boolean)	0.19.10

Setting	Layer	Default	Values	Since
context.autoResume	repo	true	not validated - read by plugin/crew/com mands/migrate.m d (expects boolean)	0.19.1 0
context.staleHandoff.maxAgeHours	repo	72	not validated - read by plugin/crew/hoo ks/scripts/crew _state.py (expects integer)	0.16.3 3
context.staleHandoff.maxCommitsBehind	repo	3	not validated - read by plugin/crew/hoo ks/scripts/crew _state.py (expects integer)	0.16.3 3

Resume

Setting	Layer	Default	Values	Since	Summary
resume.auto	machine-arms	null	null true false (checked in plugin/crew/ /hooks/scr ipts/crew_re sume.py)	1.0.40	Auto-resume after /clear or a manual /compact. Only the machine file can arm it (exactly true); a repo false vetoes it.

Setting	Layer	Default	Values	Since	Summary
<code>resume.typeDelaySeconds</code>	both	2	whole seconds; fraction cut, negative or non-number reads as the default (coerced in <code>plugin/crew/hooks/scripts/crew_autocycle.py</code>)	1.0.32 1	Wait before auto-resume types its command: before the tmux ready probe, and the only wait on Windows. Read from the machine file only.
<code>resume.readyTimeoutSeconds</code>	both	15	whole seconds; fraction cut, negative or non-number reads as the default (coerced in <code>plugin/crew/hooks/scripts/crew_autocycle.py</code>)	1.0.32 1	How long the tmux ready probe waits for an idle, empty input line before it types nothing. Read from the machine file only.

Emergency

Setting	Layer	Default	Values	Since	Summary
<code>emergency.standDown</code>	repo	true	not validated - read by <code>plugin/crew/hooks/scripts/_common.sh</code> (expects	0.11.0 or earlier	Whether a declared incident may stand gates down; false

Setting	Layer	Default	Values	Since	Summary
			boolean)		forbids it.
emergency.ttlMinutes	repo	120	integer (coerced in plugin/crew/ho oks/scripts/cr ew_incident.py)	0.11.0 or earlier	Default incident lifetime; a non-integer reads as the default.
emergency.maxTtlMinutes	repo	480	integer (coerced in plugin/crew/ho oks/scripts/cr ew_incident.py)	0.11.0 or earlier	Longest incident lifetime; never below ttlMinutes.

Notify

Setting	Layer	Default	Values	Since	Summary
notify.provider	both	"none"	not validated - read by plugin/crew/ho oks/scripts/no tify.sh (expects string)	0.11.0 or earlier	Where notifications go; none is off.
notify.urlEnv	both	null	not validated - read by plugin/crew/ho oks/scripts/no tify.sh (expects string or null)	0.11.0 or earlier	Environment variable holding the webhook URL.
notify.tokenEnv	both	null	not validated - read by plugin/crew/ho oks/scripts/no tify.sh	0.11.0 or earlier	Environment variable holding the token.

Setting	Layer	Default	Values	Since	Summary
			(expects string or null)		
notify.chatId	both	null	not validated - read by plugin/crew/hooks/scripts/notify.sh (expects string or null)	0.11.0 or earlier	Chat id for chat providers.
notify.events	both	["phase", "gate", "waiting"]	not validated - read by plugin/crew/hooks/scripts/notify.sh (expects list of event names)	0.11.0 or earlier	Events that notify. A list is one leaf.

Platform

Setting	Layer	Default	Values	Since	Summary
platform.os	repo	null	not validated - read by plugin/crew/hooks/scripts/crew_platform.py (expects string or null)	0.11.0 or earlier	Detected OS, stamped by platform-sync.
platform.wsl	repo	null	not validated - read by plugin/crew/hooks/scripts/crew_platform.py (expects boolean or null)	0.11.0 or earlier	Detected WSL, stamped by platform-sync.
platform.shell	repo	null	not validated -	0.11.0	Detected shell,

Setting	Layer	Default	Values	Since	Summary
			read by plugin/crew/hooks/scripts/crew_platform.py (expects string or null)	or earlier	stamped by platform-sync.
platform.windowsHostIp	repo	null	not validated - read by plugin/crew/hooks/scripts/crew_platform.py (expects string or null)	0.11.0 or earlier	Windows host IP seen from WSL.

shellRoute

Setting	Layer	Default	Values	Since	Summary
shellRoute.mode	both	null (repo), "auto" (machine)	auto wsl powershell gitbash	1.0.54	The shell long-running jobs use on native Windows; null inherits, and an unknown value reads as auto and is named.
shellRoute.distro	both	null	not validated - read by plugin/crew/hooks/scripts/crew_shell.py (expects string or null)	1.0.54	WSL distro to route to; null takes the default distro.

Pm

Setting	Layer	Default	Values	Since	Summary
pm.enabled	both	true	not	0.11.0	Run the PM

Setting	Layer	Default	Values	Since	Summary
			validated - read by plugin/crew/ hooks/scripts/crew_state .py (expects boolean)	or earlier	brief.
pm.mode	both	"adaptive"	not validated - read by plugin/crew/ hooks/scripts/crew_state .py (expects string)	0.11.0 or earlier	How the PM brief adapts its length.
pm.quietLines	both	8	integer (coerced in plugin/crew/ hooks/scripts/crew_state .py)	0.11.0 or earlier	PM brief length when nothing changed.
pm.maxLines	both	40	integer (coerced in plugin/crew/ hooks/scripts/crew_state .py)	0.11.0 or earlier	Longest PM brief.
pm.authority	both, widening warned	"report- only"	report-only act autonomous	0.11.0 or earlier	How much the PM may do unasked. A widening is warned about; the two layers combine by precedence.
pm.ticketGranularity	both	"system"	session system	0.16.34	How big a ticket the PM

Setting	Layer	Default	Values	Since	Summary
			change		cuts.
pm.maxDispatches	both	3	integer (coerced in plugin/crew/ hooks/scripts/ crew_state .py)	0.11.0 or earlier	Roles the PM may dispatch in one pass.

Graph

Setting	Layer	Default	Values	Since	Summary
graph.enabled	repo	true	not validated - read by plugin/crew/ski lls/crew- graph/SKILL.md (expects boolean)	0.11.0 or earlier	No consumer found (CONFIG.md section 9).
graph.tool	repo	"graphify"	not validated - read by plugin/crew/ski lls/crew- graph/SKILL.md (expects string)	0.11.0 or earlier	No consumer found (CONFIG.md section 9).
graph.out	repo	"graphify- out"	not validated - read by plugin/crew/hoo ks/scripts/crew _state.py (expects path)	0.11.0 or earlier	Where the code graph is written.
graph.mode	repo	"code-only"	not validated - read by plugin/crew/ski lls/crew- graph/SKILL.md (expects string)	0.11.0 or earlier	No consumer found (CONFIG.md section 9).
graph.commitHook	repo	false	not validated -	0.11.0	No consumer

Setting	Layer	Default	Values	Since	Summary
			read by plugin/crew/skills/crew-graph/SKILL.md (expects boolean)	or earlier	found (CONFIG.md section 9).

Docs

Setting	Layer	Default	Values	Since	Summary
docs.theme	both	null	not validated - read by plugin/crew/skills/crew-house-style/SKILL.md (expects string or null)	0.16.33	House-style theme for built documents; null uses the skill's own choice.
docs.reportTheme	both	null	not validated - read by plugin/crew/skills/crew-house-style/SKILL.md (expects string or null)	0.16.33	Theme for findings reports.

Bitbucket

Setting	Layer	Default	Values	Since	Summary
bitbucket.mergeGate.enabled	both	false	not validated - read by plugin/crew/commands/promote.md (expects boolean)	0.16.33	Let /crew:promote drive the Bitbucket merge gate.
bitbucket.mergeGate.branch	both	null	not validated -	0.16.3	Branch the Bitbucket

Setting	Layer	Default	Values	Since	Summary
			read by plugin/crew /commands/p romote.md (expects string or null)	3	merge gate protects.
bitbucket.mergeGate.preset	both	"standar d"	not validated - read by plugin/crew /commands/p romote.md (expects string)	0.16.3 3	Selects nothing today (CONFIG.md section 9).

GitHub

Setting	Layer	Default	Values	Since	Summary
github.mergeGate.enabled	both	false	not validated - read by plugin/crew/c ommands/promo te.md (expects boolean)	0.19.30	Let /crew:promot e drive the GitHub merge gate.
github.mergeGate.branch	both	null	not validated - read by plugin/crew/c ommands/promo te.md (expects string or null)	0.19.30	Branch the GitHub merge gate protects.

Install

Setting	Layer	Default	Values	Since	Summary
install.policy	both, ratchet	"manual"	manual ask auto (ratchet: narrower layer wins; listed narrowest first)	0.19.18	Whether crew may install a missing prerequisite.

Guards

Setting	Layer	Default	Values	Since	Summary
guards.terraformApply	both, ratchet	"block"	block ask allow (ratchet: narrower layer wins; listed narrowest first)	0.19.30	terraform apply and friends.
guards.forcePush	both, ratchet	"block"	block ask allow (ratchet: narrower layer wins; listed narrowest first)	0.19.30	git push --force.
guards.adminMerge	both, ratchet	"block"	block ask allow (ratchet: narrower layer wins; listed narrowest first)	0.19.30	gh pr merge --admin.
guards.mergeGate	both,	"block"	block ask	0.19.30	Taking a live

Setting	Layer	Default	Values	Since	Summary
			allow (ratchet: narrower layer wins; listed narrowest first)		repo's merge gate down (read by /crew:gate).
guards.cloudDestructive	both, ratchet	"block"	block ask allow (ratchet: narrower layer wins; listed narrowest first)	1.0.25	Destructive cloud CLI commands.
guards.sqlDestructive	both, ratchet	"block"	block ask allow (ratchet: narrower layer wins; listed narrowest first)	1.0.25	Destructive SQL.
guards.prodDatabase	both, ratchet	"none"	none read full (ratchet: narrower layer wins; listed narrowest first)	0.19.30	How much of a declared production database crew may reach.
guards.prodServer	both, ratchet	"none"	none read full (ratchet: narrower layer wins;	0.19.30	How much of a declared production host crew may

Setting	Layer	Default	Values	Since	Summary
			listed narrowest first)		reach.
<code>guards.roleWrites</code>	both, ratchet	"off"	block report off (ratchet: narrower layer wins; listed narrowest first)	0.19.92	Enforce each role's write scope. Default off; a malformed value reads as block.
<code>guards.cloudGuard</code>	both, ratchet	"off"	block report off (ratchet: narrower layer wins; listed narrowest first)	1.0.25	Whether the cloud guard judges commands at all. Default off; report logs only.

Production

Setting	Layer	Default	Values	Since	Summary
<code>production.databases</code>	repo	[]	not validated - read by plugin/crew/hoo ks/scripts/crew _config.py (expects list of globs)	0.19.30	Globs naming production databases.
<code>production.hosts</code>	repo	[]	not validated - read by plugin/crew/hoo ks/scripts/crew _config.py	0.19.30	Globs naming production hosts.

Setting	Layer	Default	Values	Since	Summary
			(expects list of globs)		

Cloud

Setting	Layer	Default	Values	Since	Summary
cloud.awsProfiles	repo	[]	not validated - read by plugin/crew/hooks/scripts/cloud_guard.py (expects list of names)	1.0.25	AWS profiles this repo may use.
cloud.awsRegions	repo	[]	not validated - read by plugin/crew/hooks/scripts/cloud_guard.py (expects list of names)	1.0.25	AWS regions this repo may use.
cloud.azureSubscriptions	repo	[]	not validated - read by plugin/crew/hooks/scripts/cloud_guard.py (expects list of names)	1.0.25	Azure subscriptions this repo may use.

Environments

Setting	Layer	Default	Values	Since	Summary
environments.nonProd	repo	[]	not validated - read by plugin/crew/hooks/scri	1.0.37	Terraform targets that are not production

Setting	Layer	Default	Values	Since	Summary
			pts/crew_config.py (expects list of globs)		and may run unattended.
environments.prodUnattended	both, ratchet	false	false true (ratchet: narrower layer wins; listed narrowest first)	1.0.37	Whether production terraform may run unattended; true only when both layers say so.

Change

Setting	Layer	Default	Values	Since	Summary
change.requester	both	null	not validated - read by plugin/crew/hooks/scripts/crew_change.py (expects string or null)	0.19.31	Who requests the change.
change.implementor	both	null	not validated - read by plugin/crew/hooks/scripts/crew_change.py (expects string or	0.19.31	Who implements the change.

Setting	Layer	Default	Values	Since	Summary
			null)		
change.requireForProduction	both, ratchet	false	true false (ratchet: narrower layer wins; listed narrowest first)	0.19.31	Require an approved change request before /crew:promote production: a repo may turn it on, never off.
change.sdpTemplate	both	"Change Management Request"	not validated - read by plugin/crew/hooks/scripts/crew_change.py (expects string)	0.19.31	SDP template for a change request.
change.jiraIssueType	both	"Change"	not validated - read by plugin/crew/hooks/scripts/crew_change.py (expects string)	0.19.31	Jira issue type for a change request.
change.category	both	null	not validated - read by plugin/crew/hooks/scripts/crew_change.py	0.19.31	Change category.

Setting	Layer	Default	Values	Since	Summary
			(expects string or null)		

Git

Setting	Layer	Default	Values	Since	Summary
git.forbiddenTrailers	both	[]	list of trailer tokens (letters, digits and -, no :) (checked in plugin/crew/hooks/scripts/crew_trailers.py)	1.0.328	Commit trailer tokens the owner forbids, reported by /crew:done. The two layers combine by union, so a repo can add a token and never remove the machine owner's; a value that is not a list of tokens makes the list unknown, never empty (CONFIG.md section 22).

Scope

Setting	Layer	Default	Values	Since	Summary
scope.mode	repo	"off"	off report block auto	1.0.25	Whether the scope guard enforces a ticket's Touch list; a value

Setting	Layer	Default	Values	Since	Summary
					outside these fails closed to block.
scope.allowCliApproval	repo	false	false true (checked in plugin/crew/hooks/scripts/crew_ticket.py)	1.0.25	Whether a CLI-written approval receipt counts; only exactly true allows it.

Autopilot

Setting	Layer	Default	Values	Since	Summary
autopilot.mode	both, stricter wins	"off"	off plan (checked in plugin/crew/hooks/scripts/crew_autopilot.py); personal: listed strictest first, the stricter wins	1.0.41	Only the exact string plan arms /crew:autopilot; anything else reads as off, with a warning.
autopilot.maxPhases	both, stricter wins	12	positive integer (checked in plugin/crew/hooks/scripts/crew_autopilot.py); personal: the smaller wins	1.0.41	Phases one run may take; anything but a positive integer reads as 12, with a warning.
autopilot.deploy	both, strict	"none"	none nonprod	1.0.42	Where a deploy may run without

Setting	Layer	Default	Values	Since	Summary
	server wins		all; personal: listed strictest first, the stricter wins		asking; anything else reads as none.
autopilot.approval	both, strict er wins	"risk"	human risk self; personal: listed strictest first, the stricter wins	1.0.42	Who approves a ticket under autopilot; anything else reads as human.
autopilot.questions	both, strict er wins	"risk"	human risk self; personal: listed strictest first, the stricter wins	1.0.42	Who answers a ticket's open questions under autopilot; anything else reads as human.
autopilot.maxAutoReplans	repo	0	non- negative integer (checked in plugin/crew/ hooks/scripts/crew_au topilot.py)	1.0.33 9	Successor plans autopilot may start by rejecting an out- of-rounds BLOCK review itself; 0 is off, and anything but a non-negative integer reads as 0, and above 5 as 5, with a warning.
autopilot.sleep.schedule	repo	null	HH:MM- HH:MM or null (checked in plugin/crew/ hooks/script	1.0.33 2	A nightly window, HH:MM-HH:MM in machine local time (may cross midnight); inside it the two sleep

Setting	Layer	Default	Values	Since	Summary
			s/crew_sleep.py)		overrides apply. Anything else is could not tell: only a stricter override applies.
autopilot.sleep.approval	repo	null	null human self risk (checked in plugin/crew/hooks/scripts/crew_sleep.py)	1.0.332	autopilot.approval inside the sleep window; null keeps the day value; anything else counts as human, the strictest, with a warning.
autopilot.sleep.questions	repo	null	null human self risk (checked in plugin/crew/hooks/scripts/crew_sleep.py)	1.0.332	autopilot.questions inside the sleep window; null keeps the day value; anything else counts as human, the strictest, with a warning.
autopilot.ship	repo	"merge"	pr merge	1.0.349	After /crew:done: pr pushes and opens the PR; merge also merges it (a merge commit) once the required checks allow. Anything else reads as pr, with a warning.
autopilot.knownFailures	repo	[]	list of check names (checked in plugin/crew/hooks/scripts/crew_autop	1.0.349	Required checks whose fail does not block a merge, matched by exact name; anything but a list of strings

Setting	Layer	Default	Values	Since	Summary
			ilot.py)		reads as [], with a warning.
autopilot.ciTimeoutMinutes	repo	60	positive integer (checked in plugin/crew/hooks/scripts/crew_autopilot.py)	1.0.349	Minutes ship waits for the required checks; still pending, or green only after it, stops. Anything but a positive integer reads as 60, with a warning.

Tickets

Setting	Layer	Default	Values	Since	Summary
tickets.baseBranch	repo	null	branch name or null (checked in plugin/crew/hooks/scripts/scope_base.py)	1.0.158	The branch ticket branches are cut from; null tries origin/HEAD's target, then origin/main, then main. A value that is not a branch name, or names no commit, makes the scope base could not tell.

Route

Setting	Layer	Default	Values	Since	Summary
route.enabled	both	false	false true (checked in plugin/crew/hooks/scripts/cr	1.0.42	Route plain-text prompts to /crew: commands; only the JSON value

Setting	Layer	Default	Values	Since	Summary
			ew_route.py)		true arms it.

Coming (Not in Code Yet)

Keys from approved tickets that have not landed. Each moves into the table above when its ticket lands, because it is then in the code; a test fails until it does (test_no_coming_key_is_in_code).

T-0009

Setting	Change	Layer	Default	Values	Summary
guards.deployWorkflow	new key	both, ratchet	block		Whether crew may dispatch a deploy workflow.
environments.workflows	new key	repo	{}		Deploy workflows per environment.

T-0012

Setting	Change	Layer	Default	Values	Summary
autopilot.maxTicketsPerRun	new key	repo	3		Tickets one goal run may work before it stops.
autopilot.maxTokensPerSession	new key	repo	200000 0		Token cap for one goal session.
autopilot.mode	changes values	repo	off	off plan backlog	Adds backlog: work a goal's tickets one at a time.

T-0029

Setting	Change	Layer	Default	Values	Summary
autopilot.maxLanes	new key	repo	the resolved pm.maxDispatches		Parallel lanes one autopilot wave may run; may only lower the limit.
autopilot.reviewPolicy	new key	repo	stop	stop clean-only fix-and-rereview	What a lane does with review findings.

T-0030

Setting	Change	Layer	Default	Values	Summary
coord.ttlMinutes	new key	set when T-0030 lands	30		Lifetime of a cross-session coordination claim (1-10080).
coord.channel	new key	set when T-0030 lands	set when T-0030 lands		Where sessions coordinate.

T-0050

Setting	Change	Layer	Default	Values	Summary
scope.allowCliApproval	change s layer	both, stricter wins	false		Becomes settable in the global file, the stricter layer winning, once its

Setting	Change	Layer	Default	Values	Summary
					reader (crew_ticket.cli_approval_allowed) reads the global layer in a harness-only follow-up to T-0050.