

Theoretical Foundations of the Age-Area Hypothesis

Matthew J. Baker

Department of Economics
Hunter College and the Graduate Center, CUNY

February 20, 2018

Abstract

The impact of past mass migrations is still felt today. One tool commonly used in theorizing about the nature and origins of mass migrations is the so-called Age-Area Hypothesis, originally advanced by Sapir (1915). The age-area hypothesis traces the origins of linguistic stocks, which are closely related to cultural and genetic similarities. One common way of stating the hypothesis is that the area of origin of a linguistic stock is where the languages comprising the stock are most different. While the hypothesis is compelling, and its predictions are often corroborated by other evidence, a cohesive theoretical structure for the Age-Area Hypothesis has never been described. This paper describes such a theoretical foundation in terms of probability, and also presents a computational algorithm for computing the relative likelihood of historical locations and migratory paths.

The age-area hypothesis - evidently first developed and applied by Sapir (1916) in his study of certain Native American Languages - is often invoked when linguistic evidence is used in support of hypotheses about where different sorts of cultures originated, how they evolved over time, and how they came to be located where they are today. Briefly stated, the hypothesis says that the geographic area where a language phylogeny originated is most likely the place where the component languages of the phylogeny are maximally differentiated.

While the question may have some of academic interest only, a wide variety of recent economic literature highlights the importance of understanding how we arrived at the current cultural mix around the globe. Coincident with this understanding is the realization that understanding where different cultures came from, and how they interacted in the past, is also of paramount importance.

Examples of the application of the linguistic age-area hypothesis abound. Sapir himself used these arguments to suggest that the so-called Na-Dene linguistic grouping originated in and around the North West Coast. As another example, Atkinson and Gray (2003) have used the results to suggest that the Indo-European languages originated in Anatolia, not, as is sometimes supposed, on the steppes of Siberia. Further applications of the idea - either implicit or explicit use of the idea - are almost too numerous to mention. Ruhlen (2001) uses the age-area hypothesis to lend insight into debates about the origins of the Na-Dene, as well as the origins of the Bantu linguistic group in Africa.

What is the existing theoretical basis for the age-area hypothesis? In spite of its wide range of applications and deep implications for human history, there is almost no theoretical support for the hypothesis. In population genetics, it is well-known that the point of maximal genetic diversity of populations is closest to the geographical point of origin. This is because migrant populations are subsets of the parent population, and hence have only a subset of the population genes. But this is certainly not the case with language; migrant populations don't migrate with only a subset of the vocabulary or grammar of the parent language!

The lack of a theoretical basis for the age area hypothesis is also a problem for its use in technical situations. For example, suppose one wished to include an ancient migratory path in a statistical model? Since the hypothesis has no theoretical underpinnings, it is difficult to see how to construct a likelihood for a certain path or migratory history.

In this paper, I develop a theoretical foundation for the age-area hypothesis, and

make some of the terms supporting the hypothesis more rigorous. The theory is based upon a particular idea that turns out to correspond with a probabilistic notion of parsimony. The idea also

1 Problem Description and Motivation

Consider the hypothetical phylogenetic tree displayed in figure 1. There are five related cultures in the example, and perhaps a linguist or geneticist has pieced together that degree of relatedness among the groups as depicted on the figure. A is the most divergent of the group, with B, C, D, E all being more closely related, and D and E being the two most closely related languages. To avoid forming impressions based on evidence that is not part of the hypothesis, we will suppose that the locations of the groups have been concealed from us, and that we have no access to archaeological or historical information about the language stock.

In terms of the Age-Area hypothesis and the ultimate source of the tree (i.e., the point at which the tree originated) - one would posit that the point of origin was A's location, as A is the most divergent language from the group. If one wanted to push the hypothesis a bit further, or even apply it recursively, one would come up with a hypothetical migratory route: the hypothesis would lead one to believe that the point of origin of the stock was A, at which point there was a migration from A to B, then from B to C, and then from C to either D or E.

There are a large number of other possibilities as well, even though the structure of the tree constrains some sorts of events. For example, an additional plausible sequence of migratory events would be for an initial migratory episode from C to A, followed by another from C to B, followed by yet another migration from C to D or E. These two migratory routes are presented in figure 1.

The age area hypothesis suggests that the second sequence of events is somehow less likely than the sequence of events described by the first. Why? For a variety of reasons - one might simply appeal to Occam's razor - the events on the left-hand side of figure 1 require only one migratory chain, while the events on the right-hand side require three separate expansions: an initial migration from A to C, followed by another from A to B. A third migratory event begins from C continues to D, and then to E. We can now pose our question as follows: if we believe these migratory events to be rare, and we wish to conserve them in explaining historical migrations, what sort of model




Figure 1: A simple phylogenetic tree

Two Hypothetical Migratory Routes




Figure 2: Potential migratory routes among a language stock consisting of five groups, following the Phylogenetic Tree in figure 1

would accomplish this?

2 A simple model

In addition to providing a foundation for the age-area hypothesis, we might lean on some additional principles that we wish to encapsulate in the theory. We might like the model to conserve on estimation of parameters, and we might also like the model to have a consistent internal logic. A simple model with transparent machinery also creates the possibility of expansion and further development. While the assumptions listed below are restrictive, one can see how they might be relaxed in future work.

Accordingly, let's make the following preliminary assumptions:

1. The entire phylogenetic tree is observed; there are no unobserved migratory events.
2. A group arrives in its current position with we might call a “propensity to migrate.” It then discharges an additional migratory rate with exponential density.
3. Once a group arrives in its current and discharges a migratory group, it is then dormant; subsequent migration from the group's location requires the beginnings of an additional migratory episode.

One good thing about this model is that it can be easily concentrated. That is, the parameters of any exponential distribution can be concentrated out of the likelihood, and this makes the workings of the model clear in that one can easily see how and why it would posit that the first sequence of events on figure 1 are more likely.

To see the basic idea, let's develop a comparison of the two scenarios described in figure 1. The first scenario requires an initial migratory event to start after time t_0 from point A . At this point, according to the model assumptions, A is dormant, and the migratory bug is transitioned to location B . After time t_1 , B emits the migratory bug to C and is then dormant, followed by C 's emission and subsequent dormancy, and then D 's. Finally, E retains the bug but never emits.

This is the only migratory episode needed to explain the positioning of the groups in the tree, and given the assumption that discharges are exponential, suppose our events are described by the distribution $\text{Exp}(\lambda)$. Then, we have the likelihood of point

A being the point of origin as:

$$P_A = \lambda e^{-\lambda t_0} \lambda e^{-\lambda t_1} \lambda e^{-\lambda t_2} \lambda e^{-\lambda t_3} e^{-\lambda t_8} \quad (1)$$

or

$$P_A = \lambda^4 e^{-\lambda(t_0+t_1+t_2+t_3+t_8)} \quad (2)$$

There are a couple of points of interest for equation (1). First, since only one migratory path is needed to explain the events, only one exponential parameter is needed for the whole process. Also, since a migratory event after t_8 is never observed, we have $1 - F(t_8, \lambda) = e^{-\lambda t_8}$; there is only one such “operational branch” when our observation period ends.

Since the migration parameter is not of as great of interest as the probability, we can take the log of equation 3 and maximize the result with respect to λ , and substitute the result back in to concentrated likelihood, giving us a closed-form expression for the probability that A is the point of origin:

$$P_A = \frac{4^4 e^{-4}}{(t_0 + t_1 + t_2 + t_3 + t_8)^4} \quad (3)$$

Of course, this is not all that meaningful without a point of comparison. So, by way of comparison, according to this model, what is the likelihood that the point of origin is C ?

In this case, the process begins with a migration after t_0 from C to A . Subsequently, no additional migrations occur from A , so A remains active. Then, after time t_1 a second migratory event arises leading from C to B , after which nothing further occurs on this branch. Then, a migratory event leads from C to D over time t_2 , and then from D to E over time t_3 , at which point nothing more happens.

The key thing about this explanation is that there are three separate migratory events needed to explain things, so we need three exponential parameters in the model. Another key thing is that we have more branches that are “alive” at the end of the process. These might suggest intuitively that this explanation is less likely than the previous, and this is indeed the case under the model. Forming the likelihood in the same way as we did above, we have:

$$P_C = \lambda_1 e^{-\lambda_1(t_0+t_4)} \lambda_2 e^{-\lambda_2(t_1+t_5)} \lambda_3^2 e^{-\lambda_3(t_2+t_3+t_8)} \quad (4)$$

So, here we have a three-parameter model, which is how the increased complexity of the explanation (the anti-Occam’s razor effect) is manifest in the probability. Concentrating 4 as above gives the result:

$$\frac{2^2 e^{-4}}{(t_0 + t_4)(t_1 + t_5)(t_2 + t_3 + t_5)} \quad (5)$$

We can form the ratio of this and the previous expression and see which tree is more likely under which configuration of the parameters. The intuition behind the explanation can be written as:

$$LR = 4 \left(1 - \frac{t_0}{T}\right) 4^2 \left(1 - \frac{t_o + t_1}{T}\right)^2$$

So we see that unless the branches t_0 and t_1 constitute a (very) large span of the tree, our model claims that A is the most likely place of origin.

3 Theorems

Theorem 1 *The Age-Area theorem*

Take the route collection R through tree T and apply to it a redirect, calling the result R' . Then, compute the concentrated likelihood of the new tree gives $p(R) > p(R')$.

4 An algorithm

As is often the case when dealing with estimation over trees, it behooves one to consider an algorithm that works backwards from the branches to the base. The algorithm presented here is essentially a pruning algorithm like Felsenstein’s with a hint of dynamic programming. The dynamic programming aspect introduces a sort of continuation maximum likelihood into the tree.

The algorithm works as follows. At termination, the result is a concentrated log-likelihood of each location being the point of origin. The following is an illustration showing how the algorithm works on the example given above.

0. Initialization: a “active” vector of zeros $A = [0, 0, 0, 0, 0]$, a vector of exponential parameters that start with zero, $E = [0, 0, 0, 0, 0]$, and a continuation likelihood

$$L = [-t_4, -t_5, -t_6, -t_7, -t_8]$$

1. Select an interior node and pick out its branches.
2. Poo