




FUKUI

RHK, RVK Series

Contents

◆ Features	1
◆ About HEI standards	1
◆ Type code.....	1
◆ Structure.....	2
◆ Cross-sectional View and Standard Material.....	3
◆ Actual Area	5
◆ Pressure–temperature Rating	5
◆ Dimensions and Weight	6

◆ Features

The RHK and RVK series are atmospheric release valves for heat exchangers, to which the HEI standards are applied. The RHK is intended for horizontal flow direction; the RVK for vertical flow direction.

◆ About HEI standards

Atmospheric release valves specified in the HEI standards shall meet the following requirements.


- ◆ The periphery of the disc shall be water-sealed.
- ◆ A manual opening and closing mechanism shall be provided.
- ◆ Valves shall be selected so as not to exceed 0.069 MPa (10 psig).

◆ Type code

RVK	1	6	1-		F				
					Material code				
					F	Cast iron		W	Steel plate welded
					S	SCPH2 or A216-WCB		—	—
					Inlet flange class (only when different) Same code as pressure class				
				Connection code					
				1-	ASME Flange		4-	JIS Flange	
				2-	JPI Flange		—	—	
				Temperature class code				Unit: °C (F°)	
				6	-29 (-20) ≤ T < 232 (450)				
				Pressure class code					
				1	Class 150 or JIS 10K or JIS B 8210 10K		3	Class 300 or JIS 30K or JIS B 8210 30K	
				2	JIS 20K or JIS B 8210 20K				
				Type code					
RVK	Vertical type			RHK	Horizontal type				


Structure

- ◆ Cast integral body
- ◆ Water supply and drain connection
- ◆ Water seal
- ◆ Valve opening handle



Cross-sectional View and Standard Material


RHK series



No.	Part name	Material	No.	Part name	Material
1	Body	FC200 or A216-WCB or SCPH2	13	Handwheel	FC200
2	Nozzle	SCS13A	14	Nut	SS400
3	Disc	SUS304	15	Stud bolt, nut	S20C
4	Bush	SUS304	16	Stud bolt, nut	S20C
5	Washer	SUS304	17	Washer	SWRH57
6	Cover flange	SM400B	18	Nut	SS400
7	Stem	SUS403	19	Plug	SUS304
8	Gland	SUS403	20	Gasket	V6502
9	Gland arm	SS400	21	Gland packing	V6232
10	Sleeve	SUS304	22	Stopper	SGP
11	Stem arm	SS400	23	Stopper	SUS340
12	Pillar	SS400	24	Water gauge	SUS304

* This shows a general structure. The structure may vary depending on the size.

RVK series



No.	Part name	Material	No.	Part name	Material
1	Body	FC200 or A216-WCB or SCPH2	14	Handwheel	FC200
2	Nozzle	SCS13A	15	Nut	SS400
3	Disc	SUS304	16	Stud bolt, nut	SS400
4	Guide	SCS13	17	Stud bolt, nut	SS400
5	Lift lever	SS400	18	Washer	SWRH57
6	Cover flange	SMB440B	19	Nut	SS400
7	Stem	SUS403	20	Pin	SUS304
8	Lift fork	SUS403	21	Pin	SUS304
9	Gland	SUS403	22	Gasket	V6502
10	Gland arm	SS400	23	Gland packing	V6137
11	Sleeve	SUS304	24	Stopper	SGP
12	Stem arm	SS400	25	Water gauge	SUS304
13	Pillar	SS400	—	—	—

* This shows a general structure. The structure may vary depending on the size.

Actual Area

Size	Seat diameter mm	Nominal lift mm	Discharge area mm ²
6*6	150	21	9896
8*8	200	28	17592
10*10	250	35	27488
12*12	300	42	39584
14*14	335	47	49464
16*16	390	55	67387
18*18	440	66	91231
20*20	490	84	129307
24*24	590	105	194621
30*30	740	126	292922


Pressure–temperature Rating

Size	Pressure (MPa)		Temperature (°C)
	Minimum	Maximum	
6*6	FV	0.04 MPa	120
8*8			
10*10			
12*12			
14*14			
16*16			
18*18			
20*20			
24*24			
30*30			


* The flow determining pressure is 0.17024 MPa (10 + 14.7 psi), as specified by the HEI standards.

* The starting pressure is 0.002–0.006 MPa (2–6 kPa).

◆ Dimensions and Weight



RHV Series



RVK Series

Dimensions and Weight						Units: mm, kg
Type	Size	Flange Class		Dimensions		Approximate weight
		Inlet	Outlet	A	B	
RHK	6×6	150	150	395	365	80
	8×8			400	495	110
	10×10			490	622	225
	12×12			545	699	305
	14×14			605	787	465
	16×16			755	914	705
	18×18			857	914	750
	20×20			890	1100	980
	24×24			973	1330	1600
	30×30			1211	1400	3000
RVK	6×6	150	150	395	356	80
	8×8			400	495	110
	10×10			490	622	225
	12×12			545	699	305
	14×14			605	787	465
	16×16			755	914	705
	18×18			840	914	730
	20×20			890	1100	980
	24×24			980	1330	1470
	30×30			1050	1400	2700



Head Office Hirakata Plant

1-6 Shodaitajika, Hirakata City, Osaka 573-1132, Japan

Tel: +81-72-857-4521 Fax: +81-72-857-3764

E-mail: fki@fkis.co.jp

Global Marketing

1-6 Shodaitajika, Hirakata City, Osaka 573-1132, Japan

Overseas

Tel: +81-72-857-4527 Fax: +81-72-857-3324

E-mail: stm@fkis.co.jp

Domestic

Tel: +81-72-857-5501 Fax: +81-72-857-5502

E-mail: osk@fkis.co.jp

Yokohama Office

Wesport Bldg. 10th Floor, 2-6-32, Takashima, Nishi-ward, Yokohama City, Kanagawa 220-0011, Japan

Tel: +81-45-441-4411 Fax: +81-45-441-0031

E-mail: ybm@fkis.co.jp

FUKUI SEISAKUSHO CO., LTD.

The product photos, structures, etc. in this document show representative examples.
Product specifications in the catalog are subject to change without notice for product improvement or quality enhancement.